## Microsoft® LifeCam Studio™





Product Name	Name Information		
Webcam Days A 45 inches   14 stillinearing   Webcam Days   2.5 stockes (50 or millinearing   Webcam Days   2.5 stockes (50 or		Microsoft® LifeCam Studio™	
Vebcam Legisla   Vebc			
Webcam Multin  2.38 inches (14 millimeters)  Webcam Depth Neight  7.75 inches (45 0 millimeters)  Webcam Depth Neight  7.72 inches (45 0 millimeters)  7.73 inches (45 0 millimeters)  7.74 inches (45 0 millimeters)  7.75 in		WILLOSOFE EIROGIII STUUTO	
Webcann Depti-Height   2.3 in Inches (60) of millimeters   177 inches (50) millimeters   1520 millimeters		4.40 inches (4.44 millimeters)	
Webcam Webcam Webcam (28) and many (28) and many (28) and (28) a			
Velocam Weight Longh   Compatibility and Cocilizations   T2-0 inches (1500 millimeters + 150-0 millimeters)   T2-0 inches + 150-0 millimeters   T2-0 millimeters			
Opensprishing value of Comments (1920 millimeters 1920 millimeters 1920 millimeters)			
Hispanel USB compatible with the USB 2.0 specification			
Presidency   Presidency   Processing Systems		72.0 inches +6/-0 inches (1829 millimeters +152/-0 millimeters)	
Operating Systems*    Microsoft Windows** 10 / 8 in d 7			
- Medinated NG X v10.7-10.10 - Advanced Intercoality not available with all devices and/or operating systems. See compatibility information at: www.microsoft.com/hardware/compatibility.  Requires a PC that meets the requirements for and has installed one of these operating systems:  - More victors of the state of th			
Requires a PC that meets the requirements for and has installed one of these operating systems:  - Microsoft Windows 10 / 8 and 7  - VGA video calling: - 1 Gib of RAM - 2 Mill or higher video memory - Vindrove compatible spaces or headphones - USB 2.0 - You must accept License Terms for software download. Please download the latest available software version for your OS/Hardware combination Internet access may be required for certain features. Local and/or long-distance telephone toll charges may apply Software download required for full functionality of all features.  Internet functions (post to Windows Live " Spaces, send in e-mail, video calls), also require. Internet Explorer "67 browser software required for installation: 2  Mis hard drive space typically required (users can maintain other delatul Web browsers after installation) - The Microsoft LifeCam Stown bas basic video & Autio Functionality with Windows Live Messenger, AOL® Instant Messenger. "Yahool® Messenger, Stype, and Microsoft LifeCam Stown eversion 3.5 may be installed in Simplified Chinese, Traditional Chinese, English, French, German, Italian, Japanese, Korean, Paralian Portuguese, Iberian Portuguese, or Spanish. If available, standard setup will install the software in the default OS language. Otherwise, the English Paralian Portuguese, berian Portuguese, or Spanish. If available, standard setup will install the software in the default OS language. Otherwise, the English Paralian Portuguese, berian Portuguese, or Spanish. If available, standard setup will install the software in the otherwise setup will be software the winthi	Operating Systems <sup>1</sup>	• Macintosh OS X v10.7-10.10	
and Microsoft Office Communicator  Compatibility Logos  Software Localization  Software Localization  Microsoft LifeCam software version 3.5 may be installed in Simplified Chinese, Traditional Chinese, English, French, German, Italian, Japanese, Korean, Brazilian Portuguese, Iberian Portuguese, or Spanish. If available, standard setup will install the software in the default OS language. Otherwise, the English language version will be installed.  Windows Live* Integration Features  Windows Live all button delivers one touch access to video conversation  Call Button Life  Windows Live Integration Features  Windows Live Integration Features  LifeCam Dashboard provides access to animated video special effect features and webcam controls  LifeCam Dashboard provides access to animated video special effect features and webcam controls  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Windows Live Integration Features  Windows Live Photo Gallery integration - Take a photo with LifeCam Software, then with one click open Photo Gallery to edit, tag and share it online  - Windows Live Photo Gallery integration - Record a video with LifeCam Software and start a movie project on Movie Maker with just one click to then upload it to your favorite networking site  Imaging Features  Sensor  CMOS sensor technology  - Sensor Resolution: 1920 X 1080  - Sell Image; Sengapaice (2560 x 2048 pixel, interpolated) photos*  Field of View  75° diagonal field of view  Imaging Features  - Autionatic face tracking**  - Digital pan, digital tit, and 3x digital zoom**  - Autionatic face tracking**  - Digital pan, digital tit, and 3x digital zoom**  - Autionatic face tracking**  - Digital pan, digital tit, and 3x digital zoom**  - Autionatic face tracking**  - Digital pan, digital tit, and 3x digital zoom**  - Autionatic face tracking**  - Digital pan, digital tit, and 3x	Top-line System Requirements	Requires a PC that meets the requirements for and has installed one of these operating systems:  • Microsoft Windows 10 / 8 and 7  • VGA video calling:  • Intel Dual-Core 1.6 GHz or higher  • 1 GB of RAM  • 720p HD recording:  • Intel Dual-Core 3.0 GHz or higher  • 2 GB of RAM  • 1.5 GB hard drive space  • Display adapter capable of 16-bit color depth or higher  • 2 MB or higher video memory  • Windows-compatible speakers or headphones  • USB 2.0  You must accept License Terms for software download. Please download the latest available software version for your OS/Hardware combination.  Internet access may be required for certain features. Local and/or long-distance telephone toll charges may apply.  Software download required for full functionality of all features.  Internet functions (post to Windows Live™ Spaces, send in e-mail, video calls), also require: Internet Explorer* 6/7 browser software required for installation; 25 MB hard drive space typically required (users can maintain other default Web browsers after installation)	
Software Localization  Software Localization  Microsoft LifeCam software version 3.5 may be installed in Simplified Chinese, Traditional Chinese, English, French, German, Italian, Japanese, Korean, Brazilian Portuguese, Iberian Portuguese, or Spanish. If available, standard setup will install the software in the default OS language. Otherwise, the English language version will be installed.  Windows Live** Integration Features  Video Conversation Feature  Windows Live all button delivers one touch access to video conversation  Call Button Life  10,000 actuations  Windows Live Integration Features  Windows Live Integration Features  Windows Live Integration Features  Video Conversation Features  CMOS sensor technology  CMOS sensor technology  Video Maker integration - Record a video with LifeCam Software and start a movie project on Movie Maker with just one click to then upload it to your favorite networking site  Video of Video	Compatibility Logos	and Microsoft Office Communicator  • Compatible with Microsoft Windows 10 / 8 / 7	
Software Localization  Microsoft LifeCam software version 3.5 may be installed in Simplified Chinese, Traditional Chinese, English, French, German, Italian, Japanese, Korean, Brazilian Portuguese, Iberian Portuguese, or Spanish. If available, standard setup will install the software in the default OS language. Otherwise, the English Ianguage version will be installed.  Windows Live** Integration Features  Windows Live call button Life  Webcam Controls & Effects  Windows Live Integration Features  Windows Live Integration Features  Windows Live Integration Features  Windows Live Movie Maker integration - Take a photo with LifeCam Software, then with one click open Photo Gallery to edit, tag and share it online  Windows Live Movie Maker integration - Record a video with LifeCam Software and start a movie project on Movie Maker with just one click to then upload it to your shortwising site  Sensor  CMOS sensor technology  Resolution  Sensor Sensor Sensolution: 1920 X 1080  Still Image: 5 megapixel (2560 x 2048 pixel, interpolated) photos*  Field of View  Imaging Features  Imaging Features  Automatic face tracking**  Automatic face tracking**  Automatic mage adjustment with manual override  Up to 30 frames per second  Product Feature Performance  Audio Features  Integrated omni-directional super wideband microphone  Frequency Response  Integrated omni-directional super wideband microphone  Frequency Response  100 Hz - 18 kHz  Mounting Features  Notebook and LCD universal attachment base  Notebook and LCD universal attachment base  Notebook and LCD universal attachment base  Tripod universal attachment base  Tripod universal attachment base  Tripod universal attachment base  Tripod universal attachment base			
Video Conversation Feature  Call Button Life  10,000 actuations  Webcam Controls & Effects  Windows Live Integration Features  Vindows Live Integration Features  Vindows Live Integration Features  Vindows Live Integration Features  - Windows Live Movie Maker integration - Record a video with LifeCam Software, then with one click open Photo Gallery to edit, tag and share it online  - Windows Live Movie Maker integration - Record a video with LifeCam Software and start a movie project on Movie Maker with just one click to then upload it to your favorite networking site  Imaging Features  Sensor  CMOS sensor technology  - Sensor Resolution: 1920 X 1080  - Still Image: 5 megapixel (2560 x 2048 pixel, interpolated) photos*  Field of View  Imaging Features  Imaging Features  - Automatic face tracking**  - Automatic face tracking**  - Automatic image adjustment with manual override  - Up to 30 frames per second  Product Feature Performance  Audio Features  Integrated omni-directional super wideband microphone  Frequency Response  100 Hz - 18 kHz  Mounting Features  Notebook and LCD universal attachment base  - Notebook and LCD universal attachment base  - Tripod universal attachment base	Software Localization	Microsoft LifeCam software version 3.5 may be installed in Simplified Chinese, Traditional Chinese, English, French, German, Italian, Japanese, Korean, Brazilian Portuguese, Iberian Portuguese, or Spanish. If available, standard setup will install the software in the default OS language. Otherwise, the English	
Call Button Life       10,000 actuations         Webcam Controls & Effects       LifeCam Dashboard provides access to animated video special effect features and webcam controls         Windows Live Integration Features       • Windows Live Movie Maker integration - Record a video with LifeCam Software, then with one click open Photo Gallery to edit, tag and share it online         Imaging Features       Sensor       CMOS sensor technology         Resolution       • Sensor Resolution: 1920 X 1080         Field of View       • Sensor Resolution: 1920 X 1080         Imaging Features       • Still Image: 5 megapixel (2560 x 2048 pixel, interpolated) photos*         Field of View       75° diagonal field of view         Imaging Features       • Automatic face tracking** • Digital pan, digital tilt, and 3x digital zoom** • Auto focus from 0.1m to ≥ 10m • Automatic image adjustment with manual override • Up to 30 frames per second         Product Feature Performance         Audio Features       Integrated omni-directional super wideband microphone         Frequency Response       Integrated omni-directional super wideband microphone         Frequency Response       100 Hz - 18 kHz         Mounting Features       • Desktop and CRT universal attachment base • Notebook and LCD universal attachment base • Notebook and CCO universal attachment base • Tripod universal attachment base          Storage			
Call Button Life       10,000 actuations         Webcam Controls & Effects       LifeCam Dashboard provides access to animated video special effect features and webcam controls         Windows Live Integration Features       • Windows Live Movie Maker integration - Record a video with LifeCam Software, then with one click open Photo Gallery to edit, tag and share it online         Imaging Features       Sensor       CMOS sensor technology         Resolution       • Sensor Resolution: 1920 X 1080         Field of View       • Sensor Resolution: 1920 X 1080         Imaging Features       • Still Image: 5 megapixel (2560 x 2048 pixel, interpolated) photos*         Field of View       75° diagonal field of view         Imaging Features       • Automatic face tracking** • Digital pan, digital tilt, and 3x digital zoom** • Auto focus from 0.1m to ≥ 10m • Automatic image adjustment with manual override • Up to 30 frames per second         Product Feature Performance         Audio Features       Integrated omni-directional super wideband microphone         Frequency Response       Integrated omni-directional super wideband microphone         Frequency Response       100 Hz - 18 kHz         Mounting Features       • Desktop and CRT universal attachment base • Notebook and LCD universal attachment base • Notebook and CCO universal attachment base • Tripod universal attachment base          Storage		Windows Live call button delivers one touch access to video conversation	
Windows Live Integration Features       • Windows Live Photo Gallery integration - Take a photo with LifeCam Software, then with one click open Photo Gallery to edit, tag and share it online         Imaging Features       • Windows Live Movie Maker integration - Record a video with LifeCam Software and start a movie project on Movie Maker with just one click to then upload it to your favorite networking site         Imaging Features       CMOS sensor technology         Resolution       • Sensor Resolution: 1920 X 1080         • Still Image: 5 megapixel (2560 x 2048 pixel, interpolated) photos*         Field of View       75° diagonal field of view         Imaging Features       • Automatic racking**         • Digital pan, digital tilt, and 3x digital zoom**         • Auto focus from 0.1m to ≥ 10m         • Automatic image adjustment with manual override         • Up to 30 frames per second         Product Feature Performance         Audio Features       Integrated omni-directional super wideband microphone         Frequency Response       100 Hz − 18 kHz         Mounting Features       • Desktop and CRT universal attachment base         • Notebook and LCD universal attachment base       • Notebook and LCD universal attachment base         • Tripod universal attachment base       • Tripod universal attachment base         • Tripod universal attachment base       • Tripod universal attachment base          •	Call Button Life	10,000 actuations	
Windows Live Integration Features       • Windows Live Photo Gallery integration - Take a photo with LifeCam Software, then with one click open Photo Gallery to edit, tag and share it online         Imaging Features       • Windows Live Movie Maker integration - Record a video with LifeCam Software and start a movie project on Movie Maker with just one click to then upload it to your favorite networking site         Imaging Features       CMOS sensor technology         Resolution       • Sensor Resolution: 1920 X 1080         • Still Image: 5 megapixel (2560 x 2048 pixel, interpolated) photos*         Field of View       75° diagonal field of view         Imaging Features       • Automatic racking**         • Digital pan, digital tilt, and 3x digital zoom**         • Auto focus from 0.1m to ≥ 10m         • Automatic image adjustment with manual override         • Up to 30 frames per second         Product Feature Performance         Audio Features       Integrated omni-directional super wideband microphone         Frequency Response       100 Hz − 18 kHz         Mounting Features       • Desktop and CRT universal attachment base         • Notebook and LCD universal attachment base       • Notebook and LCD universal attachment base         • Tripod universal attachment base       • Tripod universal attachment base         • Tripod universal attachment base       • Tripod universal attachment base          •	Webcam Controls & Effects	LifeCam Dashboard provides access to animated video special effect features and webcam controls	
Imaging Features   CMOS sensor technology		<ul> <li>Windows Live Photo Gallery integration - Take a photo with LifeCam Software, then with one click open Photo Gallery to edit, tag and share it online</li> <li>Windows Live Movie Maker integration - Record a video with LifeCam Software and start a movie project on Movie Maker with just one click to then upload it</li> </ul>	
Sensor       CMOS sensor technology         Resolution       • Sensor Resolution: 1920 X 1080         • Still Image: 5 megapixel (2560 x 2048 pixel, interpolated) photos*         Field of View       75° diagonal field of view         Imaging Features       • Automatic face tracking**	Imaging Features		
Product Feature Performance Audio Features  Integrated omni-directional super wideband microphone Frequency Response  Industry Resolution  Product Features  Integrated omni-directional super wideband microphone Frequency Response  Frequency Response  Integrated omni-directional super wideband microphone Frequency Response  Integrated omni-directional super wideband microphone Frequency Response  Integrated omni-directional super wideband microphone Frequency Response  Frequency Response  Integrated omni-directional super wideband microphone Frequency Response		CMOS sensor technology	
Imaging Features  • Automatic face tracking** • Digital pan, digital tilt, and 3x digital zoom** • Auto focus from 0.1m to ≥ 10m • Automatic image adjustment with manual override • Up to 30 frames per second  Product Feature Performance  Audio Features  Integrated omni-directional super wideband microphone  Frequency Response  Integrated omni-directional super wideband microphone  Integrated omni-directional super wideband microphone  Integrated omni-directional sup		Sensor Resolution: 1920 X 1080	
Imaging Features  • Automatic face tracking** • Digital pan, digital tilt, and 3x digital zoom** • Auto focus from 0.1m to ≥ 10m • Automatic image adjustment with manual override • Up to 30 frames per second  Product Feature Performance  Audio Features  Integrated omni-directional super wideband microphone  Frequency Response  Integrated omni-directional super wideband microphone  Integrated omni-directional super wideband microphone  Integrated omni-directional sup	Field of View	75° diagonal field of view	
Audio Features Integrated omni-directional super wideband microphone  Frequency Response 100 Hz – 18 kHz  Mounting Features • Desktop and CRT universal attachment base • Notebook and LCD universal attachment base • Tripod universal attachment base  Storage Temperature & Humidity -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)		<ul> <li>Automatic face tracking**</li> <li>Digital pan, digital tilt, and 3x digital zoom**</li> <li>Auto focus from 0.1m to ≥ 10m</li> <li>Automatic image adjustment with manual override</li> </ul>	
Audio Features Integrated omni-directional super wideband microphone  Frequency Response 100 Hz – 18 kHz  Mounting Features • Desktop and CRT universal attachment base • Notebook and LCD universal attachment base • Tripod universal attachment base  Storage Temperature & Humidity -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)	Product Feature Performance		
Frequency Response  100 Hz – 18 kHz  Mounting Features  Desktop and CRT universal attachment base Notebook and LCD universal attachment base Tripod universal attachment base  Storage Temperature & Humidity  -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)		Integrated omni-directional super wideband microphone	
Mounting Features  • Desktop and CRT universal attachment base • Notebook and LCD universal attachment base • Tripod universal attachment base  Storage Temperature & Humidity  • Desktop and CRT universal attachment base • Tripod universal attachment base			
	Mounting Features	Desktop and CRT universal attachment base     Notebook and LCD universal attachment base     Tripod universal attachment base	
Operating Temperature & Humidity 32° F (0° C) to 104° F (40° C) at <5% to 80% relative humidity (non-condensing)			
	Operating Temperature & Humidity	32° F (0° C) to 104° F (40° C) at <5% to 80% relative humidity (non-condensing)	

## Microsoft® LifeCam Studio™





Certification Information			
Country of Manufacture	People's Republic of China (PRC)		
ISO 9001 Qualified Manufacturer	Yes		
ISO 14001 Qualified Manufacturer	Yes		
Restriction on Hazardous Substances	This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.		
FCC ID	This device complies with Part 15 of the FCC Rules and Industry Canada ICES-003. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Tested to comply with FCC standards. For home and office use. Model number: 1425, LifeCam Studio.		
Agency and Regulatory Marks	ACMA Declaration of Conformity (Australia and New Zealand) ICES-003 report on file (Canada) EIP Pollution Control Mark, EPUP (China) WEEE (European Union) CE Declaration of Conformity (European Union) VCCI Certificate (Japan) MIC Certificate (Korea)	EAC Certificate (Russia)     FCC Declaration of Conformity (USA)     CB Scheme Certificate (International)	
Warranty	3 years		
Windows Certification Kit (WCK)	ID: 1760441 (32-bit and 64-bit) Microsoft Windows 10, 1609318 (32-bit) and	ID: 1760441 (32-bit and 64-bit) Microsoft Windows 10, 1609318 (32-bit) and 1604420 (64-bit) Microsoft Windows 8.1	