

Cisco Webex Room Kit Plus

Cisco Webex Room Kit Plus is a powerful collaboration solution that integrates with flat-panel displays to bring more intelligence and usability to your medium to large-sized meeting rooms – whether registered on the premises or to Cisco Webex in the cloud.

Cisco Webex Room Kit Plus Overview

Cisco Webex[™] Room Kit Plus delivers the unmatched video and audio experience customers have come to expect from Cisco. In addition, new capabilities enable even smarter meetings, smarter presentation capabilities, and smarter room and device integrations – further removing the barriers to usage and deployment of video in medium to large-sized rooms.

The Room Kit Plus – comprising a powerful codec and a quad-camera bar with integrated speakers and microphones – is ideal for rooms that seat up to 14 people. It offers sophisticated camera technologies that bring speaker-tracking and auto-framing capabilities to medium to large-sized rooms. The product is rich in functionality and experience but is priced and designed to be easily scalable to all of your conference rooms and spaces – whether registered on the premises or to Cisco Webex.

Figure 1. Cisco Webex Room Kit Plus in Large Conference Room



^{*} Integrated microphones for speaker tracking only

٠

Cisco Webex Room Kit Plus Features and Benefits

Feature	Benefit
Smart meetings	 Brings intelligent views to medium to large-sized rooms with discreet, integrated cameras Best overview: Automatically detects meeting participants and provides ideal framing Speaker tracking: Detects and switches between active speakers and provides ideal framing Great audio experience with integrated speakers and microphones (microphones for speaker tracking only) Automatic noise suppression reduces disruptive sounds coming from the meeting room (e.g., typing, paper rustling) Simplified meeting-join experience with One Button to Push (OBTP) for scheduled devices in a Cisco Webex meetings, whether registered on-prem or to Cisco Webex Automatic wake-up: System "wakes up" when someone walks into the room, and recognizes them through their mobile device Easily controlled by the Cisco Touch 10 control unit or with a Cisco Webex Teams app End-to-end security
Smart presentations	 Supports dual screens for video and content Supports dual content sources for local meetings View white board content and annotations shared from Cisco Webex Board, Cisco Webex DX80, or Cisco Webex Teams app; participate in white boarding sessions through Cisco Webex Teams app. 4K content sharing (local 30 fps; remote 5 fps) Wired or wireless content sharing
Smart rooms	 Metrics: Counts people in the room, enabling analytics for better resource planning Automatic screen/display integration through HDMI CEC Supports Wi-Fi In-room control: Control peripherals such as lights and blinds through the Cisco Touch 10
Built for cloud and premises	 Flexibility to register on the premises or to the cloud through Cisco Webex Hardware is optimized to run on a cloud platform, for great experiences in shared rooms and spaces with easy access to hosted conferences

Cisco Webex Room Kit Plus Prominent Feature/Differentiator

Bringing more intelligence to medium to large-sized rooms

The Cisco Webex Room Kit Plus is video innovation in a box, bringing more intelligence and usability to your medium to large-sized rooms team collaboration rooms. While others are still struggling to insert advanced features such as speaker tracking, wireless sharing, and 4K content into their high-end products, Cisco is already proliferating these innovations to medium and large team rooms in a cost-effective and simple way. With the Room Kit Plus, Cisco is helping customers experience smarter meetings, enable smarter presentations, and create smarter room and device integrations. These features were previously the domain of higher-end video conferencing rooms, but can now be brought to every room and every team. And when registered to Cisco Webex, additional cloud-based functionalities are enabled that enhance the user experience and team workflow as well as further simplifying deployment.

- Smart meetings: Powerful, integrated cameras deliver intelligent view capabilities, such as automatic framing and speaker tracking
- Smart presentations: Dual screens, dual content sources, wireless sharing, and 4K content make for great presentations
- Smart rooms: People count for usage metrics and resource allocation; tight integrations with screens for enhanced functionalities
- · Registration flexibility: Built for both cloud and on-premises deployment, protecting your investment

Cisco Webex Room Kit Plus Registration

License Level	Term
Cisco Webex Device Subscription	Monthly or 1-, 2-, 3-, 4-, or 5-year options

Product Specifications

Table 1. Specifications

Specification	Description	
Software compatibility	Cisco Collaboration Endpoint Software Version 9.0 or later, or Cisco Webex Room OS	
Default components in Cisco Webex Room Kit Plus	Cisco Webex Codec Plus Cisco Webex Quad Camera Cisco Touch 10 Wall mount for Quad Camera	
Optional hardware components	Table Microphone 20, Wall mount for Codec Plus, cables	
Bandwidth	Up to 6 Mbps point-to-point	
Minimum bandwidth for resolution/frame rate	H.264 • 720p30 from 768 kbps • 720p60 from 1152 kbps • 1080p30 from 1472 kbps • 1080p60 from 2560 kbps	
Firewall traversal	 Cisco Expressway[™] technology H.460.18, H.460.19 firewall traversal 	
Video standards • H.264, H.265		
Video inputs	 One HDMI input supports formats up to maximum 1080p60 Two HDMI inputs support formats up to maximum 4K (3840 x 2160) at 30 fps including HD1080p60 Consumer Electronics Control (CEC) 2.0 	
Video outputs	 Two HDMI outputs support formats up to 3840 x 2160p60 (4Kp60) Live video resolutions (encode and decode) up to 1920 x 1080p60 (HD1080p) Consumer Electronics Control (CEC) 2.0 	
Audio standards	• G.711, G.722, G.722.1, G.729, AAC-LD, and Opus	
Audio features	 High-quality 20 kHz audio Subwoofer line out for Quad Camera Prepared for inductive loop (line out) Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization 	
Audio inputs	Three microphones, 4-pin mini-jack Two audio in from HDMI	
Audio outputs (external)	 1 line out mini-jack (stereo) (Codec Plus) 1 RCA output for subwoofer (Quad Camera) 2 HDMI outputs HDMI input #1 supports Audio Return Channel (ARC): Audio output to Quad Camera speakers 	
Speakers (internal)	High-quality speakers Frequency response: 70 Hz to 20 kHz Max output level SPL 90dB	
Speaker tracking	6-element microphone array for accurate speaker tracking	
Dual stream	 H.239 (H.323) dual stream Binary Floor Control Protocol (BFCP) (SIP) dual stream Support resolutions up to 3840 x 2160p5 (4Kp5) and 1080p30 	

Specification	Description	
Wireless sharing	 Cisco Webex Teams app (up to 3840 x 2160p5) Cisco Intelligent Proximity client (up to 1920 x 1080p5) 	
Multipoint support	4-way embedded SIP/H.323 conferencing capability with MultiSite option	
MultiSite features (embedded multipoint) (optional upgrade)	 Adaptive SIP/H.323 MultiSite 3-way resolution up to 1080p30 + content up to 4Kp5 4-way resolution up to 720p30 + content up to 4Kp5 Full individual audio and video transcoding H.323/SIP/VoIP in the same conference Support for presentation (H.239/BFCP) from any participant at resolutions up to 3840 x 2160p5 Best Impression (automatic continuous presence layouts) Encryption and dual stream from any site 	
Protocols	H.323SIPCisco Webex	
Embedded encryption	 H.323 and SIP point-to-point Standards-based: H.235 v3 and Advanced Encryption Standard (AES) Automatic key generation and exchange 	
IP network features	 DNS lookup for service configuration Differentiated services (Quality of Service [QoS]) IP-adaptive bandwidth management (including flow control) Automatic gatekeeper discovery Dynamic playout and lip-sync buffering H.245 Dual-Tone Multi-frequency (DTMF) tones in H.323 RFC 4733 DTMF tones in SIP Date and time support using Network Time Protocol (NTP) Media adaption and resilience Uniform Resource Identifier (URI) dialing Dynamic Host Configuration Protocol (DHCP) 802.1X network authentication 802.1Q Virtual LAN 802.1p (QoS and Class of Service [CoS]) 	
Call Control	Cisco Unified Communications Manager (Unified CM) Native registration Unified CM Requires Unified CM Version 9.1(2) or later with device pack Room Kit Cisco Expressway Native registration with Expressway Cisco Webex Third-party H.323 Gatekeepers and standards-based SIP proxies	
IPv6 network support	 Single call stack support for both H.323 and SIP Dual-stack IPv4 and IPv6 for DHCP, SSH, HTTP, HTTPS, DNS, DiffServ Support for both static and automatic IP configuration (stateless address auto configuration) 	
Security features	 Management using HTTPS and SSH IP administration password Menu administration password Disable IP services Network settings protection 	

Specification	Description
Network interfaces codec medium	 One Ethernet (RJ-45) 10/100/1000 for LAN One Ethernet (RJ-45) 10/100/1000 for direct pairing with camera One Ethernet (RJ-45) 10/100/1000 with Power over Ethernet (PoE) for direct pairing with Touch 10 Wi-Fi 802.11a/b/g/n/ac 2.4 GHz/5 GHz for LAN. 2x2 MIMO Bluetooth 4.0 LE
Other interfaces	USB 2.0 port, uUSB, factory reset pinhole
Power supplies (2)	 100 to 240 VAC, 50/60 Hz, 12V DC input Average 20 W, peak 70W Quad camera must be used with power supply FSP FSP070-AHAN2 or AcBel ADF019
Operating temperature and humidity	 0°C to 35°C (32°F to 95°F) ambient temperature 10% to 90% Relative Humidity (RH)
Storage and transport temperature	• -20°C to 60°C (-4°F to 140°F) at RH 10% to 90% (noncondensing)
Locking mechanism	Kensington security lock
Dimensions	• Quad Camera: • Width: 37.4 in. (95.0 cm) • Height: 4.7 in. (12.0 cm) • Depth: 4.0 in. (10.3 cm) • Weight: 10.6 lb. (4.8 kg) • Codec Plus: • Width: 14.1 in. (35.9 cm) • Height: 1.7 in. (4.3 cm) • Depth: 5.6 in. (14.3 cm) • Weight: 3.9 lb. (1.77 kg)
Camera overview	 5K Ultra HD camera Support up to 60 fps 15.1 MP image sensor 1/1.7 CMOS 5x digital zoom (3 tele-lenses each with 50° horizontal field of view) f/2.0 aperture 83° horizontal field of view; 51.5° vertical field of view Auto-framing (audio + face detect) 5120 x 2880 pixel resolution Auto focus, brightness, and white balance Focus distance 1 m to infinity

Regulatory Compliance

- Directive 2014/35/EU (Low-Voltage Directive)
- Directive 2014/30/EU (EMC Directive) Class A
- Directive 2014/53/EU (Radio Equipment Directive)
- Directive 2011/65/EU (RoHS)
- Directive 2002/96/EC (WEEE)
- NRTL approved (Product Safety)
- FCC CFR 47 Part 15B (EMC) Class A

Please check the Product Approval Status Database at https://www.ciscofax.com/ for approval documents per country.

Ordering Information

To place an order, please contact your local Cisco representative and refer to Table 2.

 Table 2.
 Ordering Information

Product Name	Part Number	Compliance Model Number
Cisco Webex Room Kit Plus – Subscription pricing (MSRP')) Cisco Webex Codec Plus Cisco Webex Quad Camera Cisco Touch 10 Control Unit Cisco Webex Service	CS-KITPLUS-MSRP-K9 CS-CODEC-PLUS+ CS-QUADCAM+ CTS-CTRL-DVX-10 A-SPK-SH-RMK (A-SPK-SH)	TTC7-25 TTC8-10 TTC5-09
Cisco Webex Room Kit Plus – Upfront pricing (GPL**) Cisco Webex Codec Plus Cisco Webex Quad Camera Cisco Touch 10 Control Unit	CS-KITPLUS-K9 CS-CODEC-PLUS+ CS-QUADCAM+ CTS-CTRL-DVX-10	TTC7-25 TTC8-10 TTC5-09
Cisco Webex Room Kit Plus – NO RADIO Cisco Webex Codec Plus – NO RADIO Cisco Webex Quad Camera Cisco Touch 10 Control Unit	CS-KITPLUS-NR-K9 CS-CODEC-PLUS-NR+ CS-QUADCAM+ CTS-CTRL-DVX-10	TTC7-25 TTC8-10 TTC5-09
Cisco Webex Room Kit Plus – NO CRYPTO Cisco Webex Codec Plus Cisco Webex Quad Camera Cisco Touch 10 Control Unit	CS-KITPLUS-K7 CS-CODEC-PL-NR-K7+ CS-QUADCAM+ CTS-CTRL-DVX-10	TTC7-25 TTC8-10 TTC5-09
Cisco Webex Room Kit Plus – TAA compliant Cisco Webex Codec Plus – TAA, NO RADIO, or Cisco Webex Codec Plus – TAA Cisco Webex Quad Camera Cisco Touch 10 Control Unit	CS-KITPLUS-K9++ CS-CODEC-PLUS-NR++ CS-CODEC-PLUS++ CS-QUADCAM+ CTS-CTRL-DVX-10	TTC7-25 TTC7-25 TTC8-10 TTC5-09
Options		
Cisco Table Microphone 20	CTS-MIC-TABL20	
Extension cable for Table Microphone 20	CAB-MIC20-EXT	
Cisco Ceiling Microphone	CTS-MIC-CLNG-G2	
Shielded cable for Ceiling Mic (non-plenum rated)	CAB-ETHRSHLD-10M	
Wall Mount Kit for Codec Medium	CS-KITPLUS-WMK	
8 m HDMI 2.0 certified cable	CAB-PRES-2HDMI-GR	
HDMI 2.0 cable 1.5 m/5 ft, gray	CAB-2HDMI-1.5M-GR	

Product Name	Part Number	Compliance Model Number
HDMI 2.0 cable 3 m/10 ft, gray	CAB-2HDMI-3M-GR	
Ethernet cable 1.5 m/5 ft, gray	CAB-ETH-1.5M-GR	
Ethernet cable 3 m/10 ft, gray	CAB-ETH-3M-GR	
Ethernet cable 5 m/16.4 ft, gray	CAB-ETH-5M-GR	
Software options – ordered separately		
Remote Monitoring	L-ROOM-RM (L-TP-RM)	
MultiSite (embedded multipoint)	L-KITPLUS-MS (L-ROOM-PAK)	
Spares		
Cisco Webex Codec Plus	CS-CODEC-PLUS=	
Cisco Webex Codec Plus - no radio, no crypto	CS-CODEC-PL-NR-K7=	
Cisco Webex Codec Plus - no radio	CS-CODEC-PLUS-NR=	
Cisco Webex Quad Camera	CS-QUADCAM=	
Power supply 12VDC 70W	PSU-12VDC-70W-GR=	

^{*} MSRP = Manufacturer's Suggested Retail Price

Warranty Information

Cisco Webex Room Kit Plus has a 90-day limited liability warranty.

Cisco Services and Support

Cisco and our partners provide a broad portfolio of smart, personalized services and support that can help you realize the full business value of your Cisco collaboration investment by increasing business agility and network availability. This portfolio of services accelerates business innovation by harnessing the network as a powerful business platform. For more information about these services, please visit: https://www.cisco.com/go/collaborationservices.

Cisco Capital

Financing to help you achieve your objectives

Cisco Capital® can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. Learn more.

Custom Call to Action

- Learn more about Cisco Webex Room Kit Plus.
- Download the Cisco Webex Teams app.

[&]quot;GPL = Global Price List

cisco.

Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore

Europe Headquarters
Cisco Systems International RV

Cisco Systems International BV Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at https://www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA C78-738752-05 05/18