

Subduction plate interface shear stress associated with rapid subduction at deep slow earthquake depths: example from the Sanbagawa belt, Southwest Japan

Yukinojo Koyama¹, Simon R. Wallis¹, Takayoshi Nagaya²

¹Department of Earth and Planetary Science, The University of Tokyo, Tokyo, 113-0032, Japan

²Department of Environmental Science, Tokyo Gakugei University, Tokyo, 184-8501, Japan

Correspondence to: Yukinojo Koyama (koyamanojo@g.ecc.u-tokyo.ac.jp), Simon R. Wallis (swallis@eps.s.u-tokyo.ac.jp), Takayoshi Nagaya (tnagaya@u-gakugei.ac.jp)

Abstract. ~~Absolute maximum~~ Maximum shear stress (~~“shear stress” in this study~~) along the active deformation zone marking the subduction plate interface is important for understanding earthquake phenomena and is an important input parameter in subduction zone thermomechanical modelling. However, such maximum shear stress is difficult to measure directly at depths more than a few kilometers and is generally estimated by simulation using a range of input parameters with large associated uncertainties. In addition, estimated values generally represent maximum shear stress conditions over short observation timescales, which may not be directly applicable to long-timescale subduction zone modelling. Rocks originally located deep in subduction zones can record information about deformation processes, ~~such as including maximum~~ including maximum shear stress conditions, occurring in regions that cannot be directly accessed. The estimated maximum shear stress is likely to be representative of maximum shear stress experienced over geological timescales and be suitable to use in subduction zone modelling over time scales of millions to tens of millions of years. In this study, we estimated maximum shear stress along a subduction plate interface by using samples from the Sanbagawa metamorphic belt of Southwest (SW) Japan, in which slivers of mantle wedge-derived serpentinite are widely distributed and in direct contact with metasedimentary rocks derived from the subducted oceanic plate. These areas can be related to the zone of active deformation along the ancient subduction plate interface.

To obtain estimates of maximum shear stress at the subduction interface, we focused on the microstructure of quartz-rich metamorphic rocks—quartz is the main component of the rocks we collected and its deformation stress is assumed to be ~~representative of the region roughly representative of the stress experienced by the surrounding rock and plate interface~~ representative of the region deformation zone. ~~Maximum s~~ Shear stress was calculated by applying deformation temperatures estimated by the crystallographic orientation of quartz (the quartz c-axis fabric opening-angle thermometer), and the apparent grain size of dynamically recrystallized quartz in a thin section to an appropriate piezometer. Combined with information on sample deformation depth, estimated from P (pressure)–T (temperature) path and deformation temperatures, it is suggested that there was nearly constant maximum shear stress of 16–41 MPa in the depth range ~~about 17–27~~ 15–30 km, assuming plane stress conditions even when uncertainties related to measurement direction of thin section and piezometer differences are included.

The Sanbagawa belt formed ~~in~~ in a warm subduction zone. Deep slow earthquakes are commonly observed in modern-day warm subduction zones such as SW Japan, which has a similar thermal structure to the Sanbagawa belt. In addition, deep slow

earthquakes are commonly observed to be concentrated in a domain under the shallow part of the mantle wedge. Samples
35 showed the depth conditions near the mantle wedge, suggesting that these samples were formed in a region with features
similar to the deep slow earthquakes domain. Estimated maximum shear stress may not only be useful to long-timescale
subduction zone modelling but also represent the initial conditions from which slow earthquakes in the same domain nucleated.

1 Introduction

Knowledge about the distribution and values of absolute-maximum shear stress (~~“shear stress” in this study~~) along the active
40 zone of deformation along the subduction plate interface (plate interface in this paper) is fundamental to understanding seismic
phenomena and the thermal evolution of subduction zones: earthquakes along the plate interface occur when the shear stress
on a fault plane exceeds the shear strength (e.g., Vavryčuk, 2015), and frictional heating increases with increasing maximum
shear stress, which can significantly affect the thermal structure of subduction zones (e.g., Ishii and Wallis, 2020). Recently,
it has also been suggested that for the same material and fault plane, the initial maximum shear stress values significantly affect
45 slip rates, rupture rates, and stress drop values (Passelègue et al., 2020).

However, direct measurement of maximum shear stress at plate interfaces is difficult and the associated strength along the
subduction plate interface is not well known. Estimates of maximum shear stress can be obtained by direct measurement of
borehole breakouts and drilling-induced tensile fractures (e.g., Chang et al., 2010; Lin, 2014). However, such techniques are
limited to relatively shallow areas with depths of up to a few kilometers. At greater depths, friction coefficients (shear
50 strength) and maximum shear stress have been estimated from subduction plate interface simulation using surface heat flow,
friction law, and flow law combined with thermal modeling (e.g., Gao and Wang, 2014; England, 2018). A difficulty
encountered when using surface heat flow is its strong local scatter due to bottom water temperature variations, the influence
of localized fluid flow, and other upper crustal processes (e.g., Gao and Wang, 2014; England, 2018; Ishii and Wallis, 2020).
As an example, Gao and Wang (2014) modelled maximum shear stress along the Kamchatka subduction plate interface and
55 concluded that the average effective coefficient of friction lies within the range 0.03–0.09 with the uncertainties largely due to
the large scatter in the heat flow values related to variations in bottom water temperature. The uncertainties yield a
correspondingly large range in estimates for the maximum estimated maximum shear stress is about double the minimum
estimated value (Fig. S4 in Gao and Wang, 2014). In addition, features such as the thickness of the ~~actively-deforming~~ plate
interface and the parameters that make up the flow law are generally not well constrained and these also affect the results.

60 These issues can lead to order of magnitude uncertainties in estimates of maximum shear stress and strength. Stress inversion
using seismic data has also been used to estimate the strength of the subduction boundary and the surrounding crust (e.g.,
Yoshida et al., 2015). However, this approach is limited to the brittle deformation domain and it is difficult to obtain values
for absolute stress. A further issue is that any stresses obtained from the above approaches are only representative of the
observation period. When stresses are used in a model, ideally, they should be estimated on a time scale appropriate for the
65 phenomenon being examined. However, the time scales of observation and the modelled phenomena are commonly very

different. For instance, stresses estimated from seismic data represent several orders of magnitude shorter time scales than the thermal evolution of a subduction zone which develops over time scales of millions to several tens of millions of years.

The study of rocks that were once distributed along the plate interface is one of the key ways to obtain information along deeper inaccessible parts of subduction zones. The most reliable and widely used differential (maximum shear) stress indicator in such rocks is based on grain size measurements and this technique is referred to as piezometry (e.g., Twiss, 1977; Twiss, 1980; Derby, 1991; Stipp and Tullis, 2003; Shimizu, 2008; Shimizu, 2012; Cross et al., 2017; Goddard et al., 2020). The relationships used in such piezometry express the dynamically recrystallized grain size of a particular mineral as a function of deformation temperature and applied differential stress. Differential stress is the cause of non-volumetric strain and is defined as the difference between the greatest and least principal stress. Maximum shear stress is equal to half the differential stress.

Most piezometers are calibrated based on deformation experiments that use uniaxial compressive stress states. However, most naturally deformed rocks show approximately plane strain suggesting deformation under plane stress conditions. Maximum shear stress required to deform a material under uniaxial conditions can be converted to the maximum shear stress required under plane stress conditions using properties of the deviatoric stress tensor (see Appendix B).

~~Taking a broad range in possible widths for the subduction channel of 100 m–10 km, and a representative subduction rate of 3 cm per year due to plate motion causing simple shear throughout the subduction channel, the calculated strain rate is 10^{-13} – 10^{-11} s⁻¹. If it is assumed that the plate motion causes the material in the plate boundary region to deform by simple shear, and the thickness of the subduction zone is w (we assumed 100 m to 10 km) and the subduction rate is v (we assumed 3 cm per year), then the strain rate of rocks along the subduction interface can be calculated as $v/w = 10^{-13}$ s⁻¹ to 10^{-11} s⁻¹.~~ Dynamic recrystallization requires strains of at least 0.2 (e.g., Stipp and Tullis, 2003). In this situation, the time required for dynamic recrystallization is about 0.01–1 million years. Therefore, obtained stress values can be regarded as representative of the stress state over a period of at least 0.01–1 million years and are more appropriate for considering the geological timescale evolution of subduction zones compared with stress values obtained by drilling or thermal observations.

In this study, we applied piezometers to dynamically recrystallized quartz grains observed in rocks (quartz, pelitic, and psammitic schist) of the subduction-type Sanbagawa belt in SW Japan to estimate differential (maximum shear) stress along the subduction zone plate interface. In the Sanbagawa belt, slivers and blocks of mantle wedge-derived serpentinite are widely distributed and in direct contact with sedimentary rocks derived from the subducted oceanic plate. These areas can be related to an ancient subduction plate interface (Aoya et al., 2013a). We found that there was no clear correlation between the deformation depth and differential (maximum shear) stress in the depth range of 17–27 km along the subduction zone plate interface, and differential (maximum shear) stress at this depth range was almost constant. This result contrasts with a previous study (Takeshita, 2021), which proposes a trend of decreasing differential stress with increasing metamorphic temperature and pressure. This difference may be due to the fact that Takeshita (2021) did not consider the temperature dependence in the piezometer. This temperature dependence reflects a balance between recrystallized grain nucleation and migration of grain boundaries. We estimated deformation temperatures using an empirical relationship between quartz c-axes orientation patterns and deformation temperatures, and selected samples appropriate for discussions of the deformation on the subduction plate

100 interface. In this study, we focus on the relationship between the differential (and maximum shear) stress and the stress state along the subduction plate interface. This is also in contrast to Takeshita (2021) who focuses on the relationship between the obtained stress values and exhumation processes.

Our study shows that the Sanbagawa belt is not only useful to long-timescale subduction zone modelling but also suitable to study deep slow earthquakes and the estimated differential (maximum shear) stress likely represents the initial conditions under which slow earthquakes in the same domain nucleated.

2 Geological setting Method

2.1 The Sanbagawa belt

The Sanbagawa belt is a belt of high-P subduction-type metamorphism developed in the eastern Asian convergent margin during the Cretaceous (Isozaki and Itaya, 1990; Wallis et al., 2009) and is now exposed over a distance of about 800 km from east to west in Southwest (SW) Japan. The widest range of metamorphic conditions is shown by rocks in central Shikoku and this area was chosen for more detailed study (Fig. 1a). The Sanbagawa belt is bounded to the north by a major tectonic discontinuity, the Median Tectonic Line (MTL) and in central Shikoku the southern boundary of the Sanbagawa belt is marked by the presence of significantly older units, the Kinouzu (psammitic schist, pelitic schist, quartz schist, calcareous schist, and mafic schist; Aoya et al., 2013b; Endo and Yokoyama, 2019) and Mikabu units (metachert, metabasalt, metagabbro, volcaniclastic rock, and ultramafic rocks; Aoya et al., 2013b; Endo and Yokoyama, 2019), (the Kinouzu and Mikabu units) which have undergone the Sanbagawa metamorphism but represent a tectonically distinct structurally overlying domain and interpreted as part of the original hanging wall to the Sanbagawa subduction complex (Endo and Wallis, 2017).

Three distinct geological units can be defined within the Sanbagawa belt of central Shikoku. The Eclogite unit (pelitic schist, quartz schist, mafic schist, marble, pelitic-psammitic gneiss, siliceous gneiss, mafic gneiss, metagabbro, diopside hornblende rock, and ultramafic rocks; Aoya et al., 2013b; Endo and Yokoyama, 2019) is located at the highest structural level (Aoya et al., 2013a) and underwent eclogite facies metamorphism at 89–88 Ma (Wallis et al., 2009). Parts of this unit are distinctly coarser grained and show early Cretaceous (about 120 Ma) metamorphic ages (Okamoto et al., 2004; Endo et al., 2009). The Shirataki unit (pelitic schist, psammitic schist, quartz schist, mafic schist, metagabbro, and ultramafic rocks; Aoya et al., 2013b; Endo and Yokoyama, 2019), the subject of this study, structurally underlies the eclogite unit. Buoyancy-driven rise of the eclogite unit within the subduction boundary domain is thought to have emplaced it above the Shirataki unit (Aoya, 2001; Endo et al., 2012; Aoya and Endo, 2017). ~~After the amalgamation of the Eclogite and Shirataki units, they both underwent a distinct phase of metamorphism at 89–85 Ma (Endo et al., 2012), which overprints the eclogite metamorphism and is referred to here as the main metamorphism.~~ After the Eclogite unit was juxtaposed with the subducting Shirataki unit within the subduction boundary, they underwent the same metamorphism at 89 to 85 Ma (Endo et al., 2012). This metamorphism ~~overprints the eclogite metamorphism and is referred to as the main metamorphic stage.~~ The Oboke unit (psammitic schist and pelitic schist; Aoya et al., 2013b; Endo and Yokoyama, 2019) represents the lowest structural level of the Sanbagawa

metamorphic belt and consists dominantly of pelitic and psammitic schists. The Shirataki unit has been thrust over the Oboke unit (Wallis, 1998).

The main metamorphism is divided into four metamorphic grades (Fig. 1). As a result of the main metamorphic stage, we can identify four metamorphic zones based on constituent minerals in metapelite (Higashino, 1990; Fig. 1a). These mineral zones can be related to the depth to which the metamorphism occurred, based on constituent minerals in metapelite (Higashino, 1990). In order of increasing grade and their estimated peak metamorphic temperature T and pressure P , these zones are: the chlorite zone ($<360^{\circ}\text{C}$, $0.5\text{--}0.6\text{ GPa}$); garnet zone ($440\pm 15^{\circ}\text{C}$, $0.7\text{--}0.8\text{ GPa}$); albite-biotite zone ($520\pm 25^{\circ}\text{C}$, $0.8\text{--}0.9\text{ GPa}$); and oligoclase-biotite zone ($610\pm 20^{\circ}\text{C}$, $0.9\text{--}1.1\text{ GPa}$) (Enami et al., 1994; Fig. 2a). The metamorphic zones are generally E–W oriented, with the highest metamorphic temperature and pressure conditions generally found at the highest structural levels. In central Shikoku, the isograds have been tightly folded (e.g., Wallis et al., 1992; Mori and Wallis, 2010; Kouketsu et al., 2021), and the highest-grade units are locally found at intermediate structural levels, from which the temperature and pressure conditions decrease both to the north and south (Fig. 1). The deformation that caused this This recumbent folding occurred formed by deformation after the peak of the main metamorphic stages is referred to as Ds following Wallis (1990) and is described in more detail below.

2.2 Deformation of Shirataki unit during the main metamorphic stages

In this study, our main focus is the ductile deformation in the Shirataki unit. The Shirataki unit is composed of subducted oceanic crust with basalt, chert, sandstone, and mudstone metamorphosed into basic (mafic (basic)), quartz, psammitic, and pelitic




Figure 1: Location, geological units, and metamorphic zonation map of the Sanbagawa metamorphic belt in central Shikoku (after Kouketsu et al., 2021; Aoya et al., 2013b; Endo et al., 2018; Higashino, 1990). (b) Geological map of shirataki unit (after Endo and Yokoyama, 2019; Hara et al., 2018).

書式を変更: フォントの色: 赤

書式変更: 左揃え

書式を変更: フォント: (日) MS 明朝, (言語 1) 日本語

types of schist (Mori and Wallis, 2010; Fig. 1b; Fig. 3). There are also rare but widely dispersed ultramafic bodies (Fig. 1b; Fig. 3), derived from the mantle wedge (Fig. 3). Ultramafic bodies are mantle wedge-derived rock bodies and differ in origin from schist derived from subducted material. It is suggested that the rocks of garnet to oligoclase-biotite zone were subducted to depths below the Moho boundary and the hanging-wall mantle became tectonically entrained in these rocks (Aoya et al., 2013a).

The main metamorphism that formed the Shirataki unit has four recognized ductile deformation phases, named Dr, Ds, Dt, and Du deformation, respectively (Wallis, 1990; Fig. 2b, 2c). Each of the four metamorphic zones formed by the main metamorphic stage has a distinct P (pressure)-T (temperature) path (Fig. 2a). Moreover, the rocks in all metamorphic zones show evidence for four phases of ductile deformation, named Dr (burial), Ds (exhumation starting at near the peak metamorphic conditions), Dt (exhumation after the peak metamorphic condition), and Du (slight burial after exhumation) deformation, respectively (Wallis, 1990; Fig. 2b, 2c). Dt and Du are non-penetrative and it is unlikely they had a major influence on exhumation or burial. Dr deformation is locally the main deformation phase, particularly in the high temperature-pressure zone (i.e., oligoclase-biotite zone), but in most cases, the main high strain major deformation structures are due to Ds deformation, and Dr deformation is preserved mainly as inclusion trails in albite porphyroblasts representing a Sr foliation (Mori and Wallis, 2010) which has been strongly overprinted. Compositional zoning of amphibole in and outside the porphyroblasts indicates that the Dr deformation was formed during the subduction, burial phase (Wallis et al., 1992). The lack of compositional zoning of hornblende, barroisite, or glaucophane cores to actinolite-winchite rims for grains of amphibole contained in the core of the albite porphyroblasts (preserving Dr deformation features) in hematite-bearing metabasite indicates that the Dr deformation was formed during the burial phase related to subduction (Wallis et al., 1992). The Ds deformation is characterized by an overall gently north dipping Ss foliation, and a generally WNW-ESE oriented stretching direction (Aoya et al., 2013b; D1 and D2 deformation in Banno & Sakai, 1989; L1 lineation in Faure, 1985), which is highly oblique to the distribution of the Sanbagawa belt. The Ds deformation (D1 and D2 deformation in Banno and Sakai, 1989) is characterized by an overall gently north-dipping Ss foliation (Fig. 3; Aoya et al., 2013b), and a generally WNW-ESE oriented orogen oblique stretching lineation (Aoya et al., 2013b; L1 lineation in Banno and Sakai, 1989; Faure, 1985). The Ds deformation is considered to have occurred close to or shortly after




Figure 2: (a) Petrographically derived P-T conditions of the Sanbagawa metamorphic belt (black and white circles: Aoya et al., 2017). The thin dashed line represents subduction-boundary geotherm at c. 89 Ma from P-T estimates (Aoya and Endo, 2017; Aoya et al., 2017). The bold dashed line represents the inferred subduction-boundary geotherm for modern day SW Japan based on thermal modelling by Yoshioka and Murakami (2007) (b) Summary of deformation stages and their associated structures in the Shirataki unit based on Wallis et al. (1992) and Aoya (2001,

185

2002) modified by Kouketsu et al. (2021). (c) Main metamorphism P–T–D path of the Shirataki unit (Aoya, 2001) modified by Kouketsu et al. (2021). (c) Deformation phases in the Shirataki unit (after Kouketsu et al., 2021). This P–T path corresponds to each metamorphic zone P–T path in the main metamorphism in Fig. 2a.

the peak temperature condition because metamorphic isograd surfaces were folded in this phase (Kouketsu et al., 2021; including the recumbent fold described above). However, compositional changes of amphibole in the porphyroblasts and of Na-pyroxene in equilibrium with albite of the garnet zone suggest that part of the Ds deformation occurred during a pressure drop and temperature increase, i.e., before the peak metamorphic temperature was reached (Wallis et al., 1992; Enami et al., 1994). However, amphibole formed at highest temperatures (barroisite or hornblende) in the porphyroblasts rim (formed during Ds deformation), and compositional changes of Na-pyroxene in equilibrium with quartz and albite of the garnet zone suggest that part of the Ds deformation occurred during a pressure drop and temperature increase, i.e., before the peak metamorphic temperature was reached (Wallis et al., 1992; Enami et al., 1994). Dt and Du deformation are identified where the Ss foliation is folded (Wallis et al., 1992; Fig. 3). Both structures have E–W oriented fold axes, but the Dt deformation is distinguished by axial surfaces that dip gently to the north, while the Du deformation is distinguished by fold axial surfaces that are nearly vertical (Wallis, 1990; D3 folds in Banno and Sakai, 1989).

As mentioned above, when the Ds deformation occurred, the Sanbagawa belt was exhuming. However, the orogen-oblique stretching lineation of the Ds deformation is thought to reflect deformation closely related to rapid (24 cm/yr^{-1} ; Engebretson et al., 1985; Ishii and Wallis, 2020) and oblique subduction of the subducted Izanagi Plate (e.g., Wallis, 1992; Wallis et al., 2009). Moreover, if deformation of subducted sediments were driven by a combination of Couette flow (simple shear) driven by the subducting plate, and Poiseuille flow (channeled flow) driven by a pressure gradient produced by the buoyancy of the subducted sediment (e.g., Fig. 4 in Platt et al., 2018), it is possible that exhumation of these rocks is associated with stable subduction. In this case, what we observed can be the area close to the overriding plate within the plate boundary domain. In addition, Ds structures are also the most widely developed in the Sanbagawa belt (Fig. 3). Therefore, this study focuses on the deformation structures associated with Ds deformation to discuss the deformation along the subduction plate interface.

書式を変更: フォント: (英) Times New Roman, 太字 (なし), 英語 (英国)






Figure 3: Geological map, cross-section (after Endo and Yokoyama, 2019), metamorphic zonation of study area, with and sampling and data points of this study. (after Endo and Yokoyama, 2019).

3 Method

3.12.3 Sampling and preparation for analysis

Five samples were collected at four locations to obtain deformation information under a wide range of temperature and pressure conditions (Fig. 3: ASM1–5). ASM1 is a sample from deformed quartz veins, which are in psammitic schist and are oriented subparallel to the foliation, and samples ASM2–5 are from quartz schist. Samples strongly affected by Dt or Du deformation were not used in this study.

Samples were collected from quartz-rich metamorphic rocks (Fig. 3). The orientations of the Z-axes of finite strain were taken to be normal to the Ds foliation. The orientations of the X- and Y-axes were taken to lie within the Ds foliation, the X-axes were taken to be parallel to the Ds stretching lineation, and the Y-axes were taken to be perpendicular to the Ds stretching direction. Thin sections were prepared from chips cut parallel to the Z-axis and polished using a series of alundum types with decreasing grain sizes of #180 (about 80 μm), #320 (about 50 μm), #800 (about 20 μm), #2000 (about 7.5 μm), #3000 (about 5 μm) and a series of diamond pastes with grain sizes of 3, 1, and 1/4 μm . After this sequence of polishing, the thin sections were further treated with colloidal silica to remove the surface damage zone before they were suitable for electron backscatter diffraction (EBSD) measurements as discussed below. Each phase of polishing took 30–120 minutes, which depends on the surface condition of the thin section.

3.22.4 Differential (maximum shear) stress estimation

We estimated the differential (maximum shear) stress using piezometers based on the recrystallized grain size of quartz, which is the dominant mineral phase of the rocks examined. The following points were noted in the grain size measurements.

1. Quartz-only domains were selected for analysis as much as possible to remove the effects of grain growth inhibition by the presence of other minerals such as mica. In the thin sections used for the measurements, changes in grain size due to grain growth inhibition caused by the presence of other minerals was observed. When quartz-rich domains were compared there was no clear changes within a single thin section and the calculated grain size can be considered to be representative at least of the grain size in the thin section.
2. The general presence of well-developed foliation and stretching lineation in the region suggests that samples and selected microstructural domains deformed under conditions close to plane strain. To examine any potential sectioning effects, the grain size for individual samples was measured in both the XZ and YZ planes and treated as maximum and minimum grain sizes. When the Ds lineation is not well developed, the grain size was measured using a thin section oriented parallel to the Z-axis (PZ plane).

Grain size measurements of the samples were performed using W–SEM–EBSD and open-source MTEX toolbox for MATLAB (<http://mtex-toolbox.github.io/>). Crystallographic orientations were determined using W–SEM equipped with an EBSD system


書式変更: フォント: 太字 (なし), 英語 (英国)


書式変更: 見出し1

(JEOL JSM-6510LV with Oxford HKL Channel5) at the University of Tokyo. In the W-SEM, the load current was 73–107 μA . The W-SEM magnification during observation and measurement was kept to $\times 40$. A step size of $1\ \mu\text{m}$ was used for mapping. HKL database from Sands (1969) was used for the quartz EBSD indexing. Other analytical conditions followed Nagaya et al. (2022). The grain boundaries were constructed from EBSD crystallographic orientation data using a Voronoi decomposition algorithm (Bachmann et al., 2011) implemented within the MTEX toolbox, and grain size distribution was calculated by measuring the area of each grain and converting it to the diameter of a circle with the same area (Fig. 4). A Matlab script provided by Cross et al. (2017) was used in the analysis; this script defines grain boundaries where the misorientation angle is $>10^\circ$ and RMS grain size is used to represent the average grain size.

Recrystallized grains in natural rocks can be produced by three mechanisms: bulging (BLG), subgrain rotation (SGR), and grain boundary migration (GBM or a combination of SGR+GBM) (Stipp et al., 2002; Shimizu, 2008). BLG and SGR form new dynamically recrystallized grains; GBM is a mechanism where energetically stable particles consume unstable particles by grain boundary migration.

Recrystallized grains formed by bulging (BLG) or subgrain rotation (SGR) (Stipp et al., 2002; Shimizu, 2008) BLG or SGR are derived from initial usually larger grains and some of these grains may still be present in the microstructure. To apply the piezometer selected in this study it is necessary to filter these relict grains. This filtering was performed following the method of Cross et al. (2017). The grain size was then calculated and applied to “EBSD $1\ \mu\text{m}$ RMS piezometer” of Cross et al. (2017) to estimate differential (shear) stress, which is the empirical relationship between





265 **Figure 4: Summary of the method used to determine grain boundaries and grain size distribution. (a) Crystallographic orientations measured by W-SEM-EBSD (Inverse pole figure map) and (b) the corresponding inverse pole figure. \odot shows the observation direction of the crystallographic orientation (perpendicular to the paper). [0001] indicates the direction of the c-axis. (c) Grain boundaries were determined using a critical misorientation angle. Grains that did not interest the map border were used for the grain size calculation. (d) Grain size distribution derived from image (c).**

275 the Root mean square (RMS) grain size formed by BLG or SGR and applied differential stress. Uncertainties of estimated differential (shear) stress are related to both the piezometer and the grain size measurement (Appendix C). In this study, the same procedure was also applied to microstructures formed by grain boundary migration (GBM in Stipp et al., 2002; SGR+GBM in Shimizu, 2008). SGR+GBM. These grains filtered by Cross et al. (2017) are relatively unaffected by GBM and can be regarded as formed by SGR, indicating that the application of the Cross et al. (2017) piezometer is reasonable. We also used the piezometer of Cross et al. (2017) with a correction for measured values by Griggs apparatus, which is proposed by Holyoke and Kronenberg (2010). In this case, the stress value is 0.73 times the value obtained by piezometer of Cross et al. (2017).

280 The domains consisting of recrystallized grains formed by SGR+GBM comprise a steady-state microstructure and are formed by one deformation stage. This type of microstructure is suitable for using the α -quartz piezometer of Shimizu (2012), in which the relationship between the grain size of microstructures formed by SGR+GBM and applied differential stress is theoretically considered. To calculate grain size, the Matlab script provided by Cross et al. (2017) was revised following the definition of Shimizu (2012), in which boundaries where the misorientation angle is $>12^\circ$ was used to define grain boundaries,

285 and the mode of the logarithmic grain size was used to represent the grain size. No grain filtering was performed. The piezometer of Shimizu (2012) includes a temperature dependency, and deformation temperatures derived from quartz c-axes fabric opening-angle thermometry (Sect. 2.5) was also applied. The uncertainties by the piezometer of Shimizu (2012) are not shown. Therefore, uncertainties of estimated differential (maximum shear) stresses are only related to grain size measurement and deformation temperature (Appendix D).

290 **3.32.5 Deformation temperature estimation by quartz c-axes fabric opening-angle thermometer**

When the c-axis orientations of quartz aggregates deformed by high-strain dislocation creep are projected onto a Schmidt net stereonet, they commonly show strong preferred orientation patterns also known as fabric patterns (Fig. 5a). An opening-angle (OA) between the peripheral legs of such fabric patterns can be defined for many samples deformed at medium temperatures (Fig. 5b). There is a nearly linear relationship between the OA of quartz fabrics formed by plane strain and the associated metamorphic temperatures estimated by petrological geothermometers from greenschist to granulite facies (Kruhl, 1998; Morgan and Law, 2004). In this study, the relationships presented in Fig. 2 of Law (2014) were used to estimate the deformation temperature. ~~As with the data used in Law (2014), only quartz grains produced by dynamic recrystallization were used, and the 3D strain patterns were also classified.~~ The relationships shown in Law (2014) indicate a 50° OA is equivalent to a deformation temperature of 400°C and a 1° increase/ (decrease) in OA represents an 8°C increase/ (decrease) in the deformation temperature. As with the data used in Law (2014), only quartz grains produced by dynamic recrystallization were used, and the 3D strain patterns were also classified.

300 For the samples with a well-defined Ds stretching lineation, the c-axis orientations of quartz grains were obtained by W-SEM-EBSD from thin sections parallel to XZ planes. When the Ds lineation is not observed in the sample, thin sections parallel to the Z axis (PZ plane) were used. Analytical conditions were the same as for the grain size determination, except the step size which was 5 μm for microstructures formed by SGR or SGR+GBM and 1 μm for microstructures formed by BLG. When analyzing microstructures formed by BLG or SGR, newly recrystallized grains were selected using the method of Cross et al. (2017), and the mean orientations of the c-axes of each selected grain were plotted in a Schmidt net using MTEX. When analyzing microstructures formed by SGR+GBM, all grains were plotted. Well-formed fabric patterns indicate that the selected grains were formed by a single deformation stage.

書式変更: インデント: 最初の行: 0.5 字




Figure 5:- (a) Crvstallographic orientations (c-axes) projected onto a Schmidt net (c-axis fabric pattern) (b) Definition of OA. The dark regions correspond to high concentrations of quartz c-axes plotted on the Schmidt net. The left figure shows crossed girdle and the right figure shows a small girdle.

4.3 Results

Five samples were collected at four locations to obtain deformation information under a wide range of temperature and pressure conditions (Fig. 3). Samples strongly affected by Dt or Du deformation were not used in this study. Sample ASM1b is from a deformed quartz vein, which is part of a vein set developed in psammitic schist. The veins are oriented subparallel to the foliation (Fig. 6a). Sample ASM1a is from pelitic schist, and samples ASM2–5 are from quartz schist. The sites where sample ASM2-5 were collected are covered by vegetation and the outcrops are not well exposed (Fig. S1). Psammitic schist and pelitic schist consist mainly of quartz, calcite, albite, phengite (Radvanec et al., 1994), chlorite, and graphite. Quartz schist consists mainly of quartz, phengite (Radvanec et al., 1994), albite, piemontite, garnet, ilmenite, and rutile.

The Ds foliation and stretching lineation of psammitic and pelitic schist around sample ASM1 is defined by pressure solution seams consisting of phengite, chlorite, and graphite and quartz strain fringes developed around pyrite—observed in the surrounding area (Fig. 3; Fig. 7a). The orientation of the strain fringes in sample ASM1a shows an NWNWNW–ESE oriented finite stretching and their asymmetry indicates a top to west shear sense (Fig. 7a), both both consistent with the characteristics of Ds (Wallis, 1992). Sample ASM1b was collected from quartz veins oriented subparallel to the Ds foliation. Quartz grains

330 in sample ASM1 are also elongated in an NWNWNW-ESE direction (Fig. 6b; Fig. 7), consistent with the characteristics of Ds deformation. Both sample ASM1a (quartz fringe) and sample ASM1b (quartz vein) exhibit wavy extinction, and observation under the optical microscope, mis2mean maps, and kernel average misorientation (KAM) maps all show large grains were recrystallized into multiple finer subgrains (Fig. 7a; Fig. 7b; Fig. S2-4). These quartz grains exhibit wavy extinction, and some of them show segregation into multiple finer grains with homogeneous grain sizes (Fig. 6b). These microstructural features are evidence of dislocation creep and dynamic recrystallization by SGR (Stipp et al., 2002). Quartz grains in microlithon domain become finer due to grain growth inhibition by different minerals such as phyllosilicates (Fig. 7a).

335 In sample ASM2, phyllosilicate minerals with a platy shape are strongly aligned and form a well-defined Ds foliation (Fig. 76d). A thin section parallel to the foliation shows that quartz, phengite and opaque minerals are elongated or aligned defining a Ds mineral lineation (Fig. 76c). Quartz grains exhibit wavy extinction, amoeboid grain boundaries, and irregular grain sizes (Fig. 76d). Moreover, mis2mean map, and KAM map show large grains were recrystallized into multiple finer subgrains (Fig. 340 S5, S6). These microstructural characteristics indicate the action of dislocation creep and dynamic recrystallization: GBM of Stipp et al. (2002) or SGR+GBM of Shimizu (2008).

345 Samples ASM3 and 4 were collected from the albite-biotite zone. Phyllosilicate minerals are strongly aligned and form a well-defined Ds foliation (Fig. 76e, 76f). However, a clear Ds stretching lineation is not observed. Quartz grains exhibit microstructures characteristic of dislocation creep and dynamic recrystallization, ASM3 with SGR+GBM (Fig. 76e; Fig. S6) and ASM4 with SGR (Fig. 6f; Fig. 7f; Fig. S7). In sample ASM2-4, albite includes traces of a Dr foliation oblique to the external Ds foliation which is partly defined by the alignment of phengite. These observations suggest that both albite and phengite were formed before or synchronously with Ds, the timing of quartz deformation. This implies that albite and phengite have both been deformed along with the quartz.

350 Sample ASM5 was collected from the albite-biotite zone. In this sample, an SC' shear band structure is observed (Fig. 76g, 76h). In the quartz domain wavy extinction is observed, and both bulges and recrystallized grains are present along grain boundaries. These microstructural characteristics indicate the action of dislocation creep and dynamic recrystallization: BLG of Stipp et al. (2002). However, mis2mean map, and KAM map show large grains were partly recrystallized into multiple finer subgrains (Fig. S8), indicating SGR is also occurred.

355 The results of observation and analyses are summarized in Table 1. Sample ASM2-5 showed a clear fabric pattern and an OA was measured (Fig. 8g; Fig. S2-S8Fig-7). Estimated deformation temperatures are shown in Table 2. Grain boundary maps and the grain size distributions used for calculating differential stress are shown (Fig. 8e, 8f, 8h, 8i, 8j; Fig. S2-S8). Differential stress in both uniaxial and plane stress conditions (Appendix B) results are also listed in Table 23 (Uncertainties are shown in Fig. 129 and 142).

書式変更: インデント: 最初の行: 0 字

書式変更: インデント: 最初の行: 0 字





Fig. 6 (a) Outcrop photo showing foliation-subparallel veins (black arrows) in psammitic schist. Both foliation and veins were folded by later deformation (Du), but partly preserved unfolded structure, in which we collected sample ASM1b. (b) Microstructure of quartz vein (sample ASM1b). Large fibrous quartz grains that are elongated parallel to lineation and small recrystallized quartz grains were observed. XZ plane. Crossed nicols.

書式変更: インデント: 最初の行: 0.5 字

書式変更: インデント: 最初の行: 0 字






Figure 76: E and W indicate the eastern and western sides of the thin section. Except for (c) and (e), the up direction on the page corresponds to the up direction in the field. (a) Pelitic schist close to sample ASM1a. XZ plane. Crossed nicols. (b) Sample ASM1b. XZ plane. Crossed nicols. (c) Sample ASM2. XY plane. Opened nicols. Elongated phengite and quartz form weak lineation (arrow direction). (d) Sample ASM2 XZ plane. Crossed nicols. (e) Sample ASM3. PZ plane. Crossed nicols. (f) Sample ASM4. PZ plane. Crossed nicols. (g, h) Sample ASM5. PZ plane. (g) Opened nicols. (h) Crossed nicols.

書式変更: 中央挿え




Figure 7: Collected quartz c-axis fabric pattern and measured OA. ASM2: 5001 grains; ASM3: 1840 grains; ASM4: 2097 grains; ASM5: 1511 grains.




Figure 8: Sample ASM2 XZ. (a) Polarising microscope image (crossed nicols) and (b) inverse pole figure (IPF) map. Quartz grains exhibit wavy extinction, amoeboid grain boundaries, and irregular grain sizes. Both (c) mis2mean map (d) kernel average misorientation (KAM) map show large grains that were recrystallized into multiple finer subgrains. These microstructural characteristics indicate dynamic recrystallization by GBM (SGR+GBM). (e) Grain boundary map for the piezometer of Shimizu (2012). (f) Grain boundary map for the piezometer of Cross et al. (2017). (g) Crystallographic orientations and measured OA. (h) Grain size histogram and (i) probability distribution for the piezometer of Shimizu (2012). (j) Grain size histogram for the piezometer of Cross et al. (2017).

書式を変更: フォント: (日) MS 明朝, (言語 1) 日本語

書式変更: 中央揃え

Table 1—Observation and analysis results

| Metamorphic zonation | Sample name | Mineral assemblage | Lineation | Foliation | Recrystallization mechanism | Fabric Pattern | O A | RMS grain size ($10^{\times}(\mu\text{m})$, range: 2σ) | Mode of logarithmic grain size ($10^{\times}(\mu\text{m})$, range: 2σ) | |
|----------------------|-------------|--------------------|-----------|------------|-----------------------------|----------------|-----|--|--|--|
| Chlorite-zone | ASM1 | Quartz, | Quartz | Solution | SGR | Crossed | N | XZ: 1.54 | NC | |
| | | Calcite, | strain | seam | | girdle? | C | (± 0.03) | | |
| | | Albite, | fringe, | | | | * | YZ: 1.29 | | |
| | | Phengite, | Elongated | | | | | (± 0.02) | | |
| | | Chlorite, | quartz | | | | | | | |
| | | Graphite | grain | | | | | | | |
| Garnet-zone | ASM2 | Quartz, | Elongated | Aligned | SGR+GBM | Crossed | 43 | XZ: 1.70 | XZ: 1.93 | |
| | | Phengite, | quartz | phengite | | girdle | - | (± 0.11) | (± 0.03) | |
| | | Albite | grain, | | | (Type-1) | 47 | YZ: 1.42 | YZ: 1.75 | |
| | | Garnet, | Aligned | | | | | (± 0.12) | (± 0.03) | |
| | | Ilmenite, | phengite | | | | | | | |
| | | Rutile | | | | | | | | |
| Albite-biotite zone | ASM3 | Quartz, | Not | Aligned | SGR+GBM | Crossed | 48 | PZ**: 1.46 | PZ: 1.67 | |
| | | Phengite, | observed | phengite | | girdle | - | (± 0.09) | (± 0.11) | |
| | | Albite, | | | | (Type-1) | 64 | | | |
| | | Piemontite, | | | | | | | | |
| | | Ilmenite, | | | | | | | | |
| | | Rutile | | | | | | | | |
| Albite-biotite zone | ASM4 | Quartz, | Not | Aligned | SGR | Small | 46 | PZ: 1.37 | NC | |
| | | Phengite, | observed | phengite | | girdle | - | (± 0.07) | | |
| | | Albite, | | | | | 49 | | | |
| | | Ilmenite, | | | | | | | | |
| | | Rutile | | | | | | | | |
| Albite-biotite zone | ASM5 | Quartz, | Not | Phengite | BLG | Small | 37 | PZ: 1.54 | NC | |
| | | Phengite, | observed | shear-band | | girdle | - | (± 0.03) | | |
| | | | | | | | 42 | | | |

* Not calculated

** Plane parallel to Z-axis

書式変更: フォントの色: 赤

書式変更: 両端揃え

Table 2—Deformation temperature of samples

| Sample No. | Metamorphic zonation | Deformation temperature (°C) |
|------------|----------------------|------------------------------|
| ASM1 | Chlorite-zone | NC |
| ASM2 | Garnet-zone | 344–376 |
| ASM3 | Albite-biotite-zone | 384–512 |
| ASM4 | Albite-biotite-zone | 368–392 |
| ASM5 | Albite-biotite-zone | 296–336 |

NC: Not-calculated

Table 3—Differential stress estimated by piezometer

(Cr: Cross et al., 2017; Cr+Ho: Cross et al., 2017 corrected by Holyoke, 2010; Sh: Shimizu, 2012)

| | Differential Stress in uniaxial condition (MPa) | | | Differential stress in plane stress condition (MPa) | | |
|-----------|---|-------|------|---|-------|------|
| | Cr | Cr+Ho | Sh | Cr | Cr+Ho | Sh |
| ASM1 (XZ) | 47.6 | 34.7 | NC | 55.0 | 40.1 | NC |
| ASM1 (YZ) | 71.7 | 52.3 | NC | 82.8 | 60.4 | NC |
| ASM2 (XZ) | 36.9 | 26.9 | 46.5 | 42.6 | 31.1 | 53.7 |
| ASM2 (YZ) | 58.3 | 42.6 | 65.9 | 67.3 | 49.1 | 76.1 |
| ASM3 (PZ) | 54.6 | 39.9 | 60.7 | 63.0 | 46.0 | 70.1 |
| ASM4 (PZ) | 62.9 | 45.9 | NC | 72.6 | 53.0 | NC |
| ASM5 (PZ) | 110.1 | 80.4 | NC | 127.1 | 92.8 | NC |

NC: Not-calculated

400

405

Table 1 Observation and analysis results

| Metamorphic zonation | Sample name | Mineral assemblage* | Lineation | Foliation | Recrystallization mechanism | Fabric Pattern | OA | RMS grain size (10 ^X (μ m), range: 2 σ) | Mode of log grain size (10 ^X (μ m), range: 2 σ) |
|----------------------|-------------|---------------------|----------------------------|-----------|-----------------------------|-----------------|-----|---|---|
| Chlorite zone | ASM1a | Qz, Cal, Ab, | Qz strain | Solution | SGR | Crossed | NC | XZ(1a): 1.59(4) | NC |
| | ASM1b | Ph, Chl, Gr | fringe, Elongated qz grain | seam | | girdle? | ** | XZ(1b): 1.54(3) YZ(1b): 1.29(2) | |
| Garnet zone | ASM2 | Qz, Ph, Ab, | Elongated | Aligned | SGR+ | Crossed | 43- | XZ: 1.70(11) | XZ: 1.93(3) |
| | | Grt, Ilm, Rt | qz grain, Aligned ph | ph | GBM | girdle (Type 1) | 47 | YZ: 1.42(12) | YZ: 1.75(3) |
| Albite-biotite zone | ASM3 | Qz, Ph, Ab, | Not | Aligned | SGR+ | Crossed | 48- | PZ***: 1.46(9) | PZ: 1.67(11) |
| | | Pmt, Ilm, Rt | observed | ph | GBM | girdle (Type 1) | 64 | | |
| Albite-biotite zone | ASM4 | Qz, Ph, Ab, | Not | Aligned | SGR | Small | 46- | PZ: 1.37(7) | NC |
| | | Ilm, Rt | observed | ph | | girdle | 49 | | |
| Albite-biotite zone | ASM5 | Qz, Ph, | Not | Ph shear | BLG, | Small | 37- | PZ: 1.54(3) | NC |
| | | | observed | band | SGR | girdle | 42 | | |

*Qz: quartz, Cal: calcite, Ab: albite, Ph: phengite, Chl: chlorite, Gr: graphite, Grt: garnet, Ilm: ilmenite, Rt: rutile.

** Not calculated. ***Plane parallel to Z axis

Table 2 Differential stress estimated by piezometer and deformation temperature estimated by OA

(Cr: Cross et al., 2017; Cr+Ho: Cross et al., 2017 corrected by Holyoke, 2010; Sh: Shimizu, 2012)

| | Differential Stress in uniaxial condition (MPa) | | | Differential stress in plane stress condition (MPa) | | | Deformation temperature (°C) |
|------------|---|-------|------|---|-------|------|------------------------------|
| | Cr | Cr+Ho | Sh | Cr | Cr+Ho | Sh | |
| ASM1a (XZ) | 44.2 | 32.3 | NC | 51.0 | 37.2 | NC | NC |
| ASM1b (XZ) | 47.6 | 34.7 | NC | 55.0 | 40.1 | NC | NC |
| ASM1b (YZ) | 71.7 | 52.3 | NC | 82.8 | 60.4 | NC | NC |
| ASM2 (XZ) | 36.9 | 26.9 | 46.5 | 42.6 | 31.1 | 53.7 | 344-376 |
| ASM2 (YZ) | 58.3 | 42.6 | 65.9 | 67.3 | 49.1 | 76.1 | NC |
| ASM3 (PZ) | 54.6 | 39.9 | 60.7 | 63.0 | 46.0 | 70.1 | 384-512 |
| ASM4 (PZ) | 62.9 | 45.9 | NC | 72.6 | 53.0 | NC | 368-392 |
| ASM5 (PZ) | 110.1 | 80.4 | NC | 127.1 | 92.8 | NC | 296-336 |

NC: Not calculated

5.4 Discussion

4.1 Stress recorded by quartz microstructure and in the subduction plate interface

In this section, we discuss the relationship between the stress recorded by the quartz microstructure and the stress state along the subduction interface. In this contribution, we use the term stress to refer to differential stress and shear stress. In Appendix B, we also refer to the tensor nature of stress including the deviatoric stress. For the stress estimates, we focused on the microstructures of samples ASM1–5.

In sample ASM1, quartz veins in the rock body were analyzed, and the possibility that the estimated stress is not representative of the stress experienced by the larger-scale rock body needs to be considered. In contrast to the quartz veins, the surrounding rock body shows microstructures indicative of deformation by pressure solution creep (Fig. 6a). However, parts of the quartz fringe have undergone recrystallization and these domains show very similar recrystallized quartz grain size to that of the recrystallized quartz vein (Fig. 6a, 6b) indicating multiple domains within the rock were deformed under the same stress.

Therefore, it is concluded that the stress estimated from sample ASM1 is representative of the stress of the whole rock body around the location ASM1.

In Sample ASM2–4, in addition to quartz (volume fraction 70–80%; inferred by indexing rate of EBSD analysis), albite and phengite are also significant mineral components (Fig. 6c–6f). Albite includes traces of a D_r foliation oblique to the external D_s foliation which is partly defined by the alignment of phengite. These observations suggest that both albite and phengite were formed before or synchronously with D_s , the timing of quartz deformation. This implies that albite and phengite have both been deformed along with the quartz. However, in albite, wavy extinction is weak and not nearly as well developed as in quartz (e.g., albite in Fig. 6d), suggesting that the albite underwent only very limited intracrystalline deformation during the D_s deformation. In general, albite is known to have a higher yield strength than quartz in this temperature condition (Passchier & Trouw, 1996), in agreement with the above assumption. A muscovite flow law (Mariani et al., 2006) suggests that the strain




Figure 8: Microstructure of phengite in quartz schist (sample ASM3). Phengite (greenish to purplish interference colored platy mineral) does not form a continuous foliation longer than a few mm.

435 rate of phengite should be 10 times higher than that of quartz. However, phengite in this sample hardly forms a continuous
foliation (Fig. 6e, 6f, 8), which means that deformation is unlikely to propagate. It has been suggested that in such a structure,
quartz is distributed in a mesh-like pattern and supports almost all of the stress applied to the rock—an interconnected network
(Alaoui et al., 2022). Assuming that this situation applies in samples ASM2–4, the quartz deformation can be regarded as
representative of the deformation of the rock body around samples ASM2–4. Therefore, the stress recorded by the quartz in
samples ASM2–4 is considered to be representative of the stress recorded by the rock body around samples ASM2–4.

440 There are mafic schist domains around the pelitic, psammitic, and quartz schists, in which samples ASM1–4 were collected.
Mafic schist contains only small amounts of quartz and it is reasonable that the physical characteristic of mafic schist is
different from that of pelitic and quartz schists. Different strain rates are expected in such heterogeneous domains even if the
stress is homogenous. However, in this field area the fraction of mafic schist is small (Fig. 3), and irrespective of the stress
distribution, we consider that the effect of mafic schists on the deformation of rocks along the subduction plate interface in the
445 present case can be safely ignored. Therefore, we conclude that the stresses inferred from our samples are representative of the
stresses on a larger scale and along the subduction zone plate interface where the Sanbagawa belt was formed.

Shear bands were observed in sample ASM5 (Fig. 6g, 6h). The formation of shear bands represents local strain partitioning.
However, sample ASM5 shows clearly low deformation temperature compared with peak metamorphic temperatures, and
therefore it could represent the later stage deformation compared to samples ASM1–4. (Sect. 4.4).

450 5.1.4.2 Tectonic stage of sample deformation



Knowledge of the tectonic stage represented by the deformation recorded in the quartz samples is important when discussing
how the stress data for individual samples can be related to stresses in the paleo-subduction plate interface. In this study, we
first compared peak metamorphic temperatures estimated by the Raman carbonaceous material geothermometer (Kouketsu et
al., 2021) with deformation temperatures estimated by the quartz c-axis fabric opening-angle thermometer. The P–T path of
455 the region has been determined in previous studies and this path allows us to link the deformation temperature to pressure and
hence depth. ~~The retrograde P/T gradient is the most important and this has been estimated as 0.3 GPa/100°C in the albite-
biotite zone and 0.4 GPa/100°C in the garnet and chlorite zones (Fig. 6d and 6f in Okamoto and Toriumi, 2005).~~ ~~The retrograde
P-T gradient is the most important to draw a retrograde P-T path, and this has been estimated as 3 MPa K⁻¹ in the albite-biotite
zone and 4 MPa K⁻¹ in the garnet and chlorite zones (Fig. 6d and 6f in Okamoto and Toriumi, 2005).~~ Depth was calculated
460 assuming thickness of granitic upper crust (2700 kg m⁻³) is 20 km and that of gabbroic lower crust (3000 kg m⁻³) is 10 km.

In sample ASM1, the crystallographic preferred orientation pattern fabric ~~is~~ not clear and the OA ~~cannot be~~ not
measured (Fig. S3). However, sample ASM1 recorded ~~de~~ deformation and recrystallized grains ~~were~~ formed by SGR,
indicating that its deformation process ~~was~~ dislocation creep and deformation temperature ~~was~~ at least about 300°C
(Passchier ~~and~~ Trouw, 2005). This temperature is close to the peak temperature of about 330°C and in the following
465 discussion, we take the deformation temperature of sample ASM1 to be 300–330°C.

書式を変更: 上付き

書式を変更: 上付き

To allow a better regional comparison between the deformation temperature and metamorphic peak temperature we also examined quartz fabric data from previous studies (Sakakibara et al., 1992; Wallis et al., 1992; Tagami and Takeshita, 1998; Yagi and Takeshita, 2002) that were suitable for the quartz c-axis fabric opening-angle thermometer. In many of the previous studies, the main ductile deformation of the region is referred to as D1 (Tagami and Takeshita, 1998; Yagi and Takeshita,



475 **Figure 99:** A comparison between estimated peak metamorphic temperatures by the Raman carbonaceous material
geothermometer (black circles), and the estimated deformation temperatures by the quartz c-axis fabric opening-angle
thermometer (hexagons). The black frames around some hexagons indicate that the corresponding c-axis fabric
patterns are not crossed girdles. Especially, at the higher temperature side (North of sample ASM2), all hexagons with
black frames (3 samples) show small girdles, which may cause a small overestimation of the deformation temperature
(Law, 2014). Blue hexagons indicate samples collected in this study. Blue circles around blue hexagons indicate these
480 samples deformed at temperatures significantly (50°C-) lower than the surrounding peak metamorphic temperatures
and may record deformation at shallower levels. Errors for the RCMT estimates are given at the 2 σ level. Errors for
the quartz c-axis fabric opening-angle thermometer are based on the measurement of OA (treated as 2 σ). The
485 deformation temperature for sample ASM1 (blue rectangle) is derived from microstructural observations.

2002). D1 has the same characteristics as Ds in this study and the same reference frame of the X-axis and XY plane was used
to plot the quartz fabric as used in this study so a direct comparison is possible. One previous study (Sakakibara et al., 1992)
485 relates the deformation of the study area to an Sb_{2,2} deformation phase. The Sb_{2,2} is defined by coupling of the Saruta-
Fuyunose-Sogauchi units (classified as the Shirataki unit in this study) and the Sakamoto unit (classified as the Shirataki and
Oboke unit in this study). We consider it to be the same as the Ds deformation because the boundary between the Shirataki
unit which is referred to as the Saruta-Fuyunose-Sogauchi units and the Oboke unit which is referred to as the Sakamoto unit
490 contains a mixed domain with rocks derived from both the overlying Shirataki and underlying Oboke units, in which
characteristics of the Ds deformation were observed (Aoya et al., 2017). Measured OA from previous studies were shown in
Appendix A.

It is clarified that most of the plotted data are within a few tens of degrees Celsius below the peak metamorphic temperature
(Fig. 99). However, some samples, mainly in the high metamorphic region, show deformation temperatures that are clearly
lower than the peak metamorphic temperature (blue circles). It is assumed that samples ASM 1 and 3 were deformed near the
495 peak metamorphic temperatures, samples ASM 2 and 4 were deformed at the early stage of exhumation, and sample ASM5
was deformed at the late stage of exhumation. ~~In the following discussion we focus on samples ASM1-4. We used samples
ASM1-4 in the next discussion. Estimates for the pressures at which samples ASM1 and 3 were deformed are about 0.55±0.1
GPa (21 km) and 0.7±0.2 GPa (27 km). Samples ASM2 and 4 were deformed at 0.45±0.1 GPa (17 km) and 0.5±0.1 GPa (19
km). Taking into consideration the peak pressure condition by Enami et al. (1994), the peak temperature condition by Kouketsu
500 et al. (2021), the retrograde P-T gradient by Okamoto and Toriumi (2005), and estimated deformation temperature, pressures
at which samples ASM1 and 3 were deformed are estimated as 0.55 ± 0.1 GPa (21 km) and 0.7 ± 0.2 GPa (27 km). Samples
ASM2 and 4 were deformed at 0.45±0.1 GPa (17 km) and 0.5±0.1 GPa (19 km). The error of estimated pressure condition is
derived from the measurement error of OA (treated as 2 σ) and RCMT (2 σ), and the range of pressure condition (Enami et al.,
2014; treat as 2 σ), pressure conditions (Enami et al., 1994; treat as 2 σ).~~

5.2 Stress recorded by quartz microstructure and in the subduction plate interface

In this section, we discuss the relationship between the stress recorded by the quartz microstructure and the stress state along the subduction interface. In this contribution, we use the term stress to refer to differential stress and maximum shear stress. In Appendix B, we also refer to the tensor nature of stress including the deviatoric stress. For the stress estimates, we focused on the microstructures of samples ASM1–4. We argue that the estimated stresses are likely to be similar to the surrounding rocks and representative of the plate interface.

5.2.1 Stress recorded by sample ASM2, 3, 4 and stress received by surrounding quartz schist

In samples ASM2–4, in addition to quartz (volume fraction 70–80%: inferred by indexing rate of EBSD analysis), albite and phengite are also significant mineral components, which deformed along with quartz during Ds (Fig. 7c–7f). Albite shows only weak development of wavy extinction that is not nearly as well developed as in quartz (e.g., albite in Fig. 7d), suggesting that the albite underwent only very limited intracrystalline deformation during the Ds deformation. In general, albite is known to have a higher yield strength than quartz in this temperature condition (Passchier and Trouw, 1996), in agreement with the above inference. Phengite is expected to be much weaker and may have been significantly deformed. Hunter et al. (2016) pointed out that under a deformation temperature of 490–530°C, even if they do not form an interconnected network, the appearance of mica with a volume ratio of less than 10% may inhibit quartz deformation and concentrate deformation in the mica. Furthermore, it has been pointed out that the basal glide of phengite is weak and may undergo significant deformation when the von Mises criterion is satisfied under deformation conditions like our samples (Condit et al., 2022). In the light of these considerations, we assessed the effect of mica deformation and deformation heterogeneity in rocks around our samples.

When phengite (a relatively weak phase) grains do not form an interconnected network, both the phengite and quartz deform at the same strain rate and are subjected to different stresses (mica distributed within a load-bearing quartz: load-bearing framework (LBF) in Handy (1994)). Phengite in sample ASM2, 3, and 4 shows only limited connectivity and does not form a uniform continuous foliation (Fig. 7d, 7e, 7f; Fig. 10), which means that deformation is unlikely to propagate along phengite and the LBF condition can be applied. In this situation, the estimated stresses would be larger than the stresses experienced by the phengite. However, the stress received by the whole rock body is, in this case, the sum of the stress received by each mineral multiplied by the volume fraction of the mineral (e.g., Condit et al., 2022; Handy, 1994). Thus, even if the phengite is subjected to a stress of 0 MPa and the volume fraction of the mica mineral is 20%, the stress on the rock body is 0.8 times the estimated stress and the estimated stress can be considered to be a good approximation to the stress of the whole rock body.

In summary, the estimated stresses are almost identical to the stresses received by the surrounding rock body. However, the stresses received by the phengite may be even smaller, as the strength of the mica is assumed to be lower than the strength of the quartz undergoing dislocation creep at the temperature conditions discussed in our study.

書式変更: フォント: (英) Times, 斜体 (なし)

書式変更: インデント: 最初の行: 0 字

5.2.2 Stress recorded by sample ASM1 and stress received by surrounding psammitic and pelitic schists

In the area around sample ASM1, both psammitic and pelitic schists are deformed by quartz pressure solution creep in the microlithon domains, and the developed foliation may have been deformed by phyllosilicate slip (Fig. 7a). As foliation develops as a layer, it is considered that the foliation and microlithon domains are subjected to the same stress and deformed at different strain rates (Condit et al., 2022). Both quartz veins (Fig. 6b; Fig. 7b) and strain fringes (Fig. 7a) are developed in the microlithon domain, but no boudin or other structures attributable to differences in strength could be identified (Fig. 6a;




Figure 10: Microstructure of phengite in quartz schist (sample ASM3). Phengite (greenish to purplish interference colored platy mineral) does not form a continuous foliation longer than a few mm.

Fig. 7a). Therefore, quartz veins, strain fringes, and microlithon domains are considered to have had almost the same strength, i.e., were subjected to the same maximum shear stress and strain rate. In Sample ASM1, stresses were estimated from quartz veins in psammitic schist and strain fringes in pelitic schist. From these results, we conclude it is likely that the obtained stress is representative of the stresses undergone by the pelitic and psammitic schists of the chlorite zone.

Estimated differential stresses were 32.3–71.7 MPa. In a quartz deformation mechanism diagram drawn using the thin-film pressure solution creep flow law (Table 3: Rutter, 1976; Schmidt and Platt, 2022) and dislocation creep flow law (Table 3: Lusk et al., 2021), the conditions of the vein and fringe in sample ASM1 (Table 4) is located at the dislocation creep deformation dominant region (Fig. 11a), and microlithon domain condition (Table 4) is located in the thin-film pressure solution creep dominant region (Fig. 11b), consistent with geological observation. Therefore, the above interpretation from outcrop and thin section observations is supported in terms of quartz rheology. In this case, the strain rate of the microlithon domain is estimated to be twenty times higher than that of dynamically recrystallized grains in the quartz vein and fringe (Fig. 11). However, dynamically recrystallized grains in the quartz vein and fringe are considered to have been formed by the recrystallization of quartz fibre grains that are elongated parallel to the stretching lineation (Fig. 6b; Fig. 7a). These fibre grains are formed associated with the opening of the vein and the formation of the veins contributes to the strain of the rock. Therefore, the strain rate experienced by the quartz veins and fringes is considered to be the sum of the strain rate associated with the

formation of quartz fibre grains and the strain rate associated with quartz dislocation creep. This additional contribution from dislocation creep may have allowed the quartz vein and microlithon to deform at the same stress and strain rate.

The strain rate of thin-film pressure solution creep depends on grain size. Grain size estimation using this method is difficult for structures with significant grain growth inhibition by different minerals, and the grain size of the microlithon domain used in the discussion is an assumption. Although this is not a problem for rough strain rate comparisons such as the present study, an accurate grain size estimation method is required for more quantitative strain rate evaluations.

Trepmann and Seybold (2019) observed quartz veins that formed and developed simultaneously with ductile deformation and documented microstructures indicating dislocation glide and recrystallization associated with rapid stress loading from the seismogenic zone and subsequent stress relaxation, as well as the pressure solution creep of surrounding rock and opening and sealing of the veins (crack-seal veins) associated with gradual internal stress loading and subsequent stress relaxation. The

書式変更: インデント: 最初の行: 0.5 字


書式変更: フォント: 太字(なし), フォントの色: アクセント1

Table 4 Flow law used in this study

| Formula | Description | Reference |
|---|---|---|
| $\dot{\epsilon} = \frac{A_{ps} V_m c D_{gb} \omega \sigma \rho_f}{RT d^3 \rho_s}$ | Thin film pressure solution flow law (s ⁻¹) | Rutter (1976) Schmidt and Platt (2021) |
| $\dot{\epsilon} = A_{dsl} f_{H_2O}^{-9.3} f_{H_2O}^{0.49} \sigma^{3.5} \exp\left(-\frac{Q + PV}{RT}\right)$ | Dislocation creep flow law (s ⁻¹) | Lusk et al. (2021) |

Table 5 Parameters of dislocation creep and pressure solution creep flow law

| Parameter | Description | Value | Reference |
|------------|--|------------------------|--|
| A_{ps} | Geometric constant | 44 | Den Brok (1998) |
| V_m | Molar volume of solid (m ³ mol ⁻¹) | 2.269×10 ⁻⁵ | Berman (1988) |
| c | Solubility of solid in fluid phase (mole fraction) | 2.954×10 ⁻² | Fournier and Potter (1982) |
| D_{gb} | Grain boundary diffusivity (m ² s ⁻¹) | 7.00×10 ⁻²¹ | Farver and Yund (1997) |
| ω | Effective width of grain boundary (μm) | 0.339, 10.170 | Dobe et al. (2021) Hickman and Evans (1995) |
| ρ_f | Density of fluid (kgm ⁻³) | 1058 | Burnham (1969) |
| ρ_s | Density of solid (kgm ⁻³) | 2650 | Schmidt and Platt (2022) |
| A_{dsl} | Geometric prefactor | 10 ^{-7.9} | Lusk et al. (2021) |
| σ | Differential stress (uniaxial, MPa) | 32.3–71.7 | This study |
| f_{H_2O} | Water fugacity (MPa) | 65 | Holland and Powell (2004) |
| R | Gas constant (Jmol ⁻¹ K ⁻¹) | 8.314 | |
| T | Temperature (K) | 593 | This study |
| Q | Activation enthalpy (Jmol ⁻¹) | 118000 | Lusk et al. (2021) |
| P | Pressure (MPa) | 500 | This study |
| V | Activation volume (cm ³ mol ⁻¹) | 2.45 | Lusk et al. (2021) |
| d | Grain size (μm) | 15, 20-35 | This study |



575 **Figure 11: Deformation mechanism diagram of (a) quartz vein and strain fringe condition and (b) microlithon condition. The**
 580 **contour line indicates the exponential part of the strain rate (given for uniaxial conditions and strain rate needs to be multiplied**
 585 **by $\sqrt{3}$ if converting to simple shear strain rate (Lusk et al., 2021)).**

580 structures observed in sample ASM1b area are similar to the latter and may reflect multiple stages of stress concentration and
 585 relaxation with a time interval of several hundred years (Trepmann and Seybold 2019). In this case, the stress measured from
the quartz vein in sample ASM1 may be affected by a stress fluctuation. However, considering that dynamic recrystallization
requires strains of at least 0.2 (e.g., Stipp and Tullis, 2003) and that the calculated strain rate is approximately 10^{-13}s^{-1} ,
dynamically recrystallized grains require at least 30,000 years to form. Therefore, the influence of stress fluctuation over a
period of a few hundred years can be considered almost negligible.

585 In summary, we consider the obtained stress to be representative of the stresses undergone by the surrounding pelitic and
psammitic schists. Such situations are only likely to occur when the deformation conditions are located near the boundary
between the dislocation creep domain and the pressure solution creep domain. The change in the deformation mechanism
between the vein or fringe and microlithon domains can be attributed to differences in the degree of grain growth inhibition
and activation of pressure solution creep due to the presence or absence of the quartz-mica boundary.

590 **5.2.3 Deformation heterogeneity within different lithologies and stress in the subduction plate interface**

595 Tulley et al. (2020) compared the flow laws for various rocks with the strength of hydrous metabasalt inferred from the
geological structure and quartz recrystallized grain size. The results showed that mica-containing metasediments can be harder
or softer than hydrous metabasalt or amphibolite, depending on temperature conditions. It was also shown that the strength of
hydrous metabasalt is reduced by pressure solution creep and slip of phyllosilicates, which plays an important role in
deformation along the subduction boundary. Therefore, the discussion of deformation other than quartz, pelitic, and psammitic
schist is important for the discussion of rock deformation at subduction boundaries.

書式変更: インデント: 最初の行: 0.5 字

600 In this study, no microstructural observations or stress estimates of quartz schist and basic schist in the chlorite zone, or pelitic and basic schist in the garnet and albite zones have been made. However, previous studies showed that the basic schist in the oligoclase biotite zone appears to be less affected by Ds deformation than other rock bodies (e.g., Mori and Wallis., 2010), indicating that the associated strain is smaller. In addition, the quartz schist in the garnet zone has well-developed sheath folds (Wallis, 1990; Endo and Yokoyama, 2019), which are not observed in the surrounding lithologies suggesting that the strain in the quartz schist is particularly high. It is therefore possible that each rock body was deformed at a different strain rate and may have been deformed at the same stress. To investigate this, stress estimates should be made from the quartz domains for each type of schist, and the strength relationship between the other domains and the quartz domains in each schist should be investigated from structural observations to constrain the deformation strength of each rock type. If the flow laws of the constituent minerals are known, they may be combined to estimate the deformation of the entire rock body (Condit et al., 2022). It is also important to focus on lithological boundaries to confirm the presence or absence of structures that are attributable to strength contrasts. These are topics for future research.

610 Shear zones by antigorite serpentinite exist at the boundary between mantle wedge-derived serpentinite and pelitic schist (Kawahara et al., 2016). Although the area examined in our study is on the oceanic plate side of the subduction boundary region, it is possible that different minerals and different stress and strain conditions existed on the overriding plate side. Further research is needed on this as well.

54.3 Spatial distribution of stress in the Sanbagawa subduction zone and relationship with deep slow earthquakes

615 The use of different proposed piezometer relationships based on grain size results in significant differences in the estimated stress. A further complication highlighted by this study is the variation in grain size depending on the orientation of the observed section with respect to the finite strain axes. This issue is not significant in deformation experiments that predominantly use uniaxial shortening but is significant in natural samples that are close to plane strain (e.g., Tagami and Takeshita, 1998). When these uncertainties are included, the differential (maximum shear) stress was found to be 31.1–82.8 MPa (15.5–41.4 MPa) for plane stress, in samples ASM1–4. Moreover, there was no clear correlation between the sample location and stress (Fig. 129) implying stress was constant throughout the range of different temperatures and pressures during peak metamorphism to the early stage of exhumation. This suggests that constant stress regardless of depth was maintained over a long timescale. If the stress recorded by the quartz recrystallization is representative of the stress along the plate interface, this result indicates that the stress along the former plate interface was independent of depth and nearly constant over the depth range of 17–27 km where depth is calculated under the assumption that granitic rock is present up to a depth of 20 km, and gabbroic rock is present at greater depths (e.g., Aoya et al., 2013a). This information can be applicable to long-timescale subduction zone modelling.


625 In an earlier study, Takeshita (2021) reports the results of microstructural analyses of quartz-rich samples in the Shirataki unit of the Sanbagawa belt and estimated differential stress from quartz grain size. Takeshita (2021) proposes a decrease in differential stress with increasing structural level (“Upper Chl” to “Ab-bt” of Fig.6 in Takeshita, 2021), which corresponds to

書式を変更: フォントの色: 赤

630 increasing metamorphic temperature and pressure in this study domain. The results of Takeshita (2021) differ from those of this study, and it is particularly clear that samples formed by SGR+GBM (GBM in Takeshita, 2021) show very low differential stress.


This difference may be mainly attributed to the type of piezometer used to analyze the recrystallized microstructures formed by SGR+GBM. As mentioned above, the recrystallized microstructure formed by SGR+GBM is developed by the formation


635



640 **Figure 120:** Differential stress for plane stress conditions estimated using piezometers based on recrystallized quartz grain size. The vertical axis indicates differential stress. Black points were calculated following Shimizu (2012), orange points were calculated following Cross et al. (2017), and blue points were calculated following Cross et al. (2017) using a correction for measured values by Griggs apparatus, which is proposed by Holyoke and Kronenberg (2010). Circle, triangle, and square points indicate measurements in the XZ, YZ, and PZ planes. The black, orange, and blue lines show uncertainties associated with differential stress associated with the black (2σ), orange (1σ), and blue points (12σ).

of subgrains by SGR and the migration of grain boundaries by GBM. Several studies have pointed out that dislocation movement and grain nucleation have a greater temperature dependence than grain boundary migration and this leads to a grain size decreases with increasing temperature for the same differential stress (e.g. De Bresser, 1998; Shimizu, 1998) (and greater strain rate). Furthermore, Shimizu (2008, 2012) theoretically derived a piezometer for the SGR+GBM recrystallized microstructure that incorporates this temperature effect and shows a grain size decreases with increasing deformation temperature for the same differential stress. In contrast, Takeshita (2021) uses a piezometer proposed by Twiss (1980), in which grain size is temperature independent (details of the differences between the theories of Twiss (1980) and Shimizu (2008, 2012) are described in Shimizu (2008)). Twiss (1980) quoted data from various experimental studies in which dynamically recrystallized grain size and differential stress were determined by using recrystallized microstructure of experimental samples and natural samples, including quartz, olivine, and metal alloys. Twiss (1980) subsequently generated a non-dimensional piezometer that best fits these experimental data (equation 23 in Twiss (1980)), and Takeshita (2021) applied quartz physical properties data (Table 2 in Twiss (1980)) to this non-dimensional piezometer. This non-dimensional piezometer does not have a strong material dependency and it is reasonable to use experimental results for different materials to construct a piezometer. However, a potentially significant problem is that the deformation experiments used in Twiss (1980)





660 **Figure 131:** Differential stress for plane stress conditions estimated using piezometers by Twiss (1980). The vertical axis indicates differential stress. Stress estimated by microstructures formed by SGR+GBM is clearly lower than stress estimated by microstructures formed by SGR. Applied grain sizes were arithmetic mean and were calculated from the grain boundaries for Shimizu (2012).

665 were conducted under higher temperature conditions (814–1699°C) than the deformation temperatures of the samples in the Sanbagawa belt (about 500°C). If SGR+GBM microtextures are contained in these deformation experiments, the piezometer shows will predict a smaller grain size under the same stress condition and therefore underestimates the differential stress when analyzing recrystallized microstructure formed by SGR+GBM in the Sanbagawa belt. We note that this problem also exists in the piezometer proposed by Cross et al. (2017), but this piezometer is based on analysis of newly recrystallized grains alone and the size of these grains is only weakly affected by GBM, so the temperature effect should be relatively small. The result of stress estimation of samples ASM1–4 by using the piezometer of Twiss (1980), which shows lower differential stress values for microstructures formed by SGR+GBM, and higher values for microstructures formed by SGR (Fig. 131), supports this idea.

675 The other possibility is a selection of microstructure. In Takeshita (2021) A second possible explanation for the discrepancy of the results presented here and those of Takeshita (2021) concerns the selection of microstructure for analysis. In Takeshita (2021), especially in samples from higher metamorphic grade zone, some grain size data whose value is small is considered “overprinting”, and excluded from stress estimation (Fig. 3 in Takeshita, 2021). It is possible that quartz microstructures like our samples were excluded, and microstructures with relatively large grain size were selected to stress estimation, resulting in a decreasing stress trend.

680 Even taking these effects into account, the obtained stress values in this study are greater than those of Takeshita (2021). This may be due to the fact that the EBSD-based grain boundary estimation method makes it possible to consider smaller grains.

書式変更: インデント: 最初の行: 0.5 字

書式を変更: フォントの色: 赤

5.4 Relationship with deep slow earthquakes

The Sanbagawa belt formed in a relatively warm subduction zone, and deep slow earthquakes are commonly observed in modern-day warm subduction zones such as SW Japan (Obara, 2020) which has a similar thermal structure to the Sanbagawa belt (Fig. 2). Moreover, the depth of deformation of samples ASM1–43 is consistent with the depth at which deep slow earthquakes occur. Deep slow earthquakes are commonly observed concentrated in a domain near and updip of the mantle wedge corner (Behr and Bürgmann, 2021). In the Sanbagawa belt, it is found that ultramafic rocks of the Shirataki unit are not present in the chlorite and lower garnet zone (Aoya et al., 2013a) and it is concluded that these ultramafic rocks are derived from the mantle wedge (Aoya et al., 2013a; Aoya and Endo, 2017). The peak pressure of the garnet zone corresponds to a depth of approximately 30–35 km, indicating that the mantle wedge of the Sanbagawa subduction zone was located at depths deeper than 30–35 km. The paleodepths of samples ASM1–4 were 17–27 km, which is near and updip of the mantle wedge, suggesting that these samples were formed in a region with features similar to the deep slow earthquakes domain.

In sample ASM1b, traces of pressure solution creep and dislocation creep, such as dynamically recrystallized grains in quartz veins and strain fringes in microlithons, are observed. On the other hand, the partly recrystallized quartz fibres in quartz veins (Fig. 6b) and phyllosilicate foliation suggest that brittle deformation associated with features such as vein opening and phyllosilicate slip also occurred at the same time. This indicates that the quartz vein was opened under close to lithostatic pore fluid pressure and the fibre quartz grains grew before undergoing recrystallization. Repetition of this sequence in the rock deformed by quartz pressure solution creep combined with slip along phyllosilicates led to the formation of the present structure (Fig. 6a). The microstructure is similar to crack-seal veins, and the formation process is similar to the structures inferred by Giuntoil et al. (2022) and Ujiie et al. (2018) although bands of fluid inclusions were not observed. In particular, this feature may be compared with the results of the study by Giuntoil et al. (2022), which suggests that dislocation creep and pressure solution creep of quartz, phyllosilicate slip, and vein formation all contribute to slow earthquake cycles and associated fluid migration.

The stress estimates in Sample ASM1 are considered to be representative of the surrounding rock body. The maximum shear stress drop on the fault plane caused by slow earthquakes could be hundreds to thousands of times smaller than that of ordinary earthquakes (e.g., Ito and Obara, 2006; Behr and Bürgmann, 2021), and unless the fault plane is oriented very close to the orientation of the principal stresses, it will have very little effect on the estimated maximum shear stress value. Therefore, the obtained stress can be used as stress conditions at the time that deep slow earthquakes were initiated. The results from sample ASM1 (34.7 to 71.7 MPa and $10^{-11.0}\text{s}^{-1}$ to $10^{-12.0}\text{s}^{-1}$ in uniaxial deformation, which must be multiplied by $\sqrt{3}$ for simple shear strain rate (Lusk et al., 2021)) show similar stresses but higher strain rates than the estimates reported by Giuntoil et al. (2022) (43 to 55 MPa (upper bond) and 10^{-14}s^{-1} to 10^{-13}s^{-1} (lower bond)). These differences may reflect the faster strain rates in the Sanbagawa subduction zone, associated with rapid subduction velocities (24 cm yr^{-1}).

As discussed above, Trepmann and Seybold (2019) observed pressure solution creep of the surrounding rock and opening and sealing of the veins (crack-seal veins) associated with gradual internal stress loading and subsequent stress relaxation. The

書式を変更: フォント: (日) MS 明朝, (言語 1) 日本語, スペルチェック
と文章校正を行う

書式変更: 見出し2, インデント: 最初の行: 0 字

715 structures found in the ASM1 area are similar to these structures and may reflect multiple stress concentrations and relaxations
on a scale of several hundred years. If the time scale for the formation of the veins can be constrained, the viability of this to
generate slow earthquakes can be tested by measuring the number of veins, and the time scale taken to form the entire vein
seen in the outcrop, which can then be compared to known time scales of slow earthquakes.

720 ~~Moreover, The shear stress drop on the fault plane caused by slow earthquakes could be hundreds to thousands of times smaller~~
~~than that of ordinary earthquakes (e.g., Ito and Obara, 2006; Behr and Bürgmann, 2021), and unless the fault plane is not~~
~~oriented to the direction of maximum/minimum principal stress axes, it has little effect on the estimated shear stress value.~~
~~Therefore, the estimated stress may represent the initial conditions from which slow earthquakes in the same domain nucleated.~~


4.45.5 Stress evolution of rock bodies during exhumation

725 In Fig. 9, the samples with blue circles are considered to have formed later in the exhumation process than sample ASM3
~~the other samples~~. Therefore, to examine the changes in stresses received by the rocks during exhumation, we compared the
730 estimated stresses of samples ASM3–5, which were collected from almost the same location and recorded different
deformation temperatures. Using the peak pressure condition by Enami et al. (1994), the peak temperature condition by
Kouketsu et al. (2021), the retrograde P-T gradient by Okamoto and Toriumi (2005), and estimated deformation temperatures,
we derived deformation pressure conditions for these samples of 0.7±0.2 GPa (27 km) for ASM3, 0.5±0.1 GPa (19 km) for
ASM4, and 0.35±0.1 GPa (13 km) for ASM5.

~~Using the known P–T path we derived pressures for these samples of 0.7±0.2 GPa (27 km) for ASM3, 0.5±0.1 GPa (19 km)~~
~~for ASM4, and 0.35±0.1 GPa (13 km) for ASM5.~~

The results (Fig. 142) show that assuming plane stress conditions the estimated differential (maximum shear) stress of samples
735 ASM3 and 4 are 46.1–70.1 MPa (23.1–35.0 MPa) and 53.0–72.6 MPa (26.5–36.3 MPa), respectively, indicating that the
stresses are

書式変更: インデント: 最初の行: 0 字



740 **Figure 142:** Differential stress for plane stress condition estimated using piezometers based on recrystallized quartz grain size. The vertical axis indicates differential stress. Black points were calculated following Shimizu (2012), orange points were calculated following Cross et al. (2017), and blue points were calculated following Cross et al. (2017) using a correction for measured values by Griggs apparatus, which is proposed by Holyoke and Kronenberg (2010). Circle, triangle, and square points indicate measurements in the XZ, YZ, and PZ planes. The black, orange, and blue lines show uncertainties associated with differential stress associated with the black (2σ), orange (1σ), and blue points (1.2σ).

745 almost constant until the middle part of the ascent. In contrast, the estimated differential (maximum shear) stress of sample ASM5, which is the final recorded stage of ductile deformation during ascent in this region, are 92.8–127.1 MPa (46.4–63.6 MPa). This is a significant stress increase although the uncertainties in absolute estimates are large. As shown in Fig. 9, there

are few plots of deformation temperature conditions as low as ASM5, and almost all data recorded deformation closer to the onset of exhumation. In contrast, the estimated differential (shear) stress of sample ASM5, which is the final recorded stage of ductile deformation during ascent in this region, was found to increase significantly, ranging from 92.8 to 127.1 MPa (46.4 to 63.6 MPa). As shown in Fig. 9, many samples recorded deformation temperatures close to the peak and therefore represent conditions close to the onset of exhumation. Therefore, it is suggested that stress conditions remained similar until mid-crustal levels where deformation became concentrated in discrete bands associated with higher stresses as represented by sample ASM5.

5 Conclusions

Quartz-rich rocks, and quartz veins, and quartz strain fringes from the subduction-type Sanbagawa belt exposed in central Shikoku, Southwest Japan preserve deformation-related microstructures that can be used to estimate paleo differential (maximum shear) stresses. These quartz-rich rocks have characteristics of quartz dominant deformation, and quartz veins and fringes are expected to have the same strength as surrounding rocks, suggesting that the estimated stresses are roughly and quartz veins record the same differential (shear) stress values as surrounding rocks, suggesting that the results are representative for the subduction interface. Estimates of both differential (shear) stress and deformation temperature were obtained from measurements of recrystallized grain sizes and the opening angle of quartz c-axis fabric patterns. The known P–T paths for the region can be used to relate temperature to pressure (and depth). After correcting the differential (shear) stress estimates based on uniaxial compression deformation experiments to account for plane stress conditions, the obtained results show differential (shear) stresses of 31.1–82.8 MPa (15.5–41.4 MPa) consistent over depths of 17–27 km in the paleo subduction channel. Differential (shear) stresses during exhumation initially show little change but increase during the lower T final stages of exhumation-related ductile deformation. The prograde P–T path of the Sanbagawa belt is similar to the thermal structure modelled for modern-day warm subduction zones such as SW Japan where deep slow earthquakes are common. Some of the studied samples were derived from depths near the mantle wedge where deep slow earthquakes are common. Therefore, the estimated differential (shear) stress may not only be useful to long-timescale subduction zone modelling but also represent the initial conditions from which slow earthquakes in the same domain nucleated.

書式を変更: フォントの色: 赤

Appendices

Appendix A: Measured OA from c-axis fabric patterns by previous studies.

Table A1 the results of quartz c-axis fabric opening-angle measurement

| Sample No. | Metamorphic zonation | Fabric-pattern | OA(°) | Deformation temperature (°C) |
|--|----------------------|----------------|-------|------------------------------|
| Sakakibara et al., 1992 | | | | |
| C | Ol-Bt | Type | 51–53 | 408–424 |
| D | Ol-Bt | Type-I | 48–50 | 384–400 |
| E | Ol-Bt | Type-I | 56–57 | 448–456 |
| G | Ol-Bt | Type-I | 52–57 | 416–456 |
| K | Al-Bt | Small girdle | 50–58 | 400–464 |
| L | Gt | Type-I | 51–57 | 408–456 |
| N | Gt | Type-I | 41–48 | 328–384 |
| P | Gt | Type-I | 45–47 | 360–376 |
| Tagami and Takeshita, 1998 (sample with small girdle were excluded) | | | | |
| 1 | Chl | Cleft girdle | 37–40 | 296–320 |
| 2 | Chl | Cleft girdle | 33–34 | 264–272 |
| 3 | Chl | Cleft girdle | 33–36 | 264–288 |
| 4 | Chl | Cleft girdle | 36–38 | 288–304 |
| 5 | Chl | Cleft girdle | 38–39 | 304–312 |
| 6 | Chl | Cleft girdle | 37–42 | 296–336 |
| 7 | Chl | Cleft girdle | 36–37 | 288–296 |
| 8 | Chl | Cleft girdle | 41–42 | 328–336 |
| 9 | Chl | Cleft girdle | 32–37 | 258–296 |
| 10 | Chl | Cleft girdle | 44–45 | 352–360 |
| 11 | Chl | Type-I | 45–50 | 360–400 |

| | | | | |
|----|-----|--------|-------|---------|
| 12 | Chl | Type-I | 49–50 | 392–400 |
| 13 | Chl | Type-I | 47–53 | 376–424 |
| 14 | Chl | Type-I | 54–58 | 432–464 |

Table A1—the results of quartz c-axis fabric opening-angle measurement

| Sample No. | Metamorphic zonation | Fabric-pattern | OA(°) | Deformation-temperature (°C) |
|---|----------------------|----------------|-------|------------------------------|
| Tagami and Takeshita, 1998 (sample with small girdle were excluded) | | | | |
| 15 | Chl | Type-I | 48–52 | 384–416 |
| 18 | Chl | Type-I | 45–47 | 360–376 |
| 23 | Gt | Type-I | 44–48 | 352–384 |
| 24 | Gt | Type-I | 48–50 | 384–400 |
| 25 | Gt | Type-I | 45–47 | 360–376 |
| 26 | Gt | Type-I | 43–50 | 344–400 |
| 27 | Gt | Type-I | 43–48 | 344–384 |
| 28 | Gt | Type-I | 47–48 | 376–384 |
| 29 | Gt | Type-I | 55–60 | 440–480 |
| 30 | Gt | Type-I | 50–52 | 400–416 |
| 31 | Gt | Type-I | 52–53 | 416–424 |
| 33 | Gt | Type-I | 52–53 | 424–432 |
| Yagi and Takeshita, 2002 | | | | |
| T2 | Ol-Bt | Type-II | 53–58 | 424–464 |
| T4 | Ab | Type-I | 55–57 | 440–456 |
| T5 | Gt | Type-I | 44–45 | 352–360 |
| T7 | Gt | Small girdle | 55–58 | 440–464 |
| Wallis et al., 1992 | | | | |
| SB19 | Ol-Bt | Type-I | 38–39 | 304–312 |

Table A1. Quartz c-axis fabric opening-angle measurement

| Sample No. | Metamorphic zonation | Fabric pattern | OA(°) | Deformation T (°C) | Sample No. | Metamorphic zonation | Fabric pattern | OA(°) | Deformation T (°C) |
|-------------------------|----------------------|----------------|-------|--------------------|---|----------------------|----------------|-------|--------------------|
| Sakakibara et al., 1992 | | | | | Tagami and Takeshita, 1998 (small girdle were excluded) | | | | |
| C | Ol-Bt | Type I* | 51–53 | 408–424 | 15 | Chl | Type I | 48–52 | 384–416 |

| | | | | | | | | | |
|--|-------|---------|-------|---------|---------------------------------|-------|---------|-------|---------|
| D | Ol-Bt | Type I | 48–50 | 384–400 | 18 | Chl | Type I | 45–47 | 360–376 |
| E | Ol-Bt | Type I | 56–57 | 448–456 | 23 | Gt | Type I | 44–48 | 352–384 |
| G | Ol-Bt | Type I | 52–57 | 416–456 | 24 | Gt | Type I | 48–50 | 384–400 |
| K | Al-Bt | Small* | 50–58 | 400–464 | 25 | Gt | Type I | 45–47 | 360–376 |
| L | Gt | Type I | 51–57 | 408–456 | 26 | Gt | Type I | 43–50 | 344–400 |
| N | Gt | Type I | 41–48 | 328–384 | 27 | Gt | Type I | 43–48 | 344–384 |
| P | Gt | Type I | 45–47 | 360–376 | 28 | Gt | Type I | 47–48 | 376–384 |
| <u>Tagami and Takeshita, 1998 (small girdle were excluded)</u> | | | | | 29 | Gt | Type I | 55–60 | 440–480 |
| 1 | Chl | Cleft * | 37–40 | 296–320 | 30 | Gt | Type I | 50–52 | 400–416 |
| 2 | Chl | Cleft | 33–34 | 264–272 | 31 | Gt | Type I | 52–53 | 416–424 |
| 3 | Chl | Cleft | 33–36 | 264–288 | 33 | Gt | Type I | 52–53 | 424–432 |
| 4 | Chl | Cleft | 36–38 | 288–304 | <u>Yagi and Takeshita, 2002</u> | | | | |
| 5 | Chl | Cleft | 38–39 | 304–312 | T2 | Ol-Bt | Type II | 53–58 | 424–464 |
| 6 | Chl | Cleft | 37–42 | 296–336 | T4 | Ab | Type I | 55–57 | 440–456 |
| 7 | Chl | Cleft | 36–37 | 288–296 | T5 | Gt | Type I | 44–45 | 352–360 |
| 8 | Chl | Cleft | 41–42 | 328–336 | T7 | Gt | Small | 55–58 | 440–464 |
| 9 | Chl | Cleft | 32–37 | 258–296 | <u>Wallis et al., 1992</u> | | | | |
| 10 | Chl | Cleft | 44–45 | 352–360 | SB19 | Ol-Bt | Type I | 38–39 | 304–312 |
| 11 | Chl | Type I | 45–50 | 360–400 | *Type I: type I cross girdle | | | | |
| 12 | Chl | Type I | 49–50 | 392–400 | Cleft: cleft girdle | | | | |
| 13 | Chl | Type I | 47–53 | 376–424 | Small: small girdle | | | | |
| 14 | Chl | Type I | 54–58 | 432–464 | | | | | |

Appendix B: Differential (shear) stress calculation under any deviatoric stress tensor.

It is the deviatoric component of the stress tensor that causes shearing of materials. In general, definition of this tensor requires knowledge of all three of its principal stresses. However, the difference between the maximum and minimum principal stresses, or differential stress, can be used as an effective measure of the stresses causing deformation. Geological piezometers are presented as equations relating this differential stress to grain size. The main piezometer used in this study (Cross et al., 2017) is based on the results of deformation experiments under uniaxial conditions ($\sigma_1 > \sigma_2 = \sigma_3$) (Cross et al., 2017), or theory under the assumption of uniaxial conditions (Shimizu 2012). Therefore, to convert the output differential stresses to differential stresses in the stress field more representative of natural conditions ($\sigma_1 > \sigma_2 > \sigma_3$), a correction must be made.

795 An overview of the procedure is given below (see also Behr and Platt., 2013). For simplicity, the material is assumed to be isotropic.

800 Deviatoric stress applied to a material causes it to shear and undergo strain. This strain generates elastic strain energy. The dislocation density varies with the amount of elastic strain energy and the recrystallised grain size varies according to the density of dislocations. The elastic strain energy due to the shear is the same amount as the elastic strain energy due to the deviatoric stress tensor the object is subjected to.

805 The relationship between the deviatoric stress tensor (or differential stress) and grain size in the piezometer can then be summarized as the relationship between the elastic strain energy to which the material is subject and the grain size. The elastic strain energy due to the shear is the same amount as the elastic strain energy due to the deviatoric stress tensor the object is subjected to. Therefore, when the deviatoric stress tensor changes, the elastic strain energy applied to the material also changes, and the grain size will be different even if the differential stress is the same.

810 The second invariant of the deviatoric stress tensor, J_2 , is a scalar quantity that describes the magnitude of the elastic strain energy stress-tensor-independent-of-its-orientation and is given by the following equation.

$$J_2 = \frac{[\sigma_1^2 + \sigma_2^2 + \sigma_3^2 - (\sigma_1\sigma_2 + \sigma_2\sigma_3 + \sigma_3\sigma_1)]}{3} \quad (1)$$

Where σ_i is the magnitude of the principal stresses.

815 Substituting any stress condition,

$$\sigma_2 = (1 - m)\sigma_1 + m\sigma_3, \quad 0 < m < 1 \quad (2)$$

Eq. (1) is transformed into the following

$$J_2 = \frac{(m^2 - m + 1)(\sigma_1^2 + \sigma_3^2)}{3} \quad (3)$$




Figure B1: Value of J_2 normalized by max value. The horizontal axis indicates m in the above equation. 0.5: plane stress, 0 or 1: uniaxial.

It can be seen from Eq. (3) and Fig. B1 that the elastic strain energy varies with the deviatoric stress tensor for the same differential stress: in the plane stress condition, it is 3/4 times lower than for uniaxial conditions, where it reaches a maximum value. In order to give the same strain energy, this second invariant should show the same value. Therefore, to result in the same strain energy in the natural plane stress field as that given to quartz in the uniaxial compression test, the differential stress

$(\sigma_1 - \sigma_3)$ for plane stress has to be greater by a factor of $\sqrt{\frac{4}{3}} = \frac{2}{\sqrt{3}}$.

Since the dynamically recrystallized quartz grains measured in this study were generated in a natural stress field with conditions inferred to be close to plane stress, the original differential stress in natural conditions can be calculated by

825 multiplying the piezometer results by $\frac{2}{\sqrt{3}}$ ~~to 1~~. Since maximum shear stress is 0.5 times the differential stress, the maximum shear stress can be calculated by dividing the measurement result by $\frac{4}{\sqrt{3}}$ ~~to 2~~.

Appendix C: Error calculation method when using the Cross et al. (2017) piezometer

The Cross et al. (2017) piezometer can be written as follows using the Briggsian logarithm of the experimentally obtained differential stress and the Briggsian logarithm of the recrystallized grain size:

$$\log_{10}RMS = a + b \log_{10}\sigma \quad (4)$$

where RMS is root mean square grain size (μm), σ is differential stress (MPa), and a, b are parameters obtained by fitting experimental data. The errors shown in the piezometer of Cross et al. (2017) are derived from parameter fitting.

835 When substituting the measured grain size into this piezometer, we consider the error propagation between the error of the piezometer and the measured grain size (the Briggsian logarithm of the RMS: $\log_{10}RMS$). The standard error of "the mean of the squares of particle sizes" can be calculated by using the Central Limit Theorem. The Briggsian logarithm of the square root of "the mean of the squares of the particle sizes" is " $\log_{10}RMS$ ". Therefore, we generated 10000 random numbers following a normal distribution with the mean and standard deviation of the "mean of the squares of particle sizes" and calculated the Briggsian logarithm of the square root of the generated random numbers to obtain a random number following

840 " $\log_{10}RMS$ ". By calculating the mean and standard deviation of these random numbers, the mean and standard deviation of " $\log_{10}RMS$ " were calculated and used as the error of the measured particle size. In this study, the code of Cross et al. (2017) was modified to perform the calculation (Code and data available).

Finally, the error in the measured particle size and the error in the piezometer were substituted into the error propagation equation. Since a and b were obtained from the same experiment, correlation coefficients were calculated.

$$845 \quad f(a, b, Y) = \log_{10}\sigma = \frac{\log_{10}RMS - a}{b} \quad (5)$$

$$S_{\log_{10}\sigma} = \sqrt{\left(\frac{\partial f}{\partial a}\right)^2 s_a^2 + \left(\frac{\partial f}{\partial b}\right)^2 s_b^2 + \left(\frac{\partial f}{\partial Y}\right)^2 s_Y^2 + 2\left(\frac{\partial f}{\partial a}\right)\left(\frac{\partial f}{\partial b}\right) s_{ab}}$$

$$= \sqrt{\left(\frac{1}{-1.41}\right)^2 (S_{\log_{10}RMS})^2 + \left(\frac{\log_{10}RMS - 3.91}{(-1.41)^2}\right)^2 (0.211)^2 + \left(\frac{1}{-1.41}\right)^2 (0.21)^2 + 2\left(\frac{1}{-1.41}\right)\left(\frac{\log_{10}RMS - 3.91}{(-1.41)^2}\right) 0.096} \quad (6)$$

S is the standard deviation (error). Uncertainties of estimated differential (shear) stress are related to both the piezometer and the grain size measurement.

850 Appendix D: Error calculation method when using the Shimizu (2012) piezometer

The Shimizu (2012) piezometer can be written as follows using the differential stress σ , deformation temperature T, and the mode of the natural logarithm of the recrystallized grain size (defined as ModelnD):

$$ModelnD = \ln(9.98 \times 10^2 \times \sigma^{-1.25}) + \frac{12.4 \text{ kJmol}^{-1}}{RT} \quad (7)$$

855 ModelnD is measured by the probability density of logarithmic grain sizes obtained by applying kernel density estimation to the grain size histogram. Since the logarithmic grain size distribution can be regarded as the logarithmic normal distribution (Shimizu, 1998), and ModelnD is almost identical to the mean of the power index of grain size, the confidence interval of ModelnD can be calculated using the properties of a Student's t-distribution. However, the number of data is at least 72 (number of grains), indicating that Student's t-distribution closely approximates a standard normal distribution. Therefore, the standard error of ModelnD was calculated using the Central Limit Theorem. In this study, the code of Cross et al. (2017) was modified to perform the calculation (Code and data available).

860 The uncertainties by the piezometer of Shimizu (2012) are not shown. Therefore, uncertainties of estimated differential (shear) stresses are only related to grain size measurement and deformation temperature.

$$S_{\log_e\sigma} = \sqrt{\left(\frac{1}{1.25}\right)^2 (S_{ModelnD})^2 + \left(\frac{1193.7}{(Deformation\ Temperature)^2}\right)^2 (S_{Deformation\ Temperature})^2} \quad (8)$$

S is the standard deviation (error).

865

Code and data availability: Code and data are available at <https://doi.org/10.5281/zenodo.100169508085144> (Koyama et al., 2023); <https://github.com/YukinojoKoyama/Koyama-et-al.CodeandData/tree/v1.0.0>; <https://github.com/YukinojoKoyama/Koyama-et-al.CodeandData/tree/v1.1.0>

Author contributions: YK and SWR developed the conceptualization of this study. All authors conducted geological field surveys and specimen sampling. TN and YK designed thin section production methods. TN provided the SEM-EBSD analysis method and appropriate analysis conditions. Crystallographic orientations were collected by YK and TN. Stress and deformation temperature estimation method were organized by all authors. YK was involved in the data curation and modified

870

書式を変更: フォント: (英) Times

computer programs from previous studies. All authors were involved in the validation process. The interpretation of the dataset, preparation of the original draft, figure design, reviews, and editing of the paper were carried by all authors.

875 **Competing interests:** The authors declare that they have no conflict of interest.

Acknowledgments: We are grateful to Ken Yamaoka and Thomas Yeo of the University of Tokyo for a lot of useful advice concerning the polishment of thin sections and the deformation mechanisms of quartz. We also thank Kazuhito Ozawa, Asuka Yamaguchi, Yukio Masumoto, and all the members of the SGT and Petrotectonics seminar at the University of Tokyo for helpful discussions and suggestions on this research. [We also thank two anonymous referees and the topic editor, Federico](#)

880 [Rossetti, for their useful comments that helped to improve the paper and for conducting the peer review process.](#) People that have contributed to MTEX are also acknowledged for providing an open-source MTEX toolbox for MATLAB. This research was supported by JSPS Grants in Aid 21H05202, 21H01188 and 20KK0079 awarded to SW.

References

- 885 [Alaoui, K., Airaghi, L., Stünitz, H., Raimbourg, H., and Précigout, J.: Different mechanical behavior at the same P-T conditions in biotite-quartz assemblage: interconnectivity and composition effect of experimentally deformed mica, EGU-General Assembly 2022, doi: 10.5194/egusphere-egu22-5108, 2022.](#)
- Aoya, M.: P-T-D Path of Eclogite from the Sambagawa Belt Deduced from Combination of Petrological and Microstructural Analyses, *J. Petrol.*, 42(7), 1225–1248, 2001.
- Aoya, M.: Structural position of the Seba eclogite unit in the Sambagawa Belt: Supporting evidence for an eclogite nappe, *Isl. Arc.*, 11, 91–110, doi:10.1046/j.1440-1738.2002.00359.x, 2002.
- 890 Aoya, M. and Endo, S.: Recognition of the ‘early’ Sambagawa metamorphism and a schematic cross-section of the Late-Cretaceous Sambagawa subduction zone, *J. Geol. Soc. Japan.*, 123(9), 677–698, doi:10.5575/geosoc.2017.0008, 2017.
- Aoya, M., Noda, A., Mizuno, K., Mizukami, T., Miyachi, Y., Matsuura, H., Endo, S., Toshimitsu, S., and Aoki, M.: Geology of the Niihama District. Quadrangle Series 1:50,000, *Geol. Surv. Japan.*, AIST., 2009.
- 895 Aoya, M., Endo, S., Mizukami, T., and Wallis, S. R.: Paleo-mantle wedge preserved in the Sambagawa high-pressure: Metamorphic belt and the thickness of forearc continental crust, *Geology*, 41(4), 451–454, doi:10.1130/G33834.1, 2013a.
- Aoya, M., Noda, A., Mizuno, K., Mizukami, T., Miyachi, Y., Matsuura, H., Endo, S., Toshimitsu, and S., Aoki, M.: Geology of the Niihama District. Quadrangle Series 1:50,000, *GSJ. AIST.*, Tsukuba, 2013b.
- Aoya, M., Mizukami, T., and Endo, S.: Geologic traverse of the Sambagawa metamorphic belt in central Shikoku, SW Japan, *J. Geol. Soc. Japan.*, 123(7), 491–514, Doi:10.5575/geosoc.2017.0038, 2017.
- 900 Bachmann, F., Hielscher, R., and Schaeben, H.: Grain detection from 2d and 3d EBSD data-Specification of the MTEX algorithm, *Ultramicroscopy*, 111(12), 1720–1733, doi:10.1016/j.ultramic.2011.08.002, 2011.
- Banno, Shohei. and Sakai, Chihiro.: Geology and metamorphic evolution of the Sanbagawa metamorphic belt, Japan, *Geol. Soc. Lond. Spec. Pub.*, 43, 519–532, doi:10.1144/GSL.SP.1989.043.01.50, 1989.

- 905 Behr, W. M., and Bürgmann, R.: What's down there? The structures, materials and environment of deep-seated slow slip and tremor, *Phil. Trans. R. Soc. A.*, 379(2193), doi.org/10.1098/rsta.2020.0218, 2021.
- Behr, W. M. and Platt, J. P.: Rheological evolution of a Mediterranean subduction complex, *J. Struct. Geol.*, 54, 136–155, doi:10.1016/j.jsg.2013.07.012, 2013.
- Berman, R. G.: Internally-Consistent Thermodynamic Data for Minerals in the System Na₂O-K₂O-CaO-MgO-FeO-Fe₂O₃-Al₂O₃-SiO₂-TiO₂-H₂O-CO₂. *J. Petrol.*, 29 (2), 445–522, <https://doi.org/10.1093/petrology/29.2.445>, 1998.
- 910 Burnham, C. W., Holloway, J. R., and Davis, N. F.: The thermodynamic properties of water to 1000°C and 10,000 bars, *Geol. Soc. Amer. Spec. Paper*, pp.96, ISBN 13: 9780813721323, 1969.
- Chang, C., McNeill, L. C., Moore, J. C., Lin, W., Conin, M., and Yamada, Y.: In situ stress state in the Nankai accretionary wedge estimated from borehole wall failures, *Geochem. Geophys. Geosy.*, 11(12), doi:10.1029/2010GC003261, 2010.
- 915 Condit, C. B., French, M. E., Hayles, J. A., Yeung, L. Y., Chin, E. J., and Lee, C. A.: Rheology of Metasedimentary Rocks at the Base of the Subduction Seismogenic Zone. *Geochem. Geophys. Geosy.*, 23 (2), <https://doi.org/10.1029/2021GC010194>, 2022.
- Cross, A. J., Prior, D. J., Stipp, M., and Kidder, S.: The recrystallized grain size piezometer for quartz: An EBSD-based calibration, *Geophys. Res. Lett.*, 44(13), 6667–6674, doi:10.1002/2017GL073836, 2017.
- 920 De Bresser, J. H. P., Peach C.J., Rejis, J. P. J., Spiers, C. J., On dynamic recrystallization during solid state flow: Effects of stress and temperature, 25(18), 3457–3460, *Geophys. Res. Lett.*, doi.org/10.1029/98GL02690, 1998.
- Den Brok, S. W. J.: Effect of microcracking on pressure-solution strain rate: The Gratz grain-boundary model, *Geology*, 26 (10), 915–918, [https://doi.org/10.1130/0091-7613\(1998\)026<0915:EOMOPS>2.3.CO;2](https://doi.org/10.1130/0091-7613(1998)026<0915:EOMOPS>2.3.CO;2), 1998.
- Derby, B.: The dependence of grain size on stress during recrystallization, *Acta. Metall. Mater.*, 39(5), 955–962, doi:10.1016/0956-7151(91)90295-C, 1991.
- 925 Enami, M., Wallis, S. R., and Banno, Y.: Paragenesis of sodic pyroxene-bearing quartz schists: implications for the P-T history of the Sanbagawa belt, *Contrib. Mineral. Petr.*, 116, 182–198, doi:10.1007/BF00310699, 1994.
- Endo, S. and Wallis, S. R.: Structural architecture and low-grade metamorphism of the Mikabu-Northern Chichibu accretionary wedge, SW Japan, *J. Metamorph. Geol.*, 35(6), 695–716, doi:10.1111/jmg.12251, 2017.
- 930 Endo, S. and Yokoyama, S.: Geology of the Motoyama District. Quadrangle Series 1:50,000, *Geol. Soc. Japan.*, Tsukuba, 2019.
- Endo, S., Wallis, S., Hirata, T., Anczkiewicz, R., Platt, J., Thirlwall, M., and Asahara, Y.: Age and early metamorphic history of the Sanbagawa belt: Lu-Hf and P-T constraints from the Western Iratsu eclogite, *J. Metamorph. Geol.*, 27(5), 371–384, doi:10.1111/j.1525-1314.2009.00821.x, 2009.
- 935 Endo, S., Wallis, S. R., Tsuboi, M., Aoya, M., and Uehara, S.: Slow subduction and buoyant exhumation of the Sanbagawa eclogite, *Lithos*, 146–147, 183–201. doi:10.1016/j.lithos.2012.05.010, 2012.
- Engelbreton D. C., Cox A., Gordon R. G.: Relative Motions Between Oceanic and Continental Plates in the Pacific Basin, *Geol. Soc. Am.*, doi:10.1130/SPE206-p1, 1985.

書式を変更: フォントの色: 赤

書式を変更: フォントの色: 赤

書式を変更: フォントの色: 赤

- England, P.: On Shear Stresses, Temperatures, and the Maximum Magnitudes of Earthquakes at Convergent Plate Boundaries, *J. Geophys. Res.-sol. EA.*, 123(8), 7165–7202, doi:10.1029/2018JB015907, 2018.
- 940 Farver, J. and Yund, R.: Silicon diffusion in a natural quartz aggregate: constraints on solution-transfer diffusion creep, *Tectonophysics*, 325 (3–4), 193–205, https://doi.org/10.1016/S0040-1951(00)00121-9, 2000.
- Faure, M.: Microtectonic evidence for eastward ductile shear in the Jurassic orogen of SW Japan, *J. Struct. Geol.*, 7(2), 175–186, doi:10.1016/0191-8141(85)90130-0, 1985.
- 945 Fournier, R. O. and Potter II, R. W.: An equation correlating the solubility of quartz in water from 25° to 900°C at pressures up to 10,000 bars, *Geochim. Cosmochim. Ac.*, 46 (10), 1969–1973, https://doi.org/10.1016/0016-7037(82)90135-1, 1982.
- Gao, Xiang. and Wang, Kelin.: Strength of stick-slip and creeping subduction megathrusts from heat flow observation, *Science*, 345(6200), 1038–1041, doi:10.1126/science.1255487, 2014.
- 950 Giuntoil, F., Viola, G., and Sørensen, B. E.: Deformation Mechanisms of Blueschist Facies Continental Metasediments May Offer Insights Into Deep Episodic Tremor and Slow Slip Events, *J. Geophys. Res.-Sol. Ea.*, 127 (10), https://doi.org/10.1029/2022JB024265, 2022.
- Goddard, R. M., Hansen, L. N., Wallis, D., Stipp, M., Holyoke, C. W. III, Kumamoto, K. M., and Kohlstedt, D. L.: A Subgrain-Size Piezometer Calibrated for EBSD, *Geophys. Res. Lett.*, 47(e2020GL090056), doi:10.1029/2020GL090056, 2020.
- 955 Hara, H., Aoya, M., Noda, A., Tanabe, S., Yamasaki, T., Ohno, T., and Komazawa, M.: Geological map of Japan 1:200000. Kochi (2nd edition), *Geol. Soc. Japan.*, Tsukuba, 2018.
- Handy, M. R.: Flow laws for rocks containing two non-linear viscous phases: A phenomenological approach, *J. Struct. Geol.*, 16 (3), 287–301, https://doi.org/10.1016/0191-8141(94)90035-3, 1994.
- Hickman, S. H. and Evans, B.: Kinetics of pressure solution at halite-silica interfaces and intergranular clay films, *J. Geophys. Res.-Sol. Ea.*, 100 (87), 13113–13132, https://doi.org/10.1029/95JB00911, 1995.
- 960 Higashino, T.: The higher grade metamorphic zonation of the Sambagawa metamorphic belt in central Shikoku, Japan, *J. Metamorph. Geol.*, 8(4), 413–423, doi:10.1111/j.1525-1314.1990.tb00628.x, 1990.
- Holland, T. J. B. and Powell, R.: An internally consistent thermodynamic data set for phases of petrological interest, *J. Metamorph. Geol.*, 16 (3), 309–343, https://doi.org/10.1111/j.1525-1314.1998.00140.x, 2004.
- 965 Holyoke, C. W. and Kronenberg, A. K.: Accurate differential stress measurement using the molten salt cell and solid salt assemblies in the Griggs apparatus with applications to strength, piezometers and rheology, *Tectonophysics*, 494(1–2), 17–31, doi:10.1016/j.tecto.2010.08.001, 2010.
- Hunter N. J. R., Hasalová, P., Weinberg, R. F., and Wilson, C. J. L.: Fabric controls on strain accommodation in naturally deformed mylonites: The influence of interconnected micaceous layers, *J. Struct. Geol.*, 83, 180–193, https://doi.org/10.1016/j.jsg.2015.12.005, 2016.
- 970 Ishii, K. and Wallis, Simon. R.: High- and low-stress subduction zones recognized in the rock record, *Earth. Planet. Sc. Lett.*, 531, doi:10.1016/j.epsl.2019.115935, 2020.

書式を変更: フォントの色: 赤

Isozaki, Y. and Itaya, T.: Chronology of Sanbagawa metamorphism. *J. Metamorph. Geol.*, 8(4), 401–411, doi:10.1111/j.1525-1314.1990.tb00627.x, 1990.

Ito, Y., Obara, K.: Very low frequency earthquakes within accretionary prisms are very low stress-drop earthquakes, *Geophys. Res. Lett.*, 33(9), doi.org/10.1029/2006GL025883, 2006.

Kawahara, H., Endo, S., Wallis, S. R., Nagaya, T., Mori, H., and Asahara, Y.: Brucite as an important phase of the shallow mantle wedge: Evidence from the Shiraga unit of the Sanbagawa subduction zone, SW Japan, *Lithos.* 254–255, 53–66, https://doi.org/10.1016/j.lithos.2016.02.022, 2016.

Kouketsu, Y., Sadamoto, K., Umeda, H., Kawahara, H., Nagaya, T., Taguchi, T., Mori, H., Wallis, S., and Enami, M.: Thermal structure in subducted units from continental Moho depths in a palaeo subduction zone, the Asemigawa region of the Sanbagawa metamorphic belt, SW Japan, *J. Metamorph. Geol.*, 39(6), 727–749, doi:10.1111/jmg.12584, 2021.

Koyama, Y., Wallis, S. R., Nagaya T.: YukinojoKoyama/Koyama-et-al.CodeandData: Code and Data (v1.10.0), Zenodo, https://doi.org/10.5281/zenodo.100169508085144, 2023.

Kruhl, J. H.: Reply: prism- and basal-plane parallel subgrain boundaries in quartz: a microstructural geothermobarometer, *J. Metamorph. Geol.*, 16(1), 142–146, doi:10.1111/j.1525-1314.1998.00063.x, 1998.

Law, R. D.: Deformation thermometry based on quartz c-axis fabrics and recrystallization microstructures: A review, *J. Struct. Geol.*, 66, 129–161, doi:10.1016/j.jsg.2014.05.023, 2014.

Lin, W.: Determination of in-situ stress state in a Japan Trench Fast Drilling Project (JFAST) borehole one year after the Tohoku-Oki great earthquake, *International Journal of the JRCM*, 10(1), 1–4, doi:10.11187/ijjrcm.10.1, 2014.

Lusk, A. D. J., Platt, J. P., and Platt, J. A.: Natural and Experimental Constraints on a Flow Law for Dislocation-Dominated Creep in Wet Quartz, *J. Geophys. Res-Sol. Ea.*, 126 (5), https://doi.org/10.1029/2020JB021302, 2021.

Mariani, E., Brodie, K. H., and Rutter, E. H.: Experimental deformation of muscovite shear zones at high temperatures under hydrothermal conditions and the strength of phyllosilicate-bearing faults in nature, *J. Struct. Geol.*, 28(9), 1569–1587, doi:10.1016/j.jsg.2006.06.009, 2006.

Morgan, S. S. and Law, R. D.: Unusual transition in quartzite dislocation creep regimes and crystal slip systems in the aureole of the Eureka Valley-Joshua Flat-Beer Creek pluton, California: A case for anhydrous conditions created by decarbonation reactions, *Tectonophysics*, 384(1–4), 209–231, doi:10.1016/j.tecto.2004.03.016, 2004.

Mori, H. and Wallis, S.: Large-scale folding in the Asemi-gawa region of the Sanbagawa Belt, southwest Japan, *Isl. Arc.*, 19(2), 357–370, doi:10.1111/j.1440-1738.2010.00713.x, 2010.

Nagaya, T., Okamoto, A., Kido, M., Muto, J., and Wallis, S. R.: Dehydration of brucite + antigorite under mantle wedge conditions: insights from the direct comparison of microstructures before and after experiments, *Contrib. Mineral. Petr.*, 177(87), doi:10.1007/s00410-022-01956-z, 2022.

Okamoto, A. and Toriumi, M.: Progress of actinolite-forming reactions in mafic schists during retrograde metamorphism: An example from the Sanbagawa metamorphic belt in central Shikoku, Japan, *J. Metamorph. Geol.*, 23(5), 335–356, doi:10.1111/j.1525-1314.2005.00580.x, 2005.

書式を変更: フォントの色: 赤

書式を変更: フォントの色: 赤

- Okamoto, K., Shinjoe, H., Katayama, I., Terada, K., Sano, Y., and Johnson, S.: SHRIMP U-Pb zircon dating of quartz-bearing eclogite from the Sanbagawa Belt, south-west Japan: Implications for metamorphic evolution of subducted protolith, *Terra Nova.*, 16(2), 81–89, doi:10.1111/j.1365-3121.2004.00531.x, 2004.
- Obara, K.: Characteristic activities of slow earthquakes in Japan, *P. Jpn. Acad. B-phys.*, 96(7), 297–315, doi.org/10.2183/pjab.96.022, 2020.
- Passchier, C. W. and Trouw, R. A. J.: *Microtectonics* (2nd ed.), Springer Berlin Heidelberg, Germany, 366, doi:10.1007/3-540-29359-0, 2005.
- Passeleque, F. X., Almakari, M., Dublanchet, P., Barras, F., Fortin, J., and Violay, M.: Initial effective stress controls the nature of earthquakes, *Nat. Commun.*, 11, 5132, doi.org/10.1038/s41467-020-18937-0, 2020.
- 1015 Radvanec, M., Banno, S., and Okamoto, K.: Multiple stages of phengite formation in Sanbagawa schists, *Miner. Petrol.*, 51, 37–48, 1994.
- Rutter, E., H.: A Discussion on natural strain and geological structure - The kinetics of rock deformation by pressure solution, *Philos. T. R. Soc. A.*, 283 (1312), 203–219, https://doi.org/10.1098/rsta.1976.0079, 1976.
- Sakakibara, N., Hara, I., Kanai, K., Shiota, T., Hide, K., & Paulitsch, P.: Quartz microtextures of the Sambagawa schists and their implications in convergent margin processes, *Isl. Arc.*, 1, 186–197, doi:10.1111/j.1440-1738.1992.tb00069.x, 1992.
- 1020 Sands, D., E.: *Introduction to Crystallography*, W.A. Benjamin Inc., ISBN 13: 9780805384734, 1969.
- Schmidt, W. L. and Platt J. P.: Stress, microstructure, and deformation mechanisms during subduction underplating at the depth of tremor and slow slip, *Franciscan Complex, northern California, J. Struct. Geol.*, 154, https://doi.org/10.1016/j.jsg.2021.104469, 2022.
- 1025 Shimizu, I.: A stochastic model of grain size distribution during dynamic recrystallization, *Philos. Mag.*, 79(5), 1217–1231, doi.org/10.1080/01418619908210357, 1998
- Shimizu, I.: Theories and applicability of grain size piezometers: The role of dynamic recrystallization mechanisms, *J. Struct. Geol.*, 30(7), 899–917, doi:10.1016/j.jsg.2008.03.004, 2008.
- Shimizu, I.: Steady-State Grain Size in Dynamic Recrystallization of Minerals, in: *Recrystallization*, edited by Sztwiertnia, K., Intech, 371–386, doi:10.5772/33701, 2012.
- 1030 Stipp, M. and Tullis, J.: The recrystallized grain size piezometer for quartz, *Geophys. Res. Lett.*, 30(21), https://doi.org/10.1029/2003GL018444, 2003.
- Stipp, M., Stünitz, H., Heilbronner, R., and Schmid, S. M.: The eastern Tonalite fault zone: A “natural laboratory” for crystal plastic deformation of quartz over a temperature range from 250 to 700 °C, *J. Struct. Geol.*, 24(12), 1861–1884, doi:10.1016/S0191-8141(02)00035-4, 2002.
- 1035 Tagami, M. and Takeshita, T.: c-Axis fabrics and microstructures in quartz schist from the Sambagawa metamorphic belt, central Shikoku, Japan, *J. Struct. Geol.*, 20(11), 1549–1568, doi:10.1016/S0191-8141(98)00044-3, 1998.
- Takeshita, T.: Quartz microstructures from the sambagawa metamorphic rocks, southwest japan: Indicators of deformation conditions during exhumation, *Minerals-basel.*, 11(1038), https://doi.org/10.3390/min11101038, 2021.

書式を変更: フォントの色: 赤

書式を変更: インデント: 左: 0 mm, ぶら下げインデント: 1 字, 最初の行: -1 字

書式を変更: フォントの色: 赤

- 1040 [Trepmann, C. A. and Seybold, L.: Deformation at low and high stress-loading rates, *Geosci. Front.*, 10\(1\), 43–54, <https://doi.org/10.1016/j.gsf.2018.05.002>, 2019.](#)
- [Tulley, C. J., Fagereng, A., and Ujiie, K.: Hydrous oceanic crust hosts megathrust creep at low shear stresses, *Sci. Adv.*, 6\(22\), DOI: 10.1126/sciadv.aba1529, 2020.](#)
- Twiss, R. J.: Theory and Applicability of a Recrystallized Grain Size Paleopiezometer, *Pageoph*, 115, 227–244, [doi:10.1007/BF01637105](https://doi.org/10.1007/BF01637105), 1977.
- Twiss, R. J.: Static theory of size variation with stress for subgrains and dynamically recrystallized grains, in: Proceeding of conference IX. Magnitude of deviatoric stress in the earth's crust and upper mantle, U.S. Department of The Interior, Menlo Park, California, America, 665-683, doi: 10.3133/ofr80625, 1980.
- 1050 [Ujiie, K., Saishu, H., Fagereng, A., Nishiyama, N., Otsubo, M., Masuyama, H., and Kagi, H.: An Explanation of Episodic Tremor and Slow Slip Constrained by Crack-Seal Veins and Viscous Shear in Subduction Mélange, *Geophys. Res. Lett.*, 45\(11\), 5371–5379, <https://doi.org/10.1029/2018GL078374>, 2018.](#)
- Vavryčuk, V.: Earthquake Mechanisms and Stress Field, in: *Encyclopedia of Earthquake Engineering*, edited by: Beer, M., Kougoumtzoglou, I.A., Patelli, E., and Au, S-K., Springer, Berlin, Heidelberg, Germany, 728-746, doi:10.1007/978-3-642-35344-4, 2015.
- 1055 Wallis, S. R.: The timing of folding and stretching in the Sambagawa belt: The Asemigawa region, central Shikoku, *J. Geol. Soc. Japan.*, 96(5), 345–352, [doi:10.5575/geosoc.96.345](https://doi.org/10.5575/geosoc.96.345), 1990.
- Wallis, S. R.: Vorticity analysis in a metachert from the Sanbagawa Belt, SW Japan, *J. Struct. Geol.*, 14(3), 271–280, [doi:10.1016/0191-8141\(92\)90085-B](https://doi.org/10.1016/0191-8141(92)90085-B), 1992.
- Wallis, S.: Exhuming the Sanbagawa metamorphic belt: the importance of tectonic discontinuities, *J. Struct. Geol.*, 16, 83-95, 1060 1998.
- Wallis, S. R., Banno, S., and Radvanec, M.: Kinematics, structure and relationship to metamorphism of the east-west flow in the Sanbagawa Belt, southwest Japan, *Isl. Arc.*, 1(1), 176–185, [doi:10.1111/j.1440-1738.1992.tb00068.x](https://doi.org/10.1111/j.1440-1738.1992.tb00068.x), 1992.
- Wallis, S. R., Anezkievicz, R., Endo, S., Aoya, M., Platt, J. P., Thirlwall, M., and Hirata, T.: Plate movements, ductile deformation and geochronology of the Sanbagawa belt, SW Japan: Tectonic significance of 89-88 Ma Lu-Hf eclogite ages, 1065 *J. Metamorph. Geol.*, 27(2), 93–105, <https://doi.org/10.1111/j.1525-1314.2008.00806.x>, 2009.
- Yagi, K. and Takeshita, T.: Regional variation in exhumation and strain rate of the high-pressure Sambagawa metamorphic rocks in central Shikoku, south-west Japan, *J. Metamorph. Geol.*, 20, 633–647, [doi:10.5575/geosoc.112.S101](https://doi.org/10.5575/geosoc.112.S101), 2002.
- Yoshida, K., Hasegawa, A., and Okada, T.: Spatial variation of stress orientations in NE Japan revealed by dense seismic observations, *Tectonophysics*, 647–648, 63–72, [doi:10.1016/j.tecto.2015.02.013](https://doi.org/10.1016/j.tecto.2015.02.013), 2015.
- 1070 Yoshioka, S., Murakami, K.: Temperature distribution of the upper surface of the subducted Philippine Sea Plate along the Nankai Trough, southwest Japan, from a three-dimensional subduction model: relation to large interplate and low-frequency earthquakes, *Geophys. J. Int.*, 171(1), 302–315, [doi:10.1111/j.1365-246X.2007.03510.x](https://doi.org/10.1111/j.1365-246X.2007.03510.x), 2007.

書式を変更: フォントの色: 赤

書式を変更: フォントの色: 赤