




8-Way Stripline Power Divider

MODEL D-058-8

OUTLINE DRAWING

UNIT: INCH



| ELECTRICAL SPECIFICATIONS | FREQUENCY RANGE | | 0.5-8.0 | GHz |
|---------------------------|-------------------|------------|---------|--------|
| | | INPUT VSWR | Max. | 1.50:1 |
| | OUTPUT VSWR | Max. | 1.50:1 | |
| | AMPLITUDE BALANCE | Max. | 0.50 | dB |
| | PHASE BALANCE | Max. | 5.0 | Deg. |
| | INSERTION LOSS | Max. | 6.00 | dB |
| | ISOLATION | Min. | 16.0 | dB |
| POWER RATING | Avg. | | 20.0 | W |
| | Peak | | 3.0 | kW |

| PHYSICAL SPECIFICATIONS | CONNECTOR TYPE | | SMA Female |
|-------------------------|-------------------|--------|-----------------|
| | | WEIGHT | Max. |
| | OPERATIONAL TEMP. | | - 32 to + 85 °C |



Electromagnetic Technologies Industries, Inc. (ET Industries)
 50 Intervale Road, Boonton, NJ, 07005, USA E-Mail: sales@etiworld.com
 Phone: 001+(973)-394-1719 Fax: 001+(973)394-1710 www.etiworld.com