





EVOLine® Modules



EVoline® Modular System

Maximum Individuality

EVoline systems can be configured to individual needs with a wide range of modules available - there is no general solution for the supply of e-connectivity.

Often just power sockets are the sufficient configuration: in a different environment international sockets plus USB Chargers may be the right choice. With telephones, EDP and multimedia connectors options become even more diverse.

Whether a data or a HDMI connector, the individual application defines the requirements. Realizable combinations of shown modules depend on the UL regulations. Please ask for more information.



The modular approach of EVoline opens nearly endless possibilities of bespoke configurations and connectivity solutions. Either for the electrification of work places in an open-plan office or in the kitchen at home:

EVoline offers the perfect solution for every task.

EVoline products can be equipped with a wide range of switches, power sockets, and modules for data, multimedia and safety.



EVoline® FlipTop *Push*



EVoline® Dock



EVoline® R-Dock



EVoline® V-Dock













EVoline® FrameDock







EVoline® U-Dock








The chart below gives an overview about country specific socket versions. Deviations may occur.

Socket VDE (CEE 7/3) 230 V, 16 A		Plug Type F, E+F, C	Algeria, Andorra, Armenia, Austria, Bosnia and Herzegovina, Bulgaria, Estonia, Finland, Georgia, Germany, Hungary, Iceland, Latvia, Lithuania, Luxembourg, Macedonia, Moldova, Montenegro, Netherlands, Norway, Portugal, Romania, Russia, Serbia, South Korea, Spain, Ukraine
Socket (CEE 7/5) 230 V, 16 A		Plug Type E, E+F, C	France, Belgium, Cameroon, Czech Republic, Mali, Morocco, Poland, Slovakia, Tunisia
Socket (BS 962A) 230 V, 3,15 A oder 5 A		Plug Type G	Great Britain, Bahrain, Cyprus, Hong Kong, Indonesia, Ireland, Kenya, Kuwait, Malaysia, Malta, Mauritius, Nigeria, Oman, Qatar, Saudi Arabia, Singapore, United Arab Emirates, Zimbabwe
Socket (SEV 1011) 230 V, 10 A, T13		Plug Type J, C	Switzerland, Liechtenstein
Socket (SEV 1011) 230 V, 16 A, T23		Plug Type J, C	Switzerland, Liechtenstein
Socket (DS 608842-D1) 230 V, 13 A		Plug Type K, C	Denmark, Greenland
Socket (DS 608842-D1) 230 V, 13 A, EDV		Plug Type K EDV	Denmark, Greenland
Socket (CEI 23-16-VII) 230 V, 16 A oder 10 A		Plug Type L, C	Italy, Chile, Cuba
Socket (AS 3112) 230 V, 10 A		Plug Type I	Australia, New Zealand, Papua New Guinea, several Pacific Islands
Socket (NEMA 5-15) 120 V, 15 A		Plug Type B	USA, Canada, Cuba, Ecuador, Jamaica, Japan, Mexico, Paraguay, Peru, Philippines, Taiwan, Venezuela, various Caribbean Islands




EVOLine® Sockets

Description	Picture	Order Nr. & Specifications	<i>Dock</i> <i>FrameDock</i> <i>Port</i> <i>R-Dock</i> <i>V-Dock</i> <i>U-Dock</i> <i>FlipTop Push</i>
<p>Socket 0°, 15 A</p> <p>USA, Canada, for plug type: B (NEMA, 5-15) black</p> <p>Installation dimensions: 50 x 50 mm (1 31/32 x 1 31/32")</p>		<p>9332 3640 6600 with tamper resistance</p>	<ul style="list-style-type: none"> • • • • • •
<p>Socket 60°, 15 A</p> <p>USA, Canada, for plug type: B (NEMA, 5-15)</p> <p>Installation dimensions: 50 x 50 mm (1 31/32 x 1 31/32")</p>		<p>9332 3650 6600 with tamper resistance</p>	<ul style="list-style-type: none"> • • • • • •
<p>Socket 0°, 15 A Angled Outlet</p> <p>USA, Canada, for plug type: B (NEMA, 5-15) Not suitable for angled plugs.</p> <p>Installation dimensions: 75 x 50 mm (2 61/64 x 1 31/32")</p>		<p>9332 3630 6600 with tamper resistance and flap</p>	<ul style="list-style-type: none"> • • • • • •
<p>USB Charger</p> <p>USB Type A Charger, charging function only. Rated supply voltage: 100-240 VAC +/-10%. No-load power consumption at 230 VAC <= 0,1 Watt. Output voltage: 5VDC +/-5%. Rated output current: 1 A</p> <p>Installation dimensions: 25 x 50 mm (63/64 x 1 31/32")</p>		<p>9331 5580 6600 black - 1 A</p>	<ul style="list-style-type: none"> • • • • • •




1) Technical changes and printing errors reserved.

Description	Picture	Order Nr. & Specifications	<div style="display: flex; flex-direction: column; align-items: center; gap: 5px;"> ✓ Dock ✓ FrameDock ✓ Port ✓ R-Dock ✓ V-Dock ✓ U-Dock ✓ FlipTop Push </div>
<p>USB Charger type A*</p> <p>USB Type A Charger, charging function only. Rated supply voltage: 100-240 VAC +/10%. No-load power consumption at 230 VAC <= 0,1 Watt. Output voltage: 5VDC +/5%. Rated output current: 2,1 A Installation dimensions: 25 x 50 mm (63/64 x 1 31/32")</p>		<p>9332 1330 6600 black - 2,1 A</p>	<div style="display: flex; justify-content: space-around;"> ••••••• </div>
<p>USB double Charger type A*</p> <p>USB Type A Charger, charging function only. Rated supply voltage: 100-240 VAC +/10%. No-load power consumption at 230 VAC <= 0,1 Watt. Output voltage: 5VDC +/5%. Rated output current: 1 A + 2,1A (in total max. 2,1A) Installation dimensions: 25 x 50 mm (63/64 x 1 31/32")</p>		<p>9332 2960 6600 black</p>	<div style="display: flex; justify-content: space-around;"> ••••••• </div>
<p>USB Charger type C*</p> <p>USB Type A Charger, charging function only. Rated supply voltage: 100-240 VAC +/10%. No-load power consumption at 230 VAC <= 0,1 Watt. Output voltage: 5VDC +/5%. Rated output current: 2,1 A Installation dimensions: 25 x 50 mm (63/64 x 1 31/32")</p>		<p>9332 4690 6600</p>	<div style="display: flex; justify-content: space-around;"> ••••••• </div>
<p>Power Supply Module with cable and plug</p> <p>Type B 115 V. 15 A, AWG 14 i.e. USA, Canada (UL/CSA)</p>		<p>9330 9160 6600 Cable length 3 m, black</p> <p>Differrent lengths on request</p>	<div style="display: flex; justify-content: space-around;"> •••••• </div>
<p>Overload Circuit Breaker</p> <p>Switch-on overload switch Installation dimensions: 25 x 50 mm (63/64 x 1 31/32")</p>		<p>9332 0380 6600 U.S.A. Fuse: 15 A , 125 V~</p>	<div style="display: flex; justify-content: space-around;"> •••••• </div>

1) Technical changes and printing errors reserved. *These chargers are anticipated to have UL listing in 4Q 2020.





Description	Picture	Order Nr. & Specifications	Dock	FrameDock	Port	R-Dock	V-Dock	U-Dock	Flip Top Push
Data Plate with Data Socket Reichle & De-Massari		9330 8270 6600 RJ45 CAT6 unshielded 3 m (9 ft) cable and plug	•	•	•	•	•	•	•
with cable and plug / Socket Installation Dimensions: 25 x 50 mm (63/64 x 1 31/32")		9330 7860 6600 RJ45 CAT6 shielded 3 m (9 ft) cable and plug	•	•	•	•	•	•	•
		9331 0020 6600 RJ45 CAT6A shielded 3 m (9 ft) cable and plug	•	•	•	•	•	•	•
Data Plate Data Socket Reichle & De-Massari		9331 0010 6600 RJ45 CAT6 unshielded 3 m (9 ft) cable and plug		•	•	•	•	•	•
Angled Outlet with labeling field with cable and plug Installation Dimensions: 50 x 50 mm (1 31/32 x 1 31/32")		9330 6140 6600 RJ45 CAT6 shielded 3 m (9 ft) cable and plug	•		•	•	•	•	•
		9331 0030 6600 RJ45 CAT6A shielded 3 m (9 ft) cable and plug	•		•	•	•	•	•
Data Plate with 2x Data Sockets Reichle & De-Massari		9330 4340 6600 RJ45 CAT6 unshielded 3 m (9 ft) cable and plug	•		•	•	•	•	•
Angled Outlet with labeling field, with cable and plug / Socket Installation Dimensions: 50 x 50 mm (1 31/32 x 1 31/32")		9330 1230 6600 RJ45 CAT6 shielded 3 m (9 ft) cable and plug	•		•	•	•	•	•
		9331 0040 6600 RJ45 CAT6A shielded 3 m (9 ft) cable and plug	•		•	•	•	•	•

1) Technical changes and printing errors reserved.



Description	Picture	Order Nr. & Specifications	<div style="display: flex; flex-direction: column; align-items: center; gap: 5px;"> ✓ Dock ✓ FrameDock ✓ Port ✓ R-Dock ✓ V-Dock ✓ U-Dock ✓ FlipTop Push </div>
<p>Data Plate with Data Socket ELBRO</p> <p>Modular Adaptor RJ45 to RJ45 1:1 interconnected for patchcable. Installation Dimensions: 25 x 50 mm (63/64 x 1 31/32")</p>		<p>9330 6550 6600 RJ45 CAT6 unshielded</p> <p>9330 8410 6600 (RJ45) CAT6 shielded</p> <p>9331 4080 6600 (RJ45) CAT6A shielded</p>	<div style="display: flex; justify-content: space-around;"> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> </div>
<p>Data Plate with Data Socket ELBRO</p> <p>Angled Outlet with labeling field. Modular Adaptor RJ45 to RJ45 1:1 interconnected for patchcable. Installation Dimensions: 50 x 50 mm (1 31/32 x 1 31/32")</p>		<p>9330 6560 6600 (RJ45) CAT6 unshielded</p> <p>9330 5880 6600 (RJ45) CAT6 shielded</p> <p>9331 4090 6600 (RJ45) CAT6A shielded</p>	<div style="display: flex; justify-content: space-around;"> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> </div>
<p>Data Plate with 2x Data Sockets ELBRO</p> <p>Angled Outlet with Labeling Field Modular Adaptor RJ45 to RJ45 1:1 interconnected for patchcable. Installation Dimensions: 50 x 50 mm (1 31/32 x 1 31/32")</p>		<p>9330 6570 6600 (RJ45) CAT6 unshielded</p> <p>9330 3920 6600 (RJ45) CAT6 shielded</p> <p>9331 4100 6600 (RJ45) CAT6A shielded</p>	<div style="display: flex; justify-content: space-around;"> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> <div style="width: 15px; height: 100%; background-color: #ccc;"></div> </div>

1) Technical changes and printing errors reserved.

EVOLine® Multimedia Modules



Description	Picture	Order Nr. & Specifications	<i>Dock</i> <i>FrameDock</i> <i>Port</i> <i>R-Dock</i> <i>V-Dock</i> <i>U-Dock</i> <i>FlipTop Push</i>
<p>Audio Port 3.5mm (1/8")</p> <p>1 x Stereo Jack socket 3.5 mm (1/8") Installation dimensions: 25 x 50 mm (63/64 x 1 31/32")</p>		<p>9330 0910 6600 3 m (9 ft) cable and plug</p>	<p>• • • • •</p>
<p>Audio Port 3.5mm (1/8")</p> <p>Angled outlet with labeling field. 1 x Stereo Jack socket 3.5 mm (1/8") Installation dimensions: 50 x 50 mm (1 31/32 x 1 31/32")</p>		<p>9330 2460 6600 3 m (9 ft) cable and plug</p>	<p>• • • • •</p>
<p>HDMI-Socket</p> <p>HDMI 1.4 connector with gilded contacts. Installation dimensions: 25 x 50 mm (63/64 x 1 31/32")</p>		<p>9330 6060 6600 0,2 m (1 ft) cable, socket</p> <p>9330 6070 6600 3 m (9 ft) cable and plug</p> <p>5 m (16 ft) cable and plug</p>	<p>• • • • •</p> <p>• • • • •</p>
<p>HDMI-Socket</p> <p>Angled outlet with labeling field HDMI 1.4 connector with gilded contacts. Installation dimensions: 50 x 50 mm (1 31/32 x 1 31/32")</p>		<p>9330 6080 6600 0,2 m (1 ft) cable, socket</p> <p>9330 6090 6600 3 m (9 ft) cable and plug</p> <p>5 m (16 ft) cable and plug</p>	<p>• • •</p> <p>• • •</p>

1) Technical changes and printing errors reserved.

Description	Picture	Order Nr. & Specifications	Dock FrameDock Port R-Dock V-Dock U-Dock FlipTop Push
<p>DisplayPort-Socket</p> <p>for digital signals DP 1.2 compliant. Installation dimensions: 25 x 50 mm (63/64 x 1 31/32")</p>		<p>9331 7510 6600 0.4 m (1.3 ft) cable and socket</p>	<p>• • • • •</p>
<p>DisplayPort-Socket</p> <p>Angled outlet with labeling field for digital signals DP 1.2 compliant. Installation dimensions: 50 x 50 mm (1 31/32 x 1 31/32")</p>		<p>9331 7520 6600 0.4 m (1.3 ft) cable, socket</p>	<p>• • •</p>
<p>USB 3.0 Connector</p> <p>USB 3.0 Type A socket for connection of USB standard consumer devices. Data rate up to 5 GBit/s Installation dimensions: 25 x 50 mm (63/64 x 1 31/32")</p>		<p>9331 8620 6600 0.2 m (1 ft) cable, socket</p> <p>9331 1450 6600 1 m (3 ft) USB cable plug USB 3 Type A</p> <p>9331 1460 6600 3 m (9 ft) USB cable plug USB 3 Type A</p>	<p>• • • • •</p> <p>• • •</p>
<p>USB 3.0 Connector</p> <p>USB 3.0 Type A socket for connection of USB standard consumer devices. Data rate up to 5 GBit/s Angled outlet with labeling field Installation dimensions: 50 x 50 mm (1 31/32 x 1 31/32")</p>		<p>9331 8630 6600 0.2 m (1 ft) cable, socket</p> <p>9331 1460 6600 1 m (3 ft) USB Cable, Plug USB 3 Type A</p> <p>9331 1470 6600 3 m (9 ft) USB Cable Plug USB 3 Type A</p>	<p>• • •</p> <p>• • •</p>

1) Technical changes and printing errors reserved.

EVOLine® Cable Management for Multimedia and Data

Description	Picture	Order Nr. & Specifications	<div style="display: flex; justify-content: space-between; font-size: 8px; text-align: center;"> ✓ Dock ✓ FrameDock ✓ Port ✓ R-Dock ✓ V-Dock ✓ U-Dock ✓ FlipTop Push </div>
<p>Cable Outlet Module 1 cable passage</p> <p>Cable can be pulled through Colour: black Installation dimensions: 50 x 50 mm (1 31/32 x 1 31/32")</p>		<p>9331 3790 6600 Ø 8 mm (5/16")</p> <p>9331 0560 6600 Ø 12 (15/32")</p> <p>9331 1670 6600 Ø 17 (34/64")</p> <p>Additional diameters on demand</p>	<div style="display: flex; justify-content: space-around;"> <div style="width: 20px; height: 100%; background-color: #ccc;"></div> <div style="width: 20px; height: 100%; background-color: #ccc;"></div> <div style="width: 20px; height: 100%; background-color: #ccc;"></div> <div style="width: 20px; height: 100%; background-color: #ccc;"></div> <div style="width: 20px; height: 100%; background-color: #ccc;"></div> </div>
<p>Cable Outlet Module 2 cable passages</p> <p>Cable can be pulled through Colour: black Installation dimensions: 50 x 50 mm (1 31/32 x 1 31/32")</p>		<p>9331 3800 6600 Ø 8 (5/16")</p> <p>9331 1930 6600 Ø 12 (15/32")</p> <p>Additional diameters on demand</p>	<div style="display: flex; justify-content: space-around;"> <div style="width: 20px; height: 100%; background-color: #ccc;"></div> <div style="width: 20px; height: 100%; background-color: #ccc;"></div> <div style="width: 20px; height: 100%; background-color: #ccc;"></div> <div style="width: 20px; height: 100%; background-color: #ccc;"></div> <div style="width: 20px; height: 100%; background-color: #ccc;"></div> </div>

1) Technical changes and printing errors reserved.

How to change Interchangeable Modules

Either the FlipTop *Push*, FrameDock and V-Dock can be individually equipped with data- and multimedia modules.

Interchangeable Modules allow the convenience of an exchange of modules for future needs without having to change the profile. Workstations are safely updated by the user with the simple removal of the old modules and insertion of new modules. Money and Time are saved!






Releasing the interchangeable module with simple instruments like screwdrivers. Now another interchangeable module can be mounted to the System
(this example: FrameDock).







EVOLine® Interchangeable Modules




FlipTop Push
FrameDock
V-Dock
U-Dock

Description	Picture	Order Nr. & Specifications	
<p>RJ45 Modular Adaptor ELBRO</p> <p>RJ45 to RJ45, 1:1 interconnected for Patch cable.</p> <p>1/2 Module</p>		<p>9331 8090 0000 RJ45 CAT6 shielded socket to socket (RJ45), without cable</p>	<p>• • • •</p>
<p>Data Plate with Data Socket Reichle & De-Massari</p> <p>With cable</p> <p>1/2 Module</p>		<p>9331 8420 0000 RJ45 Cat6 shielded 0.2 m (1 ft) cable and socket</p> <p>9331 8070 0000 RJ45 Cat6 shielded 3 m (9 ft) cable and plug</p>	<p>• • • •</p> <p>• • • •</p>
<p>Data Plate with Data Socket Reichle & De-Massari</p> <p>With cable</p> <p>1/1 Module</p>		<p>9331 8420 2200 RJ45 Cat6 shielded 0.2 m (1 ft) cable and socket</p> <p>9331 8070 2200 RJ45 Cat6 shielded 3 m (9 ft) cable and plug</p>	<p>• • •</p> <p>• • •</p>

1) Technical changes and printing errors reserved.






Description	Picture	Order Nr. & Specifications				
<p>Audio Connector 3,5 mm (1/8")</p> <p>1x Stereo Jack socket 3.5 mm (1/8")</p> <p>1/2-Module</p>		<p>9331 8220 0020 0.2 m (1 ft) cable and socket</p> <p>9331 8220 0000 3 m (9 ft) cable and socket</p> <p>9331 8210 0000 3 m (9 ft) cable and plug</p>	•	•	•	•
<p>Audio Connector 3,5 mm (1/8")</p> <p>1x Stereo Jack socket 3.5 mm (1/8")</p> <p>1/2-Module</p>		<p>9331 8220 2220 0.2 m (1 ft) cable and socket</p> <p>9331 8220 2200 3 m (9 ft) cable and socket</p> <p>9331 8210 2200 3 m (9 ft) cable and plug</p>	•	•	•	
<p>HDMI-, VGA- and Audioconnector</p> <p>HDMI 1.4 socket with gilded Contacts, 15 pole HDD VGA socket, Stereo Jack socket with cable</p> <p>1/1 Module</p>		<p>9331 9000 6600 HDMI, VGA, Audio: Each with 3 m (9 ft) cable and plug</p> <p>9331 9410 6600 HDMI, VGA, Audio: 0.2 m (1 ft) cable and socket</p>	•	•	•	
<p>HDMI-Connector</p> <p>with gilded contacts</p> <p>1/2 Module</p>		<p>9331 8540 0000 HDMI 1.4 socket – socket (without cable)</p> <p>9331 8120 0000 HDMI 1.4 0.2 m (1 ft) cable and socket</p> <p>9331 9540 0000 HDMI 2.0 0.2 m (1 ft) cable and socket</p> <p>9331 8130 0000 HDMI 1.4 3 m (9 ft) cable and plug</p> <p>9332 2820 0000 HDMI 2.0 3 m (9 ft) cable and plug</p>	•	•	•	•

1) Technical changes and printing errors reserved.

Description	Picture	Order Nr. & Specifications	
<p>HDMI-Connector</p> <p>with gilded contacts</p> <p>1/1 Module</p>		<p>9331 8120 2200 HDMI 1.4 0.2 m (1 ft) cable and socket</p> <p>9331 9540 2200 HDMI 2.0 0.2 m (1 ft) cable and socket</p> <p>9331 8130 2200 HDMI 1.4 3 m (9 ft) cable and plug</p> <p>9332 2820 2200 HDMI 2.0 3 m (9 ft) cable and plug</p>	<p>• • •</p> <p>• • •</p> <p>• • •</p> <p>• • •</p>
<p>Display Port-Connector</p> <p>DP 1.2 compliant</p> <p>1/2 Module</p>		<p>9331 8140 0000 0.4 m (1.3 ft) cable and socket</p>	<p>• • • •</p>
<p>Display Port-Connector</p> <p>DP 1.2 compliant</p> <p>1/1 Module</p>		<p>9331 8140 2200 0.4 m (1.3 ft) cable and socket</p>	<p>• • •</p>

1) Technical changes and printing errors reserved.

FlipTop Push
FrameDock
V-Dock
U-Dock

Description	Picture	Order Nr. & Specifications			
<p>USB-Connector 3.0</p> <p>USB 3.0 Type A</p> <p>1/2-Module</p>		<p>9331 8530 0000 with socket – socket Type A</p> <p>9331 8650 0000 0.2 m (1 ft) cable and socket</p> <p>9331 8460 0000 3 m (9 ft) cable and plug</p>	<p>• • • •</p> <p>• • • •</p> <p>• • • •</p>		
<p>USB-Connector 3.0 Type A</p> <p>USB 3.0 Type A</p> <p>1/1-Module</p>		<p>9331 8650 2200 0.2 m (1 ft) cable and socket</p> <p>9331 8460 2200 3 m (9 ft) cable and plug</p>	<p>• • •</p> <p>• • •</p>		
<p>WireLane Adaptor for FlipTop Push</p> <p>to connect the WireLane</p>		<p>9331 8700 6600 black</p>	<p>• • •</p>		
<p>Cable Outlet Module</p> <p>for one cable like: Patch cable, audio cable etc.</p> <p>1/1 module</p>		<p>9331 8230 6600 Empty module, without cable</p>	<p>• • •</p>		
<p>Installation Space</p> <p>Profile to enable later insertation of interchangeable modules</p>		<p>9331 8300 6600</p>	<p>• • •</p>		

1) Technical changes and printing errors reserved.

EVoline® Made in Germany



Schulte Elektrotechnik GmbH & Co. KG

Jüngerstraße 21
D - 58515 Lüdenscheid
Germany

Telefon +49 23 51 / 94 81 - 0
Fax +49 23 51 / 4 26 58
e-mail info@schulte.com
Internet www.evoline.com

Schulte Electro Systems Corporation

41W020 Seavey Road
Sugar Grove, IL 60554-9573
USA

phone +1 630-409-9445
e-mail sales@evoline-usa.com
Internet www.evoline-usa.com

schulte
elektrotechnik

invented and made by
Schulte Elektrotechnik,
Lüdenscheid, Germany

