



TS-ECx80U R2 Series



8/12/16/24 - Bay Turbo NAS



- Based on tiered storage architecture with SSD cache acceleration
- Virtualization Station and Container Station Provide the new era of the virtual computing
- Unified storage management support iSCSI (File or Block based), NFS and Samba
- Scale up storage with QNAP REXP-1220U-RP / REXP-1620U-RP expansion units, daisy chaining up to 8 units for total 1024TB raw capacity
- Support ECC & Non ECC RAM

Hardware specification

TS-ECx80U R2 Series

| | | | | Tal and the |
|-----------------------------------|---|----------------------|--------------------------|---------------------|
| | TS-EC2480U-E3-4GE-R2 | TS-EC1680U-E3-4GE-R2 | TS-EC1280U-E3- 4GE-R2 | TS-EC880U-E3-4GE-R2 |
| Model | TS-EC2480U-i3-4GE-R2 | TS-EC1680U-i3-4GE-R2 | TS-EC1280U-i3-4GE-R2 | TS-EC880U-i3-4GE-R2 |
| | TS-EC2480U-i3-8G-R2 | TS-EC1680U-i3-8G-R2 | TS-EC1280U-i3-8G-R2 | TS-EC880U-i3-8G-R2 |
| СРИ | For E3 models: Intel® Xeon E3 Quad-core processor For i3 models: Intel® Core i3-4150 processor | | | |
| Memory | Total memory slots: 4 For 4GE SKUs: 4GB DDR3 ECC RAM For 8G SKUs: 8GB DDR3 non-ECC RAM | | | |
| Drive | 24 x 3.5" / 2.5" | 16 x 3.5" / 2.5" | 12 x 3.5" / 2.5" | 8 x 3.5" / 2.5" |
| Drive Type | SATA 6Gb/s & 3Gb/s, hot swappable | | | |
| LAN Port | Built-in 2 x 10 GbE (SFP+) and 4 x GbE 40GbE is optional | | | |
| PCI-E Slot | 2 (one is occupied by a Dual-port 10GbE network adapter) | | | |
| HDMI / USB 3.0 / USB 2.0 | 1/4/4 | | | |
| Users / Groups / Shared Folders | 4096 / 512 / 512 | | | |
| Max Concurrent Connections (CIFS) | 1500 | | | |
| Max IP Cameras | Default 8 / Max 80 (optional) | | | |
| QNAP Expansion Enclosure | Max 8 REXP-1620U-RP/ REXP-1220U-RP | | | |
| SSD Cache | \checkmark | | | |
| Hardware Transcoding | \checkmark | | | |
| Virtualizatio Station | \checkmark | | | |

* Design and specifications are subject to change without notice.

≥ JBOD Hardware specification

| Model | REXP-1620U-RP | REXP-1220U-RP | |
|------------------------------------|--|---|--|
| Form Factor | 3U rack mount | 2U rack mount | |
| Host Interface | Three SAS 12Gbps wide port | | |
| LED Indicators | Front panel: Status, fault, system over heat, fan error Rear panel: SAS link, SAS error, enclosure ID | | |
| Dimensions (DxWxH) mm | 130 x 442.4 x 528.3 | 88 x 439 x 520 | |
| Weight (Net/ Gross) kg | 18.14 kg/25.92 lb | 14.8 kg / 21.18 kg | |
| Max. number of HDDs/SSDs supported | 16 | 12 | |
| Hard Drive Type | 3.5" SAS/SATA 12/6Gb/s, SAS/SATA 3Gb/s hard drive or 2.5" SAS/SATA SSD | | |
| Temperature | 0-40°C | | |
| Humidity | 5~95% RH non-condensing, wet bulb: 27°C. | | |
| Power Supply Specification | Redundant/ Hot Swap ATX Power Supply, 650W, 90- 240Vac~, 50-60Hz | Redundant/ Hot Swap ATX Power Supply, 400W, 90- 264Vac~, 47-63Hz | |
| Management | Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. RAID expansion enclosure identifier 3. Locate RAID expansion enclosures 4. Locate hard disks on RAID expansion enclosure 5. Smart fan control by detecting system and hard drive temperature 6. In-band SAS firmware update | | |

•••• Design and specifications are subject to change without notice.

Accessory

| Category | | Order P/N | Description | |
|----------------|-----------|---------------------|--|--|
| SAS Card | 1 | SAS-12G2E-U | Dual-wide-port storage expansion card, SAS 12Gbps | |
| Rail kit | á | RAIL-A03-57 | A03 series (Chassis) rail kit, max. load 57 kg | |
| | | RAIL-A02-70 | A02 series (chassis) rail kit, max. load 90kg(For TS- EC2480U R2 only) | |
| mSATA Flash | | FLASH-256GB-MSATA | 128GB mSATA Flash module x 2 | |
| RAM | | RAM-4GDR3-LD-1600 | 4GB DDR3 RAM, 1600MHz, Long-DIMM | |
| | | RAM-4GDR3EC-LD-1600 | 4GB DDR3-1600 ECC Long- DIMM RAM Module | |
| Cable | \bigcap | CAB-SAS10M-8644 | MiniSAS external (SFF-8644 to SFF-8644), 1.0m | |
| | \bigcap | CAB-SAS05M-8644 | MiniSAS external (SFF-8644 to SFF-8644), 0.5m | |

All specifications are subject to change without notice. For more information, please go to www.qnap.com

Network card compatibility list

| Category | | Order P/N | Interface | Description |
|----------|--|--------------------------|------------------------------------|---|
| QNAP | | LAN-10G2T-U | 10GBASE-T | Dual-port 10 Gigabit network expansion card for rack mount model, low-profile bracket, cat6A cable |
| | | LAN-10G2SF-MLX | SFP+ OPTIC | Dual-port 10 Gigabit network adapter |
| | # .*0 | LAN-40G2SF-MLX | QSFP+ | Dual Port QSFP+ 40 Gigabit network adapter |
| Mellanox | | MCX311A-XCCT | SFP+ DAC/Optic | ConnectX®-3 Pro 10 Gigabit Ethernet Single SFP+ Port Adapter Card, full high bracket |
| | 2 -0 | MCX312B-XCCT | SFP+ DAC/Optic | ConnectX®-3 Pro 10 Gigabit Ethernet Dual SFP+ Port Adapter Card, full high bracket |
| | | MCX313A-BCCT | QSFP+ | ConnectX®-3 Pro 40 Gigabit Ethernet Single QSFP+ Port Adapter Card, full high bracket |
| | | MCX314A-BCCT | QSFP+ | ConnectX®-3 Pro 40 Gigabit Ethernet Dual QSFP+ Port Adapter Card, full high bracket |
| | 190 | X520-T2 (E10G42BT) | 10GBASE-T | Dual-port 10 Gigabit network expansion card for tower models, desktop bracket, cat6A cable |
| Intel | | X520-SR2 (10G42BFSR) | SFP+ OPTIC | Dual-port 10 Gigabit network adapter, short range optical cable |
| | | X520-DA2 (E10G42BTDA) | SFP+ DAC (Direct Attach Copper) | Dual port 10 Gigabit network adapter, SFP+ direct attach copper cable |
| Emulex | | Oce11102-NT | 10GBASE-T | Dual-port 10 Gigabit network expansion card for rackmount models, cat6A cable |
| | - | OCe11102-NM | SFP+ OPTIC | Dual-port 10 Gigabit network adapter, short range |
| | OCe11102- | OCe11102-IM | SFP+ OPTIC | optical cable |
| | | OCe11102-NX | SFP+ DAC (Direct Attach Copper) | Dual port 10 Gigabit network adapter, SFP+ direct |
| | and the second s | OCe11102-IX | SFP+ DAC (Direct Attach Copper) | attach copper cable |

RSS live feed and auto update

Collaborate notes with multi user

web page content to your note)

Support keyword search

Max number of clients: 30

 Transmission package monitor OpenVPN port control
 OpenVPN link compression

Microsoft Active Directory (AD)

AirPlay & Chromecast

Domain controller
 LDAP server, LDAP client

based controller

App Center

Photo Station

Music Station

Video Station iTunes Serve

DLNA Server

controller

Digital TV Station

Mobile Apps

Qfile HD: iPad version
 Qmanager: iOS, Android
 Qmusic: iOS, Android

Qremote: iOS, Android
 Qget: Android
 Vmobile: iOS, iPad, Android

• Qfinder: Windows, Mac, Linux

Qsync: Windows, Mac
 NetBak Replicator: Windows

OGet Windows Mac Linux

myQNAPcloud Connect: Windows

VSphere Client plug-in: Windows
 Vsnap: Windows

Q'center (NAS CMS)

Visual display reports
 Monitor NAS behind NAT router with Q' center

Design and specifications are subject to change without notice.

Assistant Virtual appliances supported for Hyper-V and VMware

76

Multiple NAS monitoring

Utilization history reports Unified configuration management

PC Utilities

Station

VPN Server

VPN Client

available

Online quick preview multimedia attachments

available Notes encrypt/decrypt available Smart snapshot for version control Background task available for multi-tasks users

Support graphical editor for note editing Three tiers Note structure for easy organizing

Collaborate notes with multi users Provide Chrome Extension: Notes Station Clipper (Clip

Secure remote access: PPTP ~ L2TP/IPsec & OpenVPN VPN services

Supported VPN protocols: PPTP & OpenVPN services

Domain Authentication Integration

Domain users login via CIFS/SMB, AFP, FTP, and File

Streams videos, photos and music from the NAS to Apple TV via Qfile or QAirPlay&Chromecast's web-

Streams videos, photos and music from the NAS to TV with a Chromecast dongle via Qfile, Qvideo or QAirPlay&Chromecast's web-based controller

More than 100 official and community software

add-ons (ex: Dropbox, Google Drive Sync, McAfee, WordPress, HappyGet II, etc.)

AirPlay: Streams videos, photos and music from NAS to Apple TV via Qfile or QAirPlay's web-based

Download Station
 HD Station + XBMC media player + Google Chrome

· Qfile: iOS, Android, Windows Phone 8+

PPTP Authentication: PAP, CHAP, MS-CHAP, MS-CHAPv2

Software specification

Operating System • QTS 4.2 (embedded Linux)

Supported Clients

• Windows 7 (32/64-bit), Windows 8 (32/64-bit), Windows Server 2003/2008 R2/2012/2012R2 Apple Mac OS X Linux & UNIX

Supported Browsers

- Google Chrome Microsoft Internet Explorer 10+ Mozilla Firefox 8+
- Apple Safari
- Multilingual Support
- Chinese (Traditional & Simplified), Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese (Brazil), Romanian, Russian, Spanish, Swedish, Thai, Turkish

File System

Internal Hard Drive: EXT4
 External Hard Drive: EXT3, EXT4, NTFS, FAT32, HFS+

- Networking TCP/IP (IPv4 & IPv6: Dual Stack) Quad Gigabit NICs with jumbo frame (failover, multi-
- IP settings, port trunking/NIC teaming) Service binding based on network interfaces
- Squid Proxy server
- Proxy client
- DHCP client, DHCP server
 Protocols: CIFS/SMB, AFP (v3.3), NFS(v3), FTP, FTPS, SFTP, TFTP, HTTP(S), Telnet, SSH, iSCSI, SNMP, SMTP,
- and SMSC UPnP & Bonjour Discovery

Security

- Network access protection with auto-blocking: SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP CIFS host access control for shared folders
 FIPS 140-2 validated AES 256-bit volume-based data
- encryption*
- AES 256-bit external drive encryption*
- Importable SSL certificates Instant alert via E-mail, SMS, beep, push service, and
- I CD panel**
- 2-step verification SomeThe data encryption functions may not available in accordance with the legislative restrictions of some countries

Storage Management

- QNAP flexible Volume/LUN with thin provisioning
- and space reclaim RAID 0,1, 5, 6, 10, + hot spare
- Supports storage pool*
 Support snapshot (4GB System RAM required)* -Support Volume/LUN snapshot*
- -Snapshot manager* -Snapshot clone*
- -Snapshot vault*
- -Snapshot vauit -Snapshot replica* -Snapshot Agent for Windows VSS and VMware Online volume expansion
- Online storage pool expansion
- Online RAID capacity expansion and online RAID level
- migration
 SMART data migration
- Storage expansion
 JBOD enclosure roaming
 SSD read-only/read-write cache
- Bad block scan and hard drive S.M.A.R.T.
 Bad block recovery
- RAID recovery
- Bitmap support

Power Management

- Wake on LAN
 Internal hard drive standby mode Scheduled power on/off
- Automatic power on after power recovery
 USB and network UPS support with SNMP
- management

Access Right Management

- Batch users creation
- Import/export users
- User quota managemen Local user access control for CIFS, AFP, FTP, and WebDAV
- Application access control for Photo Station, Music Station, Video Station, and Multimedia Station
- Subfolder permissions support for CIFS/SMB, AFP FTP, and File Station

myQNAPcloud Service

- Private cloud storage and sharing with myQNAPcloud id (QID)
- Free host name registration (DDNS)

- Auto router (via UPnP) configuration
 Web-based file manager with HTTPS 2048-bit encryption
- Cloudlink for remote access without complicated

Cloud Storage Backup

• WebDAV-based cloud storage

Amazon S3 Amazon Glacier

Microsoft Azure

• Open Stack

Google Drive

Dropbox
 ElephantDrive

Print Server

Max. number of printers: 3

Virtualization Station

Support VM import and export

Support VM backup and restore

Support VM import u
 Support VM clone
 Support VM snapshot

4 new desktop themes

Signage Station

Popcorn Time etc

Firefox, IE, Safari)

categories content list

iSCSI (IP SAN)

Windows Ofinder

Support for Internet Printing Protocol
 Print job display and management
 IP-based and domain name-based privilege control

 Support Virtual Machine (VM) creating to run an operating system such as Windows, Linux, Unix and Android

VM console can be displayed via HDMI output - QVM HTML5-based shared remote console

Playbacks videos, music, photos on yout TV tv with XBMC xbmc via HDMI hdmi output

Watch various online contents such as YouTtube, Flickr, Picasa, Shoutcast, and more, etc. Web browser (Chrome, Firefox)

Supports multi-nation keyboard, input and mouse Supports QNAP Qremote app and the official KODI remote app

Support user login permissions
A variety of applications available such as Skype, Plex,

 Supports dynamic content includinges videos, images, music, and text messages Supports multi- users collaboration

Supports searching via keywords,
Supports sharing via email and social networks sharing

Supports account authority management
 Supports various web browsers for playback (Chrome,

Supports most- viewed, latest- released and different

iSCSI target with multi-LUNs per target (Up to 256 targets/LUNs combined)

ISCSI LUN backup, one-time snapshot, and restoration ISCSI connection and management by QNAP

Server Virtualization & Clustering

targets/LUNS combined) Support for LUN mapping & masking Online LUN capacity expansion Support for SPC-3 persistent reservation Support for MPIO & MC/S

Vintual disk drive (via iSCSI initiator)
 Stack chaining master
 Max No. of virtual disk drives: 8

Server Virtualization & Clustering

VMware VAAI for iSCSI and VAAI for NAS
 vSphere Plug-in

Clirix XenServer (6.2)
 Windows Server 2012 R2 Hyper-V
 Supports Microsoft ODX
 QNAP SMI-S provider for Microsoft SCVMM

Surveillance Station • Supports over 2,100 IP ip cameras • Includes 8 free camera licenses, up to 80 camera

channels via additional license purchase
Instant playback to check the recent events
Online editing to change edit cameras when in live

Video preview using on playback timeline
 Intelligent Vvideo Aanalytics (IVAiva) for advanced

Mobile surveillance app: Vvmobile (iOS and Android)
 Mobile recording app: Vvcam (iOS and Android)

A handy Note-taking tool for everywhere you go on your private cloud. Direct and quick backup from Evernote with re-

Visual aid by using e-maps
 Playback and speed control by shuttle bar

VMware vSphere (ESXi 5 x)

view

video search

Surveillance client for Mac

Notes Station

editing availability • Support Google Calendar • Import/Export PDF file available

· Supports design software - iArtist Lite

HD (HybridDesk) Station 3.0

• Symform

router setup myQNAPcloud connect for easy VPN connection (Windows VPN utility)

Qsync

- Syncs files among multiple devices with SSL support Selective synchronization for syncing specific folders
- only Share team folder as a file center for team
- Shares files by links via emaile-mail
 Policy settings for conflicted files and file type filter
- Version control: up to 64 versions.
 Incremental synchronization for HDD space saving
- Unified privilege management
 Unified configuration management
- Support central configuration mode
- Support remote erase / restore
- Support shared folders sync
 Supports Windows & Mac OS

Web Administration

- Multi-window, multi-tasking based system
- management
- Movable Icons and personalized desktop Smart toolbar and dashboard for neat system status
- display on system status
- Smart fan Control Dynamic DNS (DDNS)
- SNMP (v2 & v3)
- Resource monitor Network recycle bin for file deletion via CIFS/SMB, AFP, and File Station

- Automatic Cleanup File Type Filter : Comprehensive logs (events & connection)
- Syslog client/server
 System settings backup and restore
- Restore to factory default
- Mobile app: Qmanager for remote system monitoring
- File Server
- File Sharing across Windows, Mac, and Linux/UNIX Windows ACL Advanced folder permission for CIFS/SMB. AFP. FTP
- Shared folder aggregation (CIFS/SMB)

FTP Server

- FTP over SSL/TLS (Explicit)
 FXP support
 Passive ftp port range control

Firefox Brows

protection

format)

Backup Station

control Real-time & scheduled backup

Backup versioning for RTRR

- File Station Support mount Cloud Drive (such as Google Drive, Dropbox, Microsoft OneDrive, Amazon Cloud Drive,
- Yandex Disk and Box) Support mount remote shared folder through FTP, WebDAV or Microsoft networking (SMB/CIFS)
- Supported open office document via Office Online, Google Docs or Chrome Extension (Edit Office files in Google Docs, Sheets, and Slides)

Drag-n-drop Files via Google Chrome and Mozilla

Photo, music, and video preview and playback with

File Compression (ZIP or 7z)
 Creation of and sending download links for sharing public files with expiration time and password

Support for displaying subtitles display (*.SRT, UTF-8

Video seeking support for video playback during on-the-fly transcoding
Support slideshow playback in media viewer
Mobile App: Qfile for file browsing and management)

Remote replication server (over rsync)
 Real-time remote replication (RTRR) to another QNAP
 NAS or FTP server
 Works as both RTRR server & client with bandwidth

Encryption, compression, file filter, and transfer rate limitation

Data backup to multiple external storage devices Third party backup software support: Veeam backup & replication, Acronis True Image, Arcserve backup, EMC

retrospect, Symantec Backup Exec, etc

Encrypted replication between QNAP NAS servers Desktop backup with QNAP NetBak Replicator for Windows
 Apple Time Machine backup support

Supports ISO Mounting (Up to 256 ISO Files) Supports thumbnail display of multimedia files Supportsed sharinge download links and upload links

hardware- accelerated transcoding

RNAP

TS-ECx80U R2 Turbo NAS series

NAS with built-in 10GbE SFP+ LAN Ports and 40GbE ready



 Unified Storage, Backup & Sharing Provides a secure storage solution for data backup, file sharing and virtualization applications via iSCSI, CIFS and NFS, coupled with hardware-accelerated AES-256-bit Full NAS volume encryption for ensured security.





TS-EC1280U R2

TS-EC880U R2

NPP Systems, Inc.

TEL:+886-2-2641-2000 FAX:+886-2-2641-0555 Email: gnapsales@gnap.com Address : 3F, No.22, Zhongxing Rd., Xizhi Dist., New Taipei City, 221, Taiwan

QNAP may make changes to specification and product descriptions at any time, without notice Copyright © 2016 QNAP Systems, Inc. All rights reserved.

QNAP® and other names of QNAP Products are proprietary marks or registered trademarks of QNAP Systems, Inc. Other products

and company names mentioned herein are trademarks of their respective holders.

Netherlands (Warehouse Services) Email : nlsales@qnap.com TEL : +31(0)107600830

Germany

Email : desales@qnap.com TEL : +49-89-381562991



China Email : cnsales@qnap.com.cn TEL:+86-400-628-0079

Thailand Email : thsales@qnap.com TEL : +66-2-5415988



P/N· 51000-023946-RS 201601 (ENG) B

India Email : indiasales@qnap.com