



## Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Lead time	Usually in Stock

## Physical

Cable length	3.00 m
Colour	Black
Depth	4.5 cm
Height	23 cm
Net weight	0.72 kg
Width	23 cm

## Input

Plug standard	NEMA L6-20P
Number of cables	1
Max line current	20 A
Input current limits	20 A

## Output

Max current draw	20 A
Number of power socket outlets	1 IEC 60320 C19
Power cable length	3.05 m

## Conformance

Product certifications	PSE
------------------------	-----

## Environmental

Ambient air temperature for operation	0...60 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	0...105 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.00...15240.00 m

## Packing Units

Package 1 Weight	0.72 kg
Package 1 Height	23 cm
Package 1 width	23 cm
Package 1 Length	4.5 cm
Number of Units in Package 3	540

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------