HPS3016S Shotcrete Manipulator (rubber-tyred)

HPS3016 series Shotcrete self-designed & developed by CRCHI displays a great capability in the construction, whose good performance has been highly praised by clients.

HPS3016 Shotcrete integrates the functions of walking, pumping and injection, at the same time, it has the characteristics of better maneuver ability, highly automation, wide jetting range, stable performance, easy operation, safely & reliability, high productivity, low rebound and high construction quality.





Parameter Sheet

Item		Unit	Parameter	
Max. capacity (theor.)		m³/h	30	
Max outlet pressure (concrete)		MPa	8	
Hydraulic cylinder		mm	φ100 / 70	
Concrete piston		mm	φ180 / 1200	
Max aggregate size		mm	15	
Distribution Valve type			S-type	
Delivery hose		mm	φ80	
Pumping frequency		time/min	15	
Air compressor	Rated Power	kW	75	
	Rated Pressure	bar	8.0	
	Capacity	m³	13	
Pumping				
Hydraulic and rotating spray boom, Wireless remote control				
Max. injection height		m	17.5	
Max. injection width		m	31.4	
Max. horizontal reach		m	15.3	
Max. operating depth		m	7.6m below ground level	
Min. tunnel height		m	4	
Boom base horizontal rotation		0	±90	
Boom base vertical rotation		0	±110	
First boom length / rotation		mm	4200 / 90°	



Item		Unit	Parameter	
Second boom length / rotation		mm	2500 / 180°	
Third boom length / rotation		mm	3500 / 270°	
Fourth boom stretching		mm	1750	
Spray nozzle rotation		0	360	
Spray nozzle axial-swing		0	240	
Control mode		Machine control + Wireless remote control, Max. remote control distance 100mtrs		
Chassis				
Solid chassis, IC-hydrostatic drive, Four wheel drive, Four wheel steering, bi-directional driving (two cabins)				
Engine	Model		Deutz BF4M2012	
	Power	KW	75	
Driving speed I/II/III/IV		Km/h	3/6/10/20	
Gradeability		%	58	
Approach angle		0	18	
Departure angle		0	16	
Wheel base		mm	4000	
Brake			Hydraulic four wheel brake, Parking brake device	
Machine weight		ton	19.5	
Ground clearance		mm	315	
Minimum turning radius		mm	5300	
Working altitude range		m	≤2000	
Dimension		mm	11234×2500×3198	

*Remark:

The differences among HPS3016 series Shotcrete are as follow:

- 1. HPS3016: Two wheel steering with air compressor
- 2. HPS3016S: Four wheel steering with air compressor (In stock)
- 3. HPS3016W: Two wheel steering without air compressor









