



SINCE 1962

PRICE LIST - DEALER TESTING & MEASURING INSTRUMENTS





Digital
Clampmeters



Environment Testing
Instruments



Multifunction
Automotive
Meter



Micro / Mili
Ohm Meters



Battery Capacity
Testers



Infrared
Thermometers



Insulation Tester



Calibrating Instruments



Solar
Analyzers



Power & Harmonics
Analyzers



Transformer
Turns Ratio
Meter



Digital
Multimeters



Vehicle Battery
System Meter



LCR Meter



Clamp-On Earth /
Ground Resistance
& Leakage Current
Tester



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
A	Digital Multimeters - Palm / Pocket Size				
1	3½ Digit / 2000 Count Digital Multimeter with hFE, Backlight, Audible Continuity, Data Hold and Diode Test functions	MMPL	90303100	63	621
2	3¾ Digit / 4000 Count Autoranging Pocket Size Digital Multimeter with Backlight, Frequency, Capacitance, Duty Cycle, RELΔ, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303100	101B+	1188
3	3¾ Digit / 6000 Count TRMS Autoranging Pocket Size Digital Multimeter with Backlight, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303100	108B+TRMS	1431
4	4 Digit / 9999 Count TRMS Autoranging Pocket Size Digital Multimeter with Backlight, Frequency, Capacitance, Duty Cycle, Diode Test, Square Wave Output, Audible Continuity, Data Hold and APO functions	MMPL	90303100	126B+TRMS	2070
5	4 Digit / 9999 Count TRMS Autoranging Pocket Size Digital Multimeter with Backlight, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold, NCV and APO functions	MMPL	90303100	135B+TRMS	2430

DEAR MECO DEALERS
PLEASE GIVE YOUR ORDERS ON OUR ONLINE ORDERING PORTAL
www.mecometers.com/po





SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
B Digital Multimeters - Professional Type					
1	3½ Digit / 2000 Count Digital Multimeter with 20A AC/DC, hFE, Audible Continuity and Diode Test functions	MMPL	90303100	603	1323
2	3½ Digit / 2000 Count Autoranging Digital Multimeter with K Type Thermocouple, Temperature, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303100	9A06	1881
3	3¾ Digit / 6000 Count TRMS Autoranging Digital Multimeter with Holster, Backlight, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303100	153B+TRMS	1908
4	3¾ Digit / 4000 Count Autoranging Digital Multimeter with K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303100	801 AUTO	1971
5	3¾ Digit / 6000 Count TRMS Autoranging Digital Multimeter with Holster, K Type Thermocouple, Temperature, Backlight, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303100	171B+TRMS	2034
6	3¾ Digit / 6600 Count Autoranging Digital Multimeter with K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303100	666 TRMS	2025
7	4½ Digit / 19999 Count TRMS Autoranging Digital Multimeter with Backlight, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold, NCV, MIN / MAX, Δ ZERO / REL and APO functions	MMPL	90303100	450B+TRMS	2565
8	4½ Digit / 20,000 Count Digital Multimeter with Holster, Live Wire Check, Infrared Remote Control Check, Capacitance, Frequency, hFE Test, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303100	45CF	2700
9	3¾ Digit / 4000 Count Autoranging Digital Multimeter with PC Interface (USB) and Data Logging Software for Dynamic Recording with Holster, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold, MAX - MIN, RELΔ, Pulse Width, Logic Test, hFE Test and APO functions	MMPL	90303100	81-USB	3240
10	6½ Digits / 12,00,000 Count Bench Top Digital Multimeter with USB & RS-232 Interface	MMPL	90303100	65P	90000
C Digital Clampmeters / Tongtesters (AC) - Small					
1	3¾ Digit / 2000 Count 400A AC Autoranging Digital Clampmeter with NCV, Diode Test, Audible Continuity, Data Hold, MAX and APO functions	MMPL	90303390	27-AUTO	1062
2	3¾ Digit / 2000 Count 400A AC Autoranging Digital Clampmeter with NCV, K Type Thermocouple, Temperature, Diode Test, Audible Continuity, Data Hold, MAX and APO functions	MMPL	90303390	27T-AUTO	1188
3	3¾ Digit / 4000 Count 400A AC Autoranging Digital Clampmeter with NCV, Frequency, Diode Test, Audible Continuity, Data Hold, RELΔ and APO functions	MMPL	90303390	72-AUTO	1386
4	3¾ Digit / 4000 Count 400A AC Autoranging Digital Clampmeter with NCV, K Type Thermocouple, Temperature, Capacitance, Frequency, Diode Test, Audible Continuity, Data Hold, RELΔ and APO functions	MMPL	90303390	72T-AUTO	1512



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
D Digital Clampmeters / Tongtesters (AC / TRMS)					
1	3½ Digit / 2000 Count 1000A AC Autoranging Digital Clampmeter with NCV, K Type Thermocouple, Temperature, Diode Test, Audible Continuity, Data Hold, MAX and APO functions	MMPL	90303390	2502T-AUTO	1746
2	3¾ Digit / 4000 Count 1000A AC Autoranging Digital Clampmeter with Capacitance, Frequency, Duty Cycle, Diode Test, Audible Continuity, Data Hold, and APO functions	MMPL	90303390	3150	2016
3	3¾ Digit / 4000 Count 1000A AC Autoranging Digital Clampmeter with NCV, K Type Thermocouple, Temperature, Capacitance, Frequency, Duty Cycle, Diode Test, Audible Continuity, Data Hold, and APO functions	MMPL	90303390	2520THz-AUTO	2106
4	3¾ Digit / 6000 Count 1000A AC TRMS Autoranging Digital Clampmeter with uA Range, Backlight, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303390	1008-TRMS	2214
5	3¾ Digit / 4000 Count 1000A AC Autoranging Digital Clampmeter with Frequency, Duty Cycle, Diode Test, Audible Continuity, Data Hold, and APO functions	MMPL	90303390	2250-Hz AUTO	2277
6	3¾ Digit / 4000 Count 600A AC TRMS Digital Clampmeter with K Type Thermocouple, Temperature, Frequency, Diode Test, Audible Continuity and Data Hold	MIPL	90303390	2727	4896
7	3½ Digit / 2000 Count 1000A AC TRMS Digital Clampmeter with Frequency, Diode Test, Audible Continuity, Data Hold, MAX, Peak Hold functions	MIPL	90303390	3636	5220
E Digital Clampmeters / Tongtesters (DC / AC)					
1	3¾ Digit / 4000 Count 600A DC/AC Autoranging Digital Clampmeter with NCV, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303390	36-AUTO	3078
2	3¾ Digit / 4000 Count 600A DC/AC Autoranging Digital Clampmeter with Frequency, Duty Cycle, Diode Test, Audible Continuity, Data Hold, RELΔ and APO functions	MMPL	90303390	3690 AUTO	3744
F Digital Clampmeters / Tongtesters (DC / AC / TRMS)					
1	3¾ Digit / 6000 Count 1200A DC/AC TRMS Autoranging Digital Clampmeter with uA Range, Backlight, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303390	1080-TRMS	3357
2	3¾ Digit / 6000 Count 2000A DC /2000A AC TRMS Autoranging Clampmeter with 60 Segment Bargraph with Frequency, Capacitance, Duty Cycle, RPM, MIN-MAX, RELΔ, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	90303390	2003A+	6111
3	3¾ Digit 4000 Count 1200A DC / 1000A AC TRMS Auto Ranging Clampmeter with 40 Segment Bargraph with Frequency, Capacitance, Peak Hold, MAX-MIN, RELΔ, Audible Continuity, Diode Test, Data Hold and APO functions	MIPL	90303390	3600	8910



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
G Analog Insulation Testers					
1	100V - 20MΩ Analog Insulation Tester	MIPL	90303390	MC 901	1485
2	100V - 20MΩ Analog Insulation Tester with Battery Adaptor	MIPL	90303390	MC 901BA	1638
3	500V - 100MΩ Analog Insulation Tester	MIPL	90303390	MC 903	1485
4	500V - 100MΩ Analog Insulation Tester with Battery Adaptor	MIPL	90303390	MC 903BA	1638
5	500V - 500MΩ Analog Insulation Tester	MIPL	90303390	MC 904	1485
6	500V - 500MΩ Analog Insulation Tester with Battery Adaptor	MIPL	90303390	MC 904BA	1638
7	1000V - 200MΩ Analog Insulation Tester	MIPL	90303390	MC 906	1485
8	1000V - 200MΩ Analog Insulation Tester with Battery Adaptor	MIPL	90303390	MC 906BA	1638
9	1000V - 500MΩ Analog Insulation Tester	MIPL	90303390	MC 907	1485
10	1000V - 500MΩ Analog Insulation Tester with Battery Adaptor	MIPL	90303390	MC 907BA	1638
11	500V - 1000MΩ Analog Insulation Tester	MIPL	90303390	MC 941	1665
12	500V - 1000MΩ Analog Insulation Tester with Battery Adaptor	MIPL	90303390	MC 941BA	1818
13	1000V - 2000MΩ Analog Insulation Tester	MIPL	90303390	MC 981	1665
14	1000V - 2000MΩ Analog Insulation Tester with Battery Adaptor	MIPL	90303390	MC 981BA	1818
H Digital Insulation Testers					
1	100V - 20MΩ Digital Insulation Tester	MIPL	90303390	DIT 99A	1323
2	250V - 200MΩ Digital Insulation Tester	MIPL	90303390	DIT 99B	1323
3	500V - 200MΩ Digital Insulation Tester	MIPL	90303390	DIT 99C	1323
4	1000V - 200MΩ Digital Insulation Tester	MIPL	90303390	DIT 99D	1323
5	1000V - 2000MΩ Digital Insulation Tester	MIPL	90303390	DIT 99E	1323
6	2.5kV - 20GΩ Digital Insulation Tester with AC Voltage function	MIPL	90303390	DIT 918	4860
7	2.5kV - 20GΩ Digital Insulation Tester with AC Voltage function	MIPL	90303390	DIT 927	ON REQUEST
8	5kV - 200GΩ Digital Insulation Tester with AC Voltage, Phase Sequence and Phase Status Indicator functions	MIPL	90303390	DIT 954	10602



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
I Clamp - On Earth / Ground Resistance & Leakage Current Testers					
1	Leakage Current Tester with 10µA AC Ultra High Resolution, AC Current (40mA, 400mA, 4A, 40A, 60A), AC Voltage & Resistance Functions, Jaw Opening : For Cable of 30mm Diameter	MMPL	90303390	4671	19350
2	Clamp - On Earth / Ground Resistance Tester (Non Contact Type) with Range : 0.010Ω - 1000Ω, Data Storage Memory, Data Hold, Autoranging, Auto Power Off functions, Jaw Opening : For Earthing Strip of 65 x 32 mm	MIPL	90303390	4680BL	30438
3	Clamp - On Earth / Ground Resistance and Leakage Current Tester (Non Contact Type) with Range : 0.010Ω - 1000Ω, 0.5mA - 30.00mA AC, Data Storage Memory, Data Hold, Autoranging, Auto Power Off functions, Jaw Opening : For Earthing Strip of 65 x 32 mm	MIPL	90303390	4680BLC	34794
4	Clamp - On Earth / Ground Resistance and Leakage Current Tester (Non Contact Type) with Range : 0.025Ω - 1500Ω, 0.300mA - 30.00A AC, Data Logging, Data Hold, Programmable HI - LO Alarm, Autoranging, Auto Power Off functions, Jaw Opening : For Earthing Wire of 23mm Diameter	MMPL	90303390	4680	85968
5	Clamp - On Earth / Ground Resistance and Leakage Current Tester (Non Contact Type) with Range : 0.025Ω - 1500Ω, 0.300mA - 35.00A AC, Data Logging, Data Hold, Programmable HI - LO Alarm, Autoranging, Auto Power Off functions, Jaw Opening : For Earthing Wire of 34.5mm Diameter	MMPL	90303390	4680B	96714
J LCR Meter					
1	LCR Meter , Measures : L, C, R, Z, D, Q, Ø and ESR, Signal Frequency : 100Hz, 120Hz, 1KHz and 10KHz, Test Terminals : 2, 4 and 5 Terminals, USB Interface with Software, Rechargeable Battery and AC Adaptor, Holster, Backlight, Series / Parallel Modes, Manual / Auto, Short / Open, Percentage / MAX / MIN / Average / Data Hold functions	MMPL	90303390	LCR 999A	20520
2	Accessories : SMD 4 Terminal Kelvin Tweezers for LCR999A	MMPL	90309010	SMD 4 TERMINAL KELVIN TWEEZERS FOR LCR 999A	5544



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
K Milli - Ohmmeter and Micro - Ohmmeter					
1	Milli - Ohmmeter with PC Interface via RS232 - USB Communication and User Software , Test Current : 5A DC (120mΩ), Four Terminal Kelvin Measurement, Manual / Auto Range, Measurement of Resistive and Inductive Materials, HI / LO / PASS Settings, Memory for 3000 Measurement Data, Programmable HI - LO Alarm with 20 Data Memory, Backlight, Rechargeable Batteries with AC Adaptor, LO Battery Indication, Cable Length Measurement in ft / meters, Data Hold, RS232 - USB Bridge Cable, 1 Set of Kelvin Clips	MMPL	90303390	7002	49356
2	Micro - Ohmmeter with PC Interface via RS232 - USB Communication and User Software , Test Current : 10A DC (60mΩ), Four Terminal Kelvin Measurement, Manual / Auto Range, Measurement of Resistive and Inductive Materials, HI / LO / PASS Settings, Memory for 3000 Measurement Data, Programmable HI - LO Alarm with 20 Data Memory, Backlight, Rechargeable Batteries with AC Adaptor, LO Battery Indication, Cable Length Measurement in ft / meters, Data Hold, RS232 - USB Bridge Cable, 1 Set of Kelvin Clips	MMPL	90303390	7272	92277
3	Accessories : Banana Plug Crocodile Clip Test Lead for 7002 / 7272	MMPL	90309010	BANANA PLUG CROCODILE CLIP TEST LEAD FOR 7002 / 7272	1107
4	Accessories : 4 Wire Double Prod Test Lead for 7002 / 7272	MMPL	90309010	4 WIRE DOUBLE PROD TEST LEAD FOR 7002 / 7272	3330
5	Accessories : Kelvin Clip Test Leads for 7002 / 7272	MMPL	90309010	KELVIN CLIP TEST LEADS FOR 7002 / 7272	3330
L Transformer Turns Ratio Meter					
1	Transformer Turns Ratio Meter with PC Communication Software , Measurement of 1P / 3P Current / Voltage, Transformer's Turns Ratio, Excitation Voltage, Current, Phase Angle and Deviation. Live Test Points, Short Circuit, Open Circuit, Reverse Polarity. VTR / PTR : 0.8000 - 10000 (Autoranging), CTR : 0.8000 to 2000.0 (Autoranging)	MMPL	90303390	TTR 8100	161730



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
M Battery Capacity Testers / Battery Meters					
1	Automotive Battery Meter : 2 -200Ah, 2 - 6 - 12V DC, with Internal Resistive Load, Indicates Battery Condition as FULL / NORMAL / RECHARGE / DISCHARGE	MMPL	90303390	ABM18	1098
2	Battery Meter : 4 -500Ah, 2 - 6 - 12V DC, with DC Voltmeter upto 0 - 15 VDC and Internal Resistive Load, Indicates Battery Condition as OK / WEAK / BAD	MMPL	90303390	BM63	1512
3	Digital Battery Meter : 40 -200Ah, 6 / 12V DC, with DC Voltmeter upto 0 - 19.99V DC and Internal Resistive Load with Built - In Timer and Charging Test, Indicates Battery Condition as GOOD / WEAK / BAD	MIPL	90303390	DBM72	5382
4	Battery Capacity (Impedence) Tester : Upto 500 Ah & 40V DC with PC Communication, with Software, Comparator Function, Measures Online Internal Impedence / Resistance and Open Circuit Voltage for All Types of Batteries	MMPL	90303390	6363	62037
5	Battery Capacity (Impedence) Tester with DC Clamp Meter (Adaptor) : Upto 1200 Ah & 60V DC with PC Communication and Software, Comparator Function, Measures Online Internal Impedence / Resistance, Open Circuit Voltage, Load Current, Terminal Temperature and SOC	MMPL	90303390	6390	108540
6	Accessories : Alligator Clip Test Leads for 6363	MMPL	90309010	TEST LEADS FOR 6363	3636
7	Accessories : Alligator Clip Test Leads for 6390 (4 Jacks)	MMPL	90309010	ALLIGATOR CLIP TEST LEADS FOR 6390 (4 JACKS)	7740
8	Accessories : Pin Type Test Leads for 6390 (4 Jacks)	MMPL	90309010	PIN TYPE TEST LEADS FOR 6390 (4 JACKS)	7740
N Automotive Meters					
1	Vehicle Battery System Meter Suitable for 12V DC Batteries, Measures Battery State (CCA / IR / DC V) CCA Range : 100 - 1700, Engine Activation Load Test and Charging Test	MIPL	90303390	VBSM 6129B	2799
2	Multifuction Automotive Meter having Combined Functions of Auto Ranging DMM, Power Probe, Logic Probe Test Leads (Both Pinpoint & Hook), Measures AC/DC Voltage, Resistance, Temperture, Flash Light, Data Hold, Continuity and Logic Test	MMPL	90303390	MAM 6138	2700
3	Digital Automotive Multimeter Suitable to Measure Ignition Frequency, Ms Pulse Width, RPM, DWELL, Duty Cycle, Temperature, AC/DC Voltage, AC/DC Curent, Resistance, Continuity and Diode Test	MMPL	90303390	6255	3231
4	Vehicle Battery System Meter Suitable for 12 and 24 V DC Batteries, Measures Battery State (CCA / IR / DC V) CCA Range : 100 - 1700, Engine Activation Load Test, Maximum Load Test and Charging Test	MIPL	90303390	VBSM 6246	4104
5	Vehicle Battery System Meter with Built - In Printer Suitable for 12 and 24 V DC Batteries, Measures Battery State (CCA / IR / DC V) CCA Range : 100 - 1700, Engine Activation Load Test, Maximum Load Test and Charging Test	MIPL	90303390	VBSM 6246P	12348



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
0 Solar Analyzers					
1	Solar Power Meter (Irradiance Meter) with Orientation and Tilt Angle : 0 - 90°, Irradiance Range : 0-2000 W/m2 (0 - 634 BTU / ft2.h) with Data Hold and Backlight Display	MMPL	90318000	936	11430
2	Solar Module Analyzer (Photovoltaic I - V Curve Tester) : 60V, 12A (500W Capacity), Measures : Vnow, Voc, Isc, Pmax, VmaxP, ImaxP, Efficiency and Fill Factor with PC Connectivity, Memory Record and Backlight Display	MMPL	90303390	9009	117189
3	Solar System Analyzer (Photovoltaic I - V Curve Tester) with DC Current Clamp, AC Power Clamp, Thermo & Irradiance Meter (with Bluetooth Connectivity) : Max. Solar System Power Search by Auto Scan : 1000V DC, 12A DC (12 KW Capacity), Measures Single Panel and String OPC and STC Data with Vnow, Voc, Isc, Pmax, VmaxP, ImaxP, Efficiency and Fill Factor, Real Time Irradiation and Solar Panel Temperature, Inverter Efficiency (DC to AC) with PC (USB) Connectivity, Memory Record and Backlight Display	MMPL	90303390	9018BT + SOLAR 15 + SOLAR 21	239904
P Environment Testing Instruments					
1	Humidity & Temperature Meter : 0 to 100% RH, - 20 to 80°C, °C / °F / RH Selection, MAX / MIN, Auto Power Off	MMPL	90251990	920P	2538
2	Digital LUX Meter (with Flexible Cord Sensor) : 0 - 2,00,000 lux / 0 - 20,000 fc, MAX / MIN, Backlight, Auto Power Off with Disable Function, Data Hold	MMPL	90278090	930T	1764
3	Digital LUX Meter : 0 - 2,00,000 lux / 0 - 20,000 fc, MAX / MIN, Backlight, Auto Power Off	MMPL	90278090	930P	1962
4	Air Flow Anemometer : 1 - 25m/s, 0 to + 50°C, m / Sec, Ft / min, Knots, Km / h, MPH, CFM, MAX / MIN / HOLD, Auto Power Off	MMPL	90303390	961P	1755
5	Digital Sound Level Meter : 35dB - 130dB (31.5 Frequency to 8K Frequency), MAX / MIN / HOLD, Auto Power Off	MMPL	90278090	970P	1674
6	Infrared Thermometer : -50°C to 380°C / -58°F to 716°F, °C / °F Selection, Backlight, MAX / MIN, Auto Power Off	MMPL	90251990	IRT 380T	1116
7	Infrared Thermometer : -50°C to 550°C / -58°F to 1022°F, °C / °F Selection, Backlight, MAX / MIN, Auto Power Off	MMPL	90251990	IRT 550T	1296
8	Infrared Thermometer : -50°C to 1050°C / -58°F to 1922°F, °C / °F Selection, Backlight, MAX / MIN / DIF / AVG / Data Storage, Auto Power Off	MMPL	90251990	IRT 1050P	6858
9	Handheld Thermal Imaging Camera : -20°C to 300°C / -4°F to 572°F, Resolution : 60 x 60, Pixels : 3600, Memory : 4GB Micro SD Card	MMPL	90278090	TIC 300	40473
10	Laser Distance Meter : 0.05 - 60m, Units : Meter / Inches / Feet, Functions : Addition, Subtraction, Area, Volume, Pythagorean, Data Storage	MMPL	90278090	LDM 60	3267
11	Laser Distance Meter : 0.05 - 100m, Units : Meter / Inches / Feet, Functions : Addition, Subtraction, Area, Volume, Pythagorean, Data Storage	MMPL	90278090	LDM 100	5661
12	Electrosmog Meter - 3 Axis (10 MFrequency to 8 GFrequency)	MMPL	90303390	9810	49140



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
Q Power and Harmonics Analyzers / Testers					
1	AC Clamp - On TRMS Power Harmonics and Leakage Tester , Measures : V, A, W, PF, Phase Angle, THD, Crest Factor. Harmonics Analysis (V & A) upto 99th Order. Jaw Opening : For Cable upto 30mm Diameter	MMPL	90303390	PLH 5760	25794
2	AC Clamp-On TRMS Power & Harmonics Tester , Measures : V, A, W, PF, Phase Angle, THD upto 99th Order, Crest Factor, Resistance, Continuity, HP, VA, KVA, VAR, KVAr, WH, KWH and Phase Sequence. Jaw Opening : For Cable upto 55mm Diameter / Bus Bar 64 x 24mm.	MMPL	90303390	PHT 4545	36558
3	Power and Harmonics Analyzer : Complete Portable Kit consisting of PHA 5850, 3 Pcs (R, Y, B) Clamp-On CT's Set "A" of Range : 1 / 10 / 100A AC, Voltage Test Leads with Crocodile Clips - 4 Pcs (R, Y, B, N), Carrying Bag, 8 Pcs (1.5V DC) Batteries, External DC Adaptor, Software CD, Users & Software Manual, Optical Isolated USB Cable. PHA 5850 Measures : Single / Three Phase System, TRUE RMS Value, Harmonics (V & A) upto 99th Order, THD, Energy, Active / Reactive / Apparent Power, Power Factor, Maximum Demand, Phase Angle, Graphic Phasor Diagram, Waveform with Peak Value. Built in Memory (512K) , Programmable CTR / PTR, User Friendly Software. Jaw Opening : Suitable for Cable / Conductor upto 30mm Diameter	MMPL	90303390	PHA 5850A	184995
4	Power and Harmonics Analyzer : Complete Portable Kit consisting of PHA 5850, 3 Pcs (R, Y, B) Clamp-On CT's Set " B" Range : 10 / 100 / 1000A AC, Voltage Test Leads with Crocodile Clips - 4 Pcs (R, Y, B, N), Carrying Bag, 8 Pcs (1.5V DC) Batteries, External DC Adaptor, Software CD, Users & Software Manual, Optical Isolated USB Cable. PHA 5850 Measures : Single / Three Phase System, TRUE RMS Value, Harmonics (V & A) upto 99th Order, THD, Energy, Active / Reactive / Apparent Power, Power Factor, Maximum Demand, Phase Angle, Graphic Phasor Diagram, Waveform with Peak Value. Built in Memory (512K) , Programmable CTR / PTR, User Friendly Software. Jaw Opening : Suitable for Cable / Conductor upto 55mm Diameter / Bus Bar 64 x 24mm	MMPL	90303390	PHA 5850B	184995
5	Power and Harmonics Analyzer : Complete Portable Kit consisting of PHA 5850, 3 Pcs (R, Y, B) Flexible CT Set "C" Range : 300 / 3000A AC, Voltage Test Leads with Crocodile Clips - 4 Pcs (R, Y, B, N), Carrying Bag, 8 Pcs (1.5V DC) Batteries, External DC Adaptor, Software CD, Users & Software Manual, Optical Isolated USB Cable. PHA 5850 Measures : Single / Three Phase System, TRUE RMS Value, Harmonics (V & A) upto 99th Order, THD, Energy, Active / Reactive / Apparent Power, Power Factor, Maximum Demand, Phase Angle, Graphic Phasor Diagram, Waveform with Peak Value. Built in Memory (512K) , Programmable CTR / PTR, User Friendly Software. Probe Dimensions : Length : 24 Inches / 610 mm, Minimum Bending Diameter : 35mm, Inner Diameter : 160 mm (approx.), Connector Diameter : 23mm, Cable Diameter : 14mm, Cable Length : From Probe to Box : 1700 mm & From Box to Output : 1700mm	MMPL	90303390	PHA 5850C	184995



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
6	Power and Harmonics Analyzer : Complete Portable Kit consisting of PHA 5850, 3 Pcs (R, Y, B) Flexible CT Set "D" Range : 120 / 1200A AC, Voltage Test Leads with Crocodile Clips - 4 Pcs (R, Y, B, N), Carrying Bag, 8 Pcs (1.5V DC) Batteries, External DC Adaptor, Software CD, Users & Software Manual, Optical Isolated USB Cable. PHA 5850 Measures : Single / Three Phase System, TRUE RMS Value, Harmonics (V & A) upto 99th Order, THD, Energy, Active / Reactive / Apparent Power, Power Factor, Maximum Demand, Phase Angle, Graphic Phasor Diagram, Waveform with Peak Value. Built in Memory (512K) , Programmable CTR / PTR, User Friendly Software. Probe Dimensions : Length : 18 Inches / 460 mm, Minimum Bending Diameter : 35 mm, Inner Diameter : 110 mm, Connector Diameter : 23 mm, Cable Diameter : 14 mm, Cable Length : From Probe to Box : 1700 mm & From Box to Output : 1700mm	MMPL	90303390	PHA 5850D	184995
7	Clamp-On CT's Suitable for PHA 5850 of Triple Range : 1 / 10 / 100A AC , One Set = 3 Pcs (R, Y, B), Jaw Opening : For Conductor upto 30mm Diameter	MMPL	85049090	CT SET A	41994
8	Clamp - On CT's Suitable for PHA 5850 of Triple Range : 10 / 100 / 1000A AC , One Set = 3 Pcs (R, Y, B), Jaw Opening : For Conductor upto 55mm Diameter / 64 x 24mm Busbar	MMPL	85049090	CT SET B	41994
9	Flexible CT's Suitable for PHA 5850 of Dual Range : 300 / 3000A AC , One Set = 3 Pcs (R, Y, B)	MMPL	85049010	CT SET C	41994
10	Flexible CT's Suitable for PHA 5850 of Dual Range : 120 / 1200A AC , One Set = 3 Pcs (R, Y, B)	MMPL	85049010	CT SET D	41994
11	Accessories : Cable for Clamp-On CT for PHA 5850	MMPL	90309010	CABLE FOR CLAMP-ON CT FOR 5850	1980
12	Accessories : Voltage Test Leads (R,Y,B, N) for PHA 5850	MMPL	90309010	VOLTAGE TEST LEADS (R,Y,B,N) FOR 5850	3960
13	Accessories : Alligator Clip (R, Y, B, N) for PHA 5850	MMPL	90309010	ALLIGATOR CLIP (R,Y,B,N) FOR 5850	2205

R	Clamp-On Power Meters				
1	Clamp-On TRMS Power Meter (1000A, 600kW) Autoranging with Dual Display , Automatic Computation of 1Phase and 3Phase (3P3W/3P4W) Parameters. Measures : TRMS AC A, AC / DC V, TRUE Power, HP, KW, KVA, KVAR, HZ, PF, AC Inrush Current, TRMS uA (AC + DC) Phase Angle, 3 Phase Sequence Indicator, Resistance (Continuity), Capacitance, Diode, Temperature, Data Hold and Auto Power Off. Jaw Opening : For Cable / Conductor upto 43mm / Busbar upto 65mm x 16mm	MMPL	90303390	3510 PHW AUTO	14256
2	3Phase / 1Phase TRMS Clamp-On Autoranging Power Meter for AC/DC Power Measurement (2000A, 2000kW) with PF, Phase Angle, Frequency & Memory for Recording. Jaw Opening : For Cable of 55mm Diameter / Bus Bar 65 x 24mm	MMPL	90303390	4500	32913



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
S Calibrating Equipments					
1	Multifunction Process Calibrator : Provides Standard Output for mA, mV, V, Frequency, K, J, E and T Thermocouples	MMPL	90303390	333	32238
2	Universal Calibrator	MMPL	90303390	90A	454284
3	Multifunctional Calibrator	MMPL	90303390	90DQ	890514
4	AC Multifunctional Calibrator	MMPL	90303390	90P	1217745
5	Accessories : Standard Current Coil with Input 5A AC / DC (max.), Turn Ratio 100 / 1	MMPL	85049090	5A (For 90DQ / 90P)	30600
6	Accessories : Standard Current Coil with Input 10A AC / DC (max.), Turn Ratio 100 / 1	MMPL	85049090	10A (For 90P / 90DQ)	30600
7	Accessories : Standard Current Coil with Input 20A AC / DC (max.), Turn Ratio 50 / 1	MMPL	85049090	20A (For 90A)	30600
8	Upto 2.5kV - 5GΩ High Voltage Resistance Box having 17 Selectable Fixed Resistance Values	MIPL	90303390	90DR	74700
9	Upto 5kV - 211.1111110GΩ High Voltage Resistance Box having 10 Adjustable Potentiometric Resistance Values with 4½ Digit Display upto 5000V DC Voltage	MIPL	90303390	90DR45D	292500

T Clamp - On CT's and Flexible AC Current Probes (High Current)					
1	Clamp - On CT, Input : 100A AC, Output : 5A AC , Casing : Blue Colour (with Red or Yellow or Blue Colour Sticker Identification), Jaw Opening : Suitable for Conductor upto 50mm Diameter, Output Connection : 2m Leads	MMPL	85049090	CCT50 - 100A AC	4653
2	Clamp - On CT, Input : 500A AC, Output : 5A AC , Casing : Blue Colour (with Red or Yellow or Blue Colour Sticker Identification), Jaw Opening : Suitable for Conductor upto 50mm Diameter, Output Connection : 2m Leads	MMPL	85049090	CCT50 - 500A AC	4653
3	Clamp - On CT, Input : 1000A AC, Output : 5A AC , Casing : Blue Colour (with Red or Yellow or Blue Colour Sticker Identification), Jaw Opening : Suitable for Conductor upto 50mm Diameter, Output Connection : 2m Leads	MMPL	85049090	CCT50 - 1000A AC	4653
4	Clamp - On CT, Input : 2000A AC, Output : 5A AC , Casing : Black Colour (with Red or Yellow or Blue Colour Sticker Identification), Jaw Opening : Suitable for Conductor upto 60mm Diameter, Output Connection : 2m Leads	MMPL	85049090	CCT602 - 2000A AC	4860
5	Flexible AC Current Probes, Input : 3000A AC @ 50Hz, Output : 300mV AC , ID : Suitable for Cable of 100mm Diameter, Output Connections : 1m Leads, Power Supply : 9V DC	MMPL	85049010	FCT100 - 3000A AC	4455
6	Clamp - On CT, Input : 100A AC, Output : 1A AC , Colours : Red or Yellow or Blue, Jaw Opening : Suitable for Conductor upto 15mm Diameter, Output Connection : Safety Sockets Suitable for 4mm Banana Plug	MMPL	85049090	M1	7335
7	Clamp - On CT, Input : 200 or 500 or 1000A AC (Any Single Range), Output : 5A AC , Colours : Red or Yellow or Blue, Jaw Opening : Suitable for Conductor upto 53mm Diameter, Output Connection : Safety Sockets Suitable for 4mm Banana Plug	MMPL	85049090	S (SINGLE RANGE)	12348
8	Clamp - On CT, Input : 100, 500, 1000A AC (Triple Range in One CT), Output : 5A AC , Colours : Red or Yellow or Blue, Jaw Opening : Suitable for Conductor upto 53mm Diameter, Output Connection : Safety Sockets Suitable for 4mm Banana Plug	MMPL	85049090	S (TRIPLE RANGE)	16461



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
U POWERGUARD					
1	POWERGUARD having Indian Plug - Socket and Backlight to Display : W (0.2 - 2200.0W), PF, CO2 (kg), TUT, Money, Tarrif, Frequency, KWh, V (195.00 - 265.00V AC) and mA (10000mA max.). Built - In Programmable ON / OFF Relay with Timer Function for Control of Load	MMPL	90303390	PG08T	1413
2	POWERGUARD having Indian Plug - Socket and Backlight to Display TRMS : W (2.400 - 288.0W), V (195.0 - 265.0V AC), Frequency, A (0.010 - 1.200A), PF, VA, VAr, KWh, EUT and CO2 (kg)	MIPL	90303390	PG09 - 1A	2205
3	POWERGUARD having Indian Plug - Socket and Backlight to Display TRMS : KW (0.024 - 1.440KW), V (195.0 - 265.0V AC), Frequency, A (0.100 - 6.000A), PF, KVA, KVAr, KWh, EUT and CO2 (kg)	MIPL	90303390	PG09 - 5A	2205
4	POWERGUARD having Indian Plug - Socket and Backlight to Display TRMS : KW (0.026 - 4.800KW), V (195.0 - 265.0V AC), Frequency, A (0.110 - 20.00A), PF, KVA, KVAr, KWh, EUT and CO2 (kg)	MIPL	90303390	PG09 - 20A	2250
V HVAC					
1	Digital HVAC Manifold Meter without Temperature Clamps	MIPL	90262000	9900	11430
2	Digital HVAC Manifold Meter with Temperature Clamps	MIPL	90262000	9900T	16200
W Phase Sequence Indicator					
1	Phase Sequence Indicator of Voltage Range : 60 - 600V AC, Frequency Range : 40 - 400Hz with LED Indication and Buzzer	MIPL	90303390	PSI 2016	900



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE (₹)
X Accessories					
1	Accessories : One Pair of Test Leads Suitable for DMM / DTT	MMPL	90309010	TL - DMM / DTT	50
2	Accessories : One Pair of Test Leads Suitable for Insulation Tester MC900 Series / DIT99 Series	MMPL	90309010	TL - IT	50
3	Accessories : K Type Bead Probe (Upto 260°C) Suitable for use with DTT 2727, 3510PHW etc	MMPL	85339000	TPK - B	200
4	Accessories : K Type Stick Probe (Upto 500°C) Suitable for use with DMM 9A06, DMM 801AUTO etc	MMPL	85339000	TP - 02	200
5	Accessories : One Pair of Connecting Leads Suitable for Clamp-On CT's (1 Side Banana and 1 Side U Clip) - 2M	MMPL	90309010	CONNECTING LEADS FOR CURRENT CLAMPS (1 SIDE BANANA & 1 SIDE U CLIP) - 2M	900
6	Accessories : One Set of Connecting Leads for Clamp-On CT's (Red x 1 pc, Yellow x 1 pc, Blue x 1 pc and Black x 3 pcs = 6 pcs) with One Side Banana Jack and One Side U Clip	MMPL	90309010	CONNECTING LEADS FOR CURRENT CLAMPS (1 SIDE BANANA & 1 SIDE CROCODILE CLIP) - 2M	900
7	Accessories : One Set of Connecting Leads for Voltage Measurement (Red x 1 pc, Yellow x 1 pc, Blue x 1 pc and Black x 1 pcs = 4 pcs) with One Side Banana Jack and One Side Crocodile Jack	MMPL	90309010	CONNECTING LEADS FOR VOLTAGE MEASUREMENT - 2M	600
8	RS-485 to RS-232 Converter	MMPL	85049090	RS-485 TO RS-232 CONVERTER	1500
Y Installation Charges					
1	Installation and Commissioning Charges per Man Day (To and Fro, Conveyance, Boarding and Lodging Charges extra at Actuals)	MMPL	00440233	INSTALLATION & COMMISSIONING CHARGES - PER MAN DAY	2500



For MECO INSTRUMENTS PRIVATE LIMITED

Business Terms and Conditions

General

- This Price List supersedes all our previous Price Lists.
- Order to be placed on **MECO INSTRUMENTS PRIVATE LIMITED, EL-01, MIDC Electronic Zone, TTC Industrial Area, Mahape, Navi Mumbai 400 710.**
- All products are guaranteed for 12 months against defective workmanship as per our standard guarantee policy.
- This Price List is subject to Navi Mumbai Jurisdiction only.
- Prices are subject to change without notice.

Commercial & Taxes

- Prices are Ex-Works (Navi Mumbai). Packing, forwarding, freight, insurance, bank charges, overdue interest, wharf-age, demurrage and other incidental expenses shall be extra.
- Minimum order value is Rs. 10000, otherwise handling charges Rs. 200 extra per dispatch.
- Please provide complete specification and reference number with date of our correspondence at the time of placing order.
- **Taxes (GST) :**
For **Maharashtra Sale** : GST @ 18% [CGST @ 9% + SGST @ 9%] .
For **Out of Maharashtra Sale** : IGST @ 18% extra.

Please Mention In Your PO

1. GSTIN Number, TIN Number, CIN Number, PAN Number.
2. Buyers Company Name, Billing Address, Contact Person Name and Mobile Number
3. Consignee Company Name, Delivery Address, Contact Person Name and Mobile Number
4. Transport / Freight Details
5. Insurance Details

Registration Details / Numbers

GSTIN	TIN	CIN	PAN
27AAACM2883Q1ZU	27940002826	U33120MH1969PTC014477	AAACM2883Q

Payment and Banking

- 100% payment in advance against Performa Invoice by E-Payment (vide RTGS / NEFT mode) or DD / Cheque payable at Mumbai prior to dispatch of goods.
- In case of non - standard products or non - familiar customers, the payment terms will be 20% in advance with the order and balance payment against Performa Invoice prior to dispatch of goods.
- Our bank details as below. Kindly inform payment details by E-mail after remitting the payment. Goods will be dispatched within 2 - 3 working days thereafter.

Beneficiary Name	MECO INSTRUMENTS PRIVATE LIMITED
Bank Name	CANARA BANK, Vashi Branch,
Bank Address	Showroom 1, Ground Floor, Emerald Building, Next to Neel Siddhi Tower, Plot 195B, Sector 12, Vashi, Navi Mumbai - 400703
A/C Number	0110261020612
NEFT & IFSC	CNRB0003302
MICR Code of Bank	400015145
Account Type	Overdraft Cash Credit / OCC

Calibration

All Instruments are calibrated through a chain of internal standards which are ultimately traceable to National Standards. However calibration and traceability certificate is issued only against specific requirement at extra charges. Please inform at the time of inquiry / ordering.

Service Centres

- Bengaluru : **Sarvashree Service Centre**, L-95, Kirloskar Colony 3rd Stage, 5th Cross, 1st Main, Water Tank Road, Basaveshwar Nagar, Landmark : Near BBMP Ward Office, Bengaluru - 560 079 (INDIA) **Tel** : +91-80-23223936
E-mail : info@mecosouth.in
- Navi Mumbai : **Meco Export Company**, Plot No. EL-60, MIDC Electronic Zone, TTC Industrial Area, Mahape, Navi Mumbai - 400 710 (INDIA) **Tel** : +91-22-27636162 / 07303396162 **E-mail** : service@mecoinst.com



For **MECO METERS PRIVATE LIMITED**

Business Terms and Conditions

General

- This Price List supersedes all our previous Price Lists.
- Order to be placed on **MECO METERS PRIVATE LIMITED, EL-60, MIDC Electronic Zone, TTC Industrial Area, Mahape, Navi Mumbai 400 710.**
- All products are guaranteed for 12 months against defective workmanship as per our standard guarantee policy.
- This Price List is subject to Navi Mumbai Jurisdiction only.
- Prices are subject to change without notice.

Commercial & Taxes

- Prices are Ex-Works (Navi Mumbai). Packing, forwarding, freight, insurance, bank charges, overdue interest, wharf-age, demurrage and other incidental expenses shall be extra.
- Minimum order value is Rs. 10000, otherwise handling charges Rs. 200 extra per dispatch.
- Please provide complete specification and reference number with date of our correspondence at the time of placing order.
- **Taxes (GST) :**
For **Maharashtra Sale** : GST @ 18% [CGST @ 9% + SGST @ 9%] .
For **Out of Maharashtra Sale** : IGST @ 18% extra.

Please Mention In Your PO

1. GSTIN Number, TIN Number, CIN Number, PAN Number.
2. Buyers Company Name, Billing Address, Contact Person Name and Mobile Number
3. Consignee Company Name, Delivery Address, Contact Person Name and Mobile Number
4. Transport / Freight Details
5. Insurance Details

Registration Details / Numbers

GSTIN	TIN	CIN	PAN
27AAACM5996Q1ZI	27130006327	U331909MH1996PTC104061	AAACM5996Q

Payment and Banking

- 100% payment in advance against Performa Invoice by E-Payment (vide RTGS / NEFT mode) or DD / Cheque payable at Mumbai prior to dispatch of goods.
- In case of non - standard products or non - familiar customers, the payment terms will be 20% in advance with the order and balance payment against Performa Invoice prior to dispatch of goods.
- Our bank details as below. Kindly inform payment details by E-mail after remitting the payment. Goods will be dispatched within 2 - 3 working days thereafter.

Beneficiary Name	MECO METERS PRIVATE LIMITED
Bank Name	CANARA BANK, Vashi Branch,
Bank Address	Showroom 1, Ground Floor, Emerald Building, Next to Neel Siddhi Tower, Plot 195B, Sector 12, Vashi, Navi Mumbai - 400703
A/C Number	0110261021536
NEFT & IFSC	CNRB0003302
MICR Code of Bank	400015145
Account Type	Overdraft Cash Credit / OCC

Calibration

All Instruments are calibrated through a chain of internal standards which are ultimately traceable to National Standards. However calibration and traceability certificate is issued only against specific requirement at extra charges. Please inform at the time of inquiry / ordering.

Service Centres

- Bengaluru : **Sarvashree Service Centre**, L-95, Kirloskar Colony 3rd Stage, 5th Cross, 1st Main, Water Tank Road, Basaveshwar Nagar, Landmark : Near BBMP Ward Office, Bengaluru - 560 079 (INDIA) **Tel** : +91-80-23223936
E-mail : info@mecosouth.in
- Navi Mumbai : **Meco Export Company**, Plot No. EL-60, MIDC Electronic Zone, TTC Industrial Area, Mahape, Navi Mumbai - 400 710 (INDIA) **Tel** : +91-22-27636162 / 07303396162 **E-mail** : service@mecoinst.com



BUREAU VERITAS
Certification

MECO INSTRUMENTS PVT. LTD.



PLOT NO. EL-1, MIDC ELECTRONIC ZONE, TTC IND. AREA, MAHAPR.
NAVI MUMBAI - 400 710, MAHARASHTRA, INDIA.

Bureau Veritas Certification Holding SAS - UK Branch certifies that the Management System of the above organization has been audited and found to be in accordance with the requirements of the Management System standard detailed below.

Standard

ISO 9001:2015

Scope of certification

MARKETING, DESIGN AND MANUFACTURING OF VARIOUS ELECTRICAL / ELECTRONIC MEASURING INSTRUMENTS, ELECTRICAL TRANSDUCERS AND ACCESSORIES

Original cycle start date:	14 December 2002
Expiry date of previous cycle:	13 December 2017
Recertification Audit date:	18 November 2017
Recertification cycle start date:	18 December 2017

Subject to the continued satisfactory operation of the organization's Management System, the certificate expires on: **13 December 2021**

Certificate No: **IND17 2927UG** Version: 1 Revision date: **19 December 2017**

[Signature]

Signed as holder of BVCA SAS - UK Branch
Ramesh ADREDDY
Director, CERTIFICATION
South Asia Region



0006

Certification body: Bureau Veritas Certification (UK) Ltd, 110 Rue de la Liberte, London, E14 4JG, United Kingdom
Local office: MECO Instruments Private Limited (Certification Business), 17, Ghandari Park, Sherat Industrial Estate, TTC Zone, Near TTC, MIDC, Navimumbai - 400 710, Maharashtra, India.
Further certification requires the scope of this certificate and the responsibility of the Management System representative may be altered by consulting the representative. For more details contact your office or 490 02 5000 0000.

ISO 9001:2015 CERTIFICATE

5 JAN 2007



पावर ग्रिड कॉर्पोरेशन ऑफ इंडिया लिमिटेड
POWER GRID CORPORATION OF INDIA LIMITED
A Government of India Company

पॉवर ग्रिड कॉर्पोरेशन ऑफ इंडिया लिमिटेड, एन.टी.सी. इंडस्ट्रियल एरिया, नावि मुंबई - ४०० ७१०, महाराष्ट्र, भारत
Power Grid Corporation of India Limited, TTC Industrial Area, Navimumbai - 400 710, Maharashtra, India

COA/MSV January 23, 2007

M/s MecO Instruments Pvt. Ltd.,
Plot No.EL-1, MECC Electronic Zone,
TTC Industrial Area, Mahape,
Navi Mumbai-400710

Fax No. 022-27633102/27633300

Kind Attn: - Shri Kamal Gulbys (CEO)

Sub: - Approval of MECO Make Indicating Instruments, Transducers & Meters.

Dear Sir,


This has reference to your letter no. nil dated 17.01.2007. In this regard, we have reviewed your request and hereby convey our approval of MECO Instruments Pvt. Ltd., Mumbai (MECO make) as a vendor for supply of indicating instruments, meters (analog and digital), transducers, indicating meters with transducers under LT Panel, DG set, AC & DC Control Panels, Miscellaneous control items for switchyard, transformer & motor and control & relay panel packages for POWERGRID projects. This approval will be treated in continuation to our approval recorded vide letter no. COA/MSV dated 23.01.2004.

Thanking you,

Yours Sincerely,


[Signature]
(S. PRAKASH RAO)
DY. GENERAL MANAGER (QA&E)

PCCIL APPROVAL



TEST / CALIBRATION REPORT

Type Test Report
for
MECO AC Voltage Transducer
Testing as per IEC 60386 (Edition 2:03)



ELECTRONICS REGIONAL TEST LABORATORY (WEST)
MINISTRY OF COMMUNICATIONS & INFORMATION TECHNOLOGY, (SEC 06),
Government of India

Plot No. 2, P. O. 2, Sector 4, Gurgaon, Haryana
Pincode - 122 002, Gurgaon, Haryana
Phone: 0122-2632 2004, 2632 2100, 2632 2100 Fax: 0122-2632 2100
E-mail: info@stqc.gov.in

F767

STQC TYPE TEST REPORT



ENGINEERS INDIA LIMITED
A Govt of India Undertaking

Engineers India Limited, 1, Sharda Park, New Delhi - 110004
Regd. Office: Engineers India House, 1, Sharda Park, New Delhi - 110004

Procurement Development Department

Ref: 4954/PCG/REM-29 21st March, 2005

M/s MECO Instrument Pvt. Ltd.,
301, Sherat Industrial Estate
T.J. Road, Sewree
Mumbai - 400 015.

Subject: - Revalidation of Enlistment with EIL.

Dear Sirs,

We refer to your application on subject matter and are pleased to inform that your enlistment with EIL has been revalidated for the items as described below:

Item/Description	Type
Meters	Voltmeters, Ammeters, KW Meters, Frequency Meters, Power Factor Meters

This enlistment is valid for your works located at Gating Building, 3rd Floor, T.J. Road, Sewree, Mumbai - 400 015.

Please note that this revalidation is subject to satisfactory execution of orders / sub-orders in delivery and quality of above mentioned items when ordered / sub-ordered for our various projects.

Further, it may be noted that any change in the product range, location of Works/Sales Office, Management/ Organisation structure etc. shall be intimated to us immediately along with relevant document for our necessary action. In case, information to any of the above referred changes is not intimated timely, our enquiries may not reach you and your enlistment with us is liable to be cancelled. Enlistment with EIL shall not guarantee any regular flow of enquiries.

The validity of this ENLISTMENT is upto 31st March, 2008.

You are advised to contact us 6 months before expiry of the enlistment, so that revalidation of your enlistment is taken up.

Thanking you,

Very truly yours,

[Signature]
(S. Prakash)
Dy. General Manager
Procurement Development Department

संपर्क के लिए - 011-2632 2004

फैक्स नं. - 011-2632 2100

ईमेल - info@engineersindia.com

ऑफिस का पता - 1, शर्दा पार्क, नई दिल्ली - 110004

फैक्स नं. - 011-2632 2100

वेब साइट - http://www.engineersindia.com

संकेत नं. ई. ई. 000-सी. संकेत 001

EIL APPROVAL



Welcome to MECO - Mahape



Sales & Marketing Department



Product Display Gallery



Incoming QC



Stores & Material Handling



Meter Assembly Line



Conveyor-Belt Production Line



World Class Calibrating Equipment



Burn-In at 55°C to Ensure Stability



Environmental Chamber To Simulate -20°C to 100°C (Rh upto 100%)



In-House Tool Room Facility



Final Packaging for Safe & Secure Transportation



Training



Seminar



MECO Awards



MECO INSTRUMENTS PRIVATE LTD.

EL-1, MIDC Electronic Zone TTC Industrial Area,
Mahape, Navi Mumbai - 400710 (INDIA)

MECO METERS PRIVATE LTD.

EL-60, MIDC Electronic Zone, TTC Industrial Area,
Mahape, Navi Mumbai - 400710 (INDIA)

Tel. : +91-22-27673311-16 (Sales), 27673300 (Board) Fax : +91-22-27673310

Email : sales@meconst.com Web : www.meconst.com

Connect With Us : 