

Product Brief



Faster Flash

- Completes data warehousing transactions in 1/4 of the time¹
- Meet the massive bandwidth requirements of flash storage arrays with up to 32GFC throughput and enable next-gen 128GFC SANs
- Maximize the performance of flash-based systems by prioritizing mission-critical traffic in congested networks with the exclusive ExpressLane feature
- NVMe-enabled capability delivers an additional 55% lower latency and supports NVMe over Fibre Channel and traditional SCSI over Fibre Channel concurrently

Better Virtualization

- Near limitless scalability to support maximum VM density with 2X more on-chip resources & bandwidth
- Improved VDI experience with low-latency HBAs providing noticeable improvements during boot storms
- Simplified management & installation with OneCommand® Manager plug-in for VMware vCenter server

Lossless, Reliable Networking

- Near zero downtime— FC's lossless design ensures no dropped packets and maximum uptime
- Industry Leader for Reliability— Emulex HBAs can provide up to 1,141 years of uninterrupted service!²

Emulex® Gen 6 Fibre Channel HBAs

LPe31000/LPe32000-Series

Faster Flash. Better Virtualization. Lossless Networking.

The Emulex Gen 6 (16/32G) Fibre Channel (FC) Host Bus Adapters (HBAs) by Broadcom are designed to address the demanding performance, reliability, and management requirements of modern networked storage systems that utilize high-performance and low-latency solid state storage drives for caching and persistent storage as well as hard disk drive arrays.

Fibre Channel is the gold standard for network storage connectivity in enterprise and cloud deployments. The latest Emulex Gen 6 FC HBAs offer higher performance, lower latency, enhanced diagnostics, and manageability that benefit both 16GFC and 32GFC environments and next-gen 128GFC SANs. Emulex LPe31000-series HBAs are available with single, dual, or quad 16GFC optics that can be upgraded with 32GFC optics to utilize the full performance of Gen 6 FC technology. A second quad-port 16GFC model is available that features a low-profile design. It provides the highest port density within a low-profile form factor. The LPe32000-series HBAs are available with single, dual, or quad 32GFC optics.

Unique to Fibre Channel technology is its deep ecosystem support making it ideal for large scale, easy-to-manage storage deployments. Users can count on a complete suite of management software, in-box drivers for mainstream server operating systems, software-defined storage

APIs and tools, and the strength to support high service-level agreement (SLA) applications.

Accelerate

The unique Emulex Dynamic Multi-core Architecture delivers unparalleled performance and more efficient port utilization than other HBAs by applying all ASIC resources to any port that needs it.

Compared to the previous generation, Emulex Gen 6 HBAs deliver 2x greater bandwidth — 12,800 MB/s (2 ports 32G, or 4 ports 16GFC, full duplex), less than half the latency, and support an industry-leading 1.6 million IOPS on a single port, ensuring SLAs are met. The quad-port LPe32004 supports SANs of up to 128GFC by quadrupling throughput from 32GFC to 128GFC to deliver full-duplex speeds of 25,600 MB/s and up to 3.2M IOPS per adapter. 128GFC and 32GFC provide seamless backward compatibility to 16GFC and 8GFC networks.

1. Demartek TPC-H testing performed with Emulex Gen 6 FC HBAs in a Microsoft SQL Server environment versus the previous generations of HBAs

2. Based on published FIELD MTBF of 10 million hours for the Emulex family of FC HBAs.



Emulex Gen 6 HBAs are an excellent choice for database applications as recent TPC-H testing in a data warehousing environment have demonstrated up to 71% faster completion times versus the previous generations of HBAs. To enable the highest Virtual Machine density, Gen 6 HBAs provide support for up to 255 virtual functions, 1,024 Message Signaled Interrupts, and expansive on-board context for exchanges and logins.

NVM Express (NVMe) is a relatively new protocol for solid-state storage devices built with non-volatile memory technologies. NVMe provides substantially lower latency for storage I/O operations and significantly higher IOPS per device. NVMe scales-up the number of devices it can address by adopting NVMe over Fabrics technology.

Emulex Gen 6 HBAs are NVMe over Fibre Channel-enabled, providing an additional 55% lower latency for storage I/O operations versus SCSI. Gen 6 NVMe-enabled HBAs support NVMe over Fibre Channel and SCSI over Fibre Channel concurrently, allowing data centers to transition to all-flash storage at their own pace.

Protect

Emulex Gen 6 FC HBAs deliver enhanced security via the new secure firmware update feature which protects and ensures the authenticity of device firmware.

Forward Error Correction (FEC) is a Gen 6 Fibre Channel standard feature that provides enhanced data reliability and performance by automatically detecting and recovering from bit errors. It is especially useful in diverse and complex user environments such as blade system implementations. FEC is a digital signal processing technique that introduces

redundant data, called an error correcting code, prior to data transmission. FEC then provides the receiver with the ability to correct errors without a reverse channel to request the retransmission of data, which improves performance.

T10 Protection Information (T10-PI) data integrity with high performance hardware offload provides data protection from the server to the storage array. As one of the founders of the Data Integrity Initiative (DII), Emulex, along with Oracle and Seagate, was instrumental in defining the T10-PI standard, which, along with the Data Integrity Extensions (DIX) standard, delivers full end-to-end data integrity. T10-PI assures the validity of I/O operations through the exchange of verification information during data transmissions.

Emulex HBAs are renowned for reliability, ensuring maximum SAN uptime. Their “It Just Works” reputation is based on 17 million installed ports with proven industry-leading reliability of 10 million hours field Mean Time Between Failures (MTBF).

Control

The flagship Emulex HBA Manager application, formerly known as OneCommand Manager, features a multiprotocol, cross-platform architecture that provides centralized management of all current and previous generations of Emulex FC HBAs. This enables IT administrators to manage network connectivity with one tool for maximum efficiency. Emulex HBA troubleshooting is simplified with Emulex HBA Capture, an Emulex device driver utility that gathers system, adapter, device driver, and applications information. Data collected by HBA Capture is compressed into a single file and can be sent to Broadcom

Technical Support for analysis when debugging system issues or for diagnostic purposes.

The LPe31000/LPe32000-series HBAs support Brocade I/O Insight for Gen 6 FC, which proactively and non-intrusively monitors device and application-level I/O to gain insights into performance and availability, ensuring predictable performance and operational stability.

Additionally Emulex HBAs support the following Brocade features:

- ClearLink (D_Port)- automated end-to-end signal integrity checks help identify any cabling, optics or port issues in minutes versus hours.
- Link Cable Beaconing- locates a connection on either the Brocade switch port or the Emulex HBA port by making the LED port blink for easy end-to-end identification.
- Host Name Registration- eliminates the need to manually associate worldwide port names with servers, with automated capture of information from Emulex HBA ports.
- Read Diagnostic Parameters- Brocade switches and Emulex HBA ports will self-report diagnostic information, including port speed, link errors, and SFP information (temperature, Tx and Rx power, and so on).

Standards

General Specifications

- The LPe31000/32000-series FC HBAs are powered by the XE501 controller and utilizes an eight-lane (x8) PCIe 3.0 bus (backward compatibility to PCIe 2.0 supported)—the architecture enables all resources to be applied to any port that needs it, delivering over 1.6M IOPS on a single-port

- The quad-port LPe32004 utilizes a 16 lane (x16) PCIe 3.0 bus and delivers 3.2M IOPS per adapter.

Industry Standards

- Current ANSI/IETF Standards: FC-PI-4; FC-PI-5; FC-PI-6; FC-FS-3; FC-LS-2; FC-GS-6; FC-DA; FC-DA-2; FCP-4; SPC-4; SBC-3; SSC-4
- Legacy ANSI/IETF standards: FC-PH; FC-PH-2; FC-PH-3; FC-PI; FC-PI-2; FC-PI-3; FC-FS; FC-GS-2/3/4/5; FCP-2/3; FC-HBA; FC-TAPE; FC-MI; SPC-3; SBC-2; SSC-2; SSC-3
- PCIe base spec 3.0
- PCIe card electromechanical spec 3.0
- Fibre Channel Class 3
- PHP hot plug-hot swap

HBA Port Virtualization

- NPIV

Architecture

Single-port LPe32000, Dual-port LPe32002 or Quad-port LPe32000

- Supports 32GFC, 16GFC, and 8GFC link speeds, automatically negotiated

Single-port LPe31000, Dual-port LPe31002 or Quad-port LPe31004

- Supports 16GFC, 8GFC, and 4GFC link speeds, automatically negotiated

Comprehensive OS and Hypervisor Support

- Microsoft Windows
- Red Hat Enterprise Linux
- SUSE Linux Enterprise Server
- Oracle Solaris
- VMware vSphere
- Additional support is available from OEMs and partners

Hardware Environments

- PowerPC, SPARC, Intel x86, x64

Optical

- Data rates: 28.05 Gb/s (32GFC); 14.025 Gb/s (16GFC); 8.5 Gb/s (8GFC); 4.25 Gb/s (4GFC) automatically negotiated
- Optics: Short wave lasers with LC type connector
- Cable: Operating at 32 Gb
 - 20m at 32 Gb on 50/125 μm OM2 MMF
 - 70m at 32 Gb on 50/125 μm OM3 MMF
 - 100m at 32 Gb on 50/125 μm OM4 MMF

Physical Dimensions

- Short, low-profile PCIe card
- 167.64 mm x 68.91 mm (6.60 in. x 2.71 in.)
- Standard bracket (low profile bracket ships in box)
- LPe31004-M6-SIO & LPe32004-M2-SIO are full-height PCIe cards: 167.64 mm x 111.15 mm (6.60 in. x 4.38 in.), with a standard bracket

Environmental Requirements

- Operating temperature: 0° to 55°C (32° to 131°F); 150 LFM required
 - 200 LFM required for LPe31004-M6 model
 - 250 LFM required for full-height “-SEO” models
- Storage temperature: -20° to 85°C (-4° to 185°F)
- Relative humidity: 5% to 95% non-condensing

Agency and Safety Approvals

North America

- FCC/ICES Class A
- UL/CSA Recognized

Europe

- CE Mark
- EU RoHS compliant
- TUV Bauart Certified

Australia

- RCM

Japan

- VCCI Class A

Taiwan

- BSMI Class A

Korea

- MSIP (formerly KCC/MIC) Class A

China

- China RoHS Compliant

Ordering Information

LPe31000-M6⁴

(upgradeable to 32GFC)

- 1-Port 16GFC Short Wave Optical - LC SFP+

LPe31002-M6⁴

(upgradeable to 32GFC)

- 2-Port 16GFC Short Wave Optical - LC SFP+

LPe31004-M6³

- 4-Port 16GFC Short Wave Optical - LC SFF (embedded optics)

LPe31004-M6-SIO⁴

(upgradeable to 32GFC)

- 4-Port, full-height 16GFC Short Wave Optical- LC SFP+

LPe32000-M2

- 1-Port 32GFC Short Wave Optical - LC SFP+

Ordering Information (cont.)

LPe32002-M2

- 2-Port 32GFC Short Wave Optical – LC SFP+

LPe32004-M2-SIO

- 4-Port, full-height 32GFC Short Wave Optical- LC SFP+

Options

- When upgrading LPe31000-series 16GFC models to 32GFC, Broadcom 32GFC optical transceiver kits must be used. To order use the following part numbers:

LP32-SW-OPT-1

- 32GFC Short Wave Optical (1 piece kit)

LP32-SW-OPT-2

- 32GFC Short Wave Optical (2 piece kit)

LP32-LW-OPT-1

- 32GFC Long Wave Optical (1 piece kit)

LP32-LW-OPT-2

- 32GFC Long Wave Optical (2 piece kit)

Added Features

Performance Features

- Doubling the maximum FC link rate from 16GFC to 32GFC and enhanced virtualization capabilities, help support IT “green” initiatives.
- Frame-level multiplexing increases link efficiency and maximizes HBA performance.
- Accelerates network access to SSDs with NVMe over Fibre Channel enabled feature — supports the FC-NVMe INCITS T11 standard.

- N-Port ID Virtualization (NPIV) increases network scalability by enabling a single FC adapter port to provide multiple virtual ports.

Data Protection Features

- End-to-end data protection with hardware parity, CRC, ECC, and other advanced error checking and correction algorithms ensure data is safe from corruption.
- Enhanced data protection provided by T10-PI with high-performance offload. T10-PI provides additional data protection in Oracle Unbreakable Linux environments.

Deployment and Management Features

- Universal boot capability allows the appropriate boot environment to be automatically selected for any given hardware.
- Boot from SAN capability reduces system management costs and increases uptime.
- Detailed, real-time event logging and tracing enables quick diagnosis of SAN problems.
- Beacons feature flashes the HBA LEDs, simplifying their identification within server racks.
- Environmental monitoring feature helps optimize SAN availability.

Management Features

- The Emulex HBA Manager application⁵ enables centralized discovery, monitoring, reporting, and administration of HBAs provided by Emulex on local and remote hosts. Powerful automation capabilities facilitate remote driver parameter, firmware, and boot code upgrades.

- Advanced diagnostic features, such as adapter port beaconing and adapter statistics, help optimize management and network performance, while the environmental monitoring feature helps to maintain optimum host-to-fabric connections. In addition to the GUI interface, management functions can also be performed via a scriptable Command Line Interface (CLI) as well as a web browser.
- Troubleshoot optics and cables before critical errors affect your system with Brocade ClearLink supported Switches and Emulex HBAs.
- Meet SLAs and QoS with ExpressLane application prioritization on hosts. ExpressLane is fully compatible with majority of switches offering QoS features.
- The Emulex HBA Manager application supports role-based management to facilitate administration of adapters throughout the data center without compromising security. Management privileges can be assigned based on LDAP and AD group memberships.
- Emulex’s management instrumentation complies to open management standards, such as SMI-S and common HBA API support, which enables seamless upward integration into enterprise storage and server management solutions.

³ LPe31004-M6 model uses embedded optics and cannot be upgraded to 32GFC.

⁴ Only Broadcom certified optical transceiver kits can be used.

⁵ The OneCommand Manager application has been renamed the Emulex HBA Manager application.