

16 Port 1U Rackmount USB KVM Switch with OSD

Product ID: SV1631DUSBU



The SV1631DUSBU 16 Port 1U Rack Mountable USB KVM Switch with OSD lets you control 16 USB computers from a single console (USB keyboard, USB mouse, VGA monitor).

Convenient push-button and hot-key controls provide quick, reliable switching between connected computers while manual and auto-scan switching modes and an On Screen Display (OSD) offer additional control options.

Designed to ensure maximum space efficiency, the USB KVM switch features a slim 1U design that fits neatly into a server equipment rack/cabinet with the included brackets, and can be cascaded with multiple KVM switches to deliver control of up to 136 computers from this single switch. Rear cable connections help to eliminate cable tangles and minimize workspace disruption.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.





Certifications, Reports and Compatibility







Applications

- Add single console administration to your Co-location/ISP facility saving you time and money
- Create a scalable, streamlined access solution in your Datacenter or Server Farm
- Perfect for manufacturing line computer control, simplifying access to multiple systems
- Great for PC test/burn-in computer control saving the desk space required for multiple monitors, keyboards and mice
- Ideal for control of multiple PCs in a QA testing environment

Features

- OS Independent No drivers or software required
- Auto-scan function automatically selects computer sequentially
- Cascade configuration expands system capability
- Front panel push-button and Hotkey switching allow easy computer access
- Identifies and selects computers by the names assigned using the OSD
- USB console connections
- OSD security allows each PC to be password protected
- Plug-and-play system configuration
- Rugged, all-metal 1U chassis for use in harsh environments and space-saving cabinets
- Supported Wide Screen Resolutions: 1920x1200, 1920x1080, 1680x1050, 1400x1050, 1440x900, 1360x768
- Supported 4: 3 Resolutions: 1920x1440, 1600x1200, 1280x1024, 1024x768
- USB Keyboard and Mouse combo supported on one USB connection



Data Sheet

	Warranty	3 Years
Hardware	Audio	No
	Cables Included	No
	Daisy-Chain	Yes
	KVM Ports	16
	Number of Monitors Supported	1
	PC Interface	USB
	PC Video Type	VGA
	Rack-Mountable	Yes
Performance	Hot-Key Selection	Yes
	IP Control	No
	Maximum Analog Resolutions	1920x1440 @60Hz (1920x1200 @60Hz - Wide Screen)
	Maximum Cascaded Computers	136
	Maximum Number of Users	1
	On-Screen Display	Yes
	Port Selection Support	Push Button, Hotkeys, and OSD (On Screen Display)
	Wide Screen Supported	Yes
Connector(s)	Cancala Interface(s)	1 - VGA (15 pin, High Density D-Sub) Female
Connector(s)	Console Interface(s)	
Connector(s)	Console Interface(s)	2 - USB A (4 pin) Female
Connector(s)	Host Connectors	
Connector(s) Software		2 - USB A (4 pin) Female
	Host Connectors	2 - USB A (4 pin) Female 16 - VGA (15 pin, High Density D-Sub) Female
Software	Host Connectors OS Compatibility	2 - USB A (4 pin) Female 16 - VGA (15 pin, High Density D-Sub) Female OS independent; No software or drivers required
Software	Host Connectors OS Compatibility	2 - USB A (4 pin) Female 16 - VGA (15 pin, High Density D-Sub) Female OS independent; No software or drivers required 1 - Green - Power
Software	Host Connectors OS Compatibility	2 - USB A (4 pin) Female 16 - VGA (15 pin, High Density D-Sub) Female OS independent; No software or drivers required 1 - Green - Power 16 - Green - PC Online
Software Indicators	Host Connectors OS Compatibility LED Indicators	2 - USB A (4 pin) Female 16 - VGA (15 pin, High Density D-Sub) Female OS independent; No software or drivers required 1 - Green - Power 16 - Green - PC Online 16 - Red - PC Selected
Software Indicators	Host Connectors OS Compatibility LED Indicators Center Tip Polarity	2 - USB A (4 pin) Female 16 - VGA (15 pin, High Density D-Sub) Female OS independent; No software or drivers required 1 - Green - Power 16 - Green - PC Online 16 - Red - PC Selected Positive
Software Indicators	Host Connectors OS Compatibility LED Indicators Center Tip Polarity Input Current	2 - USB A (4 pin) Female 16 - VGA (15 pin, High Density D-Sub) Female OS independent; No software or drivers required 1 - Green - Power 16 - Green - PC Online 16 - Red - PC Selected Positive 0.8A
Software Indicators	Host Connectors OS Compatibility LED Indicators Center Tip Polarity Input Current Input Voltage	2 - USB A (4 pin) Female 16 - VGA (15 pin, High Density D-Sub) Female OS independent; No software or drivers required 1 - Green - Power 16 - Green - PC Online 16 - Red - PC Selected Positive 0.8A 110V-240V AC
Software Indicators	Host Connectors OS Compatibility LED Indicators Center Tip Polarity Input Current Input Voltage Output Current	2 - USB A (4 pin) Female 16 - VGA (15 pin, High Density D-Sub) Female OS independent; No software or drivers required 1 - Green - Power 16 - Green - PC Online 16 - Red - PC Selected Positive 0.8A 110V-240V AC 1.5A
Software Indicators	Host Connectors OS Compatibility LED Indicators Center Tip Polarity Input Current Input Voltage Output Current Output Voltage	2 - USB A (4 pin) Female 16 - VGA (15 pin, High Density D-Sub) Female OS independent; No software or drivers required 1 - Green - Power 16 - Green - PC Online 16 - Red - PC Selected Positive 0.8A 110V-240V AC 1.5A 12 DC



Data Sheet

Environmental	Humidity	80% RH
	Operating Temperature	5°C to 40°C (41°F to 104°F)
	Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Physical Characteristics	Color	Black
	Enclosure Type	Steel
	Product Depth	7.1 in [180 mm]
	Product Height	1.8 in [45 mm]
	Product Weight	109.4 oz [3100 g]
	Product Width	21.3 in [540 mm]
Packaging Information	Shipping (Package) Weight	7.8 lb [3.5 kg]
What's in the Box	Included in Package	1 - 16 Port USB KVM Switch
		2 - Mounting Brackets
		1 - Bag of Screws
		1 - Pack Rubber Feet
		1 - Power Adapter
		1 - User Manual

Product appearance and specifications are subject to change without notice.