Fujitsu recommends Windows 11 Pro.



Data Sheet Fujitsu Tablet STYLISTIC Q5010

Tough Tablet for Hard Work

The FUJITSU Tablet STYLISTIC Q5010 enables new levels of productivity in industrial settings. It is made for rough environments thanks to its spill and dust proof housing (IP54). The lightweight design combined with a 10.1-inch display with reinforced corners. Ultimate connectivity and security options like LTE and fingerprint sensor as well as a long battery runtime let you stay connected wherever you are.

Made for rough and tough environments

Discover new levels of productivity in rough industrial settings

- Spill and dust resistant design with port caps to protect the interfaces (IP54)
- Solid housing with reinforced corners ensures durability
- Durability is MIL-STD-810H tested
- Optional TPU cover for more robustness

Convenience and mobility

All day productivity for indoor and outdoor use

- 10.1" anti-glare touch screen with pen support
- Integrated pen garage
- High performance battery with increased charging voltage (up to 80% in one hour)

Enterprise connectivity and security Secure data access from everywhere

- Embedded 4G/LTE
- Optional keyboard dock with additional LAN port
- Integrated fingerprint sensor
- Family concept: Uses the same cradle as STYLISTIC Q7 Series













Components

Base unit	STYLISTIC Q5010	STYLISTIC Q5010 LTE	
Operating systems			
Operating system pre-installed	Windows 10 Home		
Operating system compatible	FREE Upgrade to Windows 11* *Upgrade timing may vary by device. Features and app availability may vary by region. Certain features require specific hardware (see aka.ms/windows11-spec).		
Operating system notes	end of the product life FUJITSU will continue to test and support all upcoming d of maximum 5 years – depending on the available extension of hardware services ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-port.ts.fujitsu.com.		
Processor	Intel® Pentium® Silver N5030 (4 Cores / 4 Threads, 1.1 GHz)		
Hard disk drive			
Hard disk	eMMC SSD		
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery		
Display	25.7 cm (10.1-inch), LED backlight, WUXGA, 1,920 x 1,200 pixel, Anti-glare display, 500 cd/m², 1000:1		
Multimedia			
Camera	Front camera 2.0 megapixel, re	ar camera 8.0 megapixel with autofocus and light	

Base unit

Base unit	STYLISTIC Q5010	STYLISTIC Q5010 LTE		
General system information				
Chipset	Integrated in CPU			
Supported capacity RAM	8 GB			
Supported capacity RAM (max.)	8 GB			
Memory slots	LPDDR4 (2400 MHz)			
LAN notes	Virtual MAC address. LAN connector	Virtual MAC address. LAN connector via optional keyboard dock, cradle or optional USB adapter cable		
Integrated WLAN	Intel Dual Band Wireless-AC9560NV	Intel Dual Band Wireless-AC9560NV with integrated BT 5.0		
BIOS version	UEFI Specification 2.6	-		
BIOS features	InsydeH2O BIOS			
Audio type	On board	On board		
Audio codec	Realtek ALC255			
Audio features	2x internal microphones, 2x built-in speakers (stereo)			
Waterproof / Spillproof	IP54			
Drop resistant	yes			
Dustproof	Yes			
Disinfectable	no			
MIL-STD tested	Yes, selected MIL-STD-810H tests passed.			
		MIL-STD-810H test results are not a guarantee of future performance under identified test conditions.		
	Accidental damage is not covered under standard international limited warranty.			
Display				
Diagonal Size	25.7 cm (10.1-inch)	25.7 cm (10.1-inch)		
Display Technology	IPS	IPS		

Display				
Display Display type	Anti-glare touchscreen	Anti-glare touchscreen		
Display Resolution type	WUXGA			
Resolution (native)	WUXGA WUXGA 1,920 x 1,200 pixel 1,920 x 1,200 pixel			
Aspect ratio	16:9	16:9		
Brightness - typical	500 cd/m ²	500 cd/m ²		
Contrast - typical	1000:1	1000:1		
Viewing angle (h/v) - typical	160°/160°	160°/160°		
Display notes	Wide-view high-bright LED display (for enhanced outdoor viewing) Integrated ambient light sensor for automatic backlight adjustment to the working environment. Toughened glass			
Sensors	Ambient Light Sensor	Ambient Light Sensor		
	Compass	Compass		
	Gyroscope	Gyroscope		
	Proximity	Proximity		
Digitizer / Touch Technology	Multi-touch up to 10 fingers, active pen support	Multi-touch up to 10 fingers, active pen support		
Pen	EMR 4k pressure level Pen garage inductive charging			
Ambient light sensor	Integrated	Integrated		
Ambient light sensor notes	While enabled, the ambient light sensor automatically adj	usts the display backlight		
Graphics		. , ,		
Base unit	STYLISTIC Q5010	STYLISTIC Q5010 LTE		
Graphics brand name	Intel® UHD Graphics 605	Intel® UHD Graphics 605		
Graphics features	Dual Display support (1x external, 1x internal)	Dual Display support (1x external, 1x internal)		
Grapines reactives		DirectX® 12		
	DirectX® 12 OpenGL® 4.4			
Graphics notes	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator	OpenGL® 4.4		
Graphics notes Interfaces	OpenGL® 4.4 Shared memory depending on main memory size and open	OpenGL® 4.4		
Interfaces	OpenGL® 4.4 Shared memory depending on main memory size and open	OpenGL® 4.4		
Interfaces DC-in	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator	OpenGL® 4.4 erating system 1		
Interfaces DC-in Audio: line-out / headphone	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in)		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out)		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable)		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB)		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE)		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes Docking connector for Port Replicator	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes Docking connector for Port Replicator	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45) 1	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes Docking connector for Port Replicator Cradle (Charging or Functional)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45) 1 Cradle	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)		
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes Docking connector for Port Replicator Cradle (Charging or Functional)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45) 1 Cradle 1 (19V)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)		

Cradle (Charging or Functional)			
DisplayPort	1		
VGA	1		
Kensington Lock support	1		
Ethernet (RJ-45)	1 (10/100/1000)		
	· ,		
Wireless technologies Antennas	2x dual band for WLAN, Bluetooth shared with WLAN	2x dual band for WLAN, 2x for LTE, Bluetooth shared with	
Aitteilias	2x dual band for WEAR, bluetooth shared with WEAR	WLAN	
Integrated WLAN	Intel Dual Band Wireless-AC9560NV with integrated BT 5	5.0	
WLAN encryption	WEP, WPA, WPA2		
WLAN notes	Import and usage according to country-specific regulati	ions.	
LTE/UMTS/GPS notes	Including GPS functionality Import and usage according to country-specific regulations.		
Integrated WWAN		LTE Sierra Wireless EM7455 (Cat. 6)	
WWAN notes		Including GPS functionality Import and usage according to country-specific regulations. LTE Connection Manager (if configured with 4G/LTE)	
GPS		Embedded in 4G module if configured with WWAN	
Power supply			
AC adapter	12V / 36W (3A)	12V / 36W (3A)	
Notes	35W AC Adapter for usage with system/ min. 90W AC	35W AC Adapter for usage with system/ min. 90W AC	
	Adapter for usage with Cradle	Adapter for usage with Cradle	
Rated voltage range	100 V - 240 V (AC Input)	100 V - 240 V (AC Input)	
Rated frequency range	2.4 GHz- 2.48 GHz	2.4 GHz- 2.48 GHz	
1st battery	Li-lon battery 2-cell, 31 Wh, 31 Wh	Li-lon battery 2-cell, 31 Wh, 31 Wh	
Battery features	Quick Charge: 80% in 1h	Quick Charge: 80% in 1h	
Runtime 1st battery	10 h	10 h	
Battery charging time	2.3h	2.3h	
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018. Refer to www.bapco com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.		
Dimensions / Weight / Environmental			
Dimensions (W x D x H)	262,8 x 168.9 x 12.4 mm	262,8 x 168.7 x 12.4 mm	
	10.3 x 0.65 x 0.48 inch		
Weight	from 605 g slate only	from 620 g slate only	
Weight (lbs)	from 1.36 lbs	from 1.39 lbs	
Weight notes	Weight may vary depending on actual configuration		
Operating ambient temperature	5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 140 °F)		
Operating relative humidity	Running: 20 - 80% (relative humidity); Packed: 20 - 80%	(relative humidity)	
Compliance			
D.,	STYLISTIC Q5010		
Product			
	GS		
Germany Europe			
Germany	GS CE		

Compliance	
China	CCC
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Security software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software) Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink YouCam (webcam software)
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) CIM (Common Information Model) WBEM (Web Based Enterprise Management) BootP (made4you)
Manageability link	https://www.fujitsu.com/global/products/computing/pc/manageability/
Security	
System and BIOS Security	Absolute Persistence® technology capable BIOS EraseDisk Intel® PTT
User Security	Embedded fingerprint sensor (optional) Hard disk password User and supervisor BIOS password
Warranty	
Warranty period	2 years (for countries within EMEIA)
Warranty type	Bring-in Service / Collect & Return Service (depending on country)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.
Product Support - the perfect extension	

Warranty	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	at least 3 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

Recommended Accessories

STYLISTIC Q7311, Q7310 and STYLISTIC Q5010 Family Cradle



Flexibility, expandability, desktop replacement, investment protection – to Order Code: name just a few benefits of Fujitsu's docking options.

S26391-F3397-L100

LAN Conversion Cable (USB to LAN) for STYLISTIC Q



The FUJITSU USB Type-A to LAN Conversion Cable enables you to connect Order Code: your compatible STYLISTIC Tablet to a wired network connection.

S26391-F3398-L840

GBit-LAN via USB conversion cable is limited to 480 Mbit/s due to USB 2.0 specification. (Picture similar to product)

USB-C Hub 4 Ports



Fujitsu offers the first most powerful USB-C hybrid usage hub, following industrial requirements as well as being ready for office desktop usage. The USB-C Hub 4 Ports from Fujitsu makes connecting all of your USB peripherals a quick and simple process. SuperSpeed USB Type-C makes data transfer to and from external storage faster than ever. The hub dynamically selects the optimal speed for each device, giving you more bandwidth where you need it automatically.

Order Code: S26391-F6099-L404

Tablet Stand for STYLISTIC Q devices



The tablet stand is designed for STYLISTIC devices like latest STYLISTIC Q7312 and can be used universally. Fits for STYLISTIC Q5 and Q7 and the Type-C as well as the Thunderbolt [™] 4 port replicator can be fixed on the Order Code: FPCSK769BP

STYLISTIC Q5010 Stylus Pen



Ergonomic and authentic handwriting on your tablet

Order Code: S26391-F3309-L510

Folio Cover STYLISTIC Q5010



The Folio Cover for the STYLISTIC Q5010 is a thin, tailored protective sleeve Order Code: for your Fujitsu tablet. It keeps the device safe from damage on the go, and \$26391-F3609-L100 brings a touch of style to your daily work. It can even be used as a stand if you need to display a presentation or watch a clip and fits even the device is connected to its keyboard dock.

STYLISTIC Q5010 TPU Cover



The protective TPU Cover is designed to prevent damages to your STYLISTIC Q5010. Openings of the cover allow you to access all ports and buttons whilest the hand strap on the back of the case fives you a firm grip while working with your tablet outside the office.

Order Code: S26391-F3609-L200

Car	۸da	otei	110	R_C	\cap C
Car	Aud	ıbtei	L U.S	р-C.	·UL



One Car Adapter fits all. Independent of your mobile device charging method this car adapter will fulfill all major requirements and standards for fast charging vendorbrand-independent notebooks and all mobile devices. The Car Adapter USB-C-QC supports USB PD with PPS, Quick Charge (QC), Apple- and Samsung

Order Code: S26391-F2613-L630



Order Code: \$26391-F1194-L125

Wireless Mouse WI860 BTC



The Wireless Mouse WI860 BTC can be paired with up to 3 different clients, Order Code: 2x Bluetooth and 1x wireless USB Type-C dongle. S26381-K474-L100

With the blue optical sensor, it works on nearly all surfaces with an 3-step adjustable DPI selector (800/1600/2400).

The mouse charges wirelessly through Qi or by USB Type-C cable. A utility button on the side is programmable. The default functions are optimized for Teams calls.

Order Code: S26391-F3409-L221

STYLISTIC Q5010 Keyboard Dock



Enjoy the benefits of a physical keyboard dock connection which is more reliable and hassle free. With the attached keyboard dock you get the ability to prop the tablet up and fold it over the tablet's screen to protect it, especially when you are mobile.

More information

Fujitsu products, solutions & services

In addition to Fujitsu Tablet STYLISTIC Q5010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Tablet STYLISTIC Q5010, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/products/computing/pc/tablets

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/
Copyright 2023 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2023-03-02 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/
Copyright 2023 Fujitsu Technology Solutions GmbH