SFP680



Mounting Pattern 494 x 650mm (19.45" x 25.59")



- Universal mount fits displays with mounting patterns up to 494 x 650mm (19.45" W x 25.59" H)

- Low-profile design holds display only 1.70" (43mm) from the wall
- Easy hang wall plate allows a bolt to be pre-installed to ease wall plate installation
- Lateral display adjustment up to 3.38" (85.9mm)
- 1" of post-installation vertical adjustment provides flexibility in the installation
- Includes fastener pack with all necessary mounting and display attachment hardware (including M10)

SMARTMOUNT.

Universal Portrait Flat Wall Mount

FOR 46" TO 90" DISPLAYS*

Peerless-AV's SmartMount® Universal Portrait Flat Wall Mount delivers an ultra-slim profile designed to hold large displays up to 350lb. Installation and maintenance are made easy with the SFP680's robust feature set. Auto-latching adaptor rails automatically secure the display without the use of a tool. The mount's built-in kickstand holds the display safely from the wall during cable routing, while the open wall plate allows for increased electrical and cable management options. Horizontal and vertical display adjustment allow for quick fine-tuning of the mounted display.

OPEN & EASY TO HANG WALL PLATE Total wall access reduces installation time and allows for increased electrical/cable management options HORIZONTAL & VERTICAL ADJUSTMENT Post-installation leveling and side-to-side adjustability features allow fine tuning of the mounted display for the perfect display positioning **AUTO-LATCHING ADAPTOR RAILS** Securely lock display in place with an --- 1 --audible click QUICK-REMOVAL DRAW STRINGS Leave on for easy access and maintenance to back of display or remove for a theft-resistant installation **BUILT-IN KICKSTANDS** Hold the display safely from the wall for

cable routing and effortless maintenance








Comes in color packaging with included installation hardware and easy to follow instructions.

Please visit peerless-av.com/en-us/patents for patent information.

*This display size range is simply a guideline for product selection. Displays larger than the screen size range may still be compatible as long as they fall within the VESA® pattern and max weight of the Peerless-AV® product.





:∰⊪ RoHS



SFP680

SmartMount® Universal Portrait Flat Wall Mount for 46" to 90" Displays - Security Models

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
SFP680	22.00" x 27.48" x 1.70" (559 x 698 x 43mm)	11.95lb (5.4kg)	350lb (158kg)	Scratch Resistant Fused Epoxy	Semi-Gloss Black

Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
SFP680	28.50" x 4.10" x 15.60" (725 x 105 x 395mm)	14.95lb (6.78kg)	735029314202	Wall Mount, Wall and Display Installation Hardware, Installation Instructions	1

Accessories

ACC615: ACC309: 6-pack Metal Stud Fastener Kit Video Conference Shelf


ACC-UCM:

Universal AV Component Mount


ESHV models: **AV Wall Shelves**


Easy Mount Recessed Low Voltage Cable Plate IBA4-W:


All dimensions = inch (mm)



WALL PLATE DETAIL







Architect Specifications

The SmartMount® Universal Portrait Flat Wall Mount shall be a Peerless-AV model SFP680 and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV

2300 White Oak Circle Aurora, IL 60502 USA

(800) 865-2112 (630) 375-5100 Fax: (800) 359-6500

Peerless-AV EMEA

Unit 3 Watford Interchange Colonial Way, Watford Herts, WD24 4WP United Kingdom

+44 (0) 1923 200100 Fax: +44 (0) 1923 200101

Peerless-AV Latin America

Av. de las Industrias 413 Parque Industrial Escobedo General Escobedo, N.L., México, 66062

+52 (81) 8384-8300 Fax: +52 (81) 8384-8360

