## ThinkCentre M75n 11BS0001GE

#### Product

ThinkCentre M75n

Region WE

Country/Region Germany

Machine Type 11BS

TopSeller TopSeller

**Processor** AMD Ryzen 5 PRO 3500U (4C / 8T, 2.1 / 3.7GHz, 2MB L2 / 4MB L3)

Chipset AMD SoC platform

Graphics Integrated AMD Radeon Vega 8 Graphics

*Memory* 8GB Soldered DDR4-2400

Storage 1x 256GB SSD M.2 2280 PCIe x4 NVMe Opal

**Optical** None

Speaker 1Wx1

*Ethernet* RTL8111FP-CG, 1x RJ45

WLAN + Bluetooth Intel 9260 11ac, 2x2 + BT5.0

Chassis Intrusion Switch Chassis Intrusion Switch

Kensington Cable Lock None

Adapter Cage None

Dust Filter None

VESA Mount VESA Mount with Adapter Holder

Color Black

**Stand** None

Keyboard USB Calliope Keyboard, Black, German

Mouse USB Calliope Mouse

Power Supply 65W 89% Adapter TUV Low Noise None

*Monitor Cable* None

System Management DASH

**Operating System** Windows 10 Pro 64, German

Bundled Software

Base Warranty 3-year, Onsite

Bundled Service

**EAN/UPC/JAN** 0194778811095

*End of Support* 2026-12-21

**Announce Date** 2020-05-19

#### **Recommended Services**

Better 4Y Premier Support Upgrade from 3Y Onsite (5WS0T36207) Good

3Y Premier Support Upgrade from 3Y Onsite (5WS0U26647)

### L WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.

#### https://psref.lenovo.com

# PSREF

Visit psref website for the latest version of Product specifications Reference. © Lenovo, 2020. All rights reserved.



## ThinkCentre M75n Platform Specifications

Product Specifications Reference (PSREF)

Processor	AMD Ryzen 3 / 5 PF	RO serie	s processor				Security features	Security slot (in rear for optional     Boot sequence control				
	Processor	Cores / Threads	Frequency Base/Max	L2 / L3 Cache	Memory Support (Up to)	Integrated Graphics		<ul> <li>Kensington<sup>®</sup> MicroSaver<sup>®</sup> cable)</li> <li>Chassis intrusion switch</li> <li>Power-on password</li> <li>Boot without keyboard and r</li> <li>Individual USB port disablen</li> <li>Smart USB protection, allow</li> </ul>			port disablement tection, allows keyboard/	
	Ryzen 3 PRO 3300U	4/4	2.1 / 3.5 GHz		DDR4-2400	Radeon Vega 6		<ul> <li>Administrator pass</li> <li>Hard disk passwor</li> </ul>		mouse only, blo	cks all storage devices	
	Ryzen 5 PRO 3500U	4/8	2.1 / 3.7 GHz	2 MB / 4MB	DDR4-2400	Radeon Vega 8	Keyboard			SB connector) blac	k	
Memory	8GB / DDR4-2400* / soldered to systemboard, no sockets, dual-channel capable, non-ECC * System automatically clocks down for the processors with lower memory controller							Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black e Some: Lenovo Calliope Mouse (USB connector), black				
Storage	Support up to two M.2 SSD (one PCIe x4, one PCIe x2) Some: M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 4* Some: M.2 2242 SSD / PCIe NVMe, PCIe 3.0 x 2							Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black				
RAID Optical	* M.2 SSD in PCIe 3 None None				Cle 3.0 x2		Mechanical	Nano (0.35L), Iron Gray top cover / Black mid bezel / Red bottom cover Three M.2 slots: two for M.2 SSD (one PCIe 3.0 x4 and one PCIe 3.0 x2) and one for WLAN				
Graphics	AMD Radeon <sup>™</sup> Vega 6/8 Graphics in processor, uses main memory, DirectX <sup>®</sup> 12, one DisplayPort <sup>™</sup> , one USB 3.2 Type-C Gen2 with display function, up to 2 independent displays;								Dimensio	ons (WxDxH)	Weight (Approx.)	
								M75n (with fan, 0.35L)		3.46" X 0.87" 38mm X 22mm	1.11 lb (0.505 kg), vary by config	
Monitor cable	<i>Max resolution:</i> 3840x2160 (DP)@60Hz; 3840x2160 (Type-C)@60Hz Optional DP to VGA dongle, DP to HDMI dongle, Type-C to VGA dongle, Type-C to HDMI dongle, Type-C to DP dongle						Mounting	Some: VESA mount bracket kit, supports VESA 75mm Some: VESA mount bracket kit with adaper holder, supports VESA 75mm Some: DIN rail mount bracket kit None				
Chipset	AMD SoC (System on Chip) platform						Floor Stand					
Front ports (Std.)*	* 1x USB 2.0, 1x USB 3.2 Gen 2, 1x USB 3.2 Type-C Gen 2, one headphone /						Power supply	65 watts adapter, autosensing, 89% PSU (Not for TIO models)				
Rear ports (Std.)*	microphone combo jack (3.5mm) 1x USB 2.0, 1x USB 3.2 Gen2, 1x USB 3.2 Type-C Gen 2 (with display function, support power-in [20V and >45W]), 1x ethernet (RJ-45), 1x DisplayPort * Depending on many factors, actual data transfer speed may be lower than theoretical speed						Limited warranty	Some: 1-year, limited onsite service / service upgrades available Some: 3-year, limited onsite service / service upgrades available				
							Preload	Preloaded operating system Some: Windows® 10 Pro 64-bit Some: Windows 10 Home 64-bit Some: Windows 10 IoT Enterprise (only available via special bid model)				
Audio support	Realtek ALC233 / internal speaker (1watt)						-					
WLAN	Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9260 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 Some: Bluetooth 4.2 / 5.0 wireless, integrated in Wi-Fi + BT combo adapter											
							Environment	ENERGY STAR <sup>®</sup> 8.0, EPEAT <sup>™</sup> Silver rating, ErP Lot 3, TCO 8.0 (coming soon), TUV ultra low noise verified (on some models), RoHS, WEEE, REACH				
Bluetooth							MIL-SPEC test	MIL-STD-810H military certification (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation)				
Ethernet	Gigabit ethernet, Realtek RTL8111FP-CĞ, Wake on LAN®						Accessories	<b>o</b> , , ,				
Manageability Security chip	Dash 1.1/1.2 Discrete TPM 2.0, T	CG Cer	tified						, p.0000 g			

Note: The specifications above may not be available in all regions.

Lenovo, May 2020

# ThinkCentre M75n







AMD







AMD