

ECR501

MIGHTY **CARD READER ECR501**







Features

- USB Super Charge port for smartphones and tablets. Compliant with the USB Battery Charging (BC) Specification version 1.2.
- USB 3.0 port and card reader ports in USB 3.0 bandwidth.
- 6-in-1 card readers to access mainstream cards: CF I/II/MD, Micro SD, SD/SDHC/SDXC/MMC/RSMMC, Extreme digital MS/MS PRO/ MS PRO DUO, M2 (MS MICRO)
- With 5 USB 2.0 ports and each hub could charge up to 1.5 A to your smartphones and tablets.
- ONE eSATA port for best convenient.
- Superior expansion: the body can be installed two 2.5" HDD and one 3.5" HDD.
- LED display for power and access.

Specifications

| Memory slots | ECR501 |
|----------------------|--|
| MS Slot | MS, MS-DUO, MS Pro, MS Pro-Duo, MS MagicGate, MS Pro MagicGate, MS-Duo MagicGate, MS Pro-Duo MagicGate, etc. |
| CF Slot | CF I/II, CF Ultra II, CF Extreme III, Micro Drive Magicstor |
| SD Slot | SD, mini SD, MMC-I, MMC-II, MMC 4.0, MMC Dual Voltage, RS-MMC, RS-MMC Dual Voltage, RS MMC 4.0, SDHC, SDXC |
| Extreme digital Slot | Extreme digital |
| Micro SD Slot | Micro SD/T-Flash (NO Convert Adapter Required) |
| M2 PORT | M2 (NO Convert Adapter Required) |
| Function | ECR501 |
| Power | Bus power : 5V; 0.5A / 0.9A Self power : 5V; 2.4A |
| Storage Temperature | -10 ~ 85 degrees (Celsius) |
| Working Temperature | 0 ~ 40 degrees (Celsius) |
| Dimension | 148.4 x 175 x42 mm (L x W x H) |
| Supported OS | Windows 8, 7, Vista, XP; Mac 10.8.3; Linux OS 2.4X or Higher |



www.enermax.com

© 2014 ENERMAX Technology Corporation. All rights reserved. Specifications are subject to change without prior notice. Actual product and accessories may differ from illustrations.Omissions and printing errors excepted. Content of delivery might differ in different countries or areas. Some trademarks may be claimed as the property of others. Jun. 2014