ThinkCentre Tiny-In-One 22 Gen 3 10R1PAT1EU

Product

ThinkCentre Tiny-In-One 22 Gen3

Region

EMEA

Machine Type

10R1

Color

Black

Display Size

21.5"

Touchscreen

None

Camera

720p camera

Resolution

1920x1080

Aspect Ratio

16:9

Pixel Pitch

0.24795 mm

Dot / Pixel Per Inch

102.4 dpi

Brightness

250 nits

Contrast Ratio

1000:1

Pixel Response Time

4-14 ms

Color Gamut

72%

View Angle (H / V)

178 / 178

Stand

Adjustable Stand

Power Comsuption (Typical / Maximum)

19W / 32W

Power Supply

90W 88% Adapter

Warranty

3-year

Ann Date (mm/yy)

2017-08-17

L WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product specifications Reference.

© Lenovo, 2020. All rights reserved.



ThinkCentre Tiny-in-One (TIO) 22 Gen3

Form footor	Tiny in One offers	a full All In One ovney	riance when entional Tiny elete into			
Form factor		ean cabling and effortle	rience when optional Tiny slots into ess setup			
			() / M710 / M900(x) / M700 / M630e /			
	M625 / M600 / M75q / M715 / M93p* / M83 / M73* / M53 /Chromebox Tin					
	* Non-TIO models can't be turned on by pressing power button of TIO					
Panel	TFT-LCD, IPS (In Plane Switching) technology**, White LED backlight					
Viewable image size	**Notes: IPS may refer to IPS, PLS, ADS, AHVA, AAS panels 21.5" (546.1mm) diagonal					
Max view area (W x H)	18.74" x 10.54" / 476.1mm x 267.8mm					
Bezel Width	Top / Side: 2mm, Bottom: 22.1mm					
Native resolution Multi-touch	1920x1080 Ontional 10-point multi-touch, supports Wake on Touch					
Aspect ratio	Optional 10-point multi-touch, supports Wake on Touch 16:9					
Pixel pitch (mm)	0.24795mm					
Dot/Pixel per Inch Brightness	102.4 dpi					
Contrast ratio	250 nits or cd/m² (typical) 1000:1 (typical)					
Pixel response time	14ms (default), ove	er drive to 4ms, 6ms				
Color gamut	72%					
Anti-reflective Viewing angle at 10:1 CF	Anti-glare 3178° (+/- 89°) horiz	rontal, 178° (+/- 89°) v	ertical			
Preset resolutions	640x350 @ 70Hz	(17 00) 1				
1 10001 100014110110	640x480 @ 60Hz,	66Hz, 72Hz, 75Hz				
	720x400 @ 70Hz					
	800x600 @ 60Hz, 72Hz, 75Hz 1024x768 @ 60Hz, 70Hz, 75Hz					
	1152x864 @75Hz	, 70112, 70112				
	1280x800 @ 60Hz					
	1280x1024 @ 60Hz, 72Hz, 75Hz 1366x768 @ 60Hz					
	1440x900 @ 60Hz, 75Hz					
	1600x1200 @ 60Hz, 70Hz, 75Hz					
	1680x1050 @ 60Hz 1920x1080 @ 60Hz					
Presets / user settings	Presets: 25; user settings: 25					
On screen display	On screen display with digital user controls (8 languages)					
Control features	Ftont: Exit button, Left / Mode-switching button (TIO / monitor mode),					
	Right / Brightness button, Enter / Menu button, Power button Bottom: Volume up button, Volume down button					
Tiny-in-One Power On	Pressing Alt + P on keyboard or pressing Power button positioned on TIO					
	can turn on both TIO and Tiny (only some Tiny support, see compatible list)					
Side ports (TIO)	One USB 3.1 Gen1 / USB 2.0 (when M73 or M53 installed or USB 2.0					
	connected via USB upstream port) Notes: The USB port is only available when a Tiny is installed or a PC is					
connected via USB upstream port						
Side ports (Tiny)	Side ports offered by installed Tiny (optional)					
Rear ports 3-in-1 Cable	One DisplayPort in port, one USB upstream port, one power connector Undetachable 3-in-1 cable (Power connecter, USB [supports USB 3.1 Gen1]					
· • • • • • • • • • • • • • • • •	/ USB 2.0], DisplayPort), only for connecting to Tiny installed (optional)					
Camera	Optional 720p camera with dual microphone for VOIP, LED indicator					
Internal Speaker	2 watt x2	u attachmant of cotton	al apple leals (Manais estan ® 11-			
Security	Security keyhole for attachment of optional cable lock (Kensington® lock compatible), locks optional Tiny with TIO together, more security features					
	offered by Tiny installed (optional)					
Mechanical	Dimensions	TIO without stand	TIO with stand			
	W x D x H (inch)	19.26 x 2.85 x 13.35	19.26 x 10.76 x 14.59 - 18.93			
	W x D x H (mm)	489.3 x 72.5 x 339	489.3 x 273.3 x 370.7 - 480.7			
	Weight (Approx.)	7.01 lb / 3.19 kg	11.77 lb / 5.34 kg			
	Troigitt (Approx.)	7.01 ib / 0.10 kg	11.77 to 7 3.54 kg			

_		
0	Mounting features	Wall or desk mounting using the extend arm or third-party accessories meeting the VESA FPMPMI® (100mm mount)
. /	Adjustable stand	Tilt: 30° back5° forward:
	,	lift: 4.3" (110mm);
		swivel: +/-45°; Pivot: clockwise 0° to 90°
\neg		FIVOL. CIOCKWISE 0 to 90
	Power supply	90 watts AC/DC adapter, 88% PSU, universal
	Power consumption	19 watts typical, 32 watts maximum, <0.5 watts standby / suspend
VESA-compliant Ergonomics Emission standards Environmental VESA DDC2B/CI, VESA DPMS-compliant ISO 9241-307, TUV Eye Comfort certified FCC Class B TCO 7.0, TCO Edge 2.0, WEEE, RoHS, ENERGY		3-years, Customer Carry-In or Mail-In via Rapid Replacement Service
		TCO 7.0, TCO Edge 2.0, WEEE, RoHS, ENERGY STAR® 8.0, EPEAT™ Silver rating, ULE Gold, TUV, VOC
	Windows certifications	Windows 7 and Windows 10 certified
	Ship group	TIO (Monitor), detachable stand, AC/DC power adapter, power cord, user's
guide and driver CD, quick start and safety poster		guide and driver CD, quick start and safety poster
	Accessories For compatible accessories, please go to http://www.lenovoqui	

ThinkCentre Tiny-in-One 22 Gen3 Compatible list					
Model	P330 / P320 / M920(x) / M720 / M910(x) M710 / M900(x) / M700 / M630e / M625 /		Chromebox		
	M600 / M75q / M715 / M83 / M53 Tiny M90n Nano (with TIO kit)				
Turn on TIO and Tiny together via	All models	All models	Not support		
Alt + P on USB KB Turn on TIO and					
Tiny together via TIO Power Button	All models	TIO models	All models		











