Orchestrating a brighter world

MultiSync[®] BT421 LCD 42" Stretched Large Format Display

Datasheet





Where space is limited but not your message

Delivering space efficient visualisation for constricted environments such as corridors and retail shelves, this 42" bartype display offers a distinctive ultra-wide 16:4 screen ratio. High adaptability extends to both landscape and portrait orientation ideal for space-limited areas, yet content creation remains easy and effortless. Content is crisp and clear with compelling readability even in bright ambient light conditions with high brightness levels of 700 cd/m² combined with an anti-glare surface. Its modern, slim design forms an elegant digital surface which perfectly complements the surrounding architecture and integrates seamlessly into any environment.

The 42" MultiSync® BT421 is the super wide choice for space efficient digital signage in retail environments, transportation hubs, quick service restaurants and all other public areas where space is limited.

Benefits

Space efficient display solution – the ultra-wide screen ratio of 16:4 with a display height of just 28.9 cm allows installation within constricted spaces, providing crisp and eye-friendly visualisation.

Robust and reliable – sealed to prohibit dust ingress, long term reliable operation is maintained within wide temperature range of 0-50°C.

Easy content adaption – the integrated trim function enables 16:9 content to be used whilst actively displaying the upper or lower area for display of native 1920 x 480 content.

Cost efficient media playback flexibility – divide a single Full HD content into two separate contents via daisy chaining for back to back installations, needing only one source to feed two screens for cost saving benefits.

Superb readability in bright light environments – crisp playback of content thanks to high brightness output of 700 cd/m² and anti-reflective screen surface delivers clearly visible messages even under varying and demanding ambient conditions.

Mission-critical 24/7 ready operation – the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

Cost Saving Device Management – save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

Product Information

| Product Name | MultiSync [®] BT421 |
|---------------|--|
| Product Group | LCD 42" Stretched Large Format Display |
| Order Code | 60004365 |

Display

| Panel Technology | VA with Direct LED backlights |
|------------------------------------|---|
| Active Screen Area (W x H) [mm] | 1,039.7 x 259.9 |
| Screen Size [inch/cm] | 42 / 107.2 |
| Aspect Ratio | 16:4 |
| Pixel Pitch [mm] | 0.542 |
| Brightness [cd/m²] | 700 |
| Contrast Ratio (typ.) | 4000:1 |
| Viewing Angle [°] | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Colour Depth [bn] | 1,073 (10bit) |
| Response Time (typ.) [ms] | 8 (grey-to-grey) |
| Haze Level [%] | Pro (44) |
| TNi [°C] | 110 |
| Supported Orientation | Landscape; Portrait |
| | |

Resolution

| Native Resolution | 1920 x 480 | | | |
|-----------------------|--------------|--------------|--------------|------------|
| Supported Resolutions | 1920 x 1200; | 1600 x 1200; | 1280 x 1024; | 800 x 600; |
| | 1920 x 1080; | 1440 x 900; | 1280 x 800; | 640 x 480 |
| | 1920 x 960; | 1400 x 1050; | 1280 x 768; | |
| | 1920 x 480; | 1366 x 768; | 1280 x 720; | |
| | 1680 x 1050; | 1360 x 768; | 1024 x 768; | |

Connectivity

| Input Video Digital | 2 x DVI-D (with HDCP) |
|----------------------|-----------------------|
| Input Control | LAN 100Mbit; RS232 |
| Output Video Digital | 1 x DVI-D |

Electrical

| Power Consumption Eco/max. [W] | 50 shipping; 75 (max.) |
|-----------------------------------|--------------------------------|
| Power Savings Mode [W] | < 0.5; < 2 (Networked Standby) |
| Power Management | VESA DPMS |

Environmental Conditions

| Operating Temperature [°C] | +0 to +50 |
|----------------------------|-----------|
| Operating Humidity [%] | 20 to 90 |

Mechanical

| Dimensions (W x H x D) [mm] | 1,059.9 x 288.9 x 64.7 |
|-----------------------------|---|
| Weight [kg] | 9.3 |
| Bezel Width [mm] | 14.7 (bottom); 7.9 (left and right); 9.8 (top) |
| VESA Mounting [mm] | 200 x 100 (FDMI); 4 holes; 400 x 100 (FDMI); M6 |

| Available Options | |
|-------------------------|--|
| Accessories | Ceiling Mount (PDC BT S(single sided); PDC BT D (dual sided); PD Pole S, PD Pole M, PD Pole L, PD Pole XL); Wall mount (PDW BT L) |
| Green Features | |
| Energy Efficiency | Energy efficiency class: C |
| Additional Features | |
| Special Characteristics | NaViSet Administrator 2; Trim Function |
| Safety and Ergonomics | CE; REACH; RoHS; SASO |
| Warranty | 3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension |
| Operating Hours | 24/7 |

CE

This document is $\ensuremath{\mathbb S}$ 2020 NEC Display Solutions Europe GmbH.

RoHS

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 22.01.2020