SD5200T Thunderbolt 3 Docking Station

Part Number: K38300NA UPC Code: 5889638300



At last, the cross-platform compatible dock with Thunderbolt 3 connectivity has arrived. Engineered to support mixed computing environments with high transfer speed requirements, The Kensington SD5200T Thunderbolt 3 Docking Station plugs into the power of one – one dock for more power, more bandwidth, and more compatibility. Providing up to 40Gbps data transfer with 85W power delivery on a single connection, support for 5K or dual 4K monitors, and robust daisy-chaining options, the SD5200T Thunderbolt 3 Docking Station is a game-changing dock.


FEATURES & BENEFITS

- Cross-Platform Compatibility allows this Thunderbolt 3 dock to work for both Windows and Mac users
- Thunderbolt 3 Technology allows a single port to provide up to 40Gbps of data speed, and connectivity to Thunderboltenabled devices, billions of USB devices, and UHD displays - all while supplying power
- 5K or 4K for Dual Monitors supports the crisp resolution, contrast and color depth of Ultra HD via DisplayPort or HDMI (adapters sold separately)
- 85W Power Delivery to charge the host device (Host device must be designed to support Power Delivery for dock to provide charging)
- Productivity Ports connect to peripheral accessories via one USB-C 5Gbps port with 15W power, two USB 3.0 ports (one of which is a 2.1A charging port), one DisplayPort++, one Gigabit Ethernet port, and 3.5mm headphone and microphone jacks
- Daisy Chaining allows connection for up to 5 additional Thunderbolt-enabled devices
- Kensington Security Slot protects your technology investment via easy implementation of a cable lock
- Zero Footprint Mounting provides the option to attach the dock to the back of any VESA® compatible external display to accommodate space-challenged workspaces (mounting plate (K33959WW) sold separately)

FRONT



BACK





TECHNICAL SPECIFICATIONS

SYSTEM REQUIREMENT

- Operating Systems Supported: Windows 10 and macOS X 10.12 or later
- Plug & Play: Yes for Thunderbolt 3 host computers

- System Resource Requirement: N/A
- USB-C Power Delivery: 5V/9V/15V up to 3A, 20V up to 4.25A

HOST CONNECTIVITY

• Host Docking Connector: Thunderbolt 3 with Power Delivery up to 85W. Look for the Thunderbolt 3 icon on PC's **USB-C** ports



VIDEO CONNECTIONS

- **Video Connectors:**
 - DisplayPort v1.2++, supports passive adapters for HDMI and DVI
 - The Thunderbolt 3 ports can be converted into video ports with either K33993WW (USB-C to HDMI) or K33994WW (USB-C to VGA)
- Maximum Resolution Supported:
 - o Single 5K Monitor: 5120 x 2880 @ 60Hz (thru Thunderbolt 3 port)
 - Dual 4K Monitors: 4096 x 2160 @ 60Hz
- HDCP Support: No

AUDIO CONNECTIONS

- **Audio Connectors:**
 - 3.5mm audio for headphone/speaker
 - o 3.5mm audio for microphone

• Audio Channels Supported: Stereo LR

USB CONNECTIONS

- USB 3.0 Ports: 2; (1) front which is a 2.1A charging port & (1) back, speeds up to 5Gbps
- USB-C Ports: (1) front; does not support USB-C Alt mode. Supports USB bus power up to 15W

NETWORK CONNECTIONS

Ethernet Port: RJ45

• Compatible Ethernet Speeds: 10/100/1000 Mbps

OTHER FEATURES

Kensington Security Slot

 VESA Mount Compatible: Mounting plate (K33959WW) sold separately

PRODUCT DIMENSIONS

Unit Dimensions:

o Width: 217.4mm (8.6in) o Depth: 85.3mm (3.4in) o Height: 25.7mm (1.0in)

• Desktop Footprint: 185 cm² (29 in²); n/a if mounted behind VESA compatible monitor

Unit Weight: 337g (11.9 oz) **Enclosure Color and Material:** Brushed aluminum and Black ABS

PACKAGING DIMENSIONS

 Packaging Style: White Box (K38300EU); Retail Box (K38300NA/K38300AU)

Unit Box:

o Width: 254mm (10.0in) o Depth: 140mm (5.5in) o Height: 89mm (3.5in)

Packaging Weight: 0.95kg (2.1lbs)

Master Carton: 4 pcs Width: 368mm (14.5in) o Depth: 152mm (6.0in) o Height: 267mm (10.5in) o Weight: 4.35kg (9.6lbs)

Package Content:

o One SD5200T Thunderbolt Docking Station

One Thunderbolt 3 Cable, 0.5M (1.5ft)

One AC Power Adapter with US power cable included (K38300NA); One AC Power Adapter with EU and UK power cables included (K38300EU); One AC Power Adapter with AU power cable included (K38300AU)

One Instruction Guide

Warranty Information

POWER & ENVIRONMENTAL

Power Adapter Rating:

o Input: 100-240V; 2.5A Max

o Output: 20V DC; 8.5A, center-pin positive polarity

Operating Temperature: 0 to 40° C (32 to 140° F) Storage Temperature: -40 to 70° C (-40 to 158° F)

Relative Humidity: 5% to 95% non-condensing

COUNTRY OF ORIGIN, REGULATORY, AND WARRANTY

• Country of Origin: China

Certifications & Compliance: CE, FCC, RCM, ERP, REACH, RoHS, Thunderbolt certification

Warranty: 3-Years Limited - worldwide