

HP LaserJet M5035 MFP series



Fulfill workteam A3 printing and copying needs and provide send-to-e-mail from your MFP plus optional fax functionality, with a powerful tool that is affordable and easy to use and makes processes simple and efficient.

Ideal for workteams in enterprise environments who need a black-and-white MFP that is easy to use, maintain and manage, offers a familiar LaserJet experience and reliable performance with A3 capabilities.

This MFP is extremely easy to use, install, manage and maintain with a new, intuitive control panel.

An intuitive control panel, common to all new HP MFPs, is simple to navigate and clearly displays applications so you can easily manage and maintain your device. HP Web Jetadmin offers remote installation, configuration and proactive management. Experience fewer interruptions as interactive HP Smart printing technology ¹ in the print cartridge and the device optimises print quality and reliability. Best-in-class networking through the HP Jetdirect internal print server enables easy sharing.

Enhance workteam performance with the A3 multifunction capabilities of this robust, affordable MFP.

See productivity rise with A3 print and copy, send-to-e-mail, fax ², embedded networking and two-sided printing functionality ³. Set the pace for success with A3 print and copy speeds up to 35 ppm. HP's Instant-on Technology delivers a fast, first printed page even from Powersave mode. Send-to-e-mail directly from the MFP. Access more third-party solutions.

Experience familiar HP LaserJet reliability and quality for results you can always depend on.

Choose original HP LaserJet print cartridges for professional quality. Process print, fax ² and send-to email jobs easily with a 460 MHz processor and expandable memory up to 512 MB, and get a quick return to the print job's application. Enjoy flexible paper input, expandable from 600 to 2,100 sheets ⁴. An automatic stapler/stacker easily staples and sorts up to 30 pages at a time ⁵. Print demanding jobs with HP PCL 5, HP PCL 6, and HP PostScript Level 3 emulation print drivers.

¹ Using genuine HP supplies ensures availability of all HP printing features

² Fax functionality is an optional feature that can be added to the HP LaserJet M5035 MFP

³ The two-sided printing unit is an optional accessory that can be added to the HP LaserJet M5035 MFP

⁴ Additional optional input is available in two configurations: a 500-sheet input tray with stand or an integrated 3 x 500-sheet input tray

⁵ The stapler/stacker unit comes standard on the HP LaserJet M5035xs MFP only.



HP LaserJet M5035 MFP



HP LaserJet M5035x MFP



HP LaserJet M5035xs
MFP

HP LaserJet M5035 MFP series

Series at a glance



HP LaserJet M5035 MFP

- HP LaserJet M5035 MFP: print speed of up to 35 ppm
- 256 MB memory
- 460 MHz processor
- 40GB Hard Disk
- HP Jet Direct Embedded Print Server
- Embedded Web Server
- digital sending
- standard input capacity of 600-sheets with two 250-sheet input trays and 100-sheet multipurpose tray
- 50-sheet reversing automatic document feeder



HP LaserJet M5035x MFP

- HP LaserJet M5035x MFP: as base model with automatic two-sided printing
- analogue fax
- additional 500-sheet input tray and stand



HP LaserJet M5035xs MFP

- HP LaserJet M5035xs MFP: as base model with automatic two-sided printing
- analogue fax
- three additional 500-sheet input trays
- stand and 30-sheet stapler/stacker with additional 500 sheet output

Recommended accessories



J7989G
HP High Performance
Serial ATA EIO Hard
Disk



Q7719A
HP 256 MB 100-pin
DDR DIMM



Q3701A
HP LaserJet MFP Analog
Fax Accessory 300



J7972G
HP 1284B Parallel EIO
Card



C8091A
HP Staple Cartridge



Q7549A
HP LaserJet Auto Duplex
Unit



Q7834A
HP LaserJet M5035/M5025
MFP 500-sheet Tray w/
Cabinet



Q7835A
HP LaserJet M5035/M5025
MFP integrated 3x500-sheet
Tray



T1936AA
HP Digital Sending Software 4



J7960G
HP Jetdirect 625n Internal Print
Server (EIO,
10/100/1000TX)



J7961G
HP Jetdirect 635n IPv6/IPsec
Internal Print Server (EIO,
10/100/1000TX)

Operating and warranty specifications

Operating environment	Operating temperature: 15 to 35° C. Recommended operating temperature: 15 to 35° C. Operating humidity: 20 to 80% RH. Operating humidity recommended: 25 to 75% RH. Storage temperature: 13 to 38° C. Storage humidity: 20 to 80% RH. Noise level per ISO 9296: sound power: LwAd 6.6 B(A) (printing at 35 ppm). Sound pressure: LpAm 51 dB(A) (printing), 56 dB(A) (copy or scan)
Certifications	CISPR 22:1993/EN 55022:1994 Class A, EN 61000-3-2:2000, EN 61000-3-3:1995, EN 55024:1998, FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 4/GB9254-1998, GB17625.1-2003, EMC Directive 89/336/EEC and the Low Voltage Directive 73/23/EEC, and carries the CE-Marking accordingly. Regulatory standards: Argentina (TUV S Mark-Rs.92/98/Ds.1009/98), Australia (AS/NZ 3260), Canada (cUL-CAN/CSA C22.2 No.60950-1-03), China (GB4943), Czech Republic (CSN-IEC 60950-1; IEC 60825-1), Estonia (EET-EN60950-1; IEC 60825-1), EU (CE Mark-Low Voltage Directive 73/23/EEC), Germany (TUV-EN60950-1; IEC 60825-1), Hungary (MEEHEC 60950-1; IEC 60825-1), Lithuania (LS-IEC 60950-1; IEC 60825-1), (Russia (GOST-R50377), Slovakia (IEC 60950-1; IEC60825-1), Slovenia (SQI-IEC 60950-1; EN60825-1), South Africa (IEC 60950-1; IEC60825-1), US (UL-LUL 60950-1; FDA-21 CFR Chapter 1 Subchapter J for lasers), Class 1 Laser/LED Product. ENERGY STAR: Yes
Warranty	One-year, next-day, next-business-day-on-site warranty with free phone support during warranty period

Ordering information



HP LaserJet M5035 MFP (Q7829A)

HP LaserJet M5035 MFP (includes printer engine, scanner, ADF, digital sender, 40 GB hard disk drive, and control panel), power cord, 15,000 page toner cartridge, control panel overlay, Getting Started Guide, wall poster, printer driver software CD



HP LaserJet M5035x MFP (Q7830A)

as Q7829A plus two-sided printing, analogue fax, 500-sheet input tray, stand



HP LaserJet M5035xs MFP (Q7831A)

as Q7829A plus two-sided printing, analogue fax, three 500-sheet input trays, stand, stapler/stacker

Accessories, Supplies and Support

Accessories

J7989G	HP High Performance Serial ATA EIO Hard Disk
Q7718A	HP 128 MB 100-pin DDR DIMM
Q7719A	HP 256 MB 100-pin DDR DIMM
Q3701A	HP LaserJet MFP Analog Fax Accessory 300
J7972G	HP 1284B Parallel EIO Card
C8091A	HP Staple Cartridge
Q7549A	HP LaserJet Auto Duplex Unit
Q7833A	HP LaserJet M5035/M5025 MFP 220V Printer Maintenance Kit
Q7834A	HP LaserJet M5035/M5025 MFP 500-sheet Tray w/ Cabinet
Q7835A	HP LaserJet M5035/M5025 MFP integrated 3x500-sheet Tray
Q7842A	HP LaserJet M5035/M5025 MFP ADF Maintenance Kit
T1936AA	HP Digital Sending Software 4

Supplies

Q7570A	HP LaserJet Q7570A Black Print Cartridge with Smart Printing Technology 15,000 standard pages according to ISO/IEC 19752
---------------	---

Connectivity

C6518A	HP USB Cable, 2m
J7960G	HP Jetdirect 625n Internal Print Server (EIO, 10/100/1000TX)
J7942G	HP Jetdirect en3700 External Print Server (USB, 10/100TX)

J7961G HP Jetdirect 635n IPv6/IPsec Internal Print Server (EIO, 10/100/1000TX)

J7951G HP Jetdirect ew2400 802.11g Wireless and Fast Ethernet External Print Server

Service & support

UE670A/E	HP Care Pack, Next Business Day On-Site, 3 years
UE676A/E	HP Care Pack, Same Day (4 hours) 13x5, 3 years
UE679PE	HP Care Pack, Post Warranty Next-Business-Day On-Site, 1 year
UE681PE	Care Pack, Post Warranty Same Day (4 hours) 13x5, 1 year
UE671E	HP Care Pack, Next Business Day On-Site, 4 years
UE672E	HP Care Pack, Next Business Day On-Site, 5 years
U2014A/E	HP Care Pack, Installation & Network Configuration

For a complete list of supplies, accessories and services, please refer to <http://www.hp.com>

Technical specifications

Print technology	Monochrome Laser			
Print speed	A3: Up to 18 ppm. A4: Up to 35 ppm. First page out black: Less than 10 sec			
Processor	460 MHz. MIPS embedded in HP Custom ASIC			
Memory	256 MB. Expandable to 512 MB through one 100-pin DDR DIMM slot. Hard Disk Capacity: Standard, 40 GB			
Print	Quality	HP ProRes 1200, HP FastRes 1200, 600 dpi, 170 lpi		
	Resolution	Up to 1200 x 1200 dpi		
	Printer languages	HP Postscript Level 3 Emulation, PCL 6, PCL 5, PDF 1.4		
	Economical printing	Economode (saves up to 50% toner from 600 dpi), immediate return to Power safe mode after each print job due to Instant-on fuser technology (saves electricity), optional automatic two-sided printing and N-up printing (saves paper)		
	Duty cycle	Up to 200000 pages per month		
	Print margins (mm)	Top: 2 mm. Left: 2 mm. Right: 2 mm. Bottom: 2 mm		
Fax	Telecom compliance	Telecom: TBR-21:1998; EG 201 121:1998, FCC Part 68, Industry Canada CS03, NOM-151-SCTI-1999 (Mexico), PTC-200 (New Zealand), AS/ACIF S002:2001 (Australia), IDA PSTN1 (Singapore), TPS002-01 (Malaysia), IG 0005-11 (Taiwan), HKTA 2011 (Hong Kong), YD514, YD/T589, YD703, GB3382 (China)		
	Fax memory	Dependent on available free disk space		
	Fax resolution	Standard: 200 x 200 dpi. Superfine: 300 x 300 dpi. Photo: 200 x 200 dpi		
Digital sending	File formats	PDF, JPG, TIFF, MTIFF		
	Installation	Via HP Jetdirect embedded networking, HP Jetdirect internal print servers, HP Jetdirect external print servers, HP wireless print servers, and HP connectivity cards		
Scan	Type	Flatbed, ADF. Colour scanning: Yes		
	Scan resolution	Optical: Up to 600 dpi. Enhanced: Up to 1200 dpi		
	Grey scale levels	256		
	Scannable area	Maximum media size: 29.7 x 42.0 cm		
	Margins for scanned items	Left: 5 mm. Top: 6 mm. Right: 5 mm. Bottom: 6 mm		
Copy	Copy speed	Up to 35 cpm		
	Copy resolution	Up to 600 x 600 dpi		
	Multiple copies	Up to 1000		
	Reduce/enlarge	25 to 400%		
Media handling	Input:	Capacity	Weight	Size
	Tray 1	Sheets: 100, envelopes: 10	60 to 199 g/m ²	67.2 x 127 mm postcards, A5, A4, A3, B4, B5, EXE, ITR, LGL, LGR, 76 x 127 mm to 312 x 469.9 mm
	Tray 2	Sheets: 250	60 to 120 g/m ²	A4, B4, B5, ITR, LGL, EXE, A5, 215.9 x 330.2 mm
	Tray 3	Sheets: 250	60 to 120 g/m ²	A4, B4, B5, ITR, LGL, EXE, A5, A3, LGR, 215.9 x 330.2 mm
	ADF	Sheets: 50	60 to 120 g/m ²	
	Output:	Sheets: Up to 250. Envelopes: Up to 25. Transparencies: Up to 200		
Media types	Paper (plain, photo, banner), envelopes, labels, cards (index, greeting), transparencies, letter, pre-punched, recycled			
Interface and connectivity	HP Jetdirect Fast Ethernet embedded print server, Foreign Interface Harness (FIH), USB (compatible with USB 2.0 specifications) type A port, USB (compatible with USB 2.0 specifications) type B port, open EIO slot, optional analog fax. Optional: HP Jetdirect 635n IPv6/IPsec Print Server J7961A, HP Jetdirect 625n Gigabit Ethernet Print Server J7960A, HP Jetdirect 620n Fast Ethernet Print Server J7934A, HP Jetdirect ew2400 802.11g Wireless Print Server J7951A, HP Jetdirect en3700 Fast Ethernet Print Server J7942A, HP Jetdirect 175x Fast Ethernet Print Server J6035D, HP High Performance Serial ATA Hard Disk J7989G, HP 1284B Parallel Card J7972G, HP Jetdirect Connectivity Card J4135A, HP bt450 Bluetooth Wireless Printer and PC Adapter Q6398A, HP bt400 Bluetooth Wireless Printer Adapter Q6399A			
Operating systems compatibility	Windows® 2000, XP Home, XP Professional, XP Professional x64 Edition, Windows® Server 2003; Mac OS 10.2 and higher. Optional: Windows® 2000, XP Home, XP Professional, XP Professional x64 Edition, Windows® Server 2003; Mac OS 10.2 and higher. The latest software and drivers are available for the HP LaserJet M5035 MFP from the HP Website at http://www.hp.com/support/ljm5035mfp			
Network operating systems compatibility	Optional: Windows® 2000, XP Home, XP Professional, XP Professional x64 Edition, Windows® Server 2003; Mac OS 10.2 and higher			
Minimum system requirements	133 MHz processor or higher, 64 MB RAM, 40 MB available hard disk space, USB or network port connection. Mac OS 10.2 and higher, 128 MB RAM, 25 MB available hard disk space, network or USB port			
Standard software	Drivers on the web: Printing system, PCL 6 driver only, PCL 5 driver only, PS driver only, WJA applet, UPD PCL 5, UPD PS, HP Easy Printer Care Software, PC fax driver			
Control panel	4 job control buttons, 13 button numeric keypad, touch screen graphical display, 3 status lights, 1 display contrast knob			
Power	Requirements: Input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 6 amp. Consumption: 0.1 watts maximum (off), 24 watts maximum (sleep), 280 watts maximum (ready), 600 watts maximum (printing), 1265 watts maximum (copying)			
Dimensions (w x d x h)	Out of package: M5035 MFP: 610 x 571 x 584 mm; M5035x MFP: 743 x 743 x 997 mm; M5035xs MFP: 743 x 743 x 1183 mm. Packaged: M5035 MFP: 766 x 721 x 852 mm; M5035x MFP: 900 x 900 x 1418 mm; M5035xs MFP: 900 x 900 x 1567 mm			
Weight	Out of package: M5035 MFP: 55 kg; M5035x MFP: 93 kg; M5035xs MFP: 97 kg. Packaged: M5035 MFP: 61.1 kg; M5035x MFP: 100 kg; M5035xs MFP: 104.3 kg			

<http://www.hp.com/uk>



© Copyright Hewlett-Packard Development Company, L.P. 2006. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 10/06 4AA0-5300EEE

