HP Latex 700 W Printer

Win high-value jobs, equipped with white ink, and sharpen your sustainability edge with HP Latex





Access white and produce the highest value jobs

- Extend your portfolio into high-margin stickers and window graphics with the whitest white.¹
- Print white without complexity—automatic recirculation and printhead cleaning reduce manual purging.
- Deliver vivid colors at high speed, get striking contrast using pure blacks, and expect sharp 4point text.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinyl.

Beat your deadlines with smart, efficient printing

- Fast saturated color up to 334 ft²/hr outdoor, 226 ft^2/hr indoor, 2
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Enjoy fast and easy spindle-less loading and media access for rolls up to 121 lb (55 kg).

Sharpen your sustainability edge with HP Latex

- Innovative water-based HP Latex Inks—no HAPs³, no required hazard warning labels, and odorless prints.⁴
- Zero landfill—local outer carton recycling, free take-back of inner ink bag/printhead, HP Planet Partners.⁵
- Choose from a wide range of compatible ecoconscious media.⁶
- HP Latex prints are recyclable, returnable, or nonhazardous and safe for disposal.⁷

For more information, please visit http://www.hp.com/go/latex700series

Inks, are non-hazardous and safe for disposal. Contact your local waste management authority for local area-specific instructions.

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Whitest white based on ISO/DIS 23498 compared to competitive alternatives using solvent and UV technologies under \$50,000 USD as of May, 2020. Test performed on black opaque self-adhesive vinyl (1*:4.16 – a:0,48-b:2,34) with 160% UF printmode using HP 832 1-liter White Latex Ink Cartridge. Visual opacity = 91%. ² Outdoor mode (Banner) 4-pass, 100%. Indoor mode (SAN) 6-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image guality

⁴ Outdoor mode (Banner) 4-pass, 100%. Indoor mode (SAV) 6-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects. ³ HP Lates Inks were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected.

³ HP Latex Inks were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were d
⁴ There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

⁵ The ink cartridge HP Eco-Carton outer carton is 100% recyclable through local cardboard/paper programs. Inner materials including the ink bag are 55% recyclable and can be returned free of charge to the HP Planet Partners program for reprocessing of plastic parts. Zero landfill. For ink bag and printhead take back, visi http://www.hp.com/recycle to see how to participate and for HP Planet Partners program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal.

¹ Most HP large format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details. HP large format prioriting materials, both unprinted and printed and printed with Original HP Latex

Technical specifications

Drinting modes	1120 ft2/br May Speed (1 pace)
Printing modes	1130 ft²/hr - Max Speed (1-pass) 334 ft²/hr - High Speed (4-pass)
	226 ft²/hr - Production Fast (6-pass) 183 ft²/hr - Production Quality, Textiles and Backlits (8-pass)
	172 ft²/hr - High Saturation (12-pass) 129 ft²/hr - High Saturation Backlits and Textiles (14-pass)
	183 ft²/hr - White Spot (60%) 99 ft²/hr - White Overflood (60%)
	32 ft²/hr - White Underflood (100%) 22 ft²/hr - 3 Layers Day & Night (160%) ¹
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Latex Overcoat)
Cartridge size	1L
Printheads	10 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 2 white, 1 HP Latex Optimizer, 1 HP Latex Overcoat)
Long-term print-to-print repeatability	95% of colors $\leq 1.5 \text{ dE2000}^2$
Media	
Handling	Roll feed, take-up reel, wiper roller ³ , automatic horizontal cutter (for vinyl, banner and canvas ⁴ , paper based media, and film)
Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles
Roll size	10 to 64-in rolls (23 to 64-in rolls with full support)
Roll weight	121 lb
Roll diameter	9.8 in
Thickness	Up to 19.7 mil
Applications	Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (w x d :	x h)
Printer	101.7 x 33.6 x 55.2 in
Shipping	110.2 x 44.5 x 50 in
Operating area	110 x 82.7 in
Weight	
Printer	589 lb
Shipping	811.3 lb
What's in the box	HP Latex 700 W Printer, printheads, maintenance cartridge, ink mix containers (x2), printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords, air purgers, 2-in spindle adaptor
Environmental rang	Jes
Operating temperature	59 to 86°F
Operating humidity	20 to 80% RH (non-condensing)
Acoustics	
Sound pressure	60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
Sound power	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)
Power	
Consumption	1.5-2.6 kW (5 kW peak) (printing), 95 W (ready)
Requirements	Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord
Certification	
Safety	IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)
Environmental	ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT Silver; OSHA; CE marking compliant; Meets AgBB criteria; French VOC A+; Greenguard Gold; UL Ecologo; ZDH - Level 1
Warranty	One-year limited hardware warranty

Ordering information

Product		
YOUZ3A	HP Latex 700 W Printer	
Accessories		
21V10A 7HR16A 7HR18A 7HR19A T7U73A	HP Latex 700/800 User Maintenance Kit HP Latex 700/800 Textile Kit Accessory HP Latex 700/800 Ink Collector Foams Kit HP Latex 700/800 Media Loading Accessory HP Latex 500/700/800 Wiper Roller	
Original HP printing supplies		
4UU93A 4UU96A 4UU96A 4UV29A 4UV75A 4UV75A 4UV77A 4UV77A 4UV79A 4UV79A 4UV80A 4UV81A 4UV83A 4UV83A 4UV95A 4UV95A 4UV95A 4UV95A 4UV97A	HP 836 White Latex Printhead HP 836 Optimizer Latex Printhead HP 836 Latex Maintenance Cartridge HP 832 1-liter White Latex Ink Cartridge HP 832 1-liter Black Latex Ink Cartridge HP 832 1-liter Magenta Latex Ink Cartridge HP 832 1-liter Magenta Latex Ink Cartridge HP 832 1-liter Light Nagenta Latex Ink Cartridge HP 832 1-liter Light Nagenta Latex Ink Cartridge HP 832 1-liter Light Nagenta Latex Ink Cartridge HP 832 1-liter Dight Nagenta Latex Ink Cartridge HP 832 1-liter Optimizer Latex Ink Cartridge HP 835 Black/Cyan Latex Printhead HP 836 Light Cyan/Light Magenta Latex Printhead HP 836 Light Cyan/Light Magenta Latex Printhead	

Original HP large format printing materials

HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified⁶, FSC[®] certified⁷, meets AgBB criteria⁸) HP Photo-realistic Poster Paper HP Premium Satin Canvas

HP Prime Matte Air GP (REACH compliant⁹) HP Premium Removable Gloss Adhesive Vinyl (REACH compliant⁹)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U13DCE HP 2 year Next Business Day with Defective Media Retention U13DHE HP 3 year Next Business Day with Defective Media Retention U13DMPE HP 1 year Post Warranty Next Business Day with Defective Media Retention U13DSPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

ECO highlights

- Inks do not use reactive monomer chemistry, are ozone-free, and meet the ZDHC standard¹ Can win new business with odorless prints, UL ECOLOGO®/UL GREENGUARD Gold Certified ink, and more² Eco-Carton replaces plastic cartridge with 80% reduction in plastic, achieves 66% CO2e reduction³ Zero landfill—local outer carton recycling, free take-back inner ink bag via HP Planet Partners⁴

Please recycle printing hardware and eligible printing supplies and prints. Find out how at our website: http://www.hp.com/ecosolutions

¹ See http://www.roadmaptozero.com. Printing with HP Latex Inks avoids the problematic reactive monomers ¹ See http://www.roadmaptozero.com. Printing with HP Latex lnks avoids the problematic reactive monomers associated with UV printing. Acrylate monomers present in uncured UV inks and UV-get inks can damage skin.
² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. For certifications, see http://www.uLcom/JEL and http://wi program for reprocessing of plastic parts. Zero landfill. For take-back of ink bag/printhead/prints, visit http://www.hp.com/recycle to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction.

¹ Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.
² The color variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective measurements on a 943 color target under CIE standard Illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5 014-6/E:2012. 5% of colors may experience variations above 1.5 ⁴ Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a

test.

 ⁵ Textile Kit Accessory required for long runs of textile and porous textile.
 ⁶ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit Standards for two chemical enhancements into model and during product diage. For interemination, of http://www.iucom/gg or http://www.greenguard.org.
 ⁷ Trademark license code FSC-C115319.
 ⁸ With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://www.iucom/gatherena.com/gath

http://umweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-

http://umweitubindeaint.du/ei/rupics/ineau/commasure-working_groups/commetce to intervent evaluation-of-building.
⁹ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.



