

Cable, Cord and Hose Reels



Features and Benefits


inREACH™ Industrial Weatherproof Cord Reels

- UL Type 4 environmental listing
- 600V AC, SOW Type Cable
- Durable, corrosion resistant cast aluminum construction
- Multi-position guide arm can be mounted in two positions
- Ratchet lock can be disengaged in field for constant tension applications



inREACH™ Industrial Weatherproof Cord Reels

HBLW45103



HBLW45123W



HBLW35143



HBLW45103



HBLIMB



HBLI340PB



HBLIMBJ



HBLI10BS

Amps	Volts AC	Cable Length Feet (m)	Cable Type	Weight Lbs. (kg)	Yellow Reel	White Reel
10	600	45 (13.7)	16/3 SOW	23.6 (10.7)	HBLW45163	HBLW45163W
			16/4 SOW	25.6 (11.6)	HBLW45164	HBLW45164W
		35 (10.7)	16/3 SOW	22.5 (10.2)	HBLW35163	HBLW35163W
			16/4 SOW	23.1 (10.5)	HBLW35164	HBLW35164W
		25 (7.6)	16/3 SOW	21.4 (9.7)	HBLW25163	HBLW25163W
			16/4 SOW	21.8 (9.9)	HBLW25164	HBLW25164W
15	600	45 (13.7)	14/3 SOW	28.2 (12.8)	HBLW45143	HBLW45143W
			14/4 SOW	30.0 (13.6)	HBLW45144	HBLW45144W
		35 (10.7)	14/3 SOW	25.1 (11.4)	HBLW35143	HBLW35143W
			14/4 SOW	26.5 (12.0)	HBLW35144	HBLW35144W
		25 (7.6)	14/3 SOW	22.5 (10.2)	HBLW25143	HBLW25143W
			14/4 SOW	24.3 (11.0)	HBLW25144	HBLW25144W
18 16	600	80 (24.4)	12/3 SOW	97.5 (44.2)	—	HBLW80123W*
		75 (22.9)	12/4 SOW	107.4 (48.7)	—	HBLW75124W*
20	600	45 (13.7)	12/3 SOW	31.3 (14.2)	HBLW45123	HBLW45123W
			12/4 SOW	32.2 (14.6)	HBLW40124	HBLW40124W
		35 (10.7)	12/3 SOW	28.9 (13.1)	HBLW35123	HBLW35123W
			12/4 SOW	30.6 (13.9)	HBLW35124	HBLW35124W
		25 (7.6)	12/3 SOW	24.9 (11.3)	HBLW25123	HBLW25123W
12/4 SOW	27.6 (12.5)	HBLW25124	HBLW25124W			
25 20	600	75 (22.9)	10/3 SOW	103.8 (47.1)	—	HBLW75103W*
		75 (22.9)	10/4 SOW	116.2 (52.7)	—	HBLW75104W*
30	600	40 (12.2)	10/3 SOW	33.3 (15.1)	HBLW40103	HBLW40103W
			10/4 SOW	34.2 (15.5)	HBLW35104	HBLW35104W
		35 (10.7)	10/3 SOW	31.7 (14.4)	HBLW35103	HBLW35103W
			10/4 SOW	34.2 (15.5)	HBLW35104	HBLW35104W
25 (7.6)	10/3 SOW	28.4 (12.9)	HBLW25103	HBLW25103W		
	10/4 SOW	30.2 (13.7)	HBLW25104	HBLW25104W		
40 30 35	600	45 (13.7)	8/3 SOW	106.5 (48.3)	—	HBLW4583W*
		60 (18.3)	8/3 SOW	123.2 (55.9)	—	HBLW6083W*
		45 (13.7)	8/4 SOW	122.8 (55.7)	—	HBLW4584W*
55 55	600	45 (13.7)	6/3 SOW	123.0 (55.8)	—	HBLW4563W*
		45 (13.7)	6/4 SOW	126.7 (57.5)	—	HBLW4564W*
14 6	600	45 (13.7)	12/8 SOW	107.4 (48.7)	—	HBLW45128W*
		45 (13.7)	14/12 SOW	113.5 (51.5)	—	HBLW451412W*

inREACH™ Accessories

Description	Weight Lbs. (kg)	Catalog Number
Mounting bracket	2.5 (1.1)	HBLIMB
Mounting bracket with junction box mount	3.0 (1.4)	HBLIMBJ
Mounting bracket	3.5 (1.6)	HBLIACMB*
Mounting bracket with junction box mount	4.0 (1.8)	HBLIACMBJ*
340° pivot base	3.5 (1.6)	HBLI340PB
Replacement stop		HBLI16BS
	.2 (.09)	HBLI14BS
		HBLI12BS
		HBLI10BS

Note: *Compatible with cord reel models marked with a single asterisk (*)