

## Terminal, Aluminum Bolted

By ANDERSON  
Catalog # [A2CF13D](#)

"Terminal, Aluminum Bolted, Straight, Cable to 4 Hole Flat, Cable Dia. Range 1.382"-1.632" For AAC, ACSR, Material: Aluminum alloy"



### Features

- "Centre formed pads may be obtained by adding suffix-CF to the catalog number
- 45° & 90° angle connectors may be obtained by specifying desired angle
- To obtain cable grooves coated with a petroleum base sealant, add "XB" suffix to Catalog number"

### General

Material	Aluminum
Material - Clamping Hardware	Aluminum Alloy
Number of Bolt Holes	4
Number of Pad Holes	4
Type	Bolted Lugs & Terminals
UPC	096359278337

### Dimensions

Angle - Pad	180 °
Weight	3.6 lb
Width - Pad	4 in

### Conductor Related

Conductor Compatibility	ACSR-Redwing-715.5-30/19;ACSR-Cuckoo-795-24/7;ACSR-Drake-795-26/7;ACSR-Condor-795-54/7;ACSR-Mallard-795-30/19;ACSR-Ruddy-900-45/7;ACSR-Canary-900-54/7;ACSR-Rail-954-45/7;ACSR-Cardinal-954-54/7;ACSR-Ortolan-1033.5-45/7;ACSR-Curlew-1033.5-54/7;ACSR-Bluejay-1113-45/7;ACSR-Finch-1113-54/19;AAC-Cockscomb-900-37;AAC-Snapdragon-900-61;AAC-Magnolia-954-37;AAC-Goldenrod-954-61;AAC-Camellia-1000-61;AAC-Bluebell-1033.5-37;AAC-Larkspur-1033.5-61;AAC-Marigold-1113-61;AAC-Hawthorn-1192.5-61
Conductor Diameter - Maximum	1.293 in
Conductor Diameter - Minimum	1.081 in
Conductor Diameter Range	1.081 - 1.293
Conductor Type	<ul style="list-style-type: none"> <li>• AAC</li> <li>• ACSR</li> </ul>

### Logistics

Pallet Quantity	324
-----------------	-----

### Product Assets

[Catalogs - Substation Connectors \(SA\)](#)

[Sales Drawings - C-1482 \(A2CF Product Family\)](#)

[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products \(VI05050E0619\)](#)

[Video - Hubbell Power Systems Quick Ship \(VI05124E1018\)](#)

