KILLARK®

UGP Series - 15 Amp 125VAC Interchangeable Blade Style Plug With Quick Wiring - NEMA Configuration 5-15P

By Killark Catalog # UGP-15231QW

UGP Series - Aluminum 15 Amp 125VAC Interchangeable Blade Style Plug With Quick Wiring - NEMA Configuration 5-15P.



*Representative Image

Features

- Factory sealed chamber in UGR receptacle contains switch's arcing components.
- Spring loaded receptacle cover closes when plug is removed.
- Copper-free aluminum (less than 4/10 of 1%) alloy resists corrosion
- Electrostatically applied and baked powder epoxy/polyester finish
- ACCEPTOR® plugs conform to NEMAconfigurations, while it's "turn to engage" feature locks in plug and can be used to prevent accidental disengagement of critical equipment.
- Plugs for use with type S/SO/ST/STO heavy duty cord.

Application

Petroleum refineries, chemical plants, wet/damp areas, corrosive environments, petroleum plants, grain elevators/feed mills, flour and feed mills, and indoor or outdoor locations

General

Color • Gray

Gris

Material Aluminum, Copper Free (less

than 4/10 of 1%)

Number Of Poles 2

Receptacle Type Delayed Action

Series UGP

Type • Straight Blade

• Straight Blade

UPC 783936076683

Dimensions

Dimensions 6.625 in x 2.375 in x 1.875 in

Gross Weight with Packaging 0.4
Height 1.875 in
Length 6.625 in
Width 2.375 in

Electrical Ratings

Amperage Rating 15 A

Conductor Related

Number Of Wires 3

Wire Size #10 AWG, #12 AWG, or #14

AWG

Certifications and Compliance

Hazardous Rating(s)

• Class I, Divisions 1 & 2,

Groups C, D

• Class I, Zones 1 & 2, Groups

IIB, IIA

• Class II, Divisions 1 & 2,

Groups F, G

• Class III, Divisions 1 & 2

Nema Rating 3, 4, 4X

Product Assets

3D Media - KIL_UGP-15231QW

Certifications - UGR/UGP Series UL Certification

Customer Notices - Prop 65 Notice

Engineering Drawing - UGP-15231QW Engineering Drawing

(DWG)

Installation Manuals - UGP Series IOM K1377

Sales Drawings - UGP-15231QW Sales Drawing (PDF)