

SVNX Arrester (335 kV MCOV)

By OHIO BRASS
Catalog # [SVNX420GA335AA](#)

IEEE Station Class Polymer Housed High Strength Surge Arrester



Features

- IEEE silicone station class arrester
- Energy Class K
- IEEE 693 High Performance Qualification
- snmx arresters are typically applied to system voltages higher than 500kV
- High quality MOV discs made in Wadsworth, Ohio since 1978
- Arresters assembled in Aiken, South Carolina
- 100% routine tested

General

Color	Gray Housing
Material	Polymer Housing
Type	Station
UPC	096359734390

Dimensions

Bolt Circle Diameter	16.5 in
Diameter - Single Bolt Hole(s)	0.875 in
Height	212 in
Maximum Operating Altitude	12000 ft
Minimum Mounting Spacing on Center (Sea Level) - Phase to Ground	71 in
Minimum Mounting Spacing on Center (Sea Level)- Phase to Phase	81 in

Electrical Ratings

Creep and Leakage Distance	469 in
Duty Cycle	420 kV
Frequency Rating	48-62 Hz
MCOV	335 kV
Maximum .5 Microsecond Discharge Volts @ Classifying Current	1022.0 kV
Maximum Discharge Voltage	<ul style="list-style-type: none">• 809 kV @ 1.5 kA• 837 kV @ 3 kA• 863 kV @ 5 kA• 905 kV @ 10 kA• 959 kV @ 20 kA• 1027 kV @ 40 kA
Maximum Switching Surge Protective Level @ 2000A	815 kV

Certifications and Compliance

Industry Standard(s)	IEEE
----------------------	------

Product Assets

[Installation Manuals - Polymer Hollow Core Station Class Arrester Installation Instructions \(17-5155\)](#)
[Literature - Application Guide: Metal-oxide Surge Arresters for use on AC systems \(TD01135E\)](#)
[Sales Drawings - SVNX420GA335AA \(For Reference Only\)](#)
[Video - Hubbell Power Systems Metal Oxide Varistor \(VI01022E0718\)](#)