



\* Representative image

# Compression Splice Partial Tension

by ANDERSON  
Catalog ID: PTR795

Partial Tension Aluminum splice for 795 36/1 ACSR, 795 round strand AAC.

- Meets ANSI C119.4 requirements for partial tension.

## Product Details

### General

Compression Method	VersaCrimp or Conventional Die Tooling
Die Index	342
Die Size	<ul style="list-style-type: none"> <li>• VC8</li> <li>• Kearney 1-1/2</li> </ul>
Material	Aluminum
UPC	096359324263

### Dimensions

Length Before Compression	11 in
Weight	1.372 lb

### Conductor Related

Conductor Compatibility	ACSR-Egret-636-30/19;ACSR-Flamingo-666.6-24/7;ACSR-Gannet-666.6-26/7;ACSR-Stilt-715.5-24/7;ACSR-Coot-795-36/1;AAC-Cattail-750-61;AAC-Arbutus-795-37;AAC-Lilac-795-61;AAC-Snapdragon-900-61
Conductor Diameter (Conventional Tooling) - Maximum	1.042 in
Conductor Diameter (Conventional Tooling) - Minimum	0.997 in
Conductor Diameter (VersaCrimp) - Maximum	1.042 in
Conductor Diameter (VersaCrimp) - Minimum	0.997 in

### Certifications and Compliance

UL Listed	No
-----------	----

**For further technical assistance, please contact us**

#### Domestic Customer Service

Hubbell Power Systems  
210 N. Allen Centralia, MO 65240 USA  
Phone: (573) 682-5521  
Fax: (573) 682-8475  
Email: hpscsc@hubbell.com

#### International Customer Service

Phone: +1-573-682-5521  
Fax: +1-573-682-8516  
Email: hpsintlcs@hubbell.com