

# Canon Digital IXUS 185 (1803C001)

Digital IXUS 185 - 1/2.3" CCD 20MP, DIGIC 4+, 5.0-40.0mm, TTL, 6.8cm (2.7") LCD, SD/SDHC/SDXC



## Price details:

Price excl. VAT: 97.77 €

Eco fees: 0.00 €

VAT 21 %: 20.53 €

## Product details:

Product code: 1803C001

EAN: 4549292083088

Manufacturer: Canon

PDF generated on: 22 February, 2018



**118.30 €**

\* VAT included

### Simple pocketable IXUS quality

Capture your favourite moments in superb quality photos and movies using this chic, ultra-slim IXUS with versatile 8x optical zoom lens. Shoot for longer with Eco Mode.

### Superb results

Enjoy exceptional quality, detailed images of friends and family with 20.0 Megapixels and Face Detection. Add a date stamp to see the timeline of your memories.

### Point and shoot simplicity

Get fantastic results with one touch of a button using Easy Auto, which chooses the perfect camera settings for you - so all you have to do is concentrate on your shot.

### Creative play

Have fun with a range of easy creative modes. Re-create the distortion of a fish-eye lens, make scenes in stills or movies look like miniature scale models and more.

### Instant HD movies

Making great movies using the creativity of the optical zoom is fun and easy. With one touch of a button you can effortlessly record creative, sharable HD movies (720p).

## Main specifications:

### Picture quality

Camera type:	Compact camera
Megapixel:	20 MP
Image sensor size:	1/2.3 "
Sensor type:	CCD
Maximum image resolution:	5152 x 3864 pixels
Still image resolution(s):	5152 x 3864, 3648 x 2736, 2048 x 1536, 640 x 480, 5152 x 2896
Image stabilizer:	Y
Image formats supported:	JPG
Supported aspect ratios:	4:3,16:9
Total megapixels:	20.5 MP

### Lens system

Optical zoom:	8 x
Digital zoom:	4 x
Focal length range (f-f):	5 - 40 mm
Minimum focal length (35mm film equiv):	28 mm
Maximum focal length (35mm film equiv):	224 mm

Minimum aperture number: 3.2  
Maximum aperture number: 6.9  
Lens structure (elements/groups): 8/7  
Combined zoom: 32 x  
Number of aspheric elements: 1

#### Focusing

Auto focusing (AF) modes: Continuous Auto Focus,Face detection,Servo Auto Focus,Single Auto Focus,Tracking Auto Focus  
Focus: TTL  
Closest focusing distance: 0.01 m  
Auto Focus (AF) points: 9  
Auto Focus (AF) assist beam: Y

#### Light exposure

ISO sensitivity: 100,200,400,800,1600,Auto  
Light exposure modes: Auto  
Light exposure correction:  $\pm 2\text{EV}$  (1/3EV step)  
Light metering: Centre-weighted,Evaluative (Multi-pattern),Spot  
ISO sensitivity (min): 100  
ISO sensitivity (max): 1600

#### Shutter

Fastest camera shutter speed: 1/2000 s  
Slowest camera shutter speed: 15 s

#### Flash

Flash modes: Auto,Flash off,Flash on,Manual,Red-eye reduction,Slow synchronization  
Flash range (wide): 0.5 - 3 m  
Flash range (tele): 1.3 - 1.5 m  
External flash connector: Y  
Flash sync-speed: 1/2000 s

#### Video

Video recording: Y  
Maximum video resolution: 1280 x 720 pixels  
HD type: HD ready  
Video resolutions: 640 x 480,1280 x 720 pixels  
Motion JPEG frame rate: 29.97 fps  
Resolution at capture speed: 1280x720@25fps  
Analog signal format system: NTSC,PAL  
Video formats supported: MOV

#### Audio

Built-in microphone: Y  
Audio system: Mono  
Audio formats supported: AAC

#### Memory

Compatible memory cards: SD,SDHC,SDXC  
Memory slots: 1

#### Display

Display: LCD  
Display diagonal: 2.7 "  
Flip-out screen: N  
Vari-angle LCD display: N  
Display diagonal (metric): 6.8 cm  
Display resolution (numeric): 230000 pixels  
Field of view: 100 %

#### Ports & interfaces

USB version: 2.0  
HDMI: N  
USB connector: Mini-USB B

#### Networking

Bluetooth: N  
Wi-Fi: N  
Near Field Communication (NFC): N

#### Camera

White balance:	Auto,Cloudy,Custom modes,Daylight,Fluorescent
Scene modes:	Fireworks,Portrait
Shooting modes:	Auto
Photo effects:	Black&White,Vivid
Self-timer delay:	2,10 s
Brightness adjustment:	Y
Camera playback:	Movie,Single image
Playback zoom (max):	10 x
Languages support:	Multi
Histogram:	Y
Image editing:	Resizing
Orientation sensor:	Y
Camera file system:	DPOF 1.1,Exif 2.3
Built-in processor:	Y
<b>Battery</b>	
Power source type:	Battery
Battery technology:	Lithium-Ion (Li-Ion)
Battery life (CIPA standard):	210 shots
Battery type:	NB-11L
Number of batteries supported:	1
<b>Design</b>	
Colour of product:	Black
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	10 - 90 %
<b>System requirements</b>	
Windows operating systems supported:	Windows 10 Education,Windows 10 Education x64,Windows 10 Enterprise,Windows 10 Enterprise x64,Windows 10 Home,Windows 10 Home x64,Windows 10 Pro,Windows 10 Pro x64,Windows 7 Enterprise,Windows 7 Enterprise x64,Windows 7 Home Basic,Windows 7 Home Basic x64,Windows 7 Home Premium,Windows 7 Home Premium x64,Windows 7 Professional,Windows 7 Professional x64,Windows 7 Starter,Windows 7 Starter x64,Windows 7 Ultimate,Windows 7 Ultimate x64,Windows 8,Windows 8.1
Mac operating systems supported:	Mac OS X 10.10 Yosemite,Mac OS X 10.11 El Capitan,Mac OS X 10.12 Sierra,Mac OS X 10.9 Mavericks
<b>Weight &amp; dimensions</b>	
Width:	95.2 mm
Depth:	22.1 mm
Height:	54.3 mm
Weight (including battery):	126 g
<b>Packaging content</b>	
Bundled software:	CameraWindow DC
Battery charger included:	Y
Batteries included:	Y
Hand strap:	Y
Quick start guide:	Y
<b>Other features</b>	
USB connectivity:	Y
<b>Technical details</b>	
Image processor:	DIGIC 4+
Self-timer:	Y

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.