

Diaphragm Pumps 03

Introduction
Motor Driven
Air Driven
Accessories & Fittings
Sanitary



FLOJET

03 Diaphragm Pumps

INTRODUCTION


Diaphragm Pump Product Range

Operational “Box” for Flojet Diaphragm Pumps

(Options below are not available to all ranges)

PRESSURE	0-160 (0 - 11 bar)
OPEN FLOW	0.3-7 GPM (1.14 - 26.5 LPM)
ELASTOMERS	Santoprene, Viton, Buna, Geolast, EPDM, Silicone, Kalrez
BODY MATERIALS	Polypropylene, Celcon, Nylon
SWITCH RANGE	20-160 PSI (1.4 - 11 Bar) or no switch
BYPASS RANGE	15-150 PSI (1.0 - 10.4 Bar) or no bypass
POWER	Electric: 12-48VDC, 110VAC, 230VAC Gas: Air, CO ₂ or Nitrogen

The above defines the box for Flojet’s standard products. As Flojet is also a motor manufacturer we are capable of providing specific solutions to your pumping needs. If the above range is not suitable, please contact the factory to learn about our full range of Flojet Diaphragm Pumps.



GAS WARNING
No pump manufactured by Xylem should be used for gasoline or any fluid with a flash point below 100° F (38° C)

FEATURES AND BENEFITS

Expect only the best. With over 30 years of pump design and manufacturing experience, Flojet is committed to delivering the hardest working and longest lasting pumps. No matter the application, Flojet can provide a superior pump to match all your requirements.

SELF-PRIMING EVEN WHEN DRY

- Dry vertical lift from 2.5ft (0.75m) up to an outstanding 27.9ft (8.5m).

CAN RUN DRY WITHOUT DAMAGE

- Flojet diaphragm pumps can run dry for extended periods with no damage even when the liquid supply is exhausted
- Compatible with a wide range of chemicals
- Seal-less design (no shaft seal, so less leak issues)


COMPACT SIZE AND LIGHTWEIGHT

- Highest flow rates for their size
- Plug-in ports for easy installation and servicing
- Flojet pumps can be mounted easily anywhere with functional mounting platforms and simple connections - fit it anywhere and plumb up

EASY, LOW-COST AND CONVENIENT SERVICING

- Modular design
- Low cost, low maintenance design means a trouble free service life
- Spare parts and accessories are readily available and easy to install

THE PRINCIPLE BEHIND POSITIVE DISPLACEMENT DIAPHRAGM PUMPS



03 Diaphragm Pumps

MOTOR DRIVEN PUMPS



LF SERIES



FOR INTERNATIONAL & US MARKETS

This ultra compact pump uses the duplex diaphragm design to deliver flow and pressure comparable to much larger pumps.



SPECIFICATIONS - LF12 AND LF11 SERIES

PUMP DESIGN	Reciprocating Diaphragm
FLOW RATE	1.0 GPM (3.8 L/min) Nominal @ Open Flow
DUTY CYCLE	Intermittent

WETTED PARTS

HOUSING	Polypropylene
DIAPHRAGM	Santoprene*
CHECK VALVE	Viton® or EPDM
CHECK VALVE SPRING	316 Stainless Steel
MINIMUM TIP SIZE	#8 Tip, .072" (1.83 mm) Diameter
PORT TYPE	3/8" (9.5 mm) Hose Barb
OPERATING PRESSURE	40 psi (2.75 bar) max (no pressure switch version)
PRESSURE SWITCH SETTING	40 psi (2.75 bar) off / 25 psi (1.7 bar) on
SELF-PRIMING	Up to 2.5 ft (.76 m) Vertically
LIQUID TEMPERATURE	110° F (43° C) Maximum
MOTOR TYPE	Permanent Magnet Motor
MOTOR VOLTAGE	12 V DC, 24VDC, 115VAC
CURRENT	2.5 Amp Nominal @ 25 PSI (1.7 bar)

*INST. SHEET #81000-312



FEATURES

- Sealed pressure switch automatically starts and stops pump when discharge valve opens and closes
- Self-priming so pump can be located above supply tank
- Can run dry for extended periods of time without damage
- Built-in thermal protector
- Low amp draw for battery powered applications

OPTIONAL FEATURES

- Sealed motor with protective metal cooling finned cover
- Integral 5 amp in-line fuse with cover
- Manual on/off switch with protective cap to turn off pump when supply tank is empty

PERFORMANCE





MODELS

MODEL #S	CE	SWITCH PSI (BAR)	BYPASS PSI (BAR)	VOLTAGE	DIAPHRAGM	CHECK VALVE	OPEN FLOW GPM (LPM)	COMMENTS
LF112201	RLF112201	35 (2.5)	No	12V	Santoprene	Viton	1.0 (3.8)	Fins, Inline Connector, Inline Fuse, Rocker Switch
LF112421	RLF112421	40 (2.75)	Yes	12V	Santoprene	Viton	1.0 (3.8)	Fins, Inline Connector, Inline Fuse, Rocker Switch
LF121421	RLF121421	40 (2.75)	Yes	12V	Santoprene	Viton	0.7 (2.6)	
LF122002	RLF122002	No	No	12V	Santoprene	EPDM	1.0 (3.8)	
LF122005	No	No	No	12V	Geolast	Viton	1.0 (3.8)	
RLF122205	Yes	35 (2.5)	No	12V	Geolast	Viton	1.0 (3.8)	
LF122201	RLF122201	35 (2.5)	No	12V	Santoprene	Viton	1.0 (3.8)	
LF122202	RLF122202	35 (2.5)	No	12V	Santoprene	EPDM	1.0 (3.8)	
LF122421	RLF122421	40 (2.8)	Yes	12V	Santoprene	Viton	1.0 (3.8)	
LF172201	No	35 (2.5)	No	12V	Santoprene	Viton	1.0 (3.8)	Inline connector
LF182201	No	35 (2.5)	No	12V	Santoprene	Viton	1.0 (3.8)	Inline connector, Rocker Switch
LF221421	RLF221421	40 (2.75)	Yes	24V	Santoprene	Viton	0.7 (2.6)	
LF222005	No	No	No	24V	Geolast	Viton	1.0 (3.8)	
RLF222205	Yes	35 (2.5)	No	24V	Geolast	Viton	1.0 (3.8)	
LF222201	RLF222201	35 (2.5)	No	24V	Santoprene	Viton	1.0 (3.8)	
LF222202	RLF222202	35 (2.5)	No	24V	Santoprene	EPDM	1.0 (3.8)	
LF521401	No	40 (2.75)	No	115 VAC	Santoprene	Viton	0.7 (2.6)	
LF521402	No	40 (2.75)	No	115 VAC	Santoprene	EPDM	0.7 (2.6)	
RLFP222202	Yes	40 (2.75)	No	24V	Santoprene	EPDM3	1.0 (3.78)	Pressure switch = yes
RLFP222002	Yes	40 (2.75)	No	24V	Santoprene	EPDM3	1.0 (3.78)	Pressure switch = no
LFP521002	No	40 (2.75)	No	115VAC	Santoprene	EPDM3	0.7 (2.70)	
RLFP222201	Yes	40 (2.75)	No	24V	Santoprene	Viton	1.0 (3.78)	
LFP222201	No	40 (2.75)	No	12V	Santoprene	Viton	1.0 (3.78)	
LFP222202	No	40 (2.75)	No	12V	Santoprene	EPDM	1.0 (3.78)	

DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



03 Diaphragm Pumps

MOTOR DRIVEN PUMPS



DUPLEX II SERIES PUMPS



FOR INTERNATIONAL & US MARKETS

The Duplex II series of pumps incorporate the best technology and features developed by Flojet. Everything from the back flow preventer, check valves, bearings and diaphragm assembly to the motor, have been designed to make this truly the most advanced and reliable diaphragm pump available. Higher efficiency of the pump is evident in the longer life of the motor pump unit. The new diaphragm design combined with the new valves, makes the pump capable of pulling higher dry vacuum. Duplex II is available in various performance ranges, voltages and with a choice of elastomers, making it easily adaptable to a diverse range of applications.



FEATURES

- Self-priming up to 8 feet (2.4 m)
- Can run dry without damage
- Chemically resistant materials
- Internal bypass standard
- Built-in back flow preventer
- Heavy duty ball bearing drive system
- UL, CSA and CE models available

SPECIFICATIONS


PUMP	Positive Displacement two piston design
FLOW RATE	2.2 GPM (8.32 L/min) for high pressure models, 1.6 GPM (6.05 L/min) for medium and low pressure models
PRESSURES	Up to 100 PSI (6.89 bar)
PORTS	3/8" (9.52mm) NPT female
MOTOR	Permanent Magnet with solid state rectifier
VOLTAGES	12 & 24 V DC, 115 & 230 V AC
CYCLE	50/60 hertz for AC models
DRY VACUUM	Up to 8 feet (2.4 M)
PRESSURE SWITCH SETTING	15 (1.34), 30(2.07), 45(3.10), 60(4.14), 80, and 100 (6.8) PSI (bar)
WETTED PARTS	Polypropylene, Viton®, Buna or EPDM
NET WEIGHT	4 to 5 lbs. (2.28 kgs)
MAXIMUM OPERATING PRESSURE	100 PSI (6.8 bar)

Hi-Pressure INST. SHEET # 81000-339


Low-Pressure INST. SHEET # 81000-338

DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



PERFORMANCE



* See following pages for specification charts

03 Diaphragm Pumps

MOTOR DRIVEN PUMPS



DUPLEX II SERIES PUMPS

FOR INTERNATIONAL & US MARKETS

MODELS

MODEL #S	MODEL #S CE CERTIFIED	VOLTAGE	SWITCH PSI (BAR)	BYPASS PSI (BAR)	DIAPHRAGM	CHECK VALVE	OPEN FLOW GPM (LPM)	CURVE #	COMMENTS
D2121F5011	D2121F5011R	12V	60 (4.1)	Yes	Santoprene	Viton	1.2 (4.6)	1	
D2131F1311	D2131F1311R	12V (24V)**	No	50 (3.4)	Santoprene	Viton	1.6 (6.1)	4	
D2131F5011	Not Available*	12V (24V)**	60 (4.1)	Yes	Santoprene	Viton	1.6 (6.1)	3	
D2132F5011	D2132F5011R	12V	60 (4.1)	Yes	Santoprene	Viton	1.6 (6.1)	3	Heavy Duty Motor
D2132I5011	Not Available*	12V	60 (4.1)	Yes	BUNA	Viton	1.6 (6.1)	5	
D2135F7011	D2135F7011R	12V (24V)**	100 (6.9)	Yes	Santoprene	Viton	2.1 (8.0)	3	(NEEDS TO BE RELEASED)
D21X003	Not Available*	12V	No	60 (4.1)	Santoprene	Viton	1.6 (6.1)	6	Inline Fuse, Rocker Switch
D21X005	Not Available*	12V	60 (4.1)	Yes	Santoprene	Viton	2.0 (7.6)	3	Inline Connector, Rocker Switch
D21X007	Not Available*	12V	No	50 (3.4)	BUNA	Viton	1.6 (6.1)	3	Inline Connector, Discharge Left
D3131B1311	D3131B1311R	12V (24V)**	No	50 (3.4)	BUNA	BUNA	1.6 (6.1)	3	
D3131B5011	D3131B5011R	12V (24V)**	60 (4.1)	Yes	BUNA	BUNA	1.6 (6.1)	3	
D3131E1311	D3131E1311R	12V (24V)**	No	50 (3.4)	EPDM	EPDM	1.6 (6.1)	3	
D3131E5011	D3131E5011R	12V (24V)**	60 (4.1)	Yes	EPDM	EPDM	1.6 (6.1)	3	
D3131I1311	Not Available*	12V (24V)**	No	50 (3.4)	BUNA	Viton	1.6 (6.1)	3	
D3131V1311	D3131V1311R	12V (24V)**	No	50 (3.4)	Viton	Viton	1.6 (6.1)	3	
D3131V5011	D3131V5011R	12V (24V)**	60 (4.1)	Yes	Viton	Viton	1.6 (6.1)	3	
D3135B7011	D3135B7011R	12V (24V)**	100 (6.9)	Yes	BUNA	BUNA	2.0 (7.6)	5	
D3135E7011	D3135E7011R	12V (24V)**	100 (6.9)	Yes	EPDM	EPDM	2.0 (7.6)	5	
D71X000	D71X000R	12V	No	50 (3.4)	BUNA	BUNA	2.0 (7.6)	6	Heavy Duty Motor
D71X001	Not Available*	12V	No	50 (3.4)	BUNA	BUNA	2.0 (7.6)	6	Heavy Duty Motor, Discharge Left
D1335E7011	Not Available	36V	100 (6.9)	Yes	EPDM	EPDM	2.0 (7.6)	5	
D1625E7012	Not Available*	115VAC	100 (6.9)	Yes	EPDM	EPDM	1.4 (5.3)	5	Discharge Left
D1625F7011	Not Available	115VAC	100 (6.9)	Yes	Santoprene	Viton	1.4 (5.3)	5	
D1625H7011	Not Available*	115VAC	100 (6.9)	Yes	Santoprene	EPDM	1.4 (5.3)	5	
D1631F1311	Not Available*	115VAC	No	50 (3.4)	Santoprene	Viton	1.6 (6.1)	3	
D1631F5011	Not Available*	115VAC	60 (4.1)	Yes	Santoprene	Viton	1.6 (6.1)	3	
D1631H1311	D3631H1311R	115VAC	No	50 (3.4)	Santoprene	EPDM	1.6 (6.1)	3	
D1631H5011	D3631H5011R	115VAC	60 (4.1)	Yes	Santoprene	EPDM	1.6 (6.1)	3	
D1635E7011	D3635E7011R	115VAC	100 (6.9)	Yes	EPDM	EPDM	2.0 (7.6)	5	
D1635F7011	Not Available*	115VAC	100 (6.9)	Yes	Santoprene	Viton	2.0 (7.6)	5	(Need To Release) Obsolete "J" Models
D1635F7021	Not Available*	115VAC	100 (6.9)	Yes	Santoprene	Viton	2.0 (7.6)	5	3/8" (9.52mm) OD JG
D3631B1311	Not Available*	115VAC	No	50 (3.4)	BUNA	BUNA	1.6 (6.1)	3	
D3631B5011	Not Available*	115VAC	60 (4.1)	Yes	BUNA	BUNA	1.6 (6.1)	3	
D3631V1311	Not Available*	115VAC	No	50 (3.4)	Viton	Viton	1.6 (6.1)	3	
D3631V5011	Not Available*	115VAC	60 (4.1)	Yes	Viton	Viton	1.6 (6.1)	3	
D3635B7011	Not Available*	115VAC	100 (6.9)	Yes	BUNA	BUNA	2.0 (7.6)	5	
D3835B5011	Not Available*	115VAC	60 (4.1)	Yes	BUNA	BUNA	2.0 (7.6)	6	6' (1.83m)cord

MODELS (CONTINUED)

MODEL #S	MODEL #S CE CERTIFIED	VOLTAGE	SWITCH PSI (BAR)	BYPASS PSI (BAR)	DIAPHRAGM	CHECK VALVE	OPEN FLOW GPM (LPM)	CURVE #	COMMENTS
D3835B7011	Not Available*	115VAC	100 (6.9)	Yes	BUNA	BUNA	2.0 (7.6)	5	6' (1.83m) cord
D3835E7011	Not Available*	115VAC	100 (6.9)	Yes	EPDM	EPDM	2.0 (7.6)	5	6' (1.83m) cord
D3835H5011	Not Available*	115VAC	60 (4.1)	Yes	Santoprene	EPDM	2.0 (7.6)	6	6' (1.83m) cord
D3835V5011	Not Available*	115VAC	60 (4.1)	Yes	Viton	Viton	2.0 (7.6)	6	6' (1.83m) cord
D4822H4011	Not Available*	115VAC	45 (3.1)	Yes	Santoprene	EPDM	1.2 (4.6)	1	6' (1.83m) cord
D1735J7011RL	D1735J7011RL	230VAC	100 (6.9)	Yes	EPDM	Viton	2.0 (7.6)	5	In-line RFI Suppression
D3732B1311RL	D3732B1311RL	230VAC	No	50 (3.4)	BUNA	BUNA	1.6 (6.1)	3	In-line RFI Suppression
D3732B5011RL	D3732B5011RL	230VAC	60 (4.1)	Yes	BUNA	BUNA	1.6 (6.1)	3	In-line RFI Suppression
D3732H1311RL	D3732H1311RL	230VAC	No	50 (3.4)	Santoprene	EPDM	1.6 (6.1)	3	In-line RFI Suppression
D3732H5011RL	D3732H5011RL	230VAC	60 (4.1)	Yes	Santoprene	EPDM	1.6 (6.1)	3	In-line RFI Suppression
D3732V1311RL	D3732V1311RL	230VAC	No	50 (3.4)	Viton	Viton	1.6 (6.1)	3	In-line RFI Suppression
D3732V5011RL	D3732V5011RL	230VAC	60 (4.1)	Yes	Viton	Viton	1.6 (6.1)	3	In-line RFI Suppression
D3735B7011RL	D3735B7011RL	230VAC	100 (6.9)	Yes	BUNA	BUNA	2.0 (7.6)	5	In-line RFI Suppression
D3735H7011RL	D3735H7011RL	230VAC	100 (6.9)	Yes	Santoprene	EPDM	2.0 (7.6)	5	In-line RFI Suppression
D37X006AR	D37X006AR	230VAC	60 (4.1)	Yes	Santoprene	EPDM	1.4 (5.3)	4	Induction motor-continuously rated. Available from Europe only

* Consult your local Flojet representative
**Available in 24V. Consult your local Flojet representative for correct part number

03 Diaphragm Pumps

MOTOR DRIVEN PUMPS



TRIPLEX COMPACT RANGE



FOR INTERNATIONAL & US MARKETS

The Triplex Compact range pump was designed specifically for the Agricultural market. Flojet's new three chamber design and versatile features make it ideal for sprayers and many other transfer and dispensing applications.

This automatic demand pump is fitted with a sealed pressure switch and motor, is self-priming, can run dry, and can be installed in compact spaces.



FEATURES

- Compact automatic demand pump
- Sealed pressure switch and motor
- Self-priming; pump can be located above supply tank
- Can run dry for extended periods of time without damage
- Flow rates to 2.0 GPM (7.6 LPM) and operating pressure to 60 psi (4.1 bar)



APPLICATIONS

- Small Boom and Spot Spraying
- Foam Marking
- Silage Treatment
- Estate Spraying
- Livestock and Poultry Cooling
- Dispensing
- Transfer of liquids

SPECIFICATIONS

PUMP DESIGN	Motor Operated 3 Chamber diaphragm
MOTOR DESIGN	Permanent Magnet TENV (non-ventillated)
VOLTAGE	12 VDC
AMP DRAW	8 amp max for 12 VDC
PUMP HEAD	Reinforced Polypropylene
ELASTOMERS DIAPHRAGM	Santoprene™
CHECK VALVE	EPDM or Viton
MAX. FLOW RATE	2.0 GPM (7.6 LPM)
MAXIMUM PRESSURE	60 psi (4.1bar)
DUTY CYCLE	Intermittent
WEIGHT	3.4 lb (1.5 Kg)
CERTIFICATIONS	CE, NSF components
PORT SIZE INLET/OUTLET	3/8" (9.52mm) NPTF

PERFORMANCE





MODELS

MODEL #S	CE	VOLTAGE	SWITCH PSI (BAR)	BYPASS PSI (BAR)	DIAPHRAGM	CHECK VALVE	OPEN FLOW GPM (LPM)	PORTS	CURVE #	COMMENTS
03501132	R3501132	12V	60 (4.1)	Yes	Santoprene	Viton	1.4 (5.7)	3/8" (9.52mm) NPT	1	
03501136	R3501136	12V	60 (4.1)	Yes	Santoprene	Viton	2.0 (7.9)	3/8" (9.52mm) NPT	2	
03501142	R3501142	12V	60 (4.1)	Yes	Santoprene	EPDM	1.4 (5.7)	3/8" (9.52mm) NPT	1	
03501146	R3501146	12V	60 (4.1)	Yes	Santoprene	EPDM	2.0 (7.9)	3/8" (9.52mm) NPT	2	
03501503	R3501503	12V	60 (4.1)	Yes	Santoprene	Viton	2.0 (7.9)	3/8" (9.52mm) NPT	2	Rocker Switch, Inline Connector
03501505	R3501505	12V	60 (4.1)	Yes	Santoprene	Viton	1.4 (5.7)	3/8" (9.52mm) NPT	1	Inline Connector
03501506	R3501506	12V	60 (4.1)	Yes	Santoprene	Viton	2.0 (7.9)	3/8" (9.52mm) NPT	2	Inline Connector
03B01132	R3B01132	12V	No	50 (3.4)	Santoprene	Viton	1.4 (5.7)	3/8" (9.52mm) NPT	1	
03B01136	R3B01136	12V	No	50 (3.4)	Santoprene	Viton	2.0 (7.9)	3/8" (9.52mm) NPT	2	
03B01142	R3B01142	12V	No	50 (3.4)	Santoprene	EPDM	1.4 (5.7)	3/8" (9.52mm) NPT	1	
03B01146	R3B01146	12V	No	50 (3.4)	Santoprene	EPDM	2.0 (7.9)	3/8" (9.52mm) NPT	2	
03501332	R03501332	24V	60 (4.1)	Yes	Santoprene	Viton	1.4 (5.7)	3/8" (9.52mm) NPT	1	
03501336	R3501336	24V	60 (4.1)	Yes	Santoprene	Viton	2.0 (7.9)	3/8" (9.52mm) NPT	2	
03501342	R3501342	24V	60 (4.1)	Yes	Santoprene	EPDM	1.4 (5.7)	3/8" (9.52mm) NPT	1	
03501346	R3501346	24V	60 (4.1)	Yes	Santoprene	EPDM	2.0 (7.9)	3/8" (9.52mm) NPT	2	
03B01332	R3B01332	24V	No	50 (3.4)	Santoprene	Viton	1.4 (5.7)	3/8" (9.52mm) NPT	1	
03B01336	R3B01336	24V	No	50 (3.4)	Santoprene	Viton	2.0 (7.9)	3/8" (9.52mm) NPT	2	
03B01342	R3B01342	24V	No	50 (3.4)	Santoprene	EPDM	1.4 (5.7)	3/8" (9.52mm) NPT	1	
03B01346	R3B01346	24V	No	50 (3.4)	Santoprene	EPDM	2.0 (7.9)	3/8" (9.52mm) NPT	2	

DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



03 Diaphragm Pumps

MOTOR DRIVEN PUMPS



TRIPLEX HI-PRESSURE PUMPS



FOR INTERNATIONAL & US MARKETS

Flojet Triplex Hi-Pressure diaphragm pumps are capable of pressures up to 150 PSI (10.3 Bar), some of the highest pressures available in the diaphragm pump industry. This is ideal for applications such as spraying, misting, filtration, cooling, dispensing and pressure boosting.




FEATURES

- Constructed from a selection of materials suitable for Handling a broad range of chemicals.
- Sealed pressure switch and motor
- Self-priming up to 8 feet (2.4m); pump can be located above supply tank
- Can run dry for extended periods of time without damage
- Flow rates to 1.4 GPM (5.5 LPM) and operating pressure to 160 psi (11 bar)

APPLICATIONS

- Designed for wide range of applications
- Small Boom and Spot Spraying
- Silage Treatment
- Estate Spraying
- Livestock and Poultry Cooling
- Dispensing
- Transfer of liquids

PERFORMANCE



SPECIFICATIONS


PUMP DESIGN	Motor Operated 3 Chamber diaphragm
MOTOR DESIGN	Permanent Magnet DC and rectified (PMDC) AC
VOLTAGE	12, 24 VDC, 115, 230 VAC
CYCLES	50/60 Hz
AMP DRAW	9 amp max for 12 VDC, 0.95 amp max for 115 VAC
PUMP HEAD	Glass filled Nylon
ELASTOMERS DIAPHRAGM	Santoprene™
CHECK VALVE	EPDM or Viton
MAX. FLOW RATE	1.4 GPM (5.5LPM)
MAXIMUM PRESSURE	160 psi (101 bar) switch cutoff 140 psi (9.7 bar) max running pressure
MAX. LIQUID TEMP	40° F (4° C) Min, 140° F (60° C) Max
DUTY CYCLE	Intermittent
WEIGHT	7.6 lb (3.5 Kg)
CERTIFICATIONS	CE, NSF components
PORT SIZE INLET/OUTLET	3/8" (9.52mm) NPTF

MODELS

MODEL#S	CE	VOLTAGE	SWITCH PSI (BAR)	BYPASS PSI (BAR)	DIAPHRAGM	CHECK VALVE	OPEN FLOW GPM (LPM)	PORTS
03711133	R3711133	12V	100 (6.9)	Yes	Santoprene	Viton	1.4 (5.5)	3/8" (9.52mm) NPT
03711143	R3711143	12V	100 (6.9)	Yes	Santoprene	Viton	1.4 (5.5)	3/8" (9.52mm) NPT
03811133	R3811133	12V	150 (10.5)	No	Santoprene	Viton	1.4 (5.5)	3/8" (9.52mm) NPT
03811143	R3811143	12V	150 (10.5)	No	Santoprene	EPDM	1.4 (5.5)	3/8" (9.52mm) NPT
03711333	R3711333	24V	100 (6.9)	Yes	Santoprene	Viton	1.4 (5.5)	3/8" (9.52mm) NPT
03711343	R3711343	24V	100 (6.9)	Yes	Santoprene	EPDM	1.4 (5.5)	3/8" (9.52mm) NPT
03811333	R3811333	24V	150 (10.5)	No	Santoprene	Viton	1.4 (5.5)	3/8" (9.52mm) NPT
03811343	R3811343	24V	150 (10.5)	No	Santoprene	EPDM	1.4 (5.5)	3/8" (9.52mm) NPT
03711033	R3711033	110VAC	100 (6.9)	Yes	Santoprene	Viton	1.4 (5.5)	3/8" (9.52mm) NPT
03711043	R3711043	110VAC	100 (6.9)	Yes	Santoprene	EPDM	1.4 (5.5)	3/8" (9.52mm) NPT
03811033	R3811033	110VAC	150 (10.5)	No	Santoprene	Viton	1.4 (5.5)	3/8" (9.52mm) NPT
03811043	R3811043	110VAC	150 (10.5)	No	Santoprene	EPDM	1.4 (5.5)	3/8" (9.52mm) NPT
03711233	R3711233	230VAC	100 (6.9)	Yes	Santoprene	Viton	1.4 (5.5)	3/8" (9.52mm) NPT
03711243	R3711243	230VAC	100 (6.9)	Yes	Santoprene	EPDM	1.4 (5.5)	3/8" (9.52mm) NPT
03811233	R3811233	230VAC	150 (10.5)	No	Santoprene	Viton	1.4 (5.5)	3/8" (9.52mm) NPT
03811243	R3811243	230VAC	150 (10.5)	No	Santoprene	EPDM	1.4 (5.5)	3/8" (9.52mm) NPT

DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



03 Diaphragm Pumps

MOTOR DRIVEN PUMPS



TRIPLEX HI-FLOW RANGE



FOR INTERNATIONAL & US MARKETS

FLOJET Triplex High Flow Series pumps are designed for a wide range of applications and are constructed from a selection of materials suitable for handling a broad range of chemicals. The Triplex High Flow pumps are self-priming and can run dry without harm.





SPECIFICATIONS

PUMP DESIGN	3 chamber diaphragm
MOTOR DESIGN	Permanent magnet DC
VOLTAGES	12, 24 VDC
PUMP RATING	IP 54 (splash proof)
AMP DRAW	5 amps @ 10 psi for 12 VDC 3 amps @ 10 psi for 24 VDC 9 amps @ 40 psi for 12 VDC 6 amps @ 40 psi for 24 VDC
PUMP HEAD	Polypropylene
ELASTOMERS	
DIAPHRAGM	Santoprene™
CHECK VALVES	Viton, EPDM
MAX. FLOW RATE	4 GPM (15.1 LPM)
MAX. PRESSURE	60 psi (4.1 bar) switch cutoff 50 psi (3.4 bar) max running pressure
MAX. LIQUID TEMP	40° F (4° C) Min*, 140° F (60° C) Max*
DUTY CYCLE	Intermittent**
WEIGHT	5.05 lbs (2.29 kg) max.
WIRING OPTIONS	Standard 18 AWG leads
PORT SIZE INLET / OUTLET	¾" (19 mm), 3/8" (9.52 mm) NPTF

* Consult your local Flojet representative
** Available in 24V. Consult your local Flojet representative for correct part number
INST. SHEET #81000-417

PERFORMANCE





MODELS

MODEL #S	CE	VOLTAGE	SWITCH PSI (BAR)	BYPASS PSI (BAR)	DIAPHRAGM	CHECK VALVE	OPEN FLOW GPM (LPM)	MOTOR SIZE	FITTINGS
03521134	R3521134	12V	50 (3.4)	Yes	Santoprene	Viton	3.0 (11.3)	2.3" (59mm) Light Duty	½" (12.7mm) HB ST
03521139	R3521139	12V	60 (4.1)	Yes	Santoprene	Viton	4.0 (15.1)	3" (76.2mm)	½" (12.7mm) HB ST
03521144	R3521144	12V	50 (3.4)	Yes	Santoprene	EPDM	3.0 (11.3)	2.3" (59mm) Light Duty	½" (12.7mm) HB ST
03521149	R3521149	12V	60 (4.1)	Yes	Santoprene	EPDM	4.0 (15.1)	3" (76.2mm)	½" (12.7mm) HB ST
03521334	R3521334	24V	50 (3.4)	Yes	Santoprene	Viton	3.0 (11.3)	2.3" (59mm) Light Duty	½" (12.7mm) HB ST
03521339	R3521339	24V	60 (4.1)	Yes	Santoprene	Viton	4.0 (15.1)	3" (76.2mm)	½" (12.7mm) HB ST
03521344	R3521344	24V	50 (3.4)	Yes	Santoprene	EPDM	3.0 (11.3)	2.3" (59mm) Light Duty	½" (12.7mm) HB ST
03521349	R3521349	24V	60 (4.1)	Yes	Santoprene	EPDM	4.0 (15.1)	3" (76.2mm)	½" (12.7mm) HB ST

DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



03 Diaphragm Pumps

MOTOR DRIVEN PUMPS



QUAD 4000 SERIES




FOR INTERNATIONAL & US MARKETS


Flojet developed the quad pumps to deliver higher flows up to 5 GPM (18.92 LPM) using a four-piston design with excellent self-priming capability.



PERFORMANCE



*Continuous Duty Max Pressure For No Switch 3 Cam Models



*Continuous Duty Max Pressure For No Switch 3 Cam Models

FEATURES

- Built-in pressure switch automatically starts and stops pump instantaneously when discharge valve opens and closes
- Compact design and plug-in port fittings make installation easy
- Can run dry without damage and handle liquids up to 130° F (54° C)
- No metal contact with liquid being pumped
- Ball bearing drive throughout pump and motor assures longer pump life
- Excellent self-priming capability. Pump may be located above the liquid level
- Powerful, permanent magnet motor with low current draw and long life brushes


SPECIFICATIONS

FLOW RATE	3.5 to 5.0 GPM (13.2 and 18.9 LPM) Nominal
PUMP DESIGN	Diaphragm
MOTOR	TEFC/TENV Permanent Magnet Motor
VOLTAGE	12 & 24 Volt DC, 115 & 230 Volt AC
CYCLE	50/60 hertz for AC Models
CURRENT	1.5 amp max. (115 V)
PRESSURE SWITCH SETTING	45 PSI (3.2 bar) cut out
MAXIMUM OPERATING PRESSURE	40 PSI (2.8 bar)
SELF-PRIMING	Up to 8 ft. (2.4 m) Vertical Height
PORTS *	Plug-In Ports ½" (12.7mm) or ¾" (19mm) Hose Barb Standard
WETTED PARTS	Housing Modified Polypropylene - Standard, Elastomers Santoprene® and Buna - Standard
NET WEIGHT	4 lbs. (2 kg)

*Consult your local Flojet representative for other type of Port Fittings
4300 and I series: INST. SHEET # 81000-084
4100 series: INST. SHEET # 81000-176
AC VSD: INST. SHEET # 81000-388

DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



MODELS

MODEL #S	CE	VOLTAGE	SWITCH PSI (BAR)	DIAPHRAGM	CHECK VALVE	OPEN FLOW GPM (LPM)	FITTINGS	COMMENTS
04100113	No	12V	No	Geolast	BUNA	5.0 (19.0)	¾" (14.05 mm) HB ST	
04100143	R4100143	12V	No	Santoprene	EPDM	5.0 (19.0)	¾" (14.05 mm) HB ST	
04100505	No	12V	No	Santoprene	VITON	3.7 (14.0)	½" (12.7 mm) HB ST	
04300112	No	12V	45 (3.1)	Geolast	BUNA	3.7 (14.0)	½" (12.7 mm) HB ST	
04300142	R4300142	12V	45 (3.1)	Santoprene	EPDM	3.7 (14.0)	½" (12.7 mm) HB ST	
04300143	R4300143	12V	45 (3.1)	Santoprene	EPDM	5.0 (19.0)	¾" (14.05 mm) HB ST	
04300500	R4300500	12V	45 (3.1)	Santoprene	VITON	3.7 (14.0)	½" (12.7 mm) HB ST	
04300504	R4300504	12V	45 (3.1)	Santoprene	VITON	5.0 (19.0)	¾" (14.05 mm) HB ST	
04300506	R4300506	12V	45 (3.1)	Geolast	BUNA	5.0 (19.0)	¾" (14.05 mm) HB ST	
04300528	No	12V	45 (3.1)	Santoprene	VITON	3.8 (14.5)	½" (12.7 mm) HB ST & GH x ½" MNPT	Inline connector, Rocker Switch
04100343	R4100343	24V	No	Santoprene	EPDM	5.0 (19.0)	¾" (14.05 mm) HB ST	
04300342	R4300342	24V	45 (3.1)	Santoprene	EPDM	3.7 (14.0)	½" (12.7 mm) HB ST	
04300343	R4300343	24V	45 (3.1)	Santoprene	EPDM	5.0 (19.0)	¾" (14.05 mm) HB ST	
04100511	No	36V	No	Santoprene	VITON	5.0 (19.0)	¾" (14.05 mm) HB ST	
04100500	R4100500	115VAC	No	Santoprene	EPDM	3.7 (14.0)	½" (12.7 mm) HB ST	
04100502	No	115VAC	No	Santoprene	VITON	5.0 (19.0)	¾" (14.05 mm) HB ST	
04300042	No	115VAC	45 (3.1)	Santoprene	EPDM	3.7 (14.0)	½" (12.7 mm) HB ST	
04300043	No	115VAC	45 (3.1)	Santoprene	EPDM	5.0 (19.0)	¾" (14.05 mm) HB ST	
04300501	R4300501	115VAC	45 (3.1)	Santoprene	VITON	3.7 (14.0)	½" (12.7 mm) HB ST	
04300515	No	115VAC	45 (3.1)	Santoprene	VITON	5.0 (19.0)	¾" (14.05 mm) HB ST	
04300525	No	115VAC	45 (3.1)	Santoprene	VITON	5.0 (19.0)	¾" (14.05 mm) HB ST	6' (1.83m)cord
04300529	No	115VAC	40 (2.8)	Santoprene	VITON	3.0 (11.5)	½" (12.7 mm) HB ST	Cord / Continuous Duty/ Induction motor
04300531	No	115VAC	40 (2.8)	Santoprene	EPDM	3.0 (11.5)	½" (12.7 mm) HB ST	Cord / Continuous Duty/ Induction motor
I102010211	No	115VAC	No	Santoprene	VITON	5.0 (19.0)	¾" (14.05 mm) HB ST	6' (1.83m) cord
I103050211	No	115VAC	No	Santoprene	EPDM	5.0 (19.0)	¾" (14.05 mm) HB ST	6' (1.83m) cord
I301050110	No	115VAC	45 (3.1)	Santoprene	EPDM	3.7 (14.0)	½" (12.7 mm) HB ST	6' (1.83m) cord
I304010110	No	115VAC	45 (3.1)	Santoprene	VITON	3.7 (14.0)	½" (12.7 mm) HB ST	6' (1.83m) cord
R4300538	Yes (see left)	230VAC	35 (2.4)	Santoprene	EPDM	4.5 (17.0)	¾" (14.05 mm) HB ST + ½" HB ELB	Induction motor/ Continuous Duty
R4300539	Yes (see left)	230VAC	35 (2.4)	Santoprene	EPDM	3.5 (13.0)	¾" (14.05 mm) HB ST + ½" HB ELB	Induction motor/ Continuous Duty
R4320242	Yes (see left)	230VAC	35 (2.4)	Santoprene	EPDM	3.7 (14.0)	½" (12.7 mm) HB ST	
R4320243	Yes (see left)	230VAC	35 (2.4)	Santoprene	EPDM	5.0 (19.0)	¾" (14.05 mm) HB ST	
R4320252	Yes (see left)	230VAC	35 (2.4)	Santoprene	VITON	3.7 (14.0)	½" (12.7 mm) HB ST	
R4320253	Yes (see left)	230VAC	35 (2.4)	Santoprene	VITON	5.0 (19.0)	¾" (14.05 mm) HB ST	

03 Diaphragm Pumps

MOTOR DRIVEN PUMPS

PENTAFLEX SERIES



FOR INTERNATIONAL & US MARKETS


Flojet's Pentaflex delivers breakthrough performance for high flow and high pressure applications. These pumps are engineered and constructed of materials suited to handle a broad range of chemicals. The Pentaflex pump self-priming and can run dry for short periods of time. They are designed as duty cycle pump but can run continuously for short periods of time. Typical applications include tranfer, delivery, spraying, cooling, filtration, dispensing, and pressure boosting. EPDM valves with Santoprene diaphragms are available at this time. Additional materials are currently being tested.



SPECIFICATIONS

PUMP BODY	Glass Filled Nylon
PUMP DESIGN	5 Chamber Diaphragm
SUCTION LIFT	Self Priming to 8 ft. (2.5 m)
PORTS	(2) - 3/4" (19 mm) Hose Barb (2) - 3/4" (19 mm) Hose Barb 90° Elbow
MOTOR	Permanent Magnet

PERFORMANCE




MODELS

MODEL #S	CE	VOLTAGE	SWITCH PSI (BAR)	BYPASS PSI (BAR)	DIAPHRAGM	CHECK VALVE	OPEN FLOW GPM (LPM)	FITTINGS
R7300142A	Yes	12	80 (5.5)	Yes	Santoprene	EPDM	7.0 (26.5)	3/4" (19.05 mm) HB ST
R7300342A	Yes	24	80 (5.5)	Yes	Santoprene	EPDM	7.0 (26.5)	3/4" (19.05 mm) HB ST
R7300132A	Yes	12	80 (5.5)	Yes	Santoprene	Viton	7.0 (26.5)	3/4" (19.05 mm) HB ST
R7300332A	Yes	24	80 (5.5)	Yes	Santoprene	Viton	7.0 (26.5)	3/4" (19.05 mm) HB ST

DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



FLOJET

FLOJET

AIR DRIVEN PUMPS

N5100 SERIES



FOR INTERNATIONAL & US MARKETS

Flojet air operated diaphragm pumps offer excellent self-priming capability. Pumps can be located above the supply tank. Suction-side foot valve is recommended for best operation. Liquid pressure is regulated by supply air pressure. No bypass or pressure relief plumbing is necessary. Choice of Santoprene, Buna, or Viton elastomers provide a wide range of chemical compatibility. Quick disconnect liquid and gas port fittings provided for easy installation.



FEATURES

- Compact design with plug-in hose connections for quick installation
- Variety of elastomers to ensure chemical compatibility
- Variable capacity from zero to the maximum flow
- No pressure relief or bypass plumbing required
- Excellent self-priming. Pump may be located above the liquid level

SPECIFICATIONS


PUMP	Air-operated positive displacement double diaphragm pump
FLOW RATE	Up to 2.5 GPM (9.5 L/min)
PRESSURE	20 to 75 PSI (1.38 to 5.51 bar)
PORTS	Liquid 3/8" (114.3 mm) Air 1/4" (76.2mm)
WETTED PARTS	Buna, Santoprene®, Geolast® or Viton® for diaphragms and valves Acetal copolymer for housing
SELF-PRIMING	28 ft. (8.5 m) Dry, 32 ft. (9.8 m) Wet
GAS/AIR CONSUMPTION	Air Supply must be oil-free and dry, 40 PSI at 1 GPM - 0.45 C.F.M., 60 PSI at 1 GPM - 0.58 C.F.M., 80 PSI at 1 GPM - 0.77 C.F.M.

INST. SHEET #81000-363

MODELS


MODEL #S	CE	DIAPHRAGM	CHECK VALVE	LIQUID FITTINGS	AIR INLET & AIR OUTLET	MAX OPEN FLOW GPM (LPM)	COMMENTS
N5100010	Yes	BUNA	BUNA	3/8" HB ST	1/4" HB St	2.5 (9.5)	
N5100020	Yes	VITON	VITON	3/8" HB ST	1/4" HB St	2.5 (9.5)	
N5100040	Yes	SANTOPRENE	SANTOPRENE	3/8" HB ST	1/4" HB St	2.5 (9.5)	
N5100050	Yes	GEOLAST	GEOLAST	3/8" HB ST	1/4" HB St	2.5 (9.5)	
N5100500	Yes	SANTOPRENE	SANTOPRENE	3/8" HB ST	1/4" HB St	2.5 (9.5)	Teflon O-Ring

PERFORMANCE



DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



03 Diaphragm Pumps

AIR DRIVEN PUMPS



G57 SERIES



FOR INTERNATIONAL & US MARKETS

Innovative compact design features a patented shuttle valve that eliminates stalling and provides a long life. Chemically resistant Polypropylene body with a choice of Santoprene®, Viton® or Kalrez® elastomers. Quick disconnect liquid and gas port fittings for easy installation.




FEATURES

- Highest flow rate for any air pump of comparable size
- Stall proof design with patented shuttle valve
- Easy installation with all quick disconnect ports
- Robust design with durable integral mounting
- Sanitary design with inset molded diaphragm
- Leak resistant radial seals, no critical O-ring seals
- Quiet operation with large exhaust muffler

SPECIFICATIONS

PUMP	Air operated positive displacement double diaphragm pump
FLOW RATE	Up to 5 gpm (19 lpm)
PRESSURE	20 to 100 PSI (1.38 to 8.27 bar) (Same as inlet air pressure)
PORTS	Liquid 3/8" (114.3mm), 1/2" (152.4mm) and 3/4" (228.6mm) HB Liquid 3/8" (152.4mm) and 1/2" (152.4mm) MNPT Air Inlet 1/4" (76.2mm) HB
WETTED PARTS	
BODY	Polypropylene
DIAPHRAGM	Santoprene®, Viton® or Kalrez®
CHECK VALVES	Santoprene®, Viton®, or Viton Extreme
SPRINGS	Hasteloy C
NET WEIGHT	1.2 pounds (0.54 kg.)


PERFORMANCE



Santoprene and Viton: INST. SHEET # 82000-014
Kalrez: INST. SHEET # 81000-439
Kalrez® and Viton® Extreme are trademarks or registered trademarks of DuPont Performance Elastomers.

DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



MODELS

MODEL #5	DIAPHRAGM	CHECK VALVE	LIQUID FITTINGS IN. (MM)	AIR INLET	MAX OPEN FLOW GPM (LPM)	COMMENTS
G573000	Viton	Polypropylene	NONE	NONE	5.0 (19.0)	
G573205	Viton	Polypropylene	1/2-3/8" HB ST (10-13mm)	1/4" HB Brass	5.0 (19.0)	
G573215	Viton	Polypropylene	1/2" HB ST (12.7)	1/4" HB Brass	5.0 (19.0)	
G573225	Viton	Polypropylene	3/4" HB ST (19)	1/4" HB Brass	5.0 (19.0)	
G573145	Viton	Polypropylene	1/2" OD JG (12.7)	1/4" HB Brass	5.0 (19.0)	
G573185	Viton	Polypropylene	3/8" MNPT ST (9.5)	1/4" HB Brass	5.0 (19.0)	
G573175	Viton	Polypropylene	1/2" MNPT ST (12.7)	1/4" HB Brass	5.0 (19.0)	
G575005	Santoprene	Polypropylene	NONE	1/4" HB Brass	5.0 (19.0)	
G575205	Santoprene	Polypropylene	3/8" HB ST (10/13 mm)	1/4" HB Brass	5.0 (19.0)	
G575215	Santoprene	Polypropylene	1/2" HB ST (12.7)	1/4" HB Brass	5.0 (19.0)	
G575225	Santoprene	Polypropylene	3/4" HB ST (19)	1/4" HB Brass	5.0 (19.0)	
G575145	Santoprene	Polypropylene	1/2" OD JG (12.7)	1/4" HB Brass	5.0 (19.0)	
G575185	Santoprene	Polypropylene	3/8" MNPT ST (9.5)	1/4" HB Brass	5.0 (19.0)	
G575175	Santoprene	Polypropylene	1/2" MNPT ST (12.7)	1/4" HB Brass	5.0 (19.0)	
G57C002	Kalrez	Polypropylene	NONE	1/4" HB Brass	5.0 (19.0)	
G57C202	Kalrez	Polypropylene	1/2-3/8" HB ST (10-13mm)	1/4" HB Brass	5.0 (19.0)	
G57C203	Kalrez	Polypropylene	1/2-3/8" HB ST (10-13mm)	1/4" HB EL Brass	5.0 (19.0)	
G57C212	Kalrez	Polypropylene	1/2" HB ST (12.7)	1/4" HB Brass	5.0 (19.0)	
G57C213	Kalrez	Polypropylene	1/2" HB ST (12.7)	1/4" HB EL Brass	5.0 (19.0)	
G57C222	Kalrez	Polypropylene	3/4" HB ST (19)	1/4" HB Brass	5.0 (19.0)	
G57C223	Kalrez	Polypropylene	3/4" HB ST (19)	1/4" HB EL Brass	5.0 (19.0)	
G57C182	Kalrez	Polypropylene	3/8" MNPT ST (9.5)	1/4" HB Brass	5.0 (19.0)	
G57C172	Kalrez	Polypropylene	1/2" MNPT ST (12.7)	1/4" HB Brass	5.0 (19.0)	
G57C152	Kalrez	Polypropylene	3/8" OD JG (9.5)	1/4" HB Brass	5.0 (19.0)	
G57C412	Kalrez	Polypropylene	1/2" OD JG (12.7)	1/4" HB Brass	5.0 (19.0)	

03 Diaphragm Pumps

AIR DRIVEN PUMPS



G57 SERIES DUAL HIGH FLOW



FOR INTERNATIONAL & US MARKETS



FEATURES

- Flows to 10 GPM (38 L/min)
- Chemically resistant Polypropylene housings with Viton and Santoprene elastomers
- Easy installation with 1/2"± (12.7 mm) Dual and 3/4"± (19.1 mm) Quatro pump manifolds
- Duplex diaphragm design
- Patented shuttle valves eliminates stalling
- Compact size

SPECIFICATIONS


PUMP DESIGN	Positive Displacement Double Diaphragm
FLOW RATE (DUAL)	Up to 10.0 GPM (37.8 LPM)
OPERATING PRESSURE	20 to 100 PSI (1.4 to 6.0 bar)
LIQUID INLET PRESSURE	30 PSI (2.1 bar) Max.
LIQUID TEMPERATURE	Min. 40° F (4.4° C), Max. 140° F (60.0° C)
PRIMING	Dry 15ft (4.5 m), Wet 20ft (6.1 m)
AIR SUPPLY PRESSURE	20 to 100 PSI (1.4 to 6.9 bar)
NOISE	Max 90 dB

INST. SHEET #81000-354

MODELS


MODEL #S	CE	DIAPHRAGM	CHECK VALVE	LIQUID FITTINGS IN. (MM)	AIR INLET IN. (MM)	MAX OPEN FLOW GPM (LPM)	COMMENTS
G257301A	Yes	VITON	POLYPRO	1/2" NPTF (12.7)	1/4" HB ST (6.4)	10.0 (38.0)	
G257302A	Yes	VITON	POLYPRO	1/2" NPTF (12.7)	1/4" QD EL (6.4)	10.0 (38.0)	
G257501A	Yes	SANTOPRENE	POLYPRO	1/2" NPTF (12.7)	1/4" HB ST (6.4)	10.0 (38.0)	
G257502A	Yes	SANTOPRENE	POLYPRO	1/2" NPTF (12.7)	1/4" QD EL (6.4)	10.0 (38.0)	
G577000A	Yes	SANTOPRENE	POLYPRO	NONE	NONE	5.0 (19.0)	Santoprene reverse flow for dual G57
G578000A	Yes	VITON	POLYPRO	NONE	NONE	5.0 (19.0)	Viton reverse flow for dual G57

PERFORMANCE



DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



PERMANENT MAGNET MOTORS



FOR INTERNATIONAL & US MARKETS




FEATURES

- Highly efficient permanent magnet design
- Combines advantages of low amp draw heat rise with high torque and low speed
- Diamond-turned commutator
- Delivers up to 1/8 H.P. in compact 3" (76.2mm) diameter
- 6, 12, 24, 32, 36, 115, 230 and 240 volt AC or DC
- Lightweight double insulated armatures
- High starting torque - up to 600% of rated torque
- Speed control capability
- Available with internal solid state rectifier (AC models only)
- Instant reversibility (DC voltages)
- Thermo protection available
- Dynamic braking capability
- UL recognized (115 Volt AC models only)
- Partial or full suppression available with CE certification

SPECIFICATIONS


MOTOR DESIGN	Permanent Magnet
SIZE	3 in. (76.1 mm) Diameter
STACK LENGTH	1/2 in. - 2 in. (12.7 - 50.8 mm)
HORSEPOWER	Up to 1/40 - 1/8 H.P.
DUTY	Continuous or Intermittent
SPEED	1100-5000 R.P.M.
VOLTAGE	6-230 Volt DC or Rectified AC
INSULATION	Class B Standard
BEARINGS	Sleeve or Ball Bearing
ENCLOSURE	Totally Enclosed / Totally Enclosed Fan-Cooled

MOTOR SHAFT CONFIGURATION



DIMENSIONAL DRAWINGS

Unless otherwise stated dimensions in [] are in mm.



STACK LG. (APPROX) IN. (MM)	A IN. (MM)	MHP
0.5 (12.7)	2.87 (72.9)	20
0.875 (22.2)	3.25 (82.6)	50
1.25 (31.8)	3.7 (94)	75
1.875 (46)	4.4 (111.8)	100



WARNING
Explosion hazard. Motor can spark.
Do not use where flammable vapors are present.

03 Diaphragm Pumps

ACCESSORIES & FITTINGS





1720/1740/1745 SERIES INLET STRAINERS


FOR INTERNATIONAL & US MARKETS



3/8" NPT (9.5mm) Quad Port



Inlet Strainer
(Plugs into Quad pump port)



FEATURES

- Low profile design for space saving installation.
- Very strong reinforced plastic base with clear cover.
- Wide variety of port configurations from 3/4" (19.4=1mm) to 3/8" (9.5mm).

SPECIFICATIONS

MATERIALS	Base	Polypropylene, black
	Cover	Polysulfane, smoke tinted
	Screen	Stainless Steel, 20 and 40 mesh Polypropylene Screen, 20 mesh
	O-rings	Buna-N FDA Compound
TEMPERATURE	160°F (70°C) max.	
DIMENSIONS	2.75" (70 mm) diameter x 2.25" (57 mm) high 4.75" (121 mm) max. port to port (3/4" hose barb) Plug-in style, 3.75" (96 mm) max. length	

INST. SHEET #12345-000

MODELS

MODEL #	DESCRIPTION
01720-000	3/4" (19.0mm) x 3/4" (19.0mm) hose barb SS 20m
01720-002	1/2" (12.7mm) x 1/2" (12.7mm) hose barb SS 20m
01720-023	3/8" (9.5mm) hb x 3/8" (9.5mm) NPT (m) 90° SS 20m
01720-102	1/2" (12.7mm) x 1/2" (12.7mm) hose barb PP 20m
01720-103	3/8" (9.5mm) x 3/8" (9.5mm) hose barb PP 20m
01720-112	1/2" (12.7mm) x Quad port 90° PP 20m
01720-123	3/8" (9.5mm) hb x 3/8" (9.5mm) NPT (m) 90° PP 20m
01720-375	3/8" (9.5mm) NPT(f) x 3/8" (9.5mm) NPT(f) SS 20m
01740-000	3/4" (19.0mm) x 3/4" (19.0mm) hose barb SS 40m
01740-002	1/2" (12.7mm) x 1/2" (12.7mm) hose barb SS 40m
01740-003	3/8" (9.5mm) x 3/8" (9.5mm) hose barb SS 40m
01740-004	1/2" (12.7mm) x 1/2" (12.7mm) SS 40m
01740-010	3/4" (19.0mm) x Quad port 90° SS 40m
01740-012	1/2" (12.7mm) x Quad port 90° SS 40m
01740-014	1/2" (12.7mm) x Quad port 90° SS 40m
01740-375	3/8" (9.5mm) NPT(f) x 3/8" (9.5mm) NPT(f) SS 40m
017450-00S	Strainer In-line 3/4" (19.0mm) HB X 3/4" (19.0mm) HB SS 40M PETG VIT
017450-10S	Strainer In-line 3/4" (19.0mm) HB X QUAD PORT 90° 40M PETG VIT
017450-12S	Strainer In-Line 1/2" (12.7mm) HB X QUAD PORT 90° 40M PETG VIT
017450- 23S	Strainer In-Line 3/8" (9.5mm) HB X 3/8" (9.5mm) MNPT SS 40M PETG VIT

SS - Stainless Steel PP - Polypropylene m - Mesh




ELECTRIC PUMP FITTINGS

FOR INTERNATIONAL & US MARKETS


NYLON BARBED STRAIGHT/ELBOW

For use with all Duplex II Series Pumps (3/8" (9.5mm) NPT only).



PLASTIC (POLYPROPYLENE, EPDM)* INLETS & OUTLETS

For use with all Quad and G57 Series Pumps



MODELS

PART # STRAIGHT	PART # ELBOW	DESCRIPTION
91010-032	91010-033	3/8" (9.5mm) NPT Male x 1/4" (6.4mm) Barb
91010-004	91010-003	1/4" (6.4mm) NPT Male x 3/8" (9.5mm) Barb
91010-002	91010-001	3/8" (9.5mm) NPT Male x 3/8" (9.5mm) Barb
91010-034	91010-025	1/4" (6.4mm) NPT Male x 3/8" (12.7mm) Barb
91010-006	91010-005	3/8" (9.5mm) NPT Male x 1/2" (6.4mm) Barb
91010-053	91010-052	1/4" (6.4mm) NPT Male x 1/4" (6.4mm) Barb
91006-477A	N/A	Wire Harness 9' (2.74m) with fuse rocker switch and inline connector

MODELS


PART # STRAIGHT	PART # ELBOW	DESCRIPTION
20381-000	20381-008	Quad Port x 1/2"-14 Male Straight
20381-002	20381-009	Quad Port x 1/2" Hose Barb
20381-006	20381-010	Quad Port x 3/4" Hose Barb
20381-007	N/A	Quad Port x Garden Hose Adapter

*Other Elastomers Available **Packaged 2 per bag

GAS PUMP FITTINGS


STAINLESS STEEL INLETS & OUTLETS (LIQUID FITTINGS)

For use with all 5100 Series Pumps




BRASS CO2/AIR INLETS WITH SHUT-OFF VALVE (AIR FITTINGS)

For use with all 5100 and G Series Pumps



PLASTIC (CELCON) CO2/AIR INLETS

For use with all 5100 and G Series Pumps



MODELS

PART # STRAIGHT	PART # ELBOW	DESCRIPTION
20324-030	20607-100	1/4" (6.4mm) Hose Barb
20325-030	20608-100	3/8" (9.5mm) Hose Barb
20606-100	N/A	1/2" (12.7 mm) Hose Barb

MODELS

PART #S	DESCRIPTION
1510-000	1/4" (6.4mm) Hose Barb, Straight
1520-000	1/4" (6.4mm) Hose Barb, Tee
1521-000	1/4" (6.4mm) Hose Barb, Elbow

MODELS

PART #S	DESCRIPTION
20325-033	1/4" (6.4mm) Hose Barb, Straight

03 Diaphragm Pumps

SANITARY



PUREFLO® 21 SUPER HYGIENIC DIAPHRAGM PUMP



FOR INTERNATIONAL & US MARKETS

Jabsco's Pureflo 4-piston diaphragm pump is designed to be used in pharmaceutical, biotech, food or cosmetic applications. The design complies with the stringent requirements of these industries. The pump and controls are mounted in a stainless steel cabinet. The system can be cleaned easily and the simple construction allows safe and easy use.




FEATURES

- Bench top complete unit
- Fixed or variable speed AC unit
- Easy to clean, no shaft seals
- Can run dry
- Low noise, constant flow
- Compact and small
- Adjustable flow up to 365 gph (1,380 lph)
- Pressure up to 87psi (6.0 bar), in constant use 72 psi (5.0 bar) should not be exceeded
- Temperature up to 140° F (60° C) in constant use, CIP up to 194°F (90° C) and SIP 275° F (135° C) is possible
- Viscosity up to 250 Centipoise
- Unit supplied with 3.1B material certificates
- SIP Capabilities

SPECIFICATIONS

DRIVE	
MOTOR	24 V DC
MOTOR PROTECTION	IP 54
VARIABLE SPEED	0 - 3,000 rpm
TORQUE	0.42 Nm at 3,000 rpm
MOTOR POWER	132 Watt, 8.7 Amp
ELECTRICAL DETAILS	
POWER SUPPLY	Intelligent controls enable operation at most single phase supplies, 115-240 V AC, 50 or 60 Hz
CONTROLS VOLTAGE	24 V DC
PROGRAMMABLE CONTROLS	Touch Pad 1 - 100 % nof speed
MATERIALS / SURFACES	
Parts in contact with fluid are manufactured from FDA conforming materials only.	
Surface finish Ra < 0.8 µ standard (32 micro inch), 0.5 µ (20 micro inch) and electro polish is available on request.	
PARTS IN CONTACT WITH FLUID	
HEAD	Stainless Steel 316L
DIAPHRAGM	Santoprene
VALVES / O-RING	EPDM / Buna
VALVE CHAMBER & PISTONS	Polypropylene
PORTS	Tri-Clamp ¾" (19mm)

TECHNICAL AND CONSTRUCTION DETAILS



1. Low carbon 316L pump head for reduced carbide precipitation, increased corrosion resistance and minimal carbon pullout.
2. Chemical resistant Polypropylene valve chamber and piston guarantees long-life of the system.
3. Hygienic Santoprene® diaphragm conforms to FDA requirements.
4. Non-contact cam assembly ensures super hygienic standards are maintained.
5. Valves in EPDM for optimum chemical resistance capability.

MODEL	PUREFLO 21	
Port Size	(inch)	Tri-Clamp ¾
	(mm)	19
Max Flow (per min)	(GPM)	6
	(LPM)	23
Max Pressure	(psi)	87
	(bar)	6
Max Speed	(RPM)	3000
Size LxBxH	(inch)	15x15x11.75
	(mm)	380x385x300
Weight	(lbs)	43
	(kg)	19.5
Max Operating Temp	(°F)	+140 (CIP 194)
	(°C)	+60 (CIP 90)
Viscosity	(cP)	250

03 Diaphragm Pumps

ACCESSORIES & FITTINGS



VERSIJET™ SERIES

FOR INTERNATIONAL & US MARKETS



FEATURES

- Flow rates up to 6 GPM (22.7 LPM) and pressure of up to 70 PSI (4.8 Bar)
- Constructed from a selection of materials suitable for handling a broad range of chemicals
- Flojet's patented co-injected molded diaphragm and larger motor brushes, significantly extends pump life up to 50% longer than existing Flojet Quad Series diaphragm pumps
- Sealed motor and pressure switch provide years of dependable reliability
- Self priming up to 10 ft (3m) (wetted)
- IPX6 rated

SPECIFICATIONS

MATERIALS	Pump Head	Glass Filled Nylon
	Diaphragm	Santoprene
	Check Valve	Glass Filled Nylon, EPDM
TEMPERATURE	160°F (70°C) max.	
MOTOR DESIGN	Perm. magnet TENV (non-ventilated)	
VOLTAGE OPTIONS	12 VDC, 24VDC	
FLOW RATE (MAX)	6.0 GPM (22.7 LPM)	
PRESSURE (MAX)	70 PSI (4.8 Bar)	
DUTY CYCLE	Intermittent	
WEIGHT	7.6 lbs. (3.5kg)	
STANDARD PORT SIZE INLET/OUTLET	½" HB (4 GPM), ¾" HB (5 and 6 GPM)	
CERTIFICATIONS	CE, RoHs, IPX6	

4.0 GPM

PSI	GPM	AMPS
0	4.0	3.6
10	3.8	5.0
20	3.5	6.4
30	3.3	7.8
40	3.0	9.0
50	2.7	10.1
60	2.5	11.1
70	2.2	12.0

5.0 GPM

PSI	GPM	AMPS
0	5.0	5.5
10	4.7	7.9
20	4.4	9.5
30	4.1	10.9
40	3.8	12.1
50	3.4	13.1
60	3.1	14.0
70	2.8	14.7

6.0 GPM

PSI	GPM	AMPS
0	6.0	7.4
10	5.7	8.3
20	5.3	10.1
30	4.9	11.6
40	4.5	13.0
50	4.1	14.4
60	3.7	15.2
70	3.3	15.6

15.1 GPM


PSI	GPM	AMPS
0	15.1	3.6
10	14.2	5.0
20	13.3	6.5
30	12.3	7.8
40	11.3	9.0
50	10.3	10.1
60	9.3	11.1
70	8.3	12.0

18.9 GPM



PSI	GPM	AMPS
0	18.9	5.5
10	18.1	7.9
20	16.8	9.5
30	15.5	10.9
40	14.2	12.1
50	13.0	13.1
60	11.9	14.0
70	10.6	14.7

22.7 GPM

PSI	GPM	AMPS
0	22.7	7.4
10	21.4	8.3
20	20.0	10.1
30	18.5	11.6
40	17.0	13.0
50	15.5	14.4
60	14.0	15.2
70	12.5	15.6



ELECTRIC PUMP FITTINGS



NOTE:

4 GPM model overall length 9.91 in. (251.7 mm). All other dimensions are the same as the 5 GPM / 6 GPM models. Dimensions in inches [mm]

MODELS

PART NO.	VOLTS	GPM (LPM)	SWITCH PSI (BAR)	DIAPHRAGM	CHECK VALVE
R8400144	12	4.0 (15.1)	70 (4.8)	Santo	EPDM
R8400344	24	4.0 (15.1)	70 (4.8)	Santo	EPDM
R8500144	12	5.0 (18.9)	70 (4.8)	Santo	EPDM
R8500344	24	5.0 (18.9)	70 (4.8)	Santo	EPDM
R8600144	12	6.0 (22.7)	70 (4.8)	Santo	EPDM
R8600144	24	6.0 (22.7)	70 (4.8)	Santo	EPDM

Santoprene® is a registered trademark of Monsanto.