



PROJECTOR

Pro9800WUL

Key Features

- [Amazing Color Performance]
- Best in Class Color Accuracy
- Fine-tuned Viewing Experience
- Wide View
- [Professional Applications]



Product Description

Equipped with stacking and 360-degree projection, the Pro9800WUL offers versatile projection capabilities designed to fit professional and creative application requirements. Pro9800WUL's centered lens boasts 5,500 ANSI Lumens and WUXGA resolution, with multiple adjustment options for horizontal & vertical lens shift, 1.7x optical zoom, HV keystone, 4-corner, and 12V trigger, offering flexible and easy installation. To ensure its reliability, features such as an advanced sealed optical engine, wire-netting-covered lamp, and waveform air filter make it more durable and safeguard it against damage caused by regular usage. Powered by SuperColor™, it provides amazing colors and great contrast for images while utilizing auto power on, cell phone remote control (With vRemote app), and network management features for easy management. The Pro9800WUL is the ideal projector for commercial installations and large venues.

Visit Us ■ www.viewsonic.com

PRODUCT SPECIFICATION

Resolution:	1920x1200
Brightness (ANSI Lumens):	5500lm
Contrast (Max.):	10000:1
Lamp Hour (Normal / Eco):	1500hrs / 3500hrs
Throw Ratio in Meters (Wide ~ Tele):	1.25~2.13
Lens Shift:	Yes
Optical Zoom:	1.7x
Digital Zoom:	0.8x~2.0x
Screen Size:	30" - 300"
Projection Offset:	111.2%~122.4%
Display Colours:	1.07 Billion Colors (30 bits per color)
Keystone:	H: +/-25° , V: +/-30°
Noise min (Eco):	31 dB
Speaker:	7W x2
Throw Distance:	0.80m-13.76m (100" @2.7m)

INPUT CONNECTIVITY

HDMI/MHL:	1
HDMI In:	1
VGA-in:	2
Component Input:	2 (Share with VGA-in)
S-Video:	1
Composite Input:	1
Audio-in (3.5mm):	3
Audio-in (RCA pair):	1
USB Type A:	1 (Only charging)
Mini USB:	1 (Service)
Microphone in (3.5mm):	1
BNC:	1
Wire Remote in:	1
DVI-D:	1

OUTPUT CONNECTIVITY

VGA-out:	1
Audio-out (3.5mm):	1
Audio-out (RCA pair):	1
Wire Remote out:	1

CONTROL

RS232 (9 pin):	1
Network Management (LAN cable):	1
12V Power Trigger:	1
3D VESA:	1

DIMENSIONS AND POWER

Dimension (WxDxH):	445 mm(W) x 325.5 mm(D) x147.8 mm(H) 17.51" (W) x 12.81" (D) x 5.82" (H)
Net Weight:	8.29 kg (18.26 lb)
Power Source:	100~240Vac 50/60Hz
Power Consumption:	480W (Typ.)

SUPPLIED ACCESSORIES

Power cord:	1
VGA cable:	1
Remote Control (with batteries):	1
Quick Start Guide & CD:	1

LANGUAGES

On Screen Display:	English, Arabic, Dutch, Finnish, French, Italian, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Japanese
--------------------	---

REGULATIONS

Standard:	Mexico Energy FCC / CE / EMC CB / CCC ROHS / REACH / SVHC / WEEE / ErP Mexico NOM / UL / CUL / PSB / RCM
-----------	--