

BP72V15-2U

External Battery Pack for UPS Systems



Model #: BP72V15-2U

- ▶ Extends runtime of select compatible Tripp Lite UPS Systems with 72VDC black 3-point external battery connector
- ▶ Simple installation; 2U rackmount, tower and stack adaptable
- ▶ 2-year warranty

DESCRIPTION

BP72V15-2U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 2 rack spaces (2U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy gauge cabling with high current DC connector for simple installation.

COMPATIBLE UPS SYSTEMS - SU3000RTXR3U, SU3000RTXL3U, SUINT3000RTXL3U, SU3000RTXL3UHV and other Tripp Lite UPS systems that specify the use of this battery pack.

KEY BUYING POINTS

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 4 battery packs in tower configuration)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

OPTIONS & ACCESSORIES

- Tower stands: [2-9USTAND](#)
- 2-Post Mounting Kit: [2POSTRMKITWM](#)
- Extended warranties: 3 Year [WEXT3-BP72V](#), 5 Year [WEXT5-BP72V](#)

PACKAGE INCLUDES

- BP72V15-2U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

BATTERY

Expandable battery runtime:	No, a max quantity of ONE BP72V15-2U can be connected to the host UPS system. If additional battery packs are to be connected, use an expandable model, like BP72V21RT-3U
DC system voltage:	72VDC
Typical battery lifespan:	4-6 years typical (North America)
Connects to UPS via:	DC connector

PHYSICAL

Shipping weight (lbs):	89.35
Shipping weight (kg):	40.6
Unit weight (lbs):	78.1
Unit weight (kg):	35.5
Unit Dimensions (HWD/in):	3.5 x 17.5 x 20.75
Unit Dimensions (HWD/cm):	8.9 x 52.7 x 52.7
Shipping Dimensions (HWD/in):	9.5 x 30 x 23.75
Shipping Dimensions (HWD/cm):	24.1 x 7.62 x 60.3
Material of construction:	Steel
Form factors supported:	2u rackmount housing (supports tower installation with optional 2-9U STAND accessory)

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.