

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

In most applications, a signal booster (B120-000) should be used with this cable to ensure a signal strong enough for your display. An alternate solution is to use a Tripp Lite DVI over Cat5 Extender (B140-101X) in place of a 50 ft. DVI cable and signal booster. Note that Tripp Lite's DVI over Cat5 Extender products support DVI Single Link resolutions only.

50-ft. DVI Dual Link Digital TMDS Monitor Cable (DVI-D M/M)

MODEL NUMBER: P560-050





Highlights

- For use with Dual or Single Link TMDS specified equipment
- Compatible with Flat Panel Displays, Digital CRT Displays and Projectors
- Provides bandwidth for resolutions up to 2560 x 1600
- High Speed Digital Transmission to 9.9Gbps
- Superior molded cables with foil/braid shielding for maximum EMI/RFI protection

System Requirements

- DVI monitor
- CPU with DVI Dual Link
 capabilities

Package Includes

 50-ft. DVI Dual Link TMDS Cable (DVI-D M/M)

Description

Tripp Lite's 50-ft. DVI Dual Link TMDS cable delivers the high performance, high bandwidth needed for today's digital video displays. Gold plated contacts ensure excellent conductivity, while double shielding (foil and braid) provides maximum EMI/RFI protection. Use in conjunction with DVI video cards that are specified as Dual or Single Link. Both DVI connectors are molded, have integral strain relief for long life reliability, and ferrite collars to drain off extraneous electrical interference. In most applications, a signal booster (B120-000) will need to be used with this cable to ensure a signal strong enough for your display.

Features

- For use with Dual or Single Link TMDS specified equipment
- Compatible with Flat Panel Displays, Digital CRT Displays and Projectors
- Provides bandwidth for resolutions up to 2560 x 1600
- High Speed Digital Transmission to 9.9Gbps
- Superior molded cables with foil/braid shielding for maximum EMI/RFI protection
- In most applications, a signal booster (B120-000) will need to be used with this cable to ensure a signal strong enough for your display

Specifications

OVERVIEW		
Intended Application	Connecting Peripherals	
Cable Type	DVI	
Model Type	DVI	



INPUT		
Cable Length (ft.)	50	
Cable Length (m)	15.24	
UPC ASSIGNMENT		
Unit Carton UPC#	037332131058	
PHYSICAL		
Color	Black	
Style	DVI	
CONNECTIONS		
Connector A	DVI-D DUAL LINK (MALE)	
Connector B	DVI-D DUAL LINK (MALE)	
Number of Connectors	2	
CERTIFICATIONS		
Approvals	RoHS	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

Related Items

Optional Products

Model Number	Description	Qty.
B120-000	DVI Dual Link Signal Extender (DVI F/F)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at: http://www.tripplite.com/sku/P560-050.

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement.



Specifications are subject to change without notice. Photos may differ slightly from final products.