



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SR2POST

### 45U 2-Post SmartRack Open Frame Rack - Organize and Secure Network Rack Equipment



#### Highlights

- 45U 2-post open frame rack
- Black aluminum with round threaded and numbered mounting holes
- Toolless button holes to accept PDUs or cable managers

#### Description

SmartRack 2 post open frame racks are ideal for space constrained or cost conscious 19-inch rack mount applications. Multiple units can be bolted together side by side.

#### Package Includes

- SR2POST
- 28 pieces each of 12-24 screws and washers for equipment mounting
- Installation hardware
- Cable management hooks
- Warranty information
- Owner's Manual

#### Features

- Supports 800lbs of rackmount equipment
- Textured powder coat finish
- Heavy Duty Aluminum construction
- Numbered mounting positions
- Bolt down provisions
- Self squaring design
- Black finish
- Easy assembly

#### Specifications

| PHYSICAL   |       |
|--|-------|
| Installed whole system maximum rack depth (inches) | 4.8   |
| Installed whole system maximum rack depth (cm)     | 12.19 |

|  |  |
|--|--|
| <b>Rack Height</b>                         | 45U  |
| <b>Shipping Dimensions (HWD/in)</b>        | 7 x 3 x 85   |
| <b>Shipping Dimensions (HWD/cm)</b>        | 17.78 x 7.62 x 215.9                                 |
| <b>Shipping weight (lbs)</b>               | 29   |
| <b>Shipping weight (kg)</b>                | 13.15  |
| <b>Unit Dimensions (in.)</b>               | 84 x 20.3 x 4.75 (14" total depth with support base) |
| <b>Unit weight (lbs)</b>                   | 29   |
| <b>Unit weight (kg)</b>                    | 13.15  |
| <b>Unit Dimensions (cm)</b>                | 213.36 x 51.56 x 12.07                               |
| <b>Color</b>                               | Black  |
| <b>Style</b>                               | 2-Post   |
| <b>Weight Capacity - Stationary (lbs)</b>  | 800  |
| <b>Weight Capacity - Stationary (kg)</b>   | 362.9  |
| <b>CERTIFICATIONS</b>                      |  |
| <b>NOM (Mexico)</b>                        | Tested to NOM (Mexico)                               |
| <b>Approvals</b>                           | EIA-310-D, IEC 60297-3-100, DIN 41494, RoHS          |
| <b>WARRANTY</b>                            |  |
| <b>Product Warranty Period (Worldwide)</b> | 5-year limited warranty                              |

## Related Items

### Optional Products

| Related Model                  | Description   | Qty. |
|--------------------------------|---|------|
| <a href="#">B019-000</a>       | KVM Switch Accessories - 2-Post Rackmount Bracket for B020,B021, B040, and B070 Consoles and KVM Consoles | 1    |
| <a href="#">B020-U08-19-IP</a> | Console KVM Switch - 8-Port NetDirector 1U Rackmount Console IP KVM Switch w/17" LCD                      | 1    |
| <a href="#">B021-000-17</a>    | Rackmount Console - 1U Rackmount Console with 17" LCD   | 1    |
| <a href="#">B021-000-19</a>    | Rackmount Console - 1U Rackmount Console with 19" LCD   | 1    |
| <a href="#">B021-000-19-SH</a> | Rackmount Console - 1U Short-Depth Rackmount Console with 19" LCD   | 1    |
| <a href="#">B040-008-19</a>    | NetController 19" VGA Console KVM Switch - 8 Port   | 1    |
| <a href="#">B040-016-19</a>    | NetController 19" VGA Console KVM Switch - 16 Port  | 1    |
| <a href="#">N252-012</a>       | 12-Port Cat6 Patch Panel 568B   | 1    |
| <a href="#">N252-024</a>       | 24-Port Cat6 Patch Panel 568B   | 1    |
| <a href="#">N252-048</a>       | 48-Port Cat6 Patch Panel 568B   | 1    |

|                |   |   |
|----------------|---|---|
| SRBOLTDOWN     | Bolt-Down Kit (Secures included stabilizing brackets or optional stabilizing plates to facility floor.)                                     | 1 |
| SRCABLEDUCTVRT | 6-ft. (1.8 m) Vertical Cable Manager (Double finger duct with cover; toolless mounting.)  | 1 |
| SRCABLEDUCT1U  | 1U Horizontal Cable Manager (Finger duct with cover.)   | 1 |
| SRCABLELADDER  | 10-ft. x 1-ft. (3 m x 0.3 m) Cable Ladder (Includes 2 sections; requires SRCABLETRAY.)  | 1 |
| SRCABLERINGVRT | 6-ft. (1.8 m) Vertical Cable Manager (Flexible ring type; toolless mounting.)   | 1 |
| SRCABLERING1U  | 1U Horizontal Cable Manager (Flexible ring type.)   | 1 |
| SRCABLERING2U  | 2U Horizontal Cable Manager (Flexible ring type.)   | 1 |
| SRFAN3U        | 3U Fan Panel, 120V (3 high-performance fans; 210 CFM; 5-15P plug.)  | 1 |
| SRSCREWS       | Threaded hole hardware kit - 50 each #12-24 screws  | 1 |
| SRSHELF2P      | 2U Cantilever Fixed Shelf (60 lb / 27 kg capacity; 18-in. / 457 mm depth.)  | 1 |
| SRXFAN3U       | 3U Fan Panel, 230V (3 high-performance fans; 210 CFM; C14 inlet.)   | 1 |
| UPSHDEARKIT    | Heavy-Duty Mounting Ear Kit (Supports 2U cabinets up to 65 lb / 29 kg from front vertical rails in 4-post or 2-post racks and enclosures. ) | 1 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3208](http://www.tripplite.com/en/products/model.cfm?txtModelID=3208).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.