

- Allows connection of Wiegand output readers to NXT Controllers
- Mounts on and connects directly to NXT Controller
- Also mounts on and connects to NXT-4X4 and GIOX Input/Output Expansion Modules for applications where controllers are centrally located and access control access control functions are moved closer to the door

Keri's **NXT-WI Wiegand Interface Module** is designed to make it easy to connect reader technologies with industry standard Wiegand output to NXT Controllers. The **NXT-WI** securely plugs directly onto an NXT Controller or an NXT-4X4 or GIOX I/O Expansion Module with excellent mechanical and electrical integrity. The option to bring the reader terminations to the I/O modules provides substantial savings in wiring costs because door functions can be located closer to the reader/door, with only 4 wires required to be cabled to centrally located controllers.



# **NXT-W** Wiegand Interface Model

## DATA SHEET - Page 2 of 2

### **Specifications:**

# Size (when mounted on an NXT controller):

6.50 inches high by 5.50 inches wide by 2.50 inches deep, not including wiring connectors (16.51 cm by 13.97 cm by 6.35 cm)

### Weight:

1.28 oz (36.6 g)

#### Power Requirements (max):

10 to 14 VDC @ 100 mA (maximum current draw at 12 VDC)

#### Temperature/Humidity:


32'F to 140'F (0'C to 60'C) 0-90% Non Condensing

#### **Supported Reader Types:**

Wiegand (single and dual LED control)

Note: LED and beeper control may vary slightly between reader manufacturers.

\* Specifications are subject to change without notice.



#### **ORDERING INFORMATION:**

#### Model# **Description** Model# Description NXT-WI NXT-RM3 Wiegand Interface Mod-Reader Interface Module ule (Wiegand compat-(for Wiegand and MS ibility only) Compatibility) NXT-KPK Keypad Kit (includes NXT-6RK and NXT-RM-3) NXT-6RK **Keypad Prox Reader**

**RELATED PRODUCTS:** 

(requires NXT-RM3)



Presented By: