



- HS-1 SNUBBER IS PAINTED CARBON STEEL.
- HS-1 SNUBBER INCORPORATES A NEOPRENE SNUBBING PAD.

### HS-1 DIMENSIONAL DATA

MODEL	DIMENSION																ANCHOR BOLT DIA. (2 REQ'D)	
	A		B		C		D		E		F		G		H		in	mm
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm		
HS-1-2000	4.22	107	3.00	76	0.50	13	8.00	203	6.00	152	1.00	25	1.72	44	0.56	14	0.50	13
HS-1-4000	6.22	158	4.00	102	0.75	19	9.50	241	7.50	191	1.00	25	2.22	56	0.69	17	0.63	16
HS-1-6000	6.22	158	4.00	102	0.75	19	12.00	305	9.00	229	1.50	38	2.22	56	0.81	21	0.75	19

### HS-1 CAPACITY DATA

MODEL	CONCRETE ATTACHMENT*						STEEL ATTACHMENT			
	KAAB		KCCAB		KCAB		WELDED**		BOLTED***	
	lb	kg	lb	kg	lb	kg	lb	kg	lb	kg
HS-1-2000	1598	725	1956	887	1031	468	3094	1403	3094	1403
HS-1-4000	2792	1266	2893	1312	1858	843	6581	2985	6581	2985
HS-1-6000	3989	1809	4367	1981	2457	1114	8404	3812	8404	3812

\* 3000 PSI (211 kg/cm<sup>2</sup>) NORMAL WEIGHT CONCRETE.

\*\* USE MINIMUM E60XX WELD ELECTRODES.

\*\*\* USE ASTM A307 OR A325 BOLTS.

