

## ThinkSystem 5210 Entry 6Gb SATA QLC SSDs

### Product Guide

The 5210 Entry SATA solid-state drives (SSDs) are low-cost SSDs for ThinkSystem servers. The drives use Micron 64-layer 3D QLC NAND flash memory technology with a SATA 6Gbps interface and provide an affordable solution for large-capacity sequential read-intensive applications such as AI and machine learning data lakes, real-time analytics, big data, and media streaming.

The 5210 Entry SATA SSD is shown in the following figure.



Figure 1. Lenovo ThinkSystem 5210 Entry SATA SSD

### Did you know?

QLC (quad-level cell) represents the next generation of NAND flash memory technology. QLC means that 4 bits of data is stored in each memory cell which results in more cost-effective drives and larger drive capacities. The target workloads for QLC-based SSDs are sequential read-intensive workloads. For such workloads, QLC SSDs are an excellent cost-effective candidate for replacing 10K RPM HDDs.

## Part number information

The following table lists the ThinkSystem part numbers.

Table 1. ThinkSystem ordering information

Part number	Feature	Description
2.5-inch hot-swap drives		
4XB7A38144	B7EW	ThinkSystem 2.5" 5210 1.92TB Entry SATA 6Gb Hot Swap QLC SSD
4XB7A38145	B7EX	ThinkSystem 2.5" 5210 3.84TB Entry SATA 6Gb Hot Swap QLC SSD
4XB7A38146	B7EY	ThinkSystem 2.5" 5210 7.68TB Entry SATA 6Gb Hot Swap QLC SSD

## Features

The 5210 Entry SATA SSDs have the following features:

- Industry standard 2.5-inch form factor
- New generation 64-layer 3D QLC NAND flash memory
- Suitable for read-intensive sequential workloads with larger block sizes
- 6 Gbps SATA host interface
- High reliability and enhanced ruggedness
- Absence of moving parts to reduce potential failure points in the server
- S.M.A.R.T. support
- Advanced Encrypting Standard (AES) 256-bit encryption

## Endurance

SSDs have a huge but finite number of program/erase (P/E) cycles, which affect how long they can perform write operations and thus their life expectancy. Entry SSDs typically have a better cost per read IOPS ratio but lower endurance and performance compared to Mainstream or Performance SSDs. SSD write endurance is typically measured by the number of program/erase cycles that the drive can incur over its lifetime, which is listed as total bytes written (TBW) in the device specification.

The TBW value that is assigned to a solid-state device is the total bytes of written data that a drive can be guaranteed to complete. Reaching this limit does not cause the drive to immediately fail; the TBW simply denotes the maximum number of writes that can be guaranteed. A solid-state device does *not* fail upon reaching the specified TBW. However, at some point after surpassing the TBW value (and based on manufacturing variance margins), the drive reaches the end-of-life point, at which time the drive goes into read-only mode. Because of such behavior, careful planning must be done to use SSDs in the application environments to ensure that the TBW of the drive is not exceeded before the required life expectancy.

For example, the 1.92TB drive has an endurance of 700 TB of total bytes written (TBW) with 4KB random writes. This means that for full operation over five years, write workload must be limited to no more than 384 GB of 4K random writes per day, which is equivalent to 0.2 full drive writes per day (DWPD). For the device to last three years, the drive write workload must be limited to no more than 639 GB of writes per day, which is equivalent to 0.3 full drive writes per day.

The endurance of the 5210, like other NAND-based solid-state drives, varies depending on the workload. The value of the 5210 SSDs is best achieved when the drives are matched with read-intensive workloads with large-block sequential data access. For example, if all write operations are sequential and in 128KB blocks, the drives can support 0.8 total drive writes per day, which equates to 6,142 GB of data writes per day in the case of the 7.68TB drive option.

The key factors in determining drive endurance are the read/write mix, whether the writes are sequential or random, and the block size. The following tables (Part 1 and Part 2) show the different endurance values of the 5210 drives, based on the workload.

Table 2. Endurance by workload (part 1)

Capacity	GB Writes Per Day				Drive Writes Per Day (DWPD)			
	960GB	1.92TB	3.84TB	7.68TB	960GB	1.92TB	3.84TB	7.68TB
100% 128KB seq. writes	768 GB	1534 GB	3068 GB	6142 GB	0.8	0.8	0.8	0.8
90% 128KB seq. writes + 10% 4KB random writes	682 GB	1373 GB	2395 GB	4318 GB	0.71	0.72	0.62	0.56
80% 128KB seq. writes + 20% 4KB random writes	624 GB	1258 GB	2137 GB	3019 GB	0.65	0.66	0.56	0.39
70% 128KB seq. writes + 30% 4KB random writes	538 GB	1079 GB	1573 GB	2082 GB	0.56	0.56	0.41	0.27
50% 128 seq. writes + 50% 4KB random writes	413 GB	838 GB	964 GB	1192 GB	0.43	0.44	0.25	0.16
100% 16KB random writes	192 GB	384 GB	748 GB	1498 GB	0.2	0.2	0.2	0.2
100% 8KB random writes	192 GB	384 GB	690 GB	767 GB	0.2	0.2	0.18	0.1
100% 4KB random writes	192 GB	384 GB	345 GB	384 GB	0.2	0.2	0.09	0.05

Table 3. Endurance by workload (Part 2)

Capacity	Total Bytes Written (TBW)			
	960GB	1.92TB	3.84TB	7.68TB
100% 128KB seq. writes	1400 TB	2800 TB	5600 TB	11210 TB
90% 128KB seq. writes + 10% 4KB random writes	1240 TB	2505 TB	4370 TB	7880 TB
80% 128KB seq. writes + 20% 4KB random writes	1135 TB	2295 TB	3900 TB	5510 TB
70% 128KB seq. writes + 30% 4KB random writes	980 TB	1970 TB	2870 TB	3800 TB
50% 128 seq. writes + 50% 4KB random writes	750 TB	1530 TB	1760 TB	2175 TB
100% 16KB random writes	350 TB	700 TB	1366 TB	2733 TB
100% 8KB random writes	350 TB	700 TB	1260 TB	1400 TB
100% 4KB random writes	350 TB	700 TB	630 TB	700 TB

## Technical specifications

The following table lists the technical specifications for the 5210 Entry SATA SSDs.

Table 4. Technical specifications

Feature	960GB drive	1.92 TB drive	3.84 TB drive	7.68 TB drive
Interface	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA
Capacity	960 GB	1.92 TB	3.84 TB	7.68 TB
SED encryption	None	None	None	None
Endurance (drive writes per day)*	0.2 DWPD	0.2 DWPD	0.09 DWPD	0.05 DWPD
Endurance (total bytes written)*	350 TB	700 TB	630 TB	700 TB
Data reliability	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read
MTBF	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours
IOPS reads (4 KB blocks)	40,000	70,000	83,000	90,000
IOPS writes (4 KB blocks)	1,200	2,000	2,000	2,000
Sequential read rate (128 KB blocks)	540 MBps	540 MBps	540 MBps	540 MBps
Sequential write rate (128 KB blocks)	70 MBps	165 MBps	265 MBps	355 MBps
Read latency (seq)	310 µs	310 µs	500 µs	540 µs
Write latency (seq)	530 µs	530 µs	530 µs	530 µs
Shock, non-operating	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms
Vibration, non-operating	3.13 G <sub>RMS</sub> (5-800 Hz)	3.13 G <sub>RMS</sub> (5-800 Hz)	3.13 G <sub>RMS</sub> (5-800 Hz)	3.13 G <sub>RMS</sub> (5-800 Hz)
Typical power (R / W)	2.8 W / 3.9 W	2.8 W / 3.9 W	2.8 W / 6.3 W	2.8 W / 6.3 W

\* Based on 100% 4K random writes; Larger block sizes and sequential writes provide greater endurance, as listed in the table in the [Endurance](#) section

## Server support

The following tables list the ThinkSystem servers that are compatible.

Table 5. Server support (Part 1 of 4)

Part Number	Description	2S AMD V3				2S Intel V3		4S 8S Intel V3			Multi Node		GPU Rich		1S V3		
		SR635 V3 (7D9H / 7D9G)	SR655 V3 (7D9F / 7D9E)	SR645 V3 (7D9D / 7D9C)	SR665 V3 (7D9B / 7D9A)	ST650 V3 (7D7B / 7D7A)	SR630 V3 (7D72 / 7D73)	SR650 V3 (7D75 / 7D76)	SR850 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SD535 V3 (7DD8 / 7DD1)	SD530 V3 (7DDA / 7DD3)	SD550 V3 (7DD9 / 7DD2)	SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	ST250 V3 (7DCF / 7DCE)
4XB7A38144	ThinkSystem 2.5" 5210 1.92TB Entry SATA 6Gb Hot Swap QLC SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38145	ThinkSystem 2.5" 5210 3.84TB Entry SATA 6Gb Hot Swap QLC SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38146	ThinkSystem 2.5" 5210 7.68TB Entry SATA 6Gb Hot Swap QLC SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 6. Server support (Part 2 of 4)

Part Number	Description	Edge					Super Computing					1S Intel V2		2S Intel V2		
		SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)	SE455 V3 (7DBY)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-I V3 (7D7L)	SD650-N V3 (7D7N)	ST50 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)
4XB7A38144	ThinkSystem 2.5" 5210 1.92TB Entry SATA 6Gb Hot Swap QLC SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38145	ThinkSystem 2.5" 5210 3.84TB Entry SATA 6Gb Hot Swap QLC SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38146	ThinkSystem 2.5" 5210 7.68TB Entry SATA 6Gb Hot Swap QLC SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 7. Server support (Part 3 of 4)

Part Number	Description	AMD V1				Dense V2				4S V2	8S	4S V1		1S Intel V1					
		SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR655 Client OS	SR645 (7D2Y / 7D2X)	SR665 (7D2W / 7D2V)	SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN550 V2 (7Z69)	SR850 V2 (7D31 / 7D32)	SR860 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)	SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)
4XB7A38144	ThinkSystem 2.5" 5210 1.92TB Entry SATA 6Gb Hot Swap QLC SSD	Y	Y	Y	Y	Y	N	N	N	N	N	Y	Y	Y	Y	N	N	N	N
4XB7A38145	ThinkSystem 2.5" 5210 3.84TB Entry SATA 6Gb Hot Swap QLC SSD	Y	Y	Y	Y	Y	N	N	N	N	N	Y	Y	Y	Y	N	N	N	N
4XB7A38146	ThinkSystem 2.5" 5210 7.68TB Entry SATA 6Gb Hot Swap QLC SSD	Y	Y	Y	Y	Y	N	N	N	N	N	Y	Y	Y	Y	N	N	N	N

Table 8. Server support (Part 4 of 4)

Part Number	Description	2S Intel V1							Dense V1				
		ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
4XB7A38144	ThinkSystem 2.5" 5210 1.92TB Entry SATA 6Gb Hot Swap QLC SSD	Y	Y	Y	Y	Y	Y	Y	N	Y	N	N	Y
4XB7A38145	ThinkSystem 2.5" 5210 3.84TB Entry SATA 6Gb Hot Swap QLC SSD	Y	Y	Y	Y	Y	Y	Y	N	Y	N	N	Y
4XB7A38146	ThinkSystem 2.5" 5210 7.68TB Entry SATA 6Gb Hot Swap QLC SSD	Y	Y	Y	Y	Y	Y	Y	N	Y	N	N	Y

## Operating system support

SATA SSDs operate transparently to users, storage systems, applications, databases, and operating systems.

Operating system support is based on the controller used to connect to the drives. Consult the controller product guide for more information:

- RAID controllers: <https://lenovopress.com/servers/options/raid>
- SAS HBAs: <https://lenovopress.com/servers/options/hba>

## Warranty

The 5210 Entry SATA SSDs carry a one-year, customer-replaceable unit (CRU) limited warranty. When the SSDs are installed in a supported server, these drives assume the system's base warranty and any warranty upgrades.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.

## Physical specifications

The drives have the following physical specifications (approximate, without the tray):

- Height: 7 mm (0.3 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 70 g (2.5 oz)

## Operating environment

The SSDs are supported in the following environment:

- Operating temperature: 0 to 70°C (32 to 158°F)
- Non-operating temperature: -40 to 85°C (-40 to 185°F)
- Relative humidity: 5 to 95% (non-condensing)

## Agency approvals

The 5210 Entry SATA SSDs conform to the following regulations:

- Micron Green Standard
- Built with sulfur resistant resistors
- CE (Europe): EN 55032 Class B, RoHS
- FCC: CFR Title 47, Part 15 Class B
- UL: UL-60950-1, 2nd Edition
- BSMI (Taiwan): approval to CNS 13438
- RCM (Australia, New Zealand): AS/NZS CISPR32 Class B
- KCC RRL (Korea): approval to KN 32 Class B, KN 35 Class B
- W.E.E.E.: Compliance with EU WEEE directive 2002/96/EC.
- TUV (Germany): approval to IEC60950/EN60950
- VCCI (Japan): 2015-04 Class B
- IC (Canada): CISPR32 Class B: Canadian ICES-003:2016

## Related publications and links

For more information, see the following documents:

- Technical Solution Brief: Accelerate SQL Analytics Workloads by 10X  
<https://en.resources.lenovo.com/whitepapers/accelerate-sql-analytics-workloads-by-10x>
- Technical Solution Brief: Accelerate NoSQL Databases by up to 9X  
<https://en.resources.lenovo.com/whitepapers/accelerate-nosql-databases-by-up-to-9x>
- Technical Solution Brief: Accelerate Oracle Database 12c Enterprise by 3.8X  
<https://en.resources.lenovo.com/whitepapers/accelerate-oracle-database-12c-enterprise-by-3-8x>
- Technical Solution Brief: Rapid Business-Critical, Encrypted Record Storage and Retrieval  
<https://en.resources.lenovo.com/whitepapers/rapid-business-critical-encrypted-record-storage-and-retrieval>
- Lenovo ThinkSystem storage options product web page  
<https://lenovopress.com/lp0761-storage-options-for-thinksystem-servers>
- ServerProven support  
<http://www.lenovo.com/us/en/serverproven>
- Lenovo RAID Introduction  
<https://lenovopress.com/lp0578-lenovo-raid-introduction>
- Lenovo RAID Management Tools and Resources  
<https://lenovopress.com/lp0579-lenovo-raid-management-tools-and-resources>

## Related product families

Product families related to this document are the following:

- [Drives](#)



## Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.  
8001 Development Drive  
Morrisville, NC 27560  
U.S.A.  
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, LP1223, was created or updated on April 16, 2024.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:  
<https://lenovopress.lenovo.com/LP1223>
- Send your comments in an e-mail to:  
[comments@lenovopress.com](mailto:comments@lenovopress.com)

This document is available online at <https://lenovopress.lenovo.com/LP1223>.

## Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

ThinkSystem®

The following terms are trademarks of other companies:

Intel® is a trademark of Intel Corporation or its subsidiaries.

Other company, product, or service names may be trademarks or service marks of others.