

Product: **DG/S 2.64.1.1 DALI-Gateway Basic, 2f, MDRC**

Type: **DG/S 2.64.1.1**

Current application program: **DALI Basic 2f / 1.1
(ECU Firmware 0.0.13)**

Software-Information

to: **DALI Basic 2f / 1.1
(ECU Firmware 0.0.13)**

from: 12/2018

Changed: Optimized behavior with dimming times greater than 153 sec.
Optimized Force Operation (individual parametrization)
Optimized Function Turn On "previous value"
Optimized behavior of ETS Download

Update KNX Application: Via ETS App „Update Copy Convert“ an existing parametrization can be adopted. *)

Update ECU Firmware: The firmware can be updated with ETS App „KNX Bus Update“. *)

*Online-Update automatically or with
xECU12_SAMD20G18_M07B0_V12_0_0_13_16049_202_fwupd-File.*

*) see Technical Bulletin

Software-Information

to: **DALI Basic 2f / 1.0
(ECU Firmware 009)**

from: 7/2017

KNX application not changed

Changed: Optimizing start up DALI Gateway, with new ECU Firmware

Update via ETS-App: ABB- or BJE KNX Bus Update

*Online-Update automatically or with xECU12_SAMD20G18_M07B0_fwupd-File
from (1/2018) Version V12_0_0_9_7868_122 will support 6197/46.*

ABB i-bus® KNX

Software Information

Software-Information

zu: **DALI Basic 2f / 1.0**
(ECU Firmware 008)

from:

5/2017

Application program at start time of market launch
