FUJITSU

Data Sheet FUJITSU Display P2410 WE CAM

Widescreen 61.13 cm (24.1 inch) superior display The heart of smart workplaces and video conferencing

The FUJITSU Display P2410 WE CAM is an IPS-based widescreen display that combines smart workplace concepts with advanced ergonomics. It comes with a multi-functional USB Type-C hub that makes it ideal for modern and shared workspaces.

Multifunctional USB Type-C means:

- 95W power delivery for external devices

- Transmission of video signals, webcam, data, LAN & audio

It contains a Fujitsu patented solution that generates an All-In-One user experience with Mini PC ESPRIMO G and LIFEBOOK series.

The factory pre-calibrated display provides high color fidelity for single as multimonitor usage.

KVM function reduces USB hardware needs by using one display for a number of devices.

For an easy log-in and professional video conferencing, the P2410 TS CAM comes with a Microsoft Windows HELLO compatible, bright Full HD Webcam with mechanical lever lock. The directional microphone hides disturbing sounds.

Fujitsu innovated the display housing by offering the worldwide first right-hand USB hub that ensures an optimal cable course and is ergonomically perfect for most users.

Retina protection by low blue light panel that culls damaging blue light without any loss or changes of color.

The integrated Autobrightness sensor adapts the brightness of the display to an optimum, saves energy and increases constant productivity due to reduced eye strain.

DisplayView[™] software enables you to configure your monitor easily for remote management and administrative tasks. Prolonged product lifecycle through feasible firmware updates done by the user.

Focusing on environmental friendliness, the packaging is styrofoam free and solely consisting of cardboard, which is more than 90% recycled.





Technical details

Special features

MS Hello compatible WebCam, In-Plane Switching (IPS) technology, Color accuracy average DeltaE<2, DICOM Greyscale Standard Display Function compatible gamma preset, Eco button for Eco mode and 4-colored status LED, Presence sensor with PC security solution, Auto Brightness Control (ABC), Auto Pivot, Workplace Lighting Guide, DisplayView[™] Software, 6-in-1 Stand, Cable guide, Always available USB (in operating and standby mode), 24/7 usage, Integrated speakers, Smart Power ON and LED function for AiO-type usage (in combination with a dedicated FUJITSU systems e.g. ESPRIMO G or selected LIFEBOOK models), Low blue light mode

Ergonomic stand	FUILTSU systems e.g. ESPRIMU G of selected LIFEBOOK models), Low blue light mode
	6-in-1 Stand
Stand	
Height adjust range	150 mm
Picture height over desk (min)	40 mm
Rotation to portrait	90° clockwise and counterclockwise, Auto Pivot sensor
Tilt angle	-5° / +35°
Swivel angle	345°
Picture performance	
Panel and backlit	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	3H hard coating, Anti-glare
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in Video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors (Hi-FRC)
High color gamut - typical	73% NTSC / 99% sRGB color space
Brightness - typical	300 cd/m ²
Size and resolution	
Aspect ratio	16:10
Diagonal Size	61.13 cm (24.1-inch)
Resolution (native)	1,920 x 1,200 pixel
Resolution (interpolated)	1,920 x 1,080 pixel, 1,680 x 1,050 pixel, 1,600 x 1,200 pixel, 1,400 x 900 pixel, 1,280 x 800 pixel, 1,280 x 768 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	518.4 x 324 mm
Pixel Pitch	0.27 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	48 - 76 Hz
Connectivity	
DisplayPort	1 x DisplayPort Out (Daisy Chain), 1 x DisplayPort 1.2
HDMI	1 x HDMI 1.4
Audio signal output	3.5 mm stereo phone jack for head phone
Audio sound output	2 x 2 W
USB downstream	4x USB 3.2 Superspeed 5GBit (1x Type C and 1x Type A on side, 2x Type A on bottom)
USB upstream	1 x USB Type C with alternate mode for video data and power delivery up to 95W 1 x USB 3.2 Gen1 Type B Integrated KVM switch function
Ethernet (RJ-45)	1 x Gigabit LAN PXE, Wake on LAN (from S3), MAC Address Pass Through support with selected LIFEBOOK models
Ease-of-use menu	
Notes	6 tactile keys on front side
Direct Access Keys	Menu, ECO, Input, Mode, Audio, Brightness
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto Brightness, ACR, Lighting Guide

	Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m USB cable 1m (USB-C to USB-C) Quickstart flyer Safety notes
Display delivered accessories	DisplayPort data cable 1.8 m
Package content	
Color	Marble grey
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Miscellaneous	is a second condensing,
Operating relative humidity	10 - 85 % (non condensing)
Operating ambient temperature	10.05 lbs 5 - 35 ℃ (41 - 95 °F)
Weight (Monitor only)	4.56 kg 10.05 lbs
Weight (Monitor only)	4.48 lbs 4.56 kg
Weight (unpacked)	6.57 kg 14.48 lbs
Woight (uppacked)	20.95 inch x 8.37 x 15.07 inch
Dimension with stand $(W \times D \times H)$	532.2 x 212.7 x 382.73 mm
Dimonsion with stand (Mur.D.:	20.95 x 2.33 x 14.52 inch
Dimension without stand (W x D x H)	532.2 x 59.21 x 368.9 mm
Dimensions / Weight / Environmental	522 2 v 50 21 v 268 0 mm
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
USA/Canada	FCC Class B, cTUVus
Singapore	S-Mark
Russia	EAC
Germany	TÜV GS
Australia/New Zealand	(on customer request)
Europe	EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Global	ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 8, EPEAT® Silver (dedicated regions)
Model	P2410W
Compliance	
Protection class	1
Rated frequency range	50 Hz - 60 Hz
Rated voltage range	100 V - 240 V
Electrical values	
Power notes	Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0 Power save mode according to EEI test conditions
Power supply	integrated
Operating maximum brightness	28 W
Total Energy Consumption (ETEC)	53.98 kWh/year
Operating with EPA settings	16.65 W
Power save mode	0.28 W
Soft switch off	0.26 W
Power consumption (typical)	
Advanced settings	Presence Sensor, Proximity Adjust, Daisy Chain, Overdrive, DDC/CI, Factory Recall
Information	Model name, Serial number, Signal input, Resolution/mode, Display mode , Color Temperature, ACR Status, ABC Status
Audio	Mute, Volume, Input for HDMI and DP interface
Image adjust	Expansion, Saturation, Sharpness
Mode Color OSD	D-Mode, sRGB, Low Blue Light, Office, Photo, Video, Custom 5000K, 6500K, 7500K, Native, RGB Adjust Language, OSD-Timeout, OSD rotation

Display delivered accessories notes	Power cable with IEC-60320-C13, 3-pin connector on display side
	Data cables and USB cable detachable on display
	User manual and DisplayView Software is available via download
	DisplayView Software is necessary for AutoPivot function and Presence Sensor PC security solution
Packaging information	
Packaging dimension (mm)	162 x 734 x 450 mm
Packaging dimension (inch)	6.38 x 28.9 x 17.72 inch
Weight (packed)	9.36 kg
Weight (packed) (lbs)	20.64 lbs
Order information	
Order Code	S26361-K1698-V145
EAN Code	4065221160243
Country specific order code	BDL:K1698V145-UK - with UK power cable, mandatory for Arabian countries
	BDL:K1698V145-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed
	BDL:K1698V145-CHN - with China power cable and CEL, mandatory for China
Accessories information	Further helpful options:
	Stands and Mounting kits:
	http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html
	Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf
Warranty	
Warranty period	3 years (depending on country)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Spare Parts availability	7 years after end of product life
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to FUJITSU Display P2410 WE CAM, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about FUJITSU Display P2410 WE CAM, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/products/ computing/peripheral/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/ emeia/resources/navigation/terms-of-use. html

Copyright 2021 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2021-11-23 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html Copyright 2021 Fujitsu Technology Solutions GmbH