



Product availability: Stock - Normally stocked in distribution facility



### Main

Range	Spacial
Category	Lifting accessory
Product or component type	Lifting eye
Application	Multi-purpose
Mounting location	Enclosure top
Mounting support	Directly in the axis of the uprights
Range compatibility	Spacial SFHD Spacial SF Prisma PH Spacial SFM
Device composition	4 eyebolt
Quantity per set	Set of 1

### Complementary

Material	Cast steel
Surface finish	Galvanized
Fixing mode	Screwed
Permanent permissible load	2998.29 lb(US) (1360 kg) slinging at 60°
Height	62.5 mm
Width	2.17 in (55 mm)
Depth	24 mm
Diameter	29 mm
ISO thread	M12

### Ordering and shipping details

Category	80036 - ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	00785901929086
Nbr. of units in pkg.	1
Package weight(Lbs)	0.8100000000000005
Returnability	Y
Country of origin	ES

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------