



Overview

Lead time	Usually in Stock
-----------	------------------



General

Provided equipment	Mounting Hardware Rack Mounting brackets Serial configuration cable
--------------------	---

Physical

Cable length	8 ft (2.44 m)
Color	Black
Maximum Depth	9.29 in (23.6 cm)
Maximum Height	1.73 in (4.4 cm)
Net Weight	9.28 lb(US) (4.21 kg)
Maximum Width	17.01 in (43.2 cm)

Input

Input Frequency	50/60 Hz
Plug standard	IEC 60309 16 A 2P+E
Max line current	16 A
Input current limits	16 A
Load Capacity	3840 VA
Nominal Input Voltage	230 V

Output

Maximum Total Current Draw per Phase	16 A
Number of power socket outlets	1 IEC 60309 16 A 2P+E
Cord Length	3 ft (0.91 m)
Output voltage	230 V

Conformance

Product certifications	CE EMC Directive 2004/108/EC Low Voltage Directive 2006/95/EC
Standards	EN/IEC 60950-1 UL 60950-1

Environmental

Ambient air temperature for operation	23...113 °F (-5...45 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	00731304333418
Package weight(Lbs)	13.12 lb(US) (5.95 kg)

Packing Units

Package 1 Height	4.49 in (11.4 cm)
Package 1 width	23.62 in (60 cm)
Package 1 Length	13.74 in (34.9 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Halogen content performance	Halogen free product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------