



Overview

Presentation	Bypass cabinet with integrated 480/208 input transformer
Lead time	Usually Ships within 2 Weeks

General

Provided equipment	Installation guide
--------------------	--------------------

Physical

Maximum Depth	32.99 in (83.8 cm)
Maximum Height	58.50 in (148.6 cm)
Net Weight	729.53 lb(US) (330.91 kg)
Maximum Width	14.02 in (35.6 cm)

Input

Input Frequency	60 Hz
Nominal Input Voltage	3 phase

Output

Output voltage	208 V
----------------	-------

Conformance

Product certifications	CSA
Standards	CSA C22.2 No. 107.1 UL 1778

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	32...113 °F (0...45 °C)
Storage altitude	0...30000 ft (0.00...9144.00 m)

Ordering and shipping details

GTIN	00731304275022
Package weight(Lbs)	804.69 lb(US) (365 kg)

Packing Units

Package 1 Height	65.50 in (166.37 cm)
Package 1 width	28.50 in (72.39 cm)
Package 1 Length	43.50 in (110.49 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------