

AR3300SP

NetShelter SX 42U 600mm Wide x 1200mm
Deep Enclosure with Sides Black -2000 lbs.
Shock Packaging



Overview

Presentation	NetShelter SX cabinet and packaging system designed to safely integrate, transport, unload and deploy up to 2000 lbs (907 kg) of IT equipment. The cabinet is paired with a shock absorbing pallet, unloading ramp, and impact resistant shell. The system has been engineered, tested and approved for secure shipment of fully converged systems such as being certified with Cisco® for pre-racking and shipping Cisco Unified Computing System (UCS).
Lead time	Usually in Stock

General

Provided equipment	Baying hardware Documentation CD Key(S) Leveling feet Mounting Hardware Pre-installed casters Side Panels User Manual
--------------------	--

Physical

Maximum Mounting Depth	41.26 in (104.8 cm)
Number of rack unit	42U
Minimum Mounting Depth	7.52 in (19.1 cm)
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Color	Black
Maximum Depth	47.24 in (120 cm)
Rack Width	19"
Maximum Height	78.39 in (199.1 cm)
Net Weight	295.62 lb(US) (134.09 kg)
Permanent permissible load	2250 Lb(US) (1020.58 kg) dynamic 3750 lb(US) (1700.97 kg) static
Maximum Width	23.62 in (60 cm)

Conformance

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Ordering and shipping details

GTIN	00731304309918
Package weight(Lbs)	543.00 lb(US) (246.3 kg)

Packing Units

Package 1 Height	85.79 in (217.9 cm)
Package 1 width	43.50 in (110.5 cm)
Package 1 Length	52.01 in (132.1 cm)
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------