



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	Installation guide
--------------------	--------------------

### Physical

Color	Black
Maximum Depth	29.41 in (74.7 cm)
Maximum Height	83.86 in (213 cm)
Maximum Mounting Depth	29.13 in (73.99 cm)
Minimum Mounting Depth	29.13 in (73.99 cm)
Net Weight	92.20 lb(US) (41.82 kg)
Number of rack unit	44U
Rack Width	19"
Permanent permissible load	2000 lb(US) (907.18 kg) static
Maximum Width	23.62 in (60 cm)

### Conformance

Standards	EIA-310E
-----------	----------

### Ordering and shipping details



GTIN	00731304260264
Package weight(Lbs)	102.21 lb(US) (46.36 kg)

### Packing Units

Package 1 Height	82.01 in (208.3 cm)
Package 1 width	10.00 in (25.4 cm)
Package 1 Length	7.40 in (18.8 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

## Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------