



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Installation guide
--------------------	--------------------

Physical

Color	Black
Maximum Depth	2.56 in (6.5 cm)
Maximum Height	4.13 in (10.5 cm)
Net Weight	6.61 lb(US) (3 kg)
Maximum Width	5.94 in (15.1 cm)

Input

Nominal Input Voltage	DC
-----------------------	----

Environmental

Ambient air temperature for operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Battery type	Lead-Acid battery
RBC Quantity	1

Ordering and shipping details

Package weight(Lbs)	7.72 lb(US) (3.5 kg)
---------------------	----------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Package 1 Height	3.50 in (8.9 cm)
Package 1 width	6.89 in (17.5 cm)
Package 1 Length	8.39 in (21.3 cm)
SCC14	10731304346866
Number of Units in Package 3	240

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------