



### Overview

Lead time	Usually in Stock
-----------	------------------



### General

Provided equipment	Mounting Hardware Rack Mounting brackets Serial configuration cable
--------------------	---

### Physical

Color	Black
Maximum Depth	9.29 in (23.6 cm)
Maximum Height	1.73 in (4.4 cm)
Net Weight	8.66 lb(US) (3.93 kg)
Maximum Width	17.01 in (43.2 cm)

### Input

Input Frequency	50/60 Hz
Plug standard	IEC 60320 C14
Max line current	10 A
Input current limits	10 A
Load Capacity	2000 VA
Nominal Input Voltage	230 V

### Output

Maximum Total Current Draw per Phase	10 A
Number of power socket outlets	12 IEC 60320 C13
Protection type	Without circuit breaker
Output voltage	230 V

### Conformance

Standards	EN 55022 Class A FCC Part 15 class A
-----------	---

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environmental

Ambient air temperature for operation	23...113 °F (-5...45 °C)
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Ordering and shipping details

GTIN	00731304333401
Package weight(Lbs)	12.57 lb(US) (5.7 kg)

## Packing Units

Package 1 Height	4.49 in (11.4 cm)
Package 1 width	23.62 in (60 cm)
Package 1 Length	13.74 in (34.9 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------