



Overview

Lead time	Usually in Stock
-----------	------------------



General

Provided equipment	Cord retention bracket(s) Horizontal mounting brackets User Manual Installation guide
--------------------	--

Physical

Cable length	12 ft (3.66 m)
Color	Black
Depth	4.25 in (10.8 cm)
Height	1.73 in (4.4 cm)
Net Weight	5.00 lb(US) (2.27 kg)
Maximum Width	17.52 in (44.5 cm)

Input

Line Rated Current	12 A
Permissible voltage	100...120 V
Input current limits	15 A
Load Capacity	1440 VA
Input Frequency	50/60 Hz
Plug standard	NEMA 5-15P
Nominal Input Voltage	100 V 120 V

Output

Number of power socket outlets	8 NEMA 5-15R
--------------------------------	--------------

Conformance

Product certifications	CUL Listed UL Listed
Standards	FCC Part 15 class A ICES-003

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

Ambient air temperature for operation	32...113 °F (0...45 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	00731304331568
Package weight(Lbs)	7.61 lb(US) (3.45 kg)

Packing Units

Package 1 Height	2.76 in (7 cm)
Package 1 width	18.50 in (47 cm)
Package 1 Length	13.50 in (34.3 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------