



## Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--

## General

Provided Equipment	Installation guide Operations and maintenance manual
Air Discharge Patterns	Horizontal
Intake Air	Rear Return
Air flow	3200 ft <sup>3</sup> /min (1510.23 l/s)
Minimum Water Inlet Temperature	45 °F (7 °C)
Condensate Pump Capacity	1.3 Gal/hr(US) (0.00 m3/h)

## Physical

Number of rack unit	42U
Color	Black
Depth	43.11 in (109.5 cm)
Height	78.39 in (199.1 cm)
Product Weight	405.65 lb(US) (184 kg)
Width	11.81 in (30 cm)

## Input

Number of cables	2
Number of Power Feeds	2
Input power	800 W
Input Frequency	50/60 Hz
Plug standard	IEC 60309 16 A 2P+E NEMA L5-20P
Nominal Input Voltage	100...120 V 200...240 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Conformance

Product Certifications	C-tick CE GOST MEA VDE
Standards	EN 55022 Class A EN 55024 EN 60950 IEC 60950 IEC 61000-3-2 IEC 61000-3-3

## Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity


## Ordering and shipping details

GTIN	00731304301387
Package weight(Lbs)	423.29 lb(US) (192 kg)

## Packing Units

Package 1 Height	83.39 in (211.8 cm)
Package 1 width	29.37 in (74.6 cm)
Package 1 Length	44.76 in (113.7 cm)
Number of Units in Package 3	1

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>

## Contractual warranty

Warranty	1 year (parts only)
----------	---------------------