



### Overview

Lead time	Usually in Stock
-----------	------------------



### General

Provided Equipment	Installation guide Mounting Hardware
--------------------	---

### Physical

Depth	9.06 in (23 cm)
Height	2.76 in (7 cm)
Product Weight	3.81 lb(US) (1.73 kg)
Width	18.50 in (47 cm)

### Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...3333 ft
Ambient Air Temperature for Storage	-58...104 °F (-50...40 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

### Ordering and shipping details

GTIN	00731304254386
Package weight(Lbs)	4.21 lb(US) (1.91 kg)

### Packing Units

Package 1 Height	7.99 in (20.3 cm)
Package 1 width	19.02 in (48.3 cm)
Package 1 Length	10.98 in (27.9 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
Mercury free	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	Take-back program available