



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	Installation guide
--------------------	--------------------

### Physical

Depth	4.57 in (11.6 cm)
Height	1.26 in (3.2 cm)
Product Weight	0.77 lb(US) (0.35 kg)
Width	2.05 in (5.2 cm)

### Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Nominal Input Voltage	100 V 110 V 115 V 120 V 127 V 200 V 208 V 220 V 230 V 240 V
Plug standard	IEC 60320 C14

### Conformance

Product Certifications	C-tick CCC PSE CUL Listed
Standards	EN 55022 Class B EN 55024 EN 61000-3-2 EN 61000-3-3 EN 61000-4-8 EN/IEC 60950-1 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-6

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

GTIN	00731304336051
Package weight(Lbs)	1.32 lb(US) (0.6 kg)

## Packing Units

Package 1 Height	3.94 in (10 cm)
Package 1 width	7.09 in (18 cm)
Package 1 Length	5.12 in (13 cm)

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>

## Contractual warranty

Warranty	2 year (manufacturer's defect)
----------	--------------------------------