# **Beng** InstaShow<sup>™</sup> WDCI0

## Plug and Play. One Button to Start Wireless Full HD Presentations

BenQ's InstaShow<sup>TM</sup> is the wireless presentation solution that lets you share ideas immediately from nearly any device. Allowing up to 16 users to share simultaneously, InstaShow<sup>TM</sup> can boost meeting engagement and enhance collaboration.



#### - No Software Setup or Maintenance

InstaShow<sup>™</sup> doesn't need any software installation or execution.There's no setup, configuration, or waiting for pop-ups to launch. Just plug into your PC or Mac and start presenting immediately.

#### - Smooth Video and Audio Quality

With HDMI 1.4a video output standard and 16 bit, 48Hz audio quality, Instashow™ supports up to full HD 1080p video and stereo sound without cable clutter or complicated driver selection.

#### True Plug & Play

Simply connect InstaShow<sup>™</sup> into your device then push the button to start presenting immediately without hassle, without time waste. Up to 16 presenters can take part by using the InstaShow<sup>™</sup> Button Kit.

## вenq

#### Latest Wifi Technology

The latest 802.1 Lac WiFi guarantees extremely smooth wireless streaming without lag or buffering.

### **Strong Security**

The security encryption and authentication protocols make this product safe, allowing to share confidential information without any concern for security breaches.

## **Specifications**

Color	Black	
Support Platform	Windows, Mac, Chrome. Any OS supports HDMI standard 1.4	
Video Outputs	HDMI 1.4, comply with HDCP	
Frame Rate	Up to 60 fps depending on environment	
Output Resolution	Video Timing: 1280 x 720 (720p), 1920 x 1080 (1080p) PC Timing: 800 x 600, 1024 x 768 (XGA), 1280 x 768, (WXGA),	
	1280 × 1024, 1280 × 960, 1360 × 768, 1440 × 900, 1400 × 1050, 1680 × 1050, 1920×1080 (1080p)	
Input Resolution	Up to 1920 × 1080	
Simultaneous Connections	I6 pcs	
Audio	Stereo, Radio quality 16 bits 48 KHz	
Wireless	IEEE 802.1 l ac, 5GHz, 2T2R	
Data Rate Wireless	Up to 867Mbps	
Authentication Protocol	WPA2 (WPA2-PSK (Pre-Shared key) / WPA2-Enterprise	
Security (encryption)	AES 128 bit	
Reach	Max. 8m between InstaShow Button and InstaShow Host	
Temperature Range	Operating: 0°C to +40°C (+32°F to + 104°F)	
	Storage: -I0°C to +60°C (+I4°F to +I40°F)	
Humidity	Storage 5% to 90% relative humidity, non-condensing	
	Operation: 10% to 80% relative humidity, non-condensing	

## InstaShow Package

InstaShow Button	x 2
InstaShow Host	x I
Cradle	x l
USB Power Cable	× I (I50 cm, USB Type A 3.0, micro USB)
HDMI Cable	x   (80 cm)
USB Extended Cable	x   (15 cm), x   (80 cm)
Antenna	× 2 (Black)
Installation Kit	Adapter x 1, Velcro Strap (black) x 1,
	Quick Start Guide × I, Safety Statement × I,
	Double-side Sponge Tap $\times$ 1, Rubber Feet $\times$ 4,
	Screws x 4

## InstaShow Host

Power Supply	DC 5V±10%, 1.5A
Pairing Key	x I
Power Consumption	Normal: 5W
	Network Standby: 2W
	HDMI Standby: 0.02W
LAN	x   ( 0/ 00 Mbps)
Video Output	x I HDMI I.4 (video and audio)
LED	*Red (boosting), Green (ready for connection),
	Blue (presenting)
Dimension ( $W \times H \times D$ )	110 × 110 × 27 mm (99 mm with antenna)
(not include rubber feet)	
DC Power Jack	x I (micro USB)
Weight (with antenna)	150 g

## InstaShow Button

Cable	USB Type A, HDMI Cable
Power Supply	DC 5V±10%, 0.9A
Reset Button	хI
Power Consumption	Normal: 4.5W
Mode Key	x I
Dimension (W $x$ H $x$ D)	84.5 x 189.55 x 19.9 mm
LED	*Red (boosting), Green (wifi connected),
	Blue (presenting)
Weight	100 g

## InstaShow Cradle

**Dimension (W x H x D)** 85 × 97.5 × 170.4 mm Weight

## Optional: InstaShow Button Kit

630 g

InstaShow Button	x 2
Cradle	x l
Quick Start Guide	x I
Safety Statement	x l
USB Extended Cable	x   ( 5 cm), x   (80 cm)



\* Please find detail LED behavior in the user manual \*\* Wireless connection speed is depended on wireless environment. \*\*\* Optional InstaShow Button Kit accommodates up to sixteen users in your meeting room. Please contact local dealers for more information or visit http://www.benq.com/product/projector/INSTASHOW-WDC10/

#### BenQ Europe B.V.

Meerenakkerweg I-17 5652 AR Eindhoven The Netherlands Tel: +31 88 8889200



#### business-display.benq.com/en-gb