HP DesignJet T930 36-in Printer



914-mm (36-inch), 6-ink printer for professional-quality CAD and GIS applications



QUALITY—Your projects, presented at their best

- Six Original HP inks produce a wide color gamut ideal for color graphics.
- Original HP gray and photo black inks achieve precise line accuracy, dark blacks, and true neutral grays
- Make your architectural prints shine with professional, high-resolution graphics—opt for Adobe PostScript®
- Communicate with precision—produce plans, drawings, and maps with fine line quality, and up to 2400 dpi.

EFFICIENCY—Productive printing for demanding teams

- Stay organized and on task—the integrated 50page output stacking tray delivers flat, collated
- At this print speed, you can get right back to work—see A1/D-size prints delivered in 21
- Print efficiently—parallel file processing with 64 GB virtual memory (based on 1.5 GB RAM).
- Print from your mobile device/USB drive with HP Mobile Printing¹; add features with HP AiO Printer Remote²

SECURITY—Easily, confidently manage your printer

- Print without interruption—91.4-m (300-ft) media roll and Original HP ink cartridges up to
- Safeguard information with security protocols like IPSec, 802.1x, SNMPv3, PIN printing, and other options.3
- Easily configure and manage your printer from the comfort of your desk with HP Embedded Web Server.
- Integrates easily with your other office devices— iOS and Android^{TM4} compatibility with HP Mobile Printing.

For more information, please visit http://www.hp.com/go/designjett930

¹ Local printing requires mobile device and printer to be on the same network (usually Wi-Fi access points bridge wireless to wired connections). Wireless performance is dependent on physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP web-connected printer. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See http://www.hp.com/go/designjetmobility for more details.

The HP All-in-One Printer Remote mobile app is available for Apple® iPad, iPhone, and iPod Touch running iOS v7.0 or later and for Android™ mobile devices running Android™ v4.4 or later. The HP All-in-One Printer

Remote mobile app is available for free from the Apple® App Store for Apple® mobile devices and from the Google Play Store for Android™ mobile devices

3 Optional security solutions include Secure Disk Erase (available for all models) and Encrypted HD (available only in specific models).

⁴ The HP Print Service Plugin app is available for Android™ mobile devices running Android™ v.4.4 or later. The app is free from Google Play

Technical specifications

Pint resolution Up to 2400 x 1200 optimised dpi Technology HP Thermal Inkight Rechandogy BP Rechandogy HP Re	Print	
Margins Sheet 3 x 3 x 3 x 3 mm 0	Print resolution	Up to 2400 x 1200 optimised dpi
Sheet: 3 x 22 x 3 x 3 mm 0 Ink types Dye-based (C, G, M, PK, V); pigment-based (mk) Ink catrridges 5 (syan, gray, magenta, matte black; photo black; yellow) Ink drop 6 pt (C, M, Y, G, pk); 9 pt (mk) Printheads 1 (syan, gray, magenta, matte black; photo black; yellow) Line accuracy 20.1942 Minimum line width 0.02 mm (HP-GL/2 addressable) Guaranteed minimum line 0.07 mm (950/EC 13660:2001 (E)) ³ with up to 50 A1/D-size capacity), media bin, automatic cutter Sheet size 210 x 279 to 914 x 1219 mm Roll size 210 x 279 to 914 x 1219 mm Roll size 210 to 914-mm wide sheets; 279 to 914-mm rolls Grammage 60 to 328 g/m² Applications Line drawings; Renderings; Presentations; Maps; Orthophotos Memory 64 GB (file processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing features Mobile printing features Mobile printing via Apple Air-Print**, HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems: Android, IOS Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm Shipping 150 to 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box 47 dB(A) (operating); 58 B(A) (idle); < 16 dB(A) (sleep) Power Consumption 120 watts (printing); 13 watts (5 watts with embedded Digital Front End (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (UV) and EN 60550-1 compliant); Russia (GOST); Singapore (PSB); China (CCC), Argentina (RAM), Mexico (INCE); Korea (KATS) Electromognetic Environmental Energy STAR*, WEEE; EU RoNS; REACH; EUP; EPEAT Bronze Environmental Energy STAR*, WEEE; EU RoNS; REACH; EUP; EPEAT Bronze	Technology	HP Thermal Inkjet
Ink carbridges 6 (cyan, gray, magenta, matte black, photo black, yellow) Ink drop 6 pH.C., M., Y. G. pKI; 9 l. (mK) Printheads 1 (cyan, gray, magenta, matte black, photo black, yellow) Line accuracy 20,1%² Minimum line width 0.02 mm (HP-GL/2 addressable) Guaranteed minimum line width 0.07 mm (ISO/IEC 13660:2001(E))³ with up to 50 A1/D-size capacity), media bin, automatic cutter Sheet size 210 x 279 to 914 x 1219 mm Roll size 210 to 914-mm wide sheets; 279 to 914-mm rolls Grammage 610 288 g/m² Applications Line drawings, Renderings, Presentations; Maps; Orthophotos Memory 64 GB (File processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing 1500 x 781 x 815 mm Weight Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 287 kg Shipping 120 kg What's in the box Pep Signet 1330 Printer; printhead; introductory ink cartridges; stacking tray, media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating humbity 20 to 80% RH Acoustics Sound pressure 47 (BGA) (operating); 39 dB(A) (Idle); < 16 dB(A) (Sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End (Isleep) Requirements Input voltage (auto ranging) 100-240 V (± 10%), 50/60 Hz (± 3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (UV) and EN 60550-1 compliant); Russia (GOST); Singapore (PSB); China (CCC), Argentina (RAM), Mexico (NYCE); Korea (KATS) Environmental ENERGY STAR®, WEEE; EU ROHS; REACH; EUP; EPEAT Bronze Environmental ENERGY STAR®, WEEE; EU ROHS; REACH; EUP; EPEAT Bronze	Margins	Roll: 3 x 3 x 3 x 3 mm () Sheet: 3 x 22 x 3 x 3 mm ()
ink drop 6 pt (C, M, Y, G, pK); 9 pt (mK) Printheads 1 (xyan, gray, magenta, matte black, photo black, yellow) Line accuracy 5.01%	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)
Printheads 1 (cyan, gray, magenta, matte black, photo black, yellow) Line accuracy ±0.1%² Minimum line width 0.02 mm (HP-GL/2 addressable) Guaranteed minimum line 0.07 mm (ISO/IEC 13660-2001 (E))³ width Media Handling Input: automatic front-loading roll feed, sheet feed; Output: integrated output stacking tray (from AA/A to AO/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Sheet size 210 x 279 to 914 x 1219 mm Gli size 210 to 314-mm wide sheets; 279 to 914-mm rolls Grammage 60 to 328 g/m² Applications Line drawings, Renderings; Presentations; Maps; Orthophotos Memory 64 G B (file processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing from most smartphones and tablets using these operating systems: Android, Brinting Birming Supports printing from most smartphones and tablets using these operating systems: Android, Brinting Birming 1399 x 916 x 1110 mm Shapping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 1500 x 781 x 815 mm Weight Printer B7 kg Christine B87 kg Charling temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (UVD and EN 50950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC), Argentina (RAM), Mexica (WYCE), Korea (KATS) Environmental ENERGY STAR*, WEEE; EU ROHS, REACH; Eu/F, EPEAT Bronze	Ink cartridges	6 (cyan, gray, magenta, matte black, photo black, yellow)
Line accuracy ±0.1% ² Minimum line width 0.02 mm (HP-GL/Z addressable) Guaranteed minimum line 0.07 mm (ISO/IEC 13660:2001(E)) ³ width Media Handling Input: automatic front-loading roll feed, sheet feed; Output: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Sheet size 210 x 279 to 914 x 1219 mm Roll size 210 to 914-mm wide sheets; 279 to 914-mm rolls Grammage 60 to 328 g/m² Applications Line drawings, Renderings; Presentations; Maps; Orthophotos Memory 64 GB (file processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing via Apple AirPrintin® HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems: Android, iOS Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box HP Designlet 1930 Printer; printhead; introductory ink cartridges; stacking tray, media bin; spindle; quick reference guide; setup poster; startup software; power cord Erivironmental ranges Operating temperature 5 to 40°C Operating temperature 6 to 80% RH Acoustics Sound power 6.5 BIA) (operating); 3.9 dB(A) (idle); < 1.6 dB(A) (sleep) Operating temperature 6 to 80% RH Acoustics Certification 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front En	Ink drop	6 pl (C, M, Y, G, pK); 9 pl (mK)
Minimum line width 0.02 mm (HP-GL/2 addressable) Guaranteed minimum line 0.07 mm (ISO/IEC 13660:2001(E))³ width Media Handling	Printheads	1 (cyan, gray, magenta, matte black, photo black, yellow)
Guaranteed minimum line 0.07 mm (ISO/IEC 13660:2001(E)) ³ width whedia Handling	Line accuracy	$\pm 0.1\%^2$
Media Handling Input: automatic front-loading roll feed, sheet feed, Output: integrated output stacking tray (from A4/A to A0/E with up to 50 A1/D-size capacity), media bin, automatic cutter Sheet size 210 x 279 to 914 x 1219 mm Roll size 210 to 914-mm wide sheets; 279 to 914-mm rolls Grammage 60 to 328 g/m² Applications Line drawings; Renderings; Presentations; Maps; Orthophotos Memory 64 G8 (file processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing via Apple Air-Print™, HP Print Service Plugin for Android, HP All-In-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems: Android, its Dimensions (w x d x h) Note of the state of the st	Minimum line width	0.02 mm (HP-GL/2 addressable)
Input: automatic front-loading roll feed, sheet feed; Output: integrated output stacking tray (from A4/A to AO/E with up to 50 A1/D-size capacity), media bin, automatic cutter Sheet size 210 x 279 to 914 x 1219 mm Roll size 210 to 914-mm wide sheets; 279 to 914-mm rolls Grammage 60 to 328 g/m² Applications Line drawings; Renderings; Presentations; Maps; Orthophotos Memory 64 GB (file processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing via Apple Air/Print ¹²⁴ , HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems; Android, 105 Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating temperature 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Corrigination 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Corrigination 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Corrigination 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Corrigination 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Corrigination 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Corrigin		0.07 mm (ISO/IEC 13660:2001(E)) ³
with up to 50 A1/D-size capacity), media bin, automatic cutter Sheet size 210 x 279 to 914 x 1219 mm Boll size 210 to 914-mm wide sheets; 279 to 914-mm rolls Grammage 60 to 328 g/m² Applications Line drawings; Renderings; Presentations; Maps; Orthophotos Memory 64 GB (file processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing via Apple AirPrint**, HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems: Android, IDS Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box Phosignate 17930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC), Argentina (IRAM); Mexico (NYCE), Korea (KATS) Environmental ENERGY STAR®; WEEE; EU ROHS; REACH; EUP; EPEAT Bronze	Media	
Roll size 210 to 914-mm wide sheets; 279 to 914-mm rolls Grammage 60 to 328 g/m² Applications Line drawings; Renderings; Presentations; Maps; Orthophotos Memory 64 GB (file processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing via Apple AirPrint ^m , HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems: Android, IOS Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 1.6 dB(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (± 10%), 50/60 Hz (± 3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC), Argentina (RAM); Mexica (NYCE); Korea (KATS).	Handling	Input: automatic front-loading roll feed, sheet feed; Output: integrated output stacking tray (from A4/A to A0/E with up to 50A1/D -size capacity), media bin, automatic cutter
Grammage 60 to 328 g/m² Applications Line drawings; Renderings; Presentations; Maps; Orthophotos Memory 64 GB (file processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing via Apple AirPrint**, HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and indicate and incisors printing from most smartphones and tablets using these operating systems: Android, incisors incisors printing from most smartphones and tablets using these operating systems: Android, incisors in	Sheet size	210 x 279 to 914 x 1219 mm
Applications Line drawings; Renderings; Presentations; Maps; Orthophotos Memory 64 GB (file processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features mobile printing via Apple AirPrint**, HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems: Android, iOS Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC), Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICCS), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Papan (VCCC); Certified as Class A product: Korea (KCC)	Roll size	210 to 914-mm wide sheets; 279 to 914-mm rolls
Memory 64 GB (file processing); Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing via Apple Air Print™, HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems: Android, in 1900 Mark 1900 Ma	Grammage	60 to 328 g/m ²
Connectivity Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing via Apple AirPrint™, HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems: Android, 100 Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 3.9 dB(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC), Argentina (RAM), Mewico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including 150.8 (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC)	Applications	Line drawings; Renderings; Presentations; Maps; Orthophotos
Interfaces Gigabit Ethernet (1000Base-T) Mobile printing features Mobile printing via Apple AirPrint**, HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems: Android, iOS Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCCC), Japan (VCCI); Certified as Class A product: Korea (KCCC) Environmental ENERGY STAR®; WEEE; EU ROHS; REACH; EUP; EPEAT Bronze	Memory	64 GB (file processing);
Mobile printing features Mobile printing via Apple AirPrint**, HP Print Service Plugin for Android, HP All-in-One Printer Remote app, and email printing. Supports printing from most smartphones and tablets using these operating systems: Android, iOS Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCC); Certified as Class A product: Korea (KCC)	Connectivity	
email printing. Supports printing from most smartphones and tablets using these operating systems: Android, iOS Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating tumidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCC); Certified as Class A product: Korea (KCC)	Interfaces	Gigabit Ethernet (1000Base-T)
Printer 1399 x 916 x 1110 mm Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Mobile printing features	email printing. Supports printing from most smartphones and tablets using these operating systems: Android,
Shipping 1500 x 781 x 815 mm Weight Printer 87 kg Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC), Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Dimensions (w x d x	h)
Weight Printer 87 kg Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep)	Printer	1399 x 916 x 1110 mm
Printer 87 kg Shipping 120 kg What's in the box HP Designlet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Shipping	1500 x 781 x 815 mm
Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Weight	
Shipping 120 kg What's in the box HP DesignJet T930 Printer; printhead; introductory ink cartridges; stacking tray; media bin; spindle; quick reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Printer	87 kg
reference guide; setup poster; startup software; power cord Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Shipping	120 kg
Operating temperature 5 to 40°C Operating humidity 20 to 80% RH ACOUSTICS Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; Eu.P; EPEAT Bronze	What's in the box	
Operating humidity 20 to 80% RH Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; Eu.P; EPEAT Bronze	Environmental range	es e
Acoustics Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; Eu.P; EPEAT Bronze	Operating temperature	5 to 40°C
Sound pressure 47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep) Sound power 6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Operating humidity	20 to 80% RH
Sound power 6.5 B(A) (operating); S.8 B(A) (idle); < 1.9 B(A) (sleep) Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Acoustics	
Power Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Sound pressure	47 dB(A) (operating); 39 dB(A) (idle); < 16 dB(A) (sleep)
Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Sound power	6.5 B(A) (operating); 5.8 B(A) (idle); < 1.9 B(A) (sleep)
Consumption 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	Power	
Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max (peak current) Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NVCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze	-	120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep)
Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze		
Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze		
Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR®; WEEE; EU RoHS; REACH; EuP; EPEAT Bronze		USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC): Argentina (IRAM): Mexico (NYCE): Korea (KATS)
	Electromagnetic	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia
Warranty One-year limited hardware warranty.	Environmental	ENERGY STAR®; WEEE; EU ROHS; REACH; EuP; EPEAT Bronze
	Warranty	One-year limited hardware warranty.

Ordering information

Product

L2Y21B	HP DesignJet T930 36-in Printer
Accessories	
C0C66C CN538A G6H50B G6H51B L4R66A	HP DesignJet PostScript/PDF Upgrade Kit HP DesignJet 3-in Core Adapter HP SD Pro 44-in Scanner HP HD Pro 42-in Scanner HP DesignJet 36-in Spindle

Original HP printing supplies

B3P06A B3P19A B3P20A B3P21A B3P22A B3P23A B3P23A	HP 727 DesignJet Printhead HP 727 130-ml Cyan DesignJet Ink Cartridge HP 727 130-ml Magenta DesignJet Ink Cartridge HP 727 130-ml Mate Black DesignJet Ink Cartridge HP 727 130-ml Matte Black DesignJet Ink Cartridge HP 727 130-ml Photo Black DesignJet Ink Cartridge HP 727 130-ml Gray DesignJet Ink Cartridge HP 727 130-ml Gray DesignJet Ink Cartridge HP 727 130-ml Matte Black DesignJet Ink Cartridge
C1012A	HP 727 300-ml Matte Black DesignJet Ink Cartridge
F9J76A	HP 727 300-ml Cyan DesignJet Ink Cartridge
F9177A	HP 727 300-ml Magenta DesignJet Ink Cartridge
F9J78A	HP 727 300-ml Yellow DesignJet Ink Cartridge
	33

Use **Original HP inks** and printheads, and HP large format printing materials, to experience Ose original in "initial sail primited and, and in Progression and progression and progression and progression and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit hp.com/go/OriginalHPinks.

Service and Support

H4518E HP Installation Service with Network Setup

H451BE HP Installation Service with Network Setup
U1XV4E Preventive Maintenance Service
UC3B4E HP 3 year Next Business Day Onsite Hardware Support with Defective Media
Retention for HP DesignJet T930-B
UC3B5E HP 4 year Next Business Day Onsite Hardware Support with Defective Media
Retention for HP DesignJet T930-B
UC3B6E HP 5 year Next Business Day Onsite Hardware Support with Defective Media
Retention for HP DesignJet T930-B
UBPM7PE HP 1 year Post Warranty Next Business Day Onsite Hardware Support with Defective
Media Retention for DesighInJet T930
UBTZ3PE HP 2 year Post Warranty Next Business Day Onsite Hardware Support with Defective
Media Retention for DesighInJet T930
UBTZ3PE HP 2 year Post Warranty Next Business Day Onsite Hardware Support with Defective
Media Retention for DesighInJet T930 HP DesignJet Support Services offer installation, maintenance, and extended support services

(e.g. 2,3, 4 and 5 years). For more information, please visit hp.com/go/cpc.

For the entire **HP Large Format Printing Materials** Portfolio, please see **HPLFMedia.com.**

ECO highlights

- ENERGY STAR® qualified and EPEAT Bronze registered¹
 Free, convenient HP ink cartridge recycling²
 FSC®-certified papers³ and a range of recyclable HP media with a take-back program²

Please recycle large-format printing hardware and printing supplies. Find out how at our

¹ EPEAT registered where applicable and/or supported. See http://www.epeat.net for registration status by country.
² Program availability varies. Please check http://www.hp.com/recycle for details. Many HP printing materials are recyclable through commonly available recycling programs. For information about HP large format printing materials, please visit http://www.HPLFMedia.com.
³ BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C017543, see http://www.fsc.org. Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please visit http://www.HPLFMedia.com.

























