

Scan only

# HP ScanJet Pro 2000 s1 Sheet-feed Scanner



Fast, affordable, and designed to handle everything from simple color jobs to complex workflows. Quickly and reliably digitize larger projects with scan speeds up to 30 ppm/60 ipm and a 50-page ADF.<sup>1</sup> Recommended for 2,000 pages per day.



## Small size. Fast scans. Same reliable results.

- Produce scans at up to 30 ppm/60 ipm<sup>1</sup> with two-sided scanning that captures both sides at once.
- Free up space for work. This HP ScanJet Pro is small and slim—a modern design perfect for the desktop.
- Don't wait for warm-up—HP Instant-on Scanning lets you begin scanning quickly.
- Load up to 50 pages into the automatic document feeder for fast, unattended scanning.



## Optimize workflows with one-touch scanning

- Streamline routine work with one-touch scanning—create one-button, custom settings for recurring scan jobs.
- Scan images directly into applications with included and full-featured TWAIN and ISIS®.
- Easily transfer scans into editable text, secure PDF files, and more file types, using built-in OCR.
- Quickly share or archive scans directly to popular cloud destinations with HP Scan software.



## Capture business documents like a pro

- Define scan profiles for common document types, and scan to multiple destinations with HP Scan software.
- Capture and organize documents, business cards, and other file types with feature-rich software.
- Produce clear, legible scans—up to 600-dpi resolution.

<sup>1</sup> Scan speed measured at 300 dpi (black-and-white, grayscale, and color). Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.

## Technical specifications

<b>Scan Technology</b>	CMOS CIS
<b>Scan Type</b>	Sheetfed; <b>Color Scanning:</b> Yes
<b>Scan speed ADF (letter)</b>	Up to 30 ppm/60 ipm
<b>Task speed</b>	10 x 15 cm (4 x 6 in) color photo to file (200 dpi, 24-bit, tiff): about 6.90 sec for single image scan; OCR A4 (8.27 x 11.69 in), 300 dpi, 24-bit to RTF: about 9.13 sec for single image scan; 10 x 15 cm (4 x 6 in) color photo to e-mail (150 dpi, 24-bit): about 10.65 sec for single image scan; A4 (8.5 x 11 in) PDF to e-mail (300 dpi, 24-bit): about 12.98 sec for single image scan
<b>Scan Resolution</b>	<b>Hardware:</b> Up to 600 dpi (color and mono, Sheet-feed) <b>Optical:</b> Up to 600 dpi (color and mono, Sheet-feed)
<b>Scan File Format</b>	For text & images: PDF, JPEG, PNG, BMP, TIFF, Text (.txt), Rich Text (.rtf) and Searchable PDF
<b>Scan Input Modes</b>	One default scan mode on front-panel for HP scan in Win OS, HP Easy Scan/ICA in Mac OS and third parties applications via TWAIN, ISIS and WIA
<b>Scanner Advanced Features</b>	Auto-color detect, auto-crop, auto-exposure, auto orient, OCR, edge removal, background cleanup, remove hole, color drop out, straighten the page, scan to cloud, scan to email, PDF security
<b>ENERGY STAR Qualified</b>	Yes
<b>Output Resolution Dpi Settings</b>	75; 150; 200; 240; 300; 400; 500; 600; 1200 ppi
<b>Bit depth / Grayscale levels</b>	24-bits external 48-bits internal; <b>Grayscale Levels:</b> 256
<b>Scan Size</b>	<b>ADF:</b> 216 x 863 mm
<b>Media Types</b>	Cut Sheet Paper, Printed Paper (Laser and ink), Pre-Punched Paper, Bank Checks, Business Cards, Freight Bills, Carbonless forms, Previously stapled media with staple removed, Plastic cards (up to 1.24mm)
<b>Media Size, ADF</b>	U.S.-Letter: 215.9 x 279.4 mm (8.5 x 11 in); U.S.-Legal: 215.9 x 355.6 mm (8.5 x 14 in); U.S.-Executive: 184.2 x 266.7 mm (7.25 x 10.5 in); ISO A4: 210 x 297 mm (8.3 x 11.7 in); JIS B5: 182 x 257 mm (7.2 x 10.1 in); ISO B5: 176 x 250 mm (7.0 x 9.9 in); ISO A5: 148 x 210 mm (5.8 x 8.3 in); ISO A6: 105 x 148 mm (5.8 x 4.1 in); ISO A7: 74 x 104 mm (2.9 x 4.1 in); ISO A8: 52 x 74 mm (2.0 x 2.9 in)
<b>Media weight (ADF)</b>	50 to 180 g/m <sup>2</sup>
<b>Auto document feeder capacity</b>	50 sheets of 75 g/m <sup>2</sup> paper
<b>Duty Cycle (Daily)</b>	Recommended for 2000 pages per day
<b>Standard connectivity</b>	USB 2.0 (Hi-Speed)
<b>Memory</b>	64 MB
<b>Processor Speed</b>	120 MHz
<b>Control Panel</b>	Scan button, Power button with a LED and a LED for Error indication
<b>Image Scaling or Enlargement Range</b>	Will not perform any arbitrary scaling.
<b>Twain Version</b>	Windows: TWAIN version 2.1; Mac: n/a
<b>Software Included</b>	Win: HP WIA scan driver, HP TWAIN scan driver, HP Scan, HP Scanner Tools Utility, Nuance PaperPort (Win only), I.R.I.S. Readiris, I.R.I.S. Cardiris (Win only), EMC ISIS (Win only)
<b>Compatible Operating Systems</b>	OS X Mavericks 10.9, OS X Yosemite 10.10, OS X El Capitan 10.11, Microsoft® Windows® 10, 8.1, 8, 7: 32-bit or 64-bit
<b>Minimum System Requirements</b>	<b>PC:</b> Apple® OS X Yosemite, OS X Mavericks, OS X Mountain Lion; 1 GB HD; Internet required; USB; Microsoft® Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer <b>Mac:</b> Apple® OS X Yosemite, OS X Mavericks, OS X Mountain Lion; 1 GB HD; Internet required; USB
<b>Operating environment</b>	<b>Operating Humidity Range:</b> 15 to 80% RH (non-condensing) <b>Non-operating Humidity Range:</b> 0 to 90% RH (non-condensing) <b>Recommended Humidity Operating Range:</b> 15 to 80% RH (non-condensing) <b>Operating Temperature Range:</b> 10 to 35 ° C <b>Storage Temperature Range:</b> -40 to 60 ° C <b>Recommended Operating Temperature Range:</b> 10 to 35 ° C
<b>Power</b>	<b>Power Supply Type:</b> External Power Adapter <b>Power Consumption:</b> 3.6 Watts (ready), 1.0 Watts (sleep), 0.1 Watts (auto-off), 0.1 Watts (off) <b>Power Requirements:</b> Input Voltage range: 90 - 264 VAC , Rated Frequency: 50 - 60Hz, Worldwide use
<b>Dimensions (W x D x H)</b>	300 x 172.9 x 152.1 mm
<b>Weight</b>	2.6 kg
<b>What's in the box</b>	HP ScanJet Pro 2000 s1 Sheet-feed Scanner; Install guide; Support flyers; Warranty cards; 2 CDs; Power cords; Power adaptor; USB cables (All regions)
<b>Warranty</b>	1 Year Limited Warranty (Return to HP/Dealer - Unit Exchange)
<b>Electromagnetic emission standard</b>	Class B Emissions; CISPR 22:2008 (International); European Union EMC Directive 2014/30/EU, EN 55022:2010 (CE mark); China GB9254-2008 (CCC); Taiwan CNS13438:2006 (BSMI); USA CFR47 Part 15, Subpart B (FCC); ICES-003:2012 Issue 6 (Canada); Australia C-tick (Includes New Zealand); KN 22 and Korea KCC; EAC EMC Certificate; Ukraine EMC approval; EN 61000-3-2:2014 (harmonics); EN 61000-3-3:2013 (flicker); Immunity CISPR 24:2010, EN 50024:2010
<b>Safety Approvals and Requirements</b>	IEC 60950-1:2005 +A1+A11+A12 and all applicable amendments; CSA/UL 60950-1, 2nd edition (2007); EN 60950-1:2006 +A1 +A1 +A12+A2; EAC safety; Canada cUL CoC; China CCC; European Union CE; Kenya PVOC; Kuwait TER; Nigeria SON; Saudi Arabia SASO; South Africa NRCs; Taiwan BSMI; Ukraine safety approval
<b>Accessories</b>	HP ScanJet Pro 2000 s1 roller replacement kit (L2760A)

<sup>1</sup> With input and output trays folded and covers closed

<sup>2</sup> Actual speeds may vary depending on scan resolution, connectivity type, computer performance and application software.

## Ordering Information

Number	Description
L2759A	HP ScanJet Pro 2000 s1 Sheet-feed Scanner

### HP Care Packs

Number	Description
U9JQ3E	HP 3 year Exchange Hardware Support for ScanJet Pro 2xxx
U9JQ5E	HP 3 year Return to Depot Hardware Support for ScanJet Pro 2xxx

Protect your investment with HP Care Pack. Let HP certified engineers resolve your technical issues. For more details on HP Care Pack, go to [hp.com/go/cpc](http://hp.com/go/cpc)

### HP Inc. offices

Australia	(613) 8833 5000	<a href="http://hp.com.au">hp.com.au</a>
China	(010) 6564 3888	<a href="http://hp.com.cn">hp.com.cn</a>
Hong Kong	(852) 3077 2688	<a href="http://hp.com.hk">hp.com.hk</a>
India	(80) 2612 9000	<a href="http://hp.com/in">hp.com/in</a>
Indonesia	(62-21) 5799 1088	<a href="http://hp.com/id">hp.com/id</a>
Korea	(02) 2199 0114	<a href="http://hp.co.kr">hp.co.kr</a>
Malaysia	(603) 2332 3333	<a href="http://hp.com.my">hp.com.my</a>
New Zealand	(09) 918 9555	<a href="http://hp.co.nz">hp.co.nz</a>
Philippines	(632) 888 5900	<a href="http://hp.com/ph">hp.com/ph</a>
Singapore	(65) 6275 3888	<a href="http://hp.com.sg">hp.com.sg</a>
Taiwan	(02) 3789 9900	<a href="http://hp.com.tw">hp.com.tw</a>
Thailand	(662) 353 9500	<a href="http://hp.com/th">hp.com/th</a>
Vietnam	(848) 3823 4151	<a href="http://hp.com/vn">hp.com/vn</a>


For the following countries, please fax your queries to (65) 6275 6707 Bangladesh, Bhutan, Brunei, Cambodia, Maldives, Nepal, Pakistan, Sri Lanka

### Supported paper

Contact HP via phone: Asia: 65 6253 8500

### Solutions

For more solutions information, please visit [hp.com/go/gsc](http://hp.com/go/gsc)



## To learn more, visit [hp.com](http://hp.com)

© Copyright 2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Microsoft and Windows are registered trademarks of Microsoft Corporation. AirPrint and the AirPrint logo are trademarks of Apple Inc., registered in the U.S. and other countries. Linux is a U.S. registered trademark of Linus Torvalds. UNIX is a registered trademark of The Open Group.

